



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 1 Reference</p> <p>Definition</p>	<p style="text-align: center;">INTERNATIONAL STANDARDS AND RECOMMENDED PRACTICES</p> <p style="text-align: center;">PART I — DIGITAL DATA COMMUNICATION SYSTEMS</p> <p style="text-align: center;">CHAPTER 1. DEFINITIONS</p> <p><i>N1. All references to “Radio Regulations” are to the Radio Regulations published by the International Telecommunication Union (ITU). Radio Regulations are amended from time to time by the decisions embodied in the Final Acts of World Radiocommunication Conferences held normally every two to three years. Further information on the ITU processes as they relate to aeronautical radio system frequency use is contained in the Handbook on Radio Frequency Spectrum Requirements for Civil Aviation including statement of approved ICAO policies (Doc 9718).</i></p> <p><i>N2. The Part of Annex 10 includes Standards and Recommended Practices for certain forms of equipment for communication systems. While the Contracting State will determine the necessity for specific installations in accordance with the conditions prescribed in the relevant Standard or Recommended Practice, review of the need for specific installation and the formulation of ICAO opinion and recommendations to Contracting States concerned, is carried out periodically by Council, ordinarily on the basis of recommendations of Regional Air Navigation Meetings (Doc 8144, Directives to Regional Air Navigation Meetings and Rules of Procedure for their Conduct).</i></p> <p><i>N3. This chapter contains general definitions relevant to communication systems. Definitions specific to each of the systems included in this volume are contained in the relevant chapters.</i></p> <p><i>N4. Material on secondary power supply and guidance material concerning reliability and availability for</i></p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p><i>communication systems is contained in Annex 10, Volume I, 2.9 and Volume I, Attachment F, respectively.</i></p> <p>Aeronautical administrative communications (AAC). Communications necessary for the exchange of aeronautical administrative messages.</p>				
Chapter 1 Reference Definition	Aeronautical operational control (AOC). Communication required for the exercise of authority over the initiation, continuation, diversion or termination of flight for safety, regularity and efficiency reasons.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Aeronautical telecommunication network (ATN). A global internetwork architecture that allows ground, air-ground and avionic data subnetworks to exchange digital data for the safety of air navigation and for the regular, efficient and economic operation of air traffic services.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Air traffic service. A generic term meaning variously, flight information service, alerting service, air traffic advisory service, air traffic control service (area control service, approach control service or aerodrome control service).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Aircraft address. A unique combination of twenty-four bits available for assignment to an aircraft for the purpose of air-ground communications, navigation and surveillance.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	Aircraft earth station (AES). A mobile earth station in the aeronautical mobile-satellite service located on board an aircraft (see also “GES”).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Automatic dependent surveillance — contract (ADS-C). A means by which the terms of an ADS-C agreement will be exchanged between the ground system and the aircraft, via a data link, specifying under what conditions ADS-C reports would be initiated, and what data would be contained in the reports.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Automatic terminal information service (ATIS). The automatic provision of current, routine information to arriving and departing aircraft throughout 24 hours or a specified portion thereof. <i>Data link-automatic terminal information service (D-ATIS).</i> The provision of ATIS via data link. <i>Voice-automatic terminal information service (Voice-ATIS).</i> The provision of ATIS by means of continuous and repetitive voice broadcasts.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Bit error rate (BER). The number of bit errors in a sample divided by the total number of bits in the sample, generally averaged over many such samples.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	Carrier-to-multipath ratio (C/M). The ratio of the carrier power received directly, i.e. without reflection, to the multipath power, i.e. carrier power received via reflection.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Carrier-to-noise density ratio (C/N₀). The ratio of the total carrier power to the average noise power in a 1 Hz bandwidth, usually expressed in dBHz.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Channel rate. The rate at which bits are transmitted over the RF channel. These bits include those bits used for framing and error correction, as well as the information bits. For burst transmission, the channel rate refers to the instantaneous burst rate over the period of the burst.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Channel rate accuracy. This is relative accuracy of the clock to which the transmitted channel bits are synchronized. For example, at a channel rate of 1.2 kbits/s, maximum error of one part in 10 ⁶ implies the maximum allowed error in the clock is $\pm 1.2 \times 10^{-3}$ Hz.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Circuit mode. A configuration of the communications network which gives the appearance to the application of a dedicated transmission path.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	Controller pilot data link communications (CPDLC). A means of communication between controller and pilot, using data link for ATC communications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Data link flight information services (D-FIS). The provision of FIS via data link.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Doppler shift. The frequency shift observed at a receiver due to any relative motion between transmitter and receiver.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	End-to-end. Pertaining or relating to an entire communication path, typically from (1) the interface between the information source and the communication system at the transmitting end to (2) the interface between the communication system and the information user or processor or application at the receiving end.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	End-user. An ultimate source and/or consumer of information.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	Energy per symbol to noise density ratio (E_s/N_0). The ratio of the average energy transmitted per channel symbol to the average noise power in a 1 Hz bandwidth, usually expressed in dB. For A-BPSK and A-QPSK, one channel symbol refers to one channel bit.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Equivalent isotropically radiated power ($e.i.r.p.$). The product of the power supplied to the antenna and the antenna gain in a given direction relative to an isotropic antenna (<i>absolute or isotropic gain</i>).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Flight information service (FIS). A service provided for the purpose of giving advice and information useful for the safe and efficient conduct of flights.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Forward error correction (FEC). The process of adding redundant information to the transmitted signal in a manner which allows correction, at the receiver, of errors incurred in the transmission.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Gain-to-noise temperature ratio. The ratio, usually expressed in dB/K, of the antenna gain to the noise at the receiver output of the antenna subsystem. The noise is expressed as the temperature that a 1 ohm resistor must be raised to produce the same noise power density.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	<p>Ground earth station (GES). An earth station in the fixed satellite service, or, in some cases, in the aeronautical mobile-satellite service, located at a specified fixed point on land to provide a feeder link for the aeronautical mobile-satellite service.</p> <p><i>Note.— This definition is used in the ITU's Radio Regulations under the term "aeronautical earth station". The definition herein as "GES" for use in the SARPs is to clearly distinguish it from an aircraft earth station (AES), which is a mobile station on an aircraft.#</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	<p>Mode S subnetwork. A means of performing an interchange of digital data through the use of secondary surveillance radar (SSR) Mode S interrogators and transponders in accordance with defined protocols.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	<p>Point-to-point. Pertaining or relating to the interconnection of two devices, particularly end-user instruments. A communication path of service intended to connect two discrete end-users; as distinguished from broadcast or multipoint service.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	<p>Slotted aloha. A random access strategy whereby multiple users access the same communications channel independently, but each communication must be confined to a fixed time slot. The same timing slot structure is known to all users, but there is no other coordination between the users.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference Definition	Time division multiple access (TDMA). A multiple access scheme based on time-shared use of an RF channel employing: (1) discrete contiguous time slots as the fundamental shared resource; and (2) a set of operating protocols that allows users to interact with a master control station to mediate access to the channel.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Time division multiplex (TDM). A channel sharing strategy in which packets of information from the same source but with different destinations are sequenced in time on the same channel.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	Transit delay. In packet data systems, the elapsed time between a request to transmit an assembled data packet and an indication at the receiving end that the corresponding packet has been received and is ready to be used or forwarded.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 1 Reference Definition	VHF digital link (VDL). A constituent mobile subnetwork of the aeronautical telecommunication network (ATN), operating in the aeronautical mobile VHF frequency band. In addition, the VDL may provide non-ATN functions such as, for instance, digitized voice.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference</p> <p>Definition</p>	<p style="text-align: center;">CHAPTER 3. AERONAUTICAL TELECOMMUNICATION NETWORK</p> <p><i>N1. Detailed technical specifications for ATN/OSI applications are contained in the Manual on Detailed Technical Specifications for the Aeronautical Telecommunication (ATN) using ISO/OSI standards and protocols (Doc 9880) and in the Manual of Technical Provisions for the Aeronautical Telecommunication Network (ATN) (Doc 9705).</i></p> <p><i>N2. Detailed technical specifications for ATN/IPS applications are contained in the Manual for the ATN using IPS standards and protocols (Doc 9896) (available electronically on the ICAO-Net).</i></p> <p style="text-align: center;">3.1 DEFINITIONS</p> <p><i>Application entity (AE).</i> An AE represents a set of ISO/OSI communication capabilities of a particular application process (see ISO/IEC 9545 for further details).</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		
<p>Chapter 3 Reference</p> <p>Definition</p>	<p><i>ATN security services.</i> A set of information security provisions allowing the receiving end system or intermediate system to unambiguously identify (i.e. authenticate) the source of the received information and to verify the integrity of that information.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference Definition	<i>ATS interfacility data communication (AIDC)</i> . Automated data exchange between air traffic services units in support of flight notification, flight coordination, transfer of control and transfer of communication.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference Definition	<i>ATS message handling service (ATSMHS)</i> . An ATN application consisting of procedures used to exchange ATS messages in store-and-forward mode over the ATN such that the conveyance of an ATS message is in general not correlated with the conveyance of another ATS message by the service provider.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference Definition	<i>ATS message handling system (AMHS)</i> . The set of computing and communication resources implemented by ATS organizations to provide the ATS message handling service.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference Definition	<i>Authorized path</i> . A communication path suitable for a given message category.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference Definition	<i>Data link initiation capability (DLIC)</i> . A data link application that provides the ability to exchange addresses, names and version numbers necessary to initiate data link applications (see Doc 4444).	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference Definition	Directory service (DIR). A service, based on the ITU-T X.500 series of recommendations, providing access to and management of structured information relevant to the operation of the ATN and its users.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference Definition	Required communication performance (RCP). A statement of the performance requirements for operational communication in support of specific ATM functions (see <i>Manual on Required Communication Performance (RCP)</i> (Doc 9869)).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.2.1 Standard	<p style="text-align: center;">3.2 INTRODUCTION</p> <p>The ATN is specifically and exclusively intended to provide digital data communications services to air traffic service provider organizations and aircraft operating agencies in support of:</p> <ul style="list-style-type: none"> a) air traffic services communications (ATSC) with aircraft; b) air traffic services communications between ATS units; c) aeronautical operational control communications (AOC); and d) aeronautical administrative communications (AAC). 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.3.1 Standard	<p style="text-align: center;">3.3 GENERAL</p> <p><i>Note.— The Standards and Recommended Practices in sections 3.4 to 3.8 define the minimum required protocols and services that will enable the global implementation of the aeronautical telecommunication network (ATN).</i></p> <p>ATN communication services shall support ATN applications.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.3.2 Standard	Requirements for implementation of the ATN shall be made on the basis of regional air navigation agreements. These agreements shall specify the area in which the communication standards for the ATN/OSI or the ATN/IPS are applicable.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.4.1 Standard	<p align="center">3.4 GENERAL REQUIREMENTS</p> <p>The ATN shall either use International Organization for Standardization (ISO) communication standards for open systems interconnection (OSI) or use the Internet Society (ISOC) communications standards for the Internet Protocol Suite (IPS).</p> <p><i>N1.ATN/IPS implementation is preferred for ground/ground networks. While ATN/OSI continues to be supported in air/ground networks, particularly when using VDL Mode 2, it is expected that future air/ground implementations will use the ATN/IPS.</i></p> <p><i>N2.Interoperability between interconnecting OSI/IPS networks is expected to be arranged prior to implementation.</i></p> <p><i>N3.Guidance material on interoperability between ATN/OSI and ATN/IPS is contained in the Manual on the Aeronautical Telecommunication Network (ATN) using Internet Protocol Suite (IPS) Standards and Protocols, (Doc 9896).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.2 Standard	The AFTN/AMHS gateway shall ensure the interoperability of AFTN and CIDIN stations and networks with the ATN.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.3 Standard	An authorized path(s) shall be defined on the basis of a predefined routing policy.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.4.4 Standard	The ATN shall transmit, relay and deliver messages in accordance with the priority classifications and without discrimination or undue delay.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.5 Standard	The ATN shall provide means to define data communications that can be carried only over authorized paths for the traffic type and category specified by the user.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.6 Standard	The ATN shall provide communication in accordance with the prescribed required communication performance (RCP). <i>Note.— The Manual on Required Communication Performance (RCP) (Doc 9869) contains the necessary information on RCP.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.7 Standard	The ATN shall operate in accordance with the communication priorities defined in Table 3-1* and Table 3-2. * Tables 3-1 and 3-2 are located at the end of this chapter.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.8 Standard	The ATN shall enable exchange of application information when one or more authorized paths exist.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.4.9 Standard	The ATN shall notify the appropriate application processes when no authorized path exists.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.10 Standard	The ATN shall make provisions for the efficient use of limited bandwidth subnetworks.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.11 Recommendation	Recommendation. — <i>The ATN should enable an aircraft intermediate system (router) to connect to a ground intermediate system (router) via different subnetworks.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.12 Recommendation	Recommendation. — <i>The ATN should enable an aircraft intermediate system (router) to connect to different ground intermediate systems (routers).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.4.13 Standard	The ATN shall enable the exchange of address information between applications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.4.14 Standard	Where the absolute time of day is used within the ATN, it shall be accurate to within 1 second of coordinated universal time (UTC). <i>Note.— The time accuracy value results in synchronization errors of up to two seconds.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.5.1.1 Standard	3.5 ATN APPLICATIONS REQUIREMENTS 3.5.1 System applications <i>Note.— System applications provide services that are necessary for operation of the ATN.</i> The ATN shall support the data link initiation capability (DLIC) applications when air-ground data links are implemented. <i>Note.— The Manual of Air Traffic Services Data Link Applications (Doc 9694, Part I) defines the data link initiation capability (DLIC) application.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.5.1.2 Standard	The ATN/OSI end-system shall support the following directory services (DIR) application functions when AMHS and/or security protocols are implemented: a) directory information retrieval; and b) directory information modification.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.5.2.1 Standard	<p style="text-align: center;">3.5.2 Air-ground applications</p> <p>The ATN shall be capable of supporting one or more of the following applications:</p> <ul style="list-style-type: none"> a) ADS-C; b) CPDLC; and c) FIS (including ATIS and METAR). <p><i>Note.— See the Manual of Air Traffic Services Data Link Applications (Doc 9694).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.5.3.1 Standard	<p style="text-align: center;">3.5.3 Ground-ground applications</p> <p>The ATN shall be capable of supporting the following AIDC applications:</p> <ul style="list-style-type: none"> a) ATS interfacility data communication (AIDC); and b) ATS message handling services applications (ATSMHS). <p><i>Note.— See the Manual of Air Traffic Services Data Link Applications (Doc 9694).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.6.1.1 Standard	<p style="text-align: center;">3.6 ATN COMMUNICATIONS SERVICE REQUIREMENTS</p> <p style="text-align: center;">3.6.1 ATN/IPS upper layer communications service</p> <p>An ATN host* shall be capable of supporting the ATN/IPS upper layers including an application layer.</p> <p><small>* An ATN host is an ATN end-system in OSI terminology; an ATN end-system is an ATN host in IPS terminology.</small></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.6.2.1 Standard	<p align="center">3.6.2 ATN/OSI upper layer communications service</p> <p>An ATN/OSI end-system (ES)* shall be capable of supporting the OSI upper layer communications service (ULCS) including session, presentation and application layers.</p> <hr/> <p>* An ATN host is an ATN end-system in OSI terminology; an ATN end-system is an ATN hose in IPS terminology.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.6.3.1 Standard	<p align="center">3.6.3 ATN/IPS communications service</p> <p>An ATN host shall be capable of supporting the ATN/IPS including the:</p> <ul style="list-style-type: none"> a) transport layer in accordance with RFC 793 (TCP) and RFC 768 (UDP); and b) network layer in accordance with RFC 2460 (IPv6). 	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.6.3.2 Standard	An IPS router shall support the ATN network layer in accordance with RFC 2460 (IPv6) and RFC 4271 (BGP), and RFC 2858 (BGP multiprotocol extensions).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.6.4.1 Standard	<p align="center">3.6.4 ATN/OSI communications service</p> <p>An ATN/OSI end-system shall be capable of supporting the ATN including the:</p> <ul style="list-style-type: none"> a) transport layer in accordance with ISO/IEC 8073 (TP4) and optionally ISO/IEC 8602 (CLTP); and b) network layer in accordance with ISO/IEC 8473 (CLNP). 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.6.4.2 Standard	An ATN intermediate system (IS) shall support the ATN network layer in accordance with ISO/IEC 8473 (CLNP) and ISO/IEC 10747 (IDRP).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.7.1 Standard	<p>3.7 ATN NAMING AND ADDRESSING REQUIREMENTS</p> <p><i>Note.— The ATN naming and addressing scheme supports the principles of unambiguous identification of intermediate systems (routers) and end-systems (hosts) and provides global address standardization.</i></p> <p>The ATN shall provide provisions for unambiguous application identification.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.7.2 Standard	The ATN shall provide provisions for unambiguous addressing.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.7.3 Standard	The ATN shall provide means to unambiguously address all ATN end-systems (hosts) and intermediate systems (routers).	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.7.4 Standard	The ATN addressing and naming plans shall allow States and organizations to assign addresses and names within their own administrative domains.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.8.1 Standard	<p style="text-align: center;">3.8 ATN SECURITY REQUIREMENTS</p> <p>The ATN shall make provisions whereby only the controlling ATS unit may provide ATC instructions to aircraft operating in its airspace.</p> <p><i>Note.— This is achieved through the current and next data authority aspects of the controller-pilot data link communications (CPDLC) application.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.8.2 Standard	The ATN shall enable the recipient of a message to identify the originator of that message.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 3 Reference 3.8.3 Standard	<p>ATN end-systems supporting ATN security services shall be capable of authenticating the identity of peer end-systems, authenticating the source of messages and ensuring the data integrity of the messages.</p> <p><i>Note.— The use of security is the default; however, its implementation is based on local policy.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.8.4 Standard	The ATN services shall be protected against service attacks to a level consistent with the application service requirements.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference Definition	<p style="text-align: center;">CHAPTER 4. AERONAUTICAL MOBILE-SATELLITE (ROUTE) SERVICE (AMS(R)S)</p> <p>N1. <i>This chapter contains Standards and Recommended Practices applicable to the use of Aeronautical Mobile-Satellite (R) Service communications technologies. The Standards and Recommended Practices in this chapter are service- and performance-oriented and are not tied to a specific technology or technique.</i></p> <p>N2. <i>Detailed Technical Specifications of AMS(R)S Systems are contained in the manual on AMS(R)S Systems are contained in the manual on AMS(R)S. This document also provides a detailed description of the AMS(R)S, including details on the Standards and Recommended Practices below.</i></p> <p style="text-align: center;">4.1 DEFINITIONS</p> <p>Connection establishment delay. Connection establishment delay, as defined in ISO 8348, includes a component, attributable to the called subnetwork (SN) service user, which is the time between the SN-CONNECT indication and the SN-CONNECT response. This user component is due to actions outside the boundaries of the satellite subnetwork and is therefore excluded from the AMS(R)S specifications.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference Definition	Data transfer delay (95th percentile). The 95th percentile of the statistical distribution of delays for which transit delay is the average.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference Definition	Data transit delay. In accordance with ISO 8348, the average value of the statistical distribution of data delays. This delay represents the subnetwork delay and does not include the connection establishment delay.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference Definition	Network (N). The word 'network' and its abbreviation “N” in ISO 8348 are replaced by the word “subnetwork” and its abbreviation “SN”, respectively, wherever they appear in relation to the subnetwork layer packet data performance.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference Definition	Residual error rate. The ratio of incorrect, lost and duplicate subnetwork service data units (SNSDUs) to the total number of SNSDUs that were sent.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference Definition	Spot beam. Satellite antenna directivity whose main lobe encompasses significantly less than the earth's surface that is within line-of-sight view of the satellite. May be designed so as to improve system resource efficiency with respect to geographical distribution of user earth stations.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference Definition	Subnetwork (SN). See <i>Network (N)</i> .	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference Definition	Subnetwork service data unit (SNSDU). An amount of subnetwork user data, the identity of which is preserved from one end of a subnetwork connection to the other.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference Definition	Total voice transfer delay. The elapsed time commencing at the instant that speech is presented to the AES or GES and concluding at the instant that the speed enters the interconnecting network of the counterpart GES or AES. This delay includes vocoder processing time, physical layer delay, RF propagation delay and any other delays within an AMS(R)S subnetwork. <i>Note.— The following terms used in this chapter are defined in Annex 10 as follows:</i> a) <i>Aeronautical telecommunication network (ATN):</i> <i>Volume III, Chapter 1.</i> b) <i>Aeronautical mobile-satellite (route) service (AMS(R)S):</i> <i>volume II, Chapter 1.1</i> c) <i>Aircraft earth station (AES):</i> <i>Volume III, Chapter 1.</i> d) <i>Ground earth station (GES):</i> <i>Volume III, Chapter 1.</i> e) <i>Subnetwork layer:</i> <i>Volume III, Chapter 6.1.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.2.1 Standard	<p style="text-align: center;">4.2 GENERAL</p> <p>Any mobile-satellite system intended to provide AMS(R)S shall conform to the requirements of this chapter.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.2.1.1 Standard	An AMS(R)S system shall support packet data service, or voice service, or both.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.2.2 Standard	Requirements for mandatory carriage of AMS(R)S system equipment including the level of system capability shall be made on the basis of regional air navigation agreements which specify the airspace of operation and the implementation timescales for the carriage of equipment. A level of system capability shall include the performance of the AES, the satellite and the GES.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.2.3 Standard	The agreements indicated in 4.2.2 shall provide at least two years' notice of mandatory carriage of airborne systems.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.2.4 Recommendation	Recommendation. — <i>Civil aviation authorities should coordinate with national authorities and service providers those implementation aspects of an AMS(R)S system that will permit its worldwide interoperability and optimum use, as appropriate.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.3.1.1 Standard	<p style="text-align: center;">4.3 RF CHARACTERISTICS</p> <p style="text-align: center;">4.3.1 Frequency Bands</p> <p><i>Note.— ITU Radio Regulations permit systems providing mobile-satellite service to use the same spectrum as AMS(R)S without requiring such systems to offer safety services. This situation has the potential to reduce the spectrum available for AMS(R)S. It is critical that States consider this issue in frequency planning and in the establishment of national or regional spectrum requirements.</i></p> <p>When providing AMS(R)S communications, an AMS(R)S system shall operate only in frequency bands which are appropriately allocated to AMS(R)S and protected by the ITU Radio Regulations.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.2.1 Standard	<p style="text-align: center;">4.3.2 Emissions</p> <p>The total emissions of the AES necessary to meet designed system performance shall be controlled to avoid harmful interference to other systems necessary to support safety and regularity of air navigation, installed on the same or other aircraft.</p> <p><i>N1.Harmful interference can result from radiated and/or conducted emissions that include harmonics, discrete spurious, intermodulation product and noise emissions, and are not necessarily limited to the "transmitter on" state.</i></p> <p><i>N2.Protection requirements for GNSS are contained in Annex 10, Volume I.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.3.2.2.1 Standard	<p style="text-align: center;">4.3.2.2 INTERFERENCE TO OTHER AMS(R)S EQUIPMENT</p> <p>Emissions from an AMS(R)S system AES shall not cause harmful interference to an AES providing AMS(R)S on a different aircraft.</p> <p><i>Note.— One method of complying with 4.3.2.2.1 is by limiting emissions in the operating band of other AMS(R)S equipment to a level consistent with the intersystem interference requirements such as contained in RTCA document DO-215. RTCA and EUROCAE may establish new performance standards for future AMS(R)S which may describe methods of compliance with this requirement.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.3.3.1 Standard	<p style="text-align: center;">4.3.3 Susceptibility</p> <p>The AES equipment shall operate properly in an interference environment causing a cumulative relative change in its receiver noise temperature ($\Delta T/T$) of 25 per cent.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1 Standard	<p style="text-align: center;">4.4 PRIORITY AND PRE-EMPTIVE ACCESS</p> <p>Every aircraft earth station and ground earth station shall be designed to ensure that messages transmitted in accordance with Annex 10, Volume II, 5.1.8, including their order of priority, are not delayed by the transmission and/or reception of other types of messages. If necessary, as a means to comply with the above requirement, message types not defined in Annex 10, Volume II, 5.1.8 shall be terminated even without warning, to allow Annex 10, Volume II, 5.1.8 type messages to be transmitted and received.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.4.2 Standard	All AMS(R)S data packets and all AMS(R)S voice calls shall be identified as to their associated priority.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.4.3 Standard	Within the same message category, the system shall provide voice communications priority over data communications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.5.1 Standard	<p style="text-align: center;">4.5 SIGNAL ACQUISITION AND TRACKING</p> <p>The AES, GES and satellites shall properly acquire and track service link signals when the aircraft is moving at a ground speed of up to 1 500 km/h (800 knots) along any heading.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.5.1.1 Recommendation	Recommendation. — <i>The AES, GES and satellites should properly acquire and track service link signals when the aircraft is moving at a ground speed of up to 2 800 km/h (1 500 knots) along any heading.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.5.2 Standard	The AES, GES and satellites shall properly acquire and track service link signals when the component of the aircraft acceleration vector in the plane of the satellite orbit is up to 0.6 g.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.5.2.1 Recommendation	Recommendation. — <i>The AES, GES, and satellites should properly acquire and track service link signals when the component of the aircraft acceleration vector in the plane of the satellite orbit is up to 1.2 g.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.1.1 Standard	4.6 PERFORMANCE REQUIREMENTS 4.6.1 Designated operational coverage An AMS(R)S system shall provide AMS(R)S throughout its designated operational coverage (DOC).	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.2.1 Standard	<p style="text-align: center;">4.6.2 Failure notification</p> <p>In the event of a service failure, an AMS(R)S system shall provide timely predictions of the time, location and duration of any resultant outages until full service is restored.</p> <p><i>Note.— Service outages may, for example, be caused by the failure of a satellite, satellite spot beam, or GES. The geographic areas affected by such outages may be a function of the satellite orbit and system design, and may vary with time.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.2.2 Standard	The system shall annunciate a loss of communications capability within 30 seconds of the time when it detects such a loss.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.3.1 Standard	<p style="text-align: center;">4.6.3 AES requirements</p> <p>The AES shall meet the relevant performance requirements contained in 4.6.4 and 4.6.5 for aircraft in straight and level flight throughout the designated operational coverage of the satellite system.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.3.1.1 Recommendation	Recommendation.— <i>The AES should meet the relevant performance requirements contained in 4.6.4 and 4.6.5 for aircraft attitudes of +20/-5 degrees of pitch and +/-25 degrees of roll throughout the DOC of the satellite system.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.4.1 Standard	<p align="center">4.6.4 Packet data service performance</p> <p>If the system provides AMS(R)S packet data service, it shall meet the standards of the following subparagraphs.</p> <p><i>Note—System performance standards for packet data service may also be found in RTCA Document DO-270.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.1 Standard	<p>An AMS(R)S system providing a packet data service shall be capable of operating as a constituent mobile subnetwork of the ATN.</p> <p><i>Note.— In addition, an AMS(R)S may provide non-ATN data functions.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.1 Standard	<p><i>4.6.4.1.2 DELAY PARAMETERS</i></p> <p><i>Note.— The term “highest priority service” denotes the priority which is reserved for distress, urgency and certain infrequent network system management messages. The term “lowest priority service” denotes the priority used for regularity of flight messages. All delay parameters are under peak-hour traffic loading conditions.</i></p> <p><i>Connection establishment delay. Connection establishment delay shall not be greater than 70 seconds.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.1.1 Recommendation	<p>Recommendation.— <i>Connection establishment delay should not be greater than 50 seconds.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.4.1.2.2 Standard	In accordance with ISO 8348, data transit delay values shall be based on a fixed subnetwork service data unit (SNSDU) length of 128 octets. Data transit delays shall be defined as average values.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.3 Standard	<i>Data transit delay, from-aircraft, highest priority.</i> From-aircraft data transit delay shall not be greater than 40 seconds for the highest priority data service.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.3.1 Recommendation	Recommendation. — <i>Data transit delay, from-aircraft, highest priority. From-aircraft data transit delay should not be greater than 23 seconds for the highest priority data service.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.3.2 Recommendation	Recommendation. — <i>Data transit delay, from-aircraft, lowest priority. From-aircraft data transit delay should not be greater than 28 seconds for the lowest priority data service.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.4 Standard	<i>Data transit delay, to-aircraft, highest priority.</i> To-aircraft data transit delay shall not be greater than 12 seconds for the highest priority data service.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.4.1.2.4.1 Recommendation	Recommendation. — <i>Data transit delay, to-aircraft, lowest priority. To-aircraft data transit delay should not be greater than 28 seconds for the lowest priority data service.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.5 Standard	<i>Data transfer delay (95th percentile), from-aircraft, highest priority. From-aircraft data transfer delay (95th percentile), shall not be greater than 80 seconds for the highest priority data service.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.5.1 Recommendation	Recommendation. — <i>Data transfer delay (95th percentile), from-aircraft, highest priority. From-aircraft data transfer delay (95th percentile), should not be greater than 40 seconds for the highest priority data service.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.5.2 Recommendation	Recommendation. — <i>Data transfer delay (95th percentile), from-aircraft, lowest priority. From-aircraft data transfer delay (95th percentile), should not be greater than 60 seconds for the lowest priority data service.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.6 Standard	<i>Data transfer delay (95th percentile), to-aircraft, highest priority. To-aircraft data transfer delay (95th percentile), shall not be greater than 15 seconds for the highest priority data service.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.4.1.2.6.1 Recommendation	Recommendation. — <i>Data transfer delay (95th percentile), to-aircraft, lowest priority. To-aircraft data transfer delay (95th percentile), should not be greater than 30 seconds for the lowest priority data service.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.7 Standard	<i>Connection release delay (95th percentile).</i> The connection release delay (95th percentile) shall not be greater than 30 seconds in either direction.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.2.7.1 Recommendation	Recommendation. — <i>The connection release delay (95th percentile) should not be greater than 25 seconds in either direction.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.3.1 Standard	4.6.4.1.3 INTEGRITY <i>Residual error rate, from-aircraft.</i> The residual error rate in the from-aircraft direction shall not be greater than 10 ⁻⁴ per SNSDU.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.3.1.1 Recommendation	Recommendation. — <i>The residual error rate in the from-aircraft direction should not be greater than 10⁻⁶ per SNSDU.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.4.1.3.2 Standard	<i>Residual error rate, to-aircraft.</i> The residual error rate in the to-aircraft direction shall not be greater than 10 ⁻⁶ per SNSDU.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.3.3 Standard	<i>Connection resilience.</i> The probability of a subnetwork connection (SNC) provider-invoked SNC release shall not be greater than 10 ⁻⁴ over any one-hour interval. <i>Note.— Connection releases resulting from GES-to-GES handover, AES log-off or virtual circuit pre-emption are excluded from this specification.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.4.1.3.4 Standard	The probability of an SNC provider-invoked reset shall not be greater 10 ⁻¹ over any one-hour interval.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.5.1 Standard	4.6.5 Voice service performance If the system provides AMS(R)S voice service, it shall meet the requirements of the following subparagraphs. <i>Note.— ICAO is currently considering these provisions in the light of the introduction of new technologies.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.5.1.1.1 Standard	<p>4.6.5.1.1 CALL PROCESSING DELAY</p> <p><i>AES origination.</i> The 95th percentile of the time delay for a GES to present a call origination event to the terrestrial network interworking interface after a call origination event has arrived at the AES interface shall not be greater than 20 seconds.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.5.1.1.2 Standard	<p><i>GES origination.</i> The 95th percentile of the time delay for an AES to present a call origination event at its aircraft interface after a call origination event has arrived at the terrestrial network interworking interface shall not be greater than 20 seconds.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.5.1.2.1 Standard	<p>4.6.5.1.2 VOICE QUALITY</p> <p>The voice transmission shall provide overall intelligibility performance suitable for the intended operational and ambient noise environment.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.5.1.2.2 Standard	<p>The total allowable transfer delay within an AMS(R)S subnetwork shall not be greater than 0.485 second.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.5.1.2.3 Recommendation	Recommendation. — <i>Due account should be taken of the effects of tandem vocoders and/or other analog/digital conversions.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.5.1.3.1 Standard	4.6.5.1.3 VOICE CAPACITY The system shall have sufficient available voice traffic channel resources such that an AES- or GES-originated AMS(R)S voice call presented to the system shall experience a probability of blockage of no more than 10 ⁻² . <i>Note.— Available voice traffic channel resources include all pre-emptable resources, including those in use by non-AMS(R)S communications.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.6.1 Standard	4.6.6 Security The system shall provide features for the protection of messages in transit from tampering.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.6.6.2 Standard	The system shall provide features for protection against denial of service, degraded performance characteristics, or reduction of system capacity when subjected to external attacks. <i>Note.— Possible methods of such attack include intentional flooding with spurious messages, intentional corruption of system software or databases, or physical destruction of the support infrastructure.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6.6.3 Standard	The system shall provide features for protection against unauthorized entry. <i>Note.— These features are intended to provide protection against spoofing and “phantom controllers”.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.7.1 Standard	4.7 SYSTEM INTERFACES An AMS(R)S system shall allow subnetwork users to address AMS(R)S communications to specific aircraft by means of the ICAO 24-bit aircraft address. <i>Note.— Provisions on the allocation and assignment of ICAO 24-bit addresses are contained in the Appendix to Chapter 9.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.7.2.1 Standard	4.7.2 Packet data service interfaces If the system provides AMS(R)S packet data service, it shall provide an interface to the ATN. <i>Note.— The detailed technical specifications related to provisions of the ATN-compliant subnetwork service are contained in Section 5.2.5 and Section 5.7.2 of Doc 9880 — Manual on Detailed Technical Specifications for the Aeronautical Telecommunication Network (ATN) (in preparation).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.7.2.2 Standard	If the system provides AMS(R)S packet data service, it shall provide a connectivity notification (CN) function.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	<p style="text-align: center;">CHAPTER 5. SSR MODE S AIR-GROUND DATA LINK</p> <p style="text-align: center;"><i>Note.— The SSR Mode S air-ground data link is also referred to as the Mode S subnetwork in the context of the aeronautical telecommunication network (ATN).</i></p> <p style="text-align: center;">5.1 DEFINITIONS RELATING TO THE MODE S SUBNETWORK</p> <p>Aircraft address. A unique combination of 24 bits available for assignment to an aircraft for the purpose of air-ground communications, navigation and surveillance.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Aircraft. The term aircraft may be used to refer to Mode S emitters (e.g. aircraft/vehicles), where appropriate.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Aircraft data circuit-terminating equipment (ADCE). An aircraft specific data circuit-terminating equipment that is associated with an airborne data link processor (ADLP). It operates a protocol unique to Mode S data link for data transfer between air and ground.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	Aircraft data link processor (ADLP). An aircraft-resident processor that is specific to a particular air-ground data link (e.g. Mode S) and which provides channel management, and segments and/or reassembles messages for transfer. It is connected to one side of aircraft elements common to all data link systems and on the other side to the air-ground link itself.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Aircraft/vehicle. May be used to describe either a machine or device capable of atmospheric flight, or a vehicle on the airport surface movement area (i.e. runways and taxiways).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Air-initiated protocol. A procedure initiated by a Mode S aircraft installation for delivering a standard length or extended length downlink message to the ground.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	BDS Comm-B Data Selector. The 8-bit BDS code determines the register whose contents are to be transferred in the MB field of a Comm-B reply. It is expressed in two groups of 4 bits each, BDS1 (most significant 4 bits) and BDS2 (least significant 4 bits).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	Broadcast. The protocol within the Mode S system that permits uplink messages to be sent to all aircraft in coverage area, and downlink messages to be made available to all interrogators that have the aircraft wishing to send the message under surveillance.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Capability report. Information identifying whether the transponder has a data link capability as reported in the capability (CA) field of an all-call reply or squitter transmission (see “data link capability report”).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Close-out. A command from a Mode S interrogator that terminates a Mode S link layer communication transaction.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Cluster of interrogators. Two or more interrogators with the same interrogator identifier (II) code, operating cooperatively to ensure that there is no interference to the required surveillance and data link performance of each of the interrogators, in areas of common coverage.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Comm-A. A 112-bit interrogation containing the 56-bit MA message field. This field is used by the uplink standard length message (SLM) and broadcast protocols.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	Comm-B. A 112-bit reply containing the 56-bit MB message field. This field is used by the downlink SLM, ground-initiated and broadcast protocols.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Comm-C. A 112-bit interrogation containing the 80-bit MC message field. This field is used by the uplink extended length message (ELM) protocol.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Comm-D. A 112-bit reply containing the 80-bit MD message field. This field is used by the downlink ELM protocol.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Connection. A logical association between peer-level entities in a communication system.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Data link capability report. Information in a Comm-B reply identifying the complete Mode S communications capabilities of the aircraft installation.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	Downlink. A term referring to the transmission of data from an aircraft to the ground. Mode S air-to-ground signals are transmitted on the 1 090 MHz reply frequency channel.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Downlink ELM (DELM). A term referring to extended length downlink communication by means of 112-bit Mode S Comm-D replies, each containing the 80-bit Comm-D message field (MD).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Extended length message (ELM). A series of Comm-C interrogations (uplink ELM) transmitted without the requirement for intervening replies, or a series of Comm-D replies (downlink ELM) transmitted without intervening interrogations.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Frame. The basic unit of transfer at the link level. In the context of Mode S subnetwork, a frame can include from one to four Comm-A or Comm-B segments, from two to sixteen Comm-C segments, or from one to sixteen Comm-D segments.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	General formatter/manager (GFM). The aircraft function responsible for formatting messages to be inserted in the transponder registers. It is also responsible for detecting and handling error conditions such as the loss of input data.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	Ground data circuit-terminating equipment (GDCE). A ground specific data circuit-terminating equipment associated with a ground data link processor (GDLP). It operates a protocol unique to Mode S data link for data transfer between air and ground.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Ground data link processor (GDLP). A ground-resident processor that is specific to a particular air-ground data link (e.g. Mode S), and which provides channel management, and segments and/or reassembles messages for transfer. It is connected on one side (by means of its DCE) to ground elements common to all data link systems, and on the other side to the air-ground link itself.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Ground-initiated Comm-B (GICB). The ground-initiated Comm-B protocol allows the interrogator to extract Comm-B replies containing data from a defined source in the MB field.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Ground-initiated protocol. A procedure initiated by a Mode S interrogator for delivering standard length or extended length messages to a Mode S aircraft installation.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	Mode S air-initiated Comm-B (AICB) protocol. A procedure initiated by a Mode S transponder for transmitting a single Comm-B segment from the aircraft installation.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Mode S broadcast protocols. Procedures allowing standard length uplink or downlink messages to be received by more than one transponder or ground interrogator respectively.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Mode S ground-initiated Comm-B (GICB) protocol. A procedure initiated by a Mode S interrogator for eliciting a single Comm-B segment from a Mode S aircraft installation, incorporating the contents of one of 255 Comm-B registers within the Mode S transponder.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Mode S multisite-directed protocol. A procedure to ensure that extraction and close-out of a downlink standard length or extended length message is affected only by the particular Mode S interrogator selected by the aircraft.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Mode S packet. A packet conforming to the Mode S subnetwork standard, designed to minimize the bandwidth required from the air-ground link. ISO 8208 packets may be transformed into Mode S packets and vice-versa.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	Mode S specific protocol (MSP). A protocol that provides restricted datagram service within the Mode S subnetwork.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Mode S specific services. A set of communication services provided by the Mode S system which are not available from other air-ground subnetworks, and therefore not interoperable.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Mode S specific services entity (SSE). An entity resident within an XDLP to provide access to the Mode S specific services.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Packet. The basic unit of data transfer among communication devices within the network layer, (e.g. an ISO 8208 packet or a Mode S packet).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Segment. A portion of a message that can be accommodated within a single MA/MB field in the case of a standard length message, or MC/MD field in the case of an extended length message. This term is also applied to the Mode S transmissions containing these fields.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	Standard length message (SLM). An exchange of digital data using selectively addressed Comm-A interrogations and/or Comm-B replies (see “Comm-A” and “Comm-B”).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Subnetwork. An actual implementation of a data network that employs a homogeneous protocol and addressing plan, and is under the control of a single authority.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Subnetwork management entity (SNME). An entity resident within a GDLP that performs subnetwork management and communicates with peer entities in intermediate or end-systems.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Timeout. The cancellation of a transaction after one of the participating entities has failed to provide a required response within a pre-defined period of time.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	Uplink. A term referring to the transmission of data from the ground to an aircraft. Mode S ground-to-air signals are transmitted on the 1 030 MHz interrogation frequency channel.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference Definition	<i>Uplink ELM (UELM)</i> . A term referring to extended length uplink communication by means of 112-bit Mode S Comm-C interrogations, each containing the 80-bit Comm-C message field (MC).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	<i>XDCE</i> . A general term referring to both the ADCE and the GDCE.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference Definition	<i>XDLP</i> . A general term referring to both the ADLP and the GDLP.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.1 Standard	<p align="center">5.2 MODE S CHARACTERISTICS</p> <p align="center">5.2.1 General provisions</p> <p><i>N1.Reference ISO document. When the term "ISO 8208" is referred to in this standard, it means the ISO Standard "Information technology — Data communications — X.25 Packet Layer Protocol for Data Terminal Equipment, Reference Number ISO/IEC 8208: 1990(E)".</i></p> <p><i>N2.The overall architecture of the Mode S subnetwork is presented in the diagram on the following page.</i></p> <p><i>N3.The processing splits into three different paths. The first consists of the processing of switched virtual circuits (SVCs), the second consists of the processing of Mode S specific service, and the third consists of the processing of subnetwork management information. SVCs utilize the reformatting process and the ADCE or GDCE function. Mode S specific services utilize the Mode S specific services entity (SSE) function.</i></p> <p><i>Message categories.</i> The Mode S subnetwork shall only carry aeronautical communications classified under categories of flight safety and flight regularity as specified in Annex 10, Volume II, Chapter 5, 5.1.8.4 and 5.1.8.6.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.1.2 Standard	<i>Signals in space.</i> The signal-in-space characteristics of the Mode S subnetwork shall conform to the provisions contained in Annex 10, Volume IV, Chapter 3, 3.1.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.3 Standard	<i>Code and byte independency.</i> The Mode S subnetwork shall be capable of code and byte independent transmission of digital data.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.1.4 Standard	<i>Data transfer.</i> Data shall be conveyed over the Mode S data link in segments using either standard length message (SLM) protocols or extended length message (ELM) protocols as defined in 3.1.2.6.11 and 3.1.2.7 of Annex 10, Volume IV. <i>N1.</i> An SLM segment is the contents of one 56-bit MA or MB field. An ELM segment is the contents of one 80-bit MC or MD field. <i>N2.</i> An SLM frame is the contents of up to four linked MA or MB fields. An ELM frame is the contents of 2 to 16 MC or 1 to 16 MD fields.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.1.5 Standard	<i>Bit numbering.</i> In the description of the data exchange fields, the bits shall be numbered in the order of their transmission, beginning with bit 1. Bit numbers shall continue through the second and higher segments of multi-segment frames. Unless otherwise stated, numerical values encoded by groups (fields) of bits shall be encoded using positive binary notation and the first bit transmitted shall be the most significant bit (MSB) (3.1.2.3.1.3 of Annex 10, Volume IV).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.1.6 Standard	<i>Unassigned bits.</i> When the length of the data is not sufficient to occupy all bit positions within a message field or subfield, the unassigned bit positions shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.1.1 Standard	<p style="text-align: center;">5.2.2 Frames</p> <p style="text-align: center;">5.2.2.1 UPLINK FRAMES</p> <p><i>SLM frame.</i> An uplink SLM frame shall be composed of up to four selectively addressed Comm-A segments.</p> <p><i>Note.— Each Comm-A segment (MA field) received by the ADLP is accompanied by the first 32 bits of the interrogation that delivered the segment (3.1.2.10.5.2.1.1 of Annex 10, Volume IV). Within these 32 bits is the 16-bit special designator (SD) field (3.1.2.6.1.4 of Annex 10, Volume IV).</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.1.1.1 Standard	<p><i>SD field.</i> When the designator identification (DI) field (bits 14-16) has a code value of 1 or 7, the special designator (SD) field (bits 17-32) of each Comm-A interrogation shall be used to obtain the interrogator identifier subfield (IIS, bits 17-20) and the linked Comm-A subfield (<i>LAS</i>, bits 30-32). The action to be taken shall depend on the value of <i>LAS</i>. The contents of <i>LAS</i> and IIS shall be retained and shall be associated with the Comm-A message segment for use in assembling the frame as indicated below. All fields other than the <i>LAS</i> field shall be as defined in 3.1.2 of Annex 10, Volume IV.</p> <p><i>Note.— The SD field structure is shown in Figure 5-1*.</i></p> <p>* All figures and tables are located at the end of this chapter.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																		
Chapter 5 Reference 5.2.2.1.1.2 Standard	<p><i>LAS coding.</i> The 3-bit <i>LAS</i> subfield shall be coded as follows:</p> <table border="0"> <tr> <td style="padding-right: 20px;"><i>LAS</i></td> <td><i>MEANING</i></td> </tr> <tr> <td>0</td> <td>single segment</td> </tr> <tr> <td>1</td> <td>linked, 1st segment</td> </tr> <tr> <td>2</td> <td>linked, 2nd but not final segment</td> </tr> <tr> <td>3</td> <td>linked, 3rd but not final segment</td> </tr> <tr> <td>4</td> <td>linked, 4th and final segment</td> </tr> <tr> <td>5</td> <td>linked, 2nd and final segment</td> </tr> <tr> <td>6</td> <td>linked, 3rd and final segment</td> </tr> <tr> <td>7</td> <td>unassigned</td> </tr> </table>	<i>LAS</i>	<i>MEANING</i>	0	single segment	1	linked, 1st segment	2	linked, 2nd but not final segment	3	linked, 3rd but not final segment	4	linked, 4th and final segment	5	linked, 2nd and final segment	6	linked, 3rd and final segment	7	unassigned	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
<i>LAS</i>	<i>MEANING</i>																						
0	single segment																						
1	linked, 1st segment																						
2	linked, 2nd but not final segment																						
3	linked, 3rd but not final segment																						
4	linked, 4th and final segment																						
5	linked, 2nd and final segment																						
6	linked, 3rd and final segment																						
7	unassigned																						
Chapter 5 Reference 5.2.2.1.1.3 Standard	<p><i>Single segment SLM frame.</i> If <i>LAS</i> = 0, the data in the MA field shall be considered a complete frame and shall be made available for further processing.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde																		
Chapter 5 Reference 5.2.2.1.1.4 Standard	<p><i>Multiple segment SLM frame.</i> The ADLP shall accept and assemble linked 56-bit Comm-A segments associated with all sixteen possible interrogator identifier (II) codes. Correct linking of Comm-A segments shall be achieved by requiring that all Comm-A segments have the same value of IIS. If <i>LAS</i> = 1 through 6, the frame shall consist of two to four Comm-A segments as specified in the following paragraphs.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde																		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.1.1.4.1 Standard	<i>Initial segment.</i> If <i>LAS</i> = 1, the MA field shall be assembled as the initial segment of an SLM frame. The initial segment shall be stored until all segments of the frame have been received or the frame is cancelled.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.1.1.4.2 Standard	<i>Intermediate segment.</i> If <i>LAS</i> = 2 or 3, the MA field shall be assembled in numerical order as an intermediate segment of the SLM frame. It shall be associated with previous segments containing the same value of IIS.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.1.1.4.3 Standard	<i>Final segment.</i> If <i>LAS</i> = 4, 5 or 6, the MA field shall be assembled as the final segment of the SLM frame. It shall be associated with previous segments containing the same value of IIS.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.1.1.4.4 Standard	<i>Frame completion.</i> The frame shall be considered complete and shall be made available for further processing as soon as all segments of the frame have been received.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.1.1.4.5 Standard	<p><i>Frame cancellation.</i> An incomplete SLM frame shall be cancelled if one or more of the following conditions apply:</p> <p>a) a new initial segment (LAS = 1) is received with the same value of IIS. In this case, the new initial segment shall be retained as the initial segment of a new SLM frame;</p> <p>b) the sequence of received LAS codes (after the elimination of duplicates) is not contained in the following list:</p> <ol style="list-style-type: none"> 1) LAS = 0 2) LAS = 1,5 3) LAS = 1,2,6 4) LAS = 1,6,2 5) LAS = 1,2,3,4 6) LAS = 1,3,2,4 7) LAS = 1,2,4,3 8) LAS = 1,3,4,2 9) LAS = 1,4,2,3 10) LAS = 1,4,3,2 <p>c) T_c seconds have elapsed since the last Comm-A segment with the same value of IIS was received (Table 5-1).</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.1.1.4.6 Standard	<p><i>Segment cancellation.</i> A received segment for an SLM frame shall be discarded if it is an intermediate or final segment and no initial segment has been received with the same value of IIS.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.1.1.4.7 Standard	<p><i>Segment duplication.</i> If a received segment duplicates a currently received segment number with the same value of IIS, the new segment shall replace the currently received segment.</p> <p><i>Note.— The action of the Mode S subnetwork protocols may result in the duplicate delivery of Comm-A segments.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.1.2 Standard	<p><i>ELM frame.</i> An uplink ELM frame shall consist of from 20 to 160 bytes and shall be transferred from the interrogator to the transponder using the protocol defined in 3.1.2.7 of Annex 10, Volume IV. The first 4 bits of each uplink ELM segment (MC field) shall contain the interrogator identifier (II) code of the Mode S interrogator transmitting the ELM. The ADLP shall check the II code of each segment of a completed uplink ELM. If all of the segments contain the same II code, the II code in each segment shall be deleted and the remaining message bits retained as user data for further processing. If all of the segments do not contain the same II code, the entire uplink ELM shall be discarded.</p> <p><i>Note.— An uplink ELM frame consists of two to sixteen associated Comm-C segments, each of which contains the 4-bit II code. Therefore, the capacity for packet transfer is 19 to 152 bytes per uplink ELM frame.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
Chapter 5 Reference 5.2.2.1 Standard	<p style="text-align: center;">5.2.2.2 DOWNLINK FRAMES</p> <p><i>SLM frame.</i> A downlink SLM frame shall be composed of up to 4 Comm-B segments. The MB field of the first Comm-B segment of the frame shall contain a 2-bit linked Comm-B subfield (LBS, bits 1 and 2 of the MB field). This subfield shall be used to control linking of up to four Comm-B segments.</p> <p><i>Note.— The LBS uses the first 2-bit positions in the first segment of a multi or single segment downlink SLM frame. Hence, 54 bits are available for Mode S packet data in the first segment of a downlink SLM frame. The remaining segments of the downlink SLM frame, if any, have 56 bits available.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde										
Chapter 5 Reference 5.2.2.1.1 Standard	<p><i>LBS coding.</i> Linking shall be indicated by the coding of the LBS subfield of the MB field of the initial Comm-B segment of the SLM frame.</p> <p>The coding of LBS shall be as follows:</p> <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;"><i>LAS</i></td> <td><i>MEANING</i></td> </tr> <tr> <td>0</td> <td>single segment</td> </tr> <tr> <td>1</td> <td>initial segment of a two-segment SLM frame</td> </tr> <tr> <td>2</td> <td>initial segment of a three-segment SLM frame</td> </tr> <tr> <td>3</td> <td>Initial segment of a four-segment SLM frame</td> </tr> </table>	<i>LAS</i>	<i>MEANING</i>	0	single segment	1	initial segment of a two-segment SLM frame	2	initial segment of a three-segment SLM frame	3	Initial segment of a four-segment SLM frame	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
<i>LAS</i>	<i>MEANING</i>														
0	single segment														
1	initial segment of a two-segment SLM frame														
2	initial segment of a three-segment SLM frame														
3	Initial segment of a four-segment SLM frame														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.2.1.2.1 Standard	5.2.2.2.1.2 <i>Linking protocol</i> In the Comm-B protocol, the initial segment shall be transmitted using the air-initiated or multisite-directed protocols. The LBS field of the initial segment shall indicate to the ground the number of additional segments to be transferred (if any). Before the transmission of the initial segment to the transponder, the remaining segments of the SLM frame (if any) shall be transferred to the transponder for transmission to the interrogator using the ground-initiated Comm-B protocol. These segments shall be accompanied by control codes that cause the segments to be inserted in ground-initiated Comm-B registers 2, 3 or 4, associated respectively with the second, third, or fourth segment of the frame.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.2.1.2.2 Standard	Close-out of the air-initiated segment that initiated the protocol shall not be performed until all segments have been successfully transferred. <i>Note.— The linking procedure including the use of the ground-initiated Comm-B protocol is performed by the ADLP.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.2.1.3 Standard	<i>Directing SLM frames.</i> If the SLM frame is to be multisite-directed, the ADLP shall determine the II code of the Mode S interrogator or cluster of interrogators (5.2.8.1.3) that shall receive the SLM frame.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.2.2.1 Standard	<p>5.2.2.2.2 <i>ELM FRAME</i></p> <p><i>Note.— A downlink ELM consists of one to sixteen associated Comm-D segments.</i></p> <p><i>Procedure.</i> Downlink ELM frames shall be used to deliver messages greater than or equal to 28 bytes and shall be formed using the protocol defined in 3.1.2.7 of Annex 10, Volume IV.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.2.2.2 Standard	<p><i>Directing ELM frames.</i> If the ELM frame is to be multisite-directed, the ADLP shall determine the II code of the Mode S interrogator or cluster of interrogators (5.2.8.1.3) that shall receive the ELM frame.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.3 Standard	<p><i>XDLP frame processing.</i> Frame processing shall be performed on all Mode S packets (except for the MSP packet) as specified in 5.2.2.3 to 5.2.2.5. Frame processing for Mode S specific services shall be performed as specified in 5.2.7.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.3.1 Standard	<p><i>Packet length.</i> All packets (including a group of packets multiplexed into a single frame) shall be transferred in a frame consisting of the smallest number of segments needed to accommodate the packet. The user data field shall be an integral multiple of bytes in length. A 4-bit parameter (LV) shall be provided in the Mode S DATA, CALL REQUEST, CALL ACCEPT, CLEAR REQUEST and INTERRUPT packet headers so that during unpacking no additional bytes are added to the user data field. The LV field shall define the number of full bytes used in the last segment of a frame. During LV calculations, the 4-bit II code in the last segment of an uplink ELM message shall be (1) ignored for uplink ELM frames with an odd number of Comm-C segments and (2) counted for uplink ELM frames with an even number of Comm-C segments. The value contained in the LV field shall be ignored if the packet is multiplexed.</p> <p><i>Note.— A specific length field is used to define the length of each element of a multiplexed packet. Therefore the LV field value is not used. LV field error handling is described in Tables 5-16 and 5-19.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.3.2 Standard	<p><i>Multiplexing.</i> When multiplexing multiple Mode S packets into single SLM on ELM frame, the following procedures shall be used. Multiplexing of the packets within the ADLP shall not be applied to packets associated with SVCs of different priorities.</p> <p><i>Note.— Multiplexing is not performed on MSP packets.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.3.2.1 Recommendation	<p><i>Multiplexing optimization</i></p> <p>Recommendation.— <i>When multiple packets are awaiting transfer to the same XDLP, they should be multiplexed into a single frame in order to optimize throughput, provided that packets associated with SVCs of different priorities are not multiplexed together.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference								
Chapter 5 Reference 5.2.2.3.2.2 Standard	<p><i>Structure.</i> The structure of the multiplexed packets shall be as follows:</p> <table border="0" style="margin-left: 40px;"> <tr> <td>HEADER:6 OR 8</td> <td>LENGTH:8</td> <td>1ST PACKET:v</td> </tr> <tr> <td></td> <td>LENGTH:8</td> <td>2ND PACKET:v</td> </tr> </table> <p><i>Note.— A number in the field signifies the field length in bits; "v" signifies that the field is of variable length.</i></p>	HEADER:6 OR 8	LENGTH:8	1ST PACKET:v		LENGTH:8	2ND PACKET:v	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde		
HEADER:6 OR 8	LENGTH:8	1ST PACKET:v											
	LENGTH:8	2ND PACKET:v											
Chapter 5 Reference 5.2.2.3.2.2.1 Standard	<p><i>Multiplexing header.</i> The header for the multiplexed packets shall be as follows:</p> <table border="0" style="margin-left: 40px;"> <tr> <td>DP:1</td> <td>MP:1</td> <td>SP:2</td> <td>ST:2</td> </tr> <tr> <td colspan="4" style="text-align: center;">FILL2:0 OR 2</td> </tr> </table> <p>Where, <i>Data packet type (DP) = 0</i> <i>MSP packet type (MP) = 1</i> <i>Supervisory packet (SP) = 3</i> <i>Supervisory type (ST) = 2</i> <i>Note.— See Figure 5-23 for a definition for the field structure used in the multiplexing header.</i></p>	DP:1	MP:1	SP:2	ST:2	FILL2:0 OR 2				CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
DP:1	MP:1	SP:2	ST:2										
FILL2:0 OR 2													
Chapter 5 Reference 5.2.2.3.2.2.2 Standard	<p><i>Length.</i> This field shall contain the length of the following packet in bytes. Any error detected in a multiplexed DATA packet, such as inconsistency between length as indicated in the LENGTH field and the length of the frame hosting that packet, shall result in the discarding of the packet unless the error can be determined to be limited to the LENGTH field, in which case a REJECT packet with the expected PS value can be sent.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde								



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.3.2.2.1 Recommendation	Recommendation. — <i>For multiplex packets, if the entire packet cannot be de-multiplexed, then the first constituent packet should be treated as a format error, and the remainder be discarded.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.3.2.3 Standard	<i>Termination.</i> The end of a frame containing a sequence of multiplexed packets shall be determined by one of the following events: a) a length field of all zeros; or b) less than eight bits left in the frame	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.3.3.1 Standard	5.2.2.3.3 <i>MODE S CHANNEL SEQUENCE PRESERVATION</i> <i>Application.</i> In the event that multiple Mode S frames from the same SVC are awaiting transfer to the same XDLP, the following procedure shall be used.	CV CAR 19, 19.B.230, (a),(1)	No Difference		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.3.3.2.1 Standard	5.2.2.3.3.2 <i>Procedure</i> <i>N1.SLM and ELM transactions can occur independently.</i> <i>N2.Uplink and downlink transactions can occur independently.</i> <i>SLM frames.</i> SLM frames awaiting transfer shall be transmitted in the order received.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.3.3.2.2 Standard	<i>ELM frames.</i> ELM frames awaiting transfer shall be transmitted in the order received.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.4.1.1 Standard	5.2.2.4 GDLP FRAME PROCESSING 5.2.2.4.1 GENERAL PROVISIONS The GDLP shall determine the data link capability of the ADLP/transponder installation from the data link capability report (5.2.9) before performing any data link activity with that ADLP.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.4.1.2 Standard	GDLP frame processing shall provide to the interrogator all data for the uplink transmission that are not provided directly by the interrogator.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.4.2 Standard	<i>Delivery status.</i> GDLP frame processing shall accept an indication from the interrogator function that a specified uplink frame that was previously transferred to the interrogator has been successfully delivered over the ground-to-air link.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.4.3 Standard	<i>Aircraft address.</i> GDLP frame processing shall receive from the interrogator along with the data in each downlink SLM or ELM frame, the 24-bit address of the aircraft that transmitted the frame. GDLP frame processing shall be capable of transferring to the interrogator the 24-bit address of the aircraft that is to receive an uplink SLM or ELM frame.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.4.4 Standard	<i>Mode S protocol type identification.</i> GDLP frame processing shall indicate to the interrogator the protocol to be used to transfer the frame: standard length message protocol, extended length message protocol or broadcast protocol.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.4.5 Standard	<i>Frame determination.</i> A Mode S packet (including multiplexed packets but excluding MSP packets) intended for uplink and less than or equal to 28 bytes shall be sent as an SLM frame. A Mode S packet greater than 28 bytes shall be sent as an uplink ELM frame for transponders with ELM capability, using M-bit processing as necessary (5.2.5.1.4.1). If the transponder does not have ELM capability, packets greater than 28 bytes shall be sent using the M-bit or S-bit (5.2.5.1.4.2) assembly procedures as necessary and multiple SLM frames. <i>Note.— The Mode S DATA, CALL REQUEST, CALL ACCEPT, CLEAR REQUEST and INTERRUPT packets are the only Mode S packets that use M-bit or S-bit sequencing.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.5.1 Standard	5.2.2.5 ADLP FRAME PROCESSING <i>General provisions.</i> With the possible exception of the last 24 bits (address/parity), ADLP frame processing shall accept from the transponder the entire content of both 56-bit and 112-bit received uplink transmissions, excluding all-call and ACAS interrogations. ADLP frame processing shall provide to the transponder all data for the downlink transmission that is not provided directly by the transponder (5.2.3.3).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.5.2 Standard	<i>Delivery status.</i> ADLP frame processing shall accept an indication from the transponder that a specified downlink frame that was previously transferred to the transponder has been closed out.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.5.3 Standard	<i>Interrogator identifier.</i> ADLP frame processing shall accept from the transponder, along with the data in each uplink SLM and ELM, the interrogator identifier (II) code of the interrogator that transmitted the frame. ADLP frame processing shall transfer to the transponder the II code of the interrogator or cluster of interrogators that shall receive a multisite-directed frame.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.5.4 Standard	<i>Mode S protocol type identification.</i> ADLP frame processing shall indicate to the transponder the protocol to be used to transfer the frame: ground-initiated, air-initiated, broadcast, multisite-directed, standard length or extended length.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.5.5 Standard	<i>Frame cancellation.</i> ADLP frame processing shall be capable of cancelling downlink frames previously transferred to the transponder for transmission but for which a close-out has not been indicated. If more than one frame is stored within the transponder, the cancellation procedure shall be capable of cancelling the stored frames selectively.	CV CAR 19, 19.B.230, (a),(1)	No Difference		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.5.6 Standard	<i>Frame determination.</i> A Mode S packet (including multiplexed packets but excluding MSP packets) intended for downlink and less than or equal to 222 bits shall be sent as an SLM frame. A Mode S packet greater than 222 bits shall be sent as a downlink ELM frame for transponders with ELM capability using M-bit processing as necessary (5.2.5.1.4.1). When M-bit processing is used, all ELM frames containing M = 1 shall contain the maximum number of ELM segments that the transponder is capable of transmitting in response to one requesting interrogation (UF = 24) (5.2.9.1). If the transponder does not have ELM capability, packets greater than 222 bits shall be sent using the M-bit or S-bit (5.2.5.1.4.2) assembly procedures and multiple SLM frames. <i>Note.— The maximum length of a downlink SLM frame is 222 bits. This is equal to 28 bytes (7 bytes for 4 Comm-B segments) minus the 2-bit linked Comm-B subfield (5.2.2.2.1.1).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		Not used in Cabo Verde
Chapter 5 Reference 5.2.2.6.1 Standard	5.2.2.6 PRIORITY MANAGEMENT <i>ADLP priority management.</i> Frames shall be transferred from the ADLP to the transponder in the following order of priority (highest first): a) Mode S specific services; b) search requests (5.2.8.1); c) frames containing only high priority SVC packets; and d) frames containing only low priority SVC packets.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.6.2 Recommendation	<p><i>GDL PRIORITY MANAGEMENT</i></p> <p>Recommendation.— <i>Uplink frames should be transferred in the following order of priority (highest first):</i></p> <ul style="list-style-type: none"> a) <i>Mode S specific services;</i> b) <i>frames containing at least one Mode S ROUTE packet (5.2.8.1);</i> c) <i>frames containing at least one high priority SVC packet; and</i> d) <i>frames containing only low priority SVC packets.</i> 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.1.1 Standard	<p style="text-align: center;">5.2.3 Data exchange interfaces</p> <p style="text-align: center;">5.2.3.1 THE DTE ISO 8208 INTERFACE</p> <p><i>General provisions.</i> The interface between the XDLP and the DTE(s) shall conform to ISO 8208 packet layer protocol (PLP). The XDLP shall support the procedures of the DTE as specified in ISO 8208. As such, the XDLP shall contain a DCE (5.2.4).</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.1.2 Standard	<p><i>Physical and link layer requirements for the DTE/DCE interface.</i> The requirements are:</p> <ul style="list-style-type: none"> a) the interface shall be code and byte independent and shall not impose restrictions on the sequence, order, or pattern of the bits transferred within a packet; and b) the interface shall support the transfer of variable length network layer packets. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.1.3.1 Standard	<p>5.2.3.1.3 DTE ADDRESS</p> <p><i>Ground DTE address.</i> The ground DTE address shall have a total length of 3 binary coded decimal (BCD) digits, as follows:</p> <p style="text-align: center;">$X_0X_1X_2$</p> <p>X_0 shall be the most significant digit. Ground DTE addresses shall be decimal numbers in the range of 0 through 255 coded in BCD. Assignment of the DTE address shall be a local issue. All DTEs connected to GDLPs having overlapping coverage shall have unique addresses. GDLPs which have a flying time less than T_r (Table 5-1) between their coverage areas shall be regarded as having overlapping coverage.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.1.3.2 Standard	<p><i>Mobile DTE address.</i> The mobile DTE address shall have a total length of 10 BCD digits, as follows:</p> <p style="text-align: center;">$X_0X_1X_2X_3X_4X_5X_6X_7X_8X_9$</p> <p>$X_0$ shall be the most significant digit. The digits X_0 to X_7 shall contain the octal representation of the aircraft address coded in BCD. The digits X_8X_9 shall identify a sub-address for specific DTEs on board an aircraft. This sub-address shall be a decimal number in the range of 0 and 15 coded in BCD. The following sub-address assignments shall be used:</p> <p style="margin-left: 40px;">00 ATN router</p> <p style="margin-left: 40px;">01 to 15 Unassigned</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.1.3.3 Standard	<p><i>Illegal DTE addresses.</i> DTE addresses outside of the defined ranges or not conforming to the formats for the ground and mobile DTE addresses specified in 5.2.3.1.3.1 and 5.2.3.1.3.2 shall be defined to be illegal DTE addresses. The detection of an illegal DTE address in a CALL REQUEST packet shall lead to a rejection of the call as specified in 5.2.5.1.5.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.1.4.1 Standard	<p>5.2.3.1.4 <i>PACKET LAYER PROTOCOL REQUIREMENTS OF THE DTE/DCE INTERFACE</i></p> <p><i>Capabilities.</i> The interface between the DTE and the DCE shall conform to ISO 8208 with the following capabilities:</p> <ul style="list-style-type: none"> a) expedited data delivery, i.e. the use of INTERRUPT packets with a user data field of up to 32 bytes; b) priority facility (with two levels, 5.2.5.2.1.1.6); c) fast select (5.2.5.2.1.1.13, 5.2.5.2.1.1.16); and d) called/calling address extension facility, if required by local conditions (i.e. the XDLP is connected to the DTE via a network protocol that is unable to contain the Mode S address as defined). <p>Other ISO 8208 facilities and the D-bit and the Q-bit shall not be invoked for transfer over the Mode S packet layer protocol.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.1.4.2 Standard	<p><i>Parameter values.</i> The timer and counter parameters for the DTE/DCE interface shall conform to the default ISO 8208 values.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.2.1.1 Standard	<p>5.2.3.2 <i>MODE S SPECIFIC SERVICES INTERFACE</i></p> <p><i>Note.—Mode S specific services consist of the broadcast Comm-A and Comm-B, GICB and MSP.</i></p> <p>5.2.3.2.1 <i>ADLP</i></p> <p><i>General provisions.</i> The ADLP shall support the accessing of Mode S specific services through the provision of one or more separate ADLP interfaces for this purpose.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.2.1.2 Standard	<i>Functional capability.</i> Message and control coding via this interface shall support all of the capabilities specified in 5.2.7.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.2.2.1 Standard	5.2.3.2.2 <i>GDLP</i> <i>General provisions.</i> The GDLP shall support the accessing of Mode S specific services through the provision of a separate GDLP interface for this purpose and/or by providing access to these services through the DTE/DCE interface.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.2.2.2 Standard	<i>Functional capability.</i> Message and control coding via this interface shall support all of the capabilities specified in 5.2.7.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.3.1.1 Standard	<p>5.2.3.3 ADLP/TRANSPONDER INTERFACE</p> <p>5.2.3.3.1 TRANSPONDER TO ADLP</p> <p>The ADLP shall accept an indication of protocol type from the transponder in connection with data transferred from the transponder to the ADLP. This shall include the following types of protocols:</p> <ul style="list-style-type: none"> a) surveillance interrogation; b) Comm-A interrogation; c) Comm-A broadcast interrogation; and d) uplink ELM. <p>The ADLP shall also accept the II code of the interrogator used to transmit the surveillance, Comm-A or uplink ELM.</p> <p><i>Note.— Transponders will not output all-call and ACAS information on this interface.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.3.1.2 Standard	<p>The ADLP shall accept control information from the transponder indicating the status of downlink transfers. This shall include:</p> <ul style="list-style-type: none"> a) Comm-B close-out; b) Comm-B broadcast timeout; and c) downlink ELM close-out. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.3.1.3 Standard	<p>The ADLP shall have access to current information defining the communication capability of the Mode S transponder with which it is operating. This information shall be used to generate the data link capability report (5.2.9).</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.3.2.1 Standard	<p>5.2.3.3.2 <i>ADLP TO TRANSPONDER</i></p> <p>The ADLP shall provide an indication of protocol type to the transponder in connection with data transferred from the ADLP to the transponder. This shall include the following types of protocols:</p> <ul style="list-style-type: none"> a) ground-initiated Comm-B; b) air-initiated Comm-B; c) multisite-directed Comm-B; d) Comm-B broadcast; e) downlink ELM; and f) multisite-directed downlink ELM. <p>The ADLP shall also provide the II code for transfer of a multisite-directed Comm-B or downlink ELM and the Comm-B data selector (BDS) code (3.1.2.6.11.2 of Annex 10, Volume IV) for a ground-initiated Comm-B.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.3.2.2 Standard	The ADLP shall be able to perform frame cancellation as specified in 5.2.2.5.5.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.4.1.1 Standard	5.2.3.4 GDLP/MODE S INTERROGATOR INTERFACE <i>5.2.3.4.1 INTERROGATOR TO GDLP</i> The GDLP shall accept an indication of protocol type from the interrogator in connection with data transferred from the interrogator to the GDLP. This shall include the following types of protocols: <ul style="list-style-type: none"> a) ground-initiated Comm-B; b) air-initiated Comm-B; c) air-initiated Comm-B broadcast; and d) downlink ELM. The GDLP shall also accept the BDS code used to identify the ground-initiated Comm-B segment.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.4.1.2 Standard	The GDLP shall accept control information from the interrogator indicating the status of uplink transfers and the status of the addressed Mode S aircraft.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.3.4.2 Standard	<i>GDLP to interrogator.</i> The GDLP shall provide an indication of protocol type to the interrogator in connection with data transferred from the GDLP to the interrogator. This shall include the following types of protocols: <ul style="list-style-type: none"> a) Comm-A interrogation; b) Comm-A broadcast interrogation; c) uplink ELM; and d) ground-initiated Comm-B request. The GDLP shall also provide the BDS code for the ground-initiated Comm-B protocol.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.1 Standard	<p style="text-align: center;">5.2.4 DCE operation</p> <p><i>Note.— The DCE process within the XDLP acts as a peer process to the DTE. The DCE supports the operations of the DTE with the capability specified in 5.2.3.1.4. The following requirements do not specify format definitions and flow control on the DTE/DCE interface. The specifications and definitions in ISO 8208 apply for these cases.</i></p> <p><i>State transitions.</i> The DCE shall operate as a state machine. Upon entering a state, the DCE shall perform the actions specified in Table 5-2. State transitions and additional action(s) shall be as specified in Table 5-3 through Table 5-12.</p> <p><i>Note.— The next state transition (if any) that occurs when the DCE receives a packet from the DTE is specified by Table 5-3 through Table 5-8. These tables are organized according to the hierarchy illustrated in Figure 5-2. The same transitions are defined in Table 5-9 through Table 5-12 when the DCE receives a packet from the XDCE (via the reformatting process).</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.4.2.1 Standard	<p style="text-align: center;">5.2.4.2 DISPOSITION OF PACKETS</p> <p>Upon receipt of a packet from the DTE, the packet shall be forwarded or not forwarded to the XDCE (via the reformatting process) according to the parenthetical instructions contained in Tables 5-3 to 5-8. If no parenthetical instruction is listed or if the parenthetical instruction indicates “do not forward”, the packet shall be discarded.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.2.2 Standard	Upon receipt of a packet from the XDCE (via the reformatting process), the packet shall be forwarded or not forwarded to the DTE according to the parenthetical instructions contained in Tables 5-9 to 5-12. If no parenthetical instruction is listed or if the parenthetical instruction indicates "do not forward", the packet shall be discarded.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.1.1.1 Standard	<p style="text-align: center;">5.2.5 Mode S packet layer processing</p> <p style="text-align: center;">5.2.5.1 GENERAL REQUIREMENTS</p> <p style="text-align: center;"><i>5.2.5.1.1 BUFFER REQUIREMENTS</i></p> <p style="text-align: center;"><i>5.2.5.1.1.1 ADLP buffer requirements</i></p> <p>The following requirements apply to the entire ADLP and shall be interpreted as necessary for each of the main processes (DCE, reformatting, ADCE, frame processing and SSE).</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.1.1.1.2 Standard	<p>The ADLP shall be capable of maintaining sufficient buffer space for fifteen SVCs:</p> <ul style="list-style-type: none"> a) maintain sufficient buffer space to hold fifteen Mode S subnetwork packets of 152 bytes each in the uplink direction per SVC for a transponder with uplink ELM capability or 28 bytes otherwise; b) maintain sufficient buffer space to hold fifteen Mode S subnetwork packets of 160 bytes each in the downlink direction per SVC for a transponder with downlink ELM capability or 28 bytes otherwise; c) maintain sufficient buffer space for two Mode S subnetwork INTERRUPT packets of 35 bytes each, (user data field plus control information), one in each direction, for each SVC; d) maintain sufficient resequencing buffer space for storing thirty-one Mode S subnetwork packets of 152 bytes each in the uplink direction per SVC for a transponder with uplink ELM capability or 28 bytes otherwise; and e) maintain sufficient buffer space for the temporary storage of at least one Mode S packet of 160 bytes undergoing M-bit or S-bit processing in each direction per SVC. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.1.1.3 Standard	The ADLP shall be capable of maintaining a buffer of 1 600 bytes in each direction to be shared among all MSPs.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.1.1.2.1 Recommendation	5.2.5.1.1.2 <i>GDLP buffer requirements</i> Recommendation. — <i>The GDLP should be capable of maintaining sufficient buffer space for an average of 4 SVCs for each Mode S aircraft in the coverage area of the interrogators connected to it, assuming all aircraft have ELM capability.</i> <i>Note.</i> — <i>Additional buffer space may be required if DTEs associated with end-systems are supported.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.2.1 Standard	5.2.5.1.2 <i>CHANNEL NUMBER POOLS</i> The XDLP shall maintain several SVC channel number pools; the DTE/DCE (ISO 8208) interface uses one set. Its organization, structure and use shall be as defined in the ISO 8208 standard. The other channel pools shall be used on the ADCE/GDCE interface.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.2.2 Standard	The GDLP shall manage a pool of temporary channel numbers in the range of 1 to 3, for each ground DTE/ADLP pair. Mode S CALL REQUEST packets generated by the GDLP shall contain the ground DTE address and a temporary channel number allocated from the pool of that ground DTE. The GDLP shall not reuse a temporary channel number allocated to an SVC that is still in the CALL REQUEST state. <i>N1.The use of temporary channel numbers allows the GDLP to have up to three call requests in process at the same time for a particular ground DTE and ADLP combination. It also allows the GDLP or ADLP to clear a channel before the permanent channel number is assigned.</i> <i>N2.The ADLP may be in contact with multiple ground DTEs at any one time. All the ground DTEs use temporary channel numbers ranging from 1 to 3.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.1.2.3 Standard	<p>The ADLP shall use the ground DTE address to distinguish the temporary channel numbers used by the various ground DTEs. The ADLP shall assign a permanent channel number (in the range of 1 to 15) to all SVCs and shall inform the GDLP of the assigned number by including it in the Mode S CALL REQUEST by ADLP or Mode S CALL ACCEPT by ADLP packets. The temporary channel number shall be included in the Mode S CALL ACCEPT by ADLP together with the permanent channel number in order to define the association of these channel numbers. The ADLP shall continue to associate the temporary channel number with the permanent channel number of an SVC until the SVC is returned to the READY (p1) state, or else, while in the DATA TRANSFER (p4) state, a Mode S CALL REQUEST by GDLP packet is received bearing the same temporary channel number. A non-zero permanent channel number in the Mode S CLEAR REQUEST by ADLP, CLEAR REQUEST by GDLP, CLEAR CONFIRMATION by ADLP or CLEAR CONFIRMATION by GDLP packet shall indicate that the permanent channel number shall be used and the temporary channel number shall be ignored. In the event that an XDLP is required to send one of these packets in the absence of a permanent channel number, the permanent channel number shall be set to zero, which shall indicate to the peer XDLP that the temporary channel number is to be used.</p> <p><i>Note.— The use of a zero permanent channel number allows the ADLP to clear an SVC when no permanent channel number is available, and allows the GDLP to do likewise before it has been informed of the permanent channel number.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.1.2.4 Standard	The channel number used by the DTE/DCE interface and that used by the ADCE/GDCE interface shall be assigned independently. The reformatting process shall maintain an association table between the DTE/DCE and the ADCE/GDCE channel numbers.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.3 Standard	<i>Receive ready and receive not ready conditions.</i> The ISO 8208 interface and the ADCE/GDCE interface management procedures shall be independent operations since each system must be able to respond to separate receive ready and receive not ready indications.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.4.1.1 Standard	<p><i>5.2.5.1.4 PROCESSING OF M-BIT AND S-BIT SEQUENCES</i></p> <p><i>Note.— M-bit processing applies to the sequencing of the DATA packet. S-bit processing applies to the sequencing of Mode S CALL REQUEST, CALL ACCEPT, CLEAR REQUEST and INTERRUPT packets.</i></p> <p><i>5.2.5.1.4.1 M-bit processing</i></p> <p><i>Note.— The packet size used on the DTE/DCE interface can be different from that used on the ADCE/GDCE interface.</i></p> <p>M-bit processing shall be used when DATA packets are reformatted (5.2.5.2). M-bit processing shall utilize the specifications contained in the ISO 8208 standard. The M-bit sequence processing shall apply on a per channel basis. The M-bit set to 1 shall indicate that a user data field continues in the subsequent DATA packet. Subsequent packets in an M-bit sequence shall use the same header format (i.e. the packet format excluding the user data field).</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.1.4.1.2 Standard	If the packet size for the XDCE (5.2.6.4.2) interface is larger than that used on the DTE/DCE interface, packets shall be combined to the extent possible as dictated by the M-bit, when transmitting a Mode S DATA packet. If the packet size is smaller on the XDCE interface than that defined on the DTE/DCE interface, packets shall be fragmented to fit into the smaller Mode S packet using M-bit assembly.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.4.1.3 Standard	A packet shall be combined with subsequent packets if the packet is filled and more packets exist in the M-bit sequence (M-bit = 1). A packet smaller than the maximum packet size defined for this SVC (partial packet) shall only be allowed when the M-bit indicates the end of an M-bit sequence. A received packet smaller than the maximum packet size with M-bit equal to 1 shall cause a reset to be generated as specified in ISO 8208 and the remainder of the sequence should be discarded.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.4.1.4 Recommendation	Recommendation. — <i>In order to decrease delivery delay, reformatting should be performed on the partial receipt of an M-bit sequence, rather than delay reformatting until the complete M-bit sequence is received.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.1.4.2 Standard	<i>S-bit processing.</i> S-bit processing shall apply only to Mode S CALL REQUEST, CALL ACCEPT, CLEAR REQUEST and INTERRUPT packets. This processing shall be performed as specified for M-bit processing (5.2.5.1.4.1) except that the packets associated with any S-bit sequence whose reassembly is not completed in <i>Tq</i> seconds (Tables 5-1 and 5-13) shall be discarded (5.2.6.3.6, 5.2.6.4.5.2 and 5.2.6.9), and receipt of a packet shorter than the maximum packet size with <i>S</i> = 1 shall cause the entire S-bit sequence to be treated as a format error in accordance with Table 5-16.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.5.1 Standard	<i>5.2.5.1.5 MODE S SUBNETWORK ERROR PROCESSING FOR ISO 8208 PACKETS</i> <i>D-bit.</i> If the XDLP receives a DATA packet with the D-bit set to 1, the XDLP shall send a RESET REQUEST packet to the originating DTE containing a cause code (<i>CC</i>) = 133 and a diagnostic code (<i>DC</i>) = 166. If the D-bit is set to 1 in a CALL REQUEST packet, the D-bit shall be ignored by the XDLP. The D-bit of the corresponding CALL ACCEPT packet shall always be set to 0. The use of <i>CC</i> is optional.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.5.2 Standard	<i>Q-bit.</i> If the XDLP receives a DATA packet with the Q-bit set to 1, the XDLP shall send a RESET REQUEST packet to the originating DTE containing <i>CC</i> = 133 and <i>DC</i> = 83. The use of <i>CC</i> is optional.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.1.5.3 Standard	<i>Invalid priority.</i> If the XDLP receives a call request with a connection priority value equal to 2 through 254, the XDLP shall clear the virtual circuit using <i>DC</i> = 66 and <i>CC</i> = 131. The use of <i>CC</i> is optional.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.5.4 Standard	<i>Unsupported facility.</i> If the XDLP receives a call request with a request for a facility that it cannot support, the XDLP shall clear the virtual circuit using <i>DC</i> = 65 and <i>CC</i> = 131. The use of <i>CC</i> is optional.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.5.5 Standard	<i>Illegal calling DTE address.</i> If the XDLP receives a call request with an illegal calling DTE address (5.2.3.1.3.3), the XDLP shall clear the virtual circuit using <i>DC</i> = 68 and <i>CC</i> = 141. The use of <i>CC</i> is optional.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.1.5.6 Standard	<i>Illegal called DTE address.</i> If the XDLP receives a call request with an illegal called DTE address (5.2.3.1.3.3), the XDLP shall clear the virtual circuit using <i>DC</i> = 67 and <i>CC</i> = 141. The use of <i>CC</i> is optional.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.1.1.1 Standard	<p>5.2.5.2 REFORMATTING PROCESS</p> <p><i>Note.— The reformatting process is divided into two subprocesses: uplink formatting and downlink formatting. For the ADLP, the uplink process of reformats Mode S packets into ISO 8208 packets and the downlink process reformats ISO 8208 packets into Mode S packets. For the GDLP, the uplink process reformats ISO 8208 packets into Mode S packets and the downlink process reformats Mode S packets into ISO 8208 packets.</i></p> <p>5.2.5.2.1 CALL REQUEST BY ADLP</p> <p>5.2.5.2.1.1 Translation into Mode S packets</p> <p><i>Translated packet format.</i> Reception by the ADLP reformatting process of an ISO 8208 CALL REQUEST packet from the local DCE shall result in the generation of corresponding Mode S CALL REQUEST by ADLP packet(s) (as determined by S-bit processing (5.2.5.1.4.2)) as follows:</p> <p>DP:1 MP:1 SP:2 ST:2 FILL2:0 or 2 P:1 FILL:1 SN:6 CH:4 AM:4 AG:8 S:1 FS:2 F:1 LV:4 UD:v</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.2 Standard	<i>Data packet type (DP).</i> This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.1.1.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.6 Standard	<i>Priority (P)</i> . This field shall be set to 0 for a low priority SVC and to 1 for a high priority SVC. The value for this field shall be obtained from the data transfer field of the priority facility of the ISO 8208 packet, and shall be set to 0 if the ISO 8208 packet does not contain the priority facility or if a priority of 255 is specified. The other fields of the priority facility shall be ignored.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.1.1.7 Standard	<i>Sequence number (SN).</i> For a particular SVC, each packet shall be numbered (5.2.6.9.4).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.8 Standard	<i>Channel number (CH).</i> The channel number shall be chosen from the pool of SVC channel numbers available to the ADLP. The pool shall consist of 15 values from 1 through 15. The highest available channel number shall be chosen from the pool. An available channel shall be defined as one in state <i>p1</i> . The correspondence between the channel number used by the Mode S subnetwork and the number used by the DTE/DCE interface shall be maintained while the channel is active. <i>Note.— Also refer to 5.2.5.1.2 on channel pool management.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.9 Standard	<i>Address, mobile (AM).</i> This address shall be the mobile DTE sub-address (5.2.3.1.3.2) in the range of 0 to 15. The address shall be extracted from the two least significant digits of the calling DTE address contained in the ISO 8208 packet and converted to binary representation. <i>Note.— The 24-bit aircraft address is transferred within the Mode S link layer.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.10 Standard	<i>Address, ground (AG).</i> This address shall be the ground DTE address (5.2.3.1.3.1) in the range of 0 to 255. The address shall be extracted from the called DTE address contained in the ISO 8208 packet and converted to binary representation.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.1.1.11 Standard	<i>Fill field.</i> The fill field shall be used to align subsequent data fields on byte boundaries. When indicated as "FILL:n", the fill field shall be set to a length of "n" bits. When indicated as "FILL1: 0 or 6", the fill field shall be set to a length of 6 bits for a non-multiplexed packet in a downlink SLM frame and 0 bit for all other cases. When indicated as "FILL2: 0 or 2", the fill field shall be set to a length of 0 bit for a non-multiplexed packet in a downlink SLM frame or for a multiplexing header and 2 bits for all other cases.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.12 Standard	<i>S field (S).</i> A value of 1 shall indicate that the packet is part of an S-bit sequence with more packets in the sequence to follow. A value of 0 shall indicate that the sequence ends with this packet. This field shall be set as specified in 5.2.5.1.4.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.13 Standard	<i>FS field (FS).</i> A value of 0 shall indicate that the packet does not contain fast select data. A value of 2 or 3 shall indicate that the packet contains fast select data. A value of 2 shall indicate normal fast select operation. A value of 3 shall indicate fast select with restricted response. An FS value of 1 shall be undefined.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.14 Standard	<i>First packet flag (F).</i> This field shall be set to 0 in the first packet of an S-bit sequence and in a packet that is not part of an S-bit sequence. Otherwise it shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.1.1.15 Standard	<i>User data length (LV)</i> . This field shall indicate the number of full bytes used in the last SLM or ELM segment as defined in 5.2.2.3.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.1.16 Standard	<i>User data field (UD)</i> . This field shall only be present if optional CALL REQUEST user data (maximum 16 bytes) or fast select user data (maximum 128 bytes) is contained in the ISO 8208 packet. The user data field shall be transferred from ISO 8208 packet unchanged using S-bit processing as specified in 5.2.5.1.4.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.2.1 Standard	<i>5.2.5.2.1.2 Translation into ISO 8208 packets</i> <i>Translation</i> . Reception by the GDLP reformat-ting process of a Mode S CALL REQUEST by ADLP packet (or an S-bit sequence of packets) from the GDCE shall result in the generation of a corresponding ISO 8208 CALL REQUEST packet to the local DCE. The translation from the Mode S packet to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.1.1 with the exceptions as specified in 5.2.5.2.1.2.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.1.2.2 Standard	<i>Called DTE, calling DTE address and length fields</i> . The calling DTE address shall be composed of the aircraft address and the value contained in the AM field of the Mode S packet, converted to BCD (5.2.3.1.3.2). The called DTE address shall be the ground DTE address contained in the AG field of the Mode S packet, converted to BCD. The length field shall be as defined in ISO 8208.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.2.1.1 Standard	<p>5.2.5.2.2 CALL REQUEST BY GDLP</p> <p>5.2.5.2.2.1 Translation into Mode S packets</p> <p>General. Reception by the GDLP reformatting process of an ISO 8208 CALL REQUEST packet from the local DCE shall result in the generation of corresponding Mode S CALL REQUEST by GDLP packet(s) (as determined by S-bit processing (5.2.5.1.4.2)) as follows:</p> <p>DP:1 MP:1 SP:2 ST:2 FILL2:0 P:1 FILL:1 SN:6 FILL:2 TC:2 AM:4 AG:8 S:1 FS:2 F:1 LV:4 UD:v</p> <p>Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.2.1.2 Standard	<p>Data packet type (DP). This field shall be set to 0.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.2.1.3 Standard	<p>MSP packet type (MP). This field shall be set to 1.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.2.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.2.1.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.2.1.6 Standard	<i>Temporary channel number field (TC)</i> . This field shall be used to distinguish multiple call requests from a GDLP. The ADLP reformatting process, upon receipt of a temporary channel number, shall assign a channel number from those presently in the READY state, p1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.2.1.7 Standard	<i>Address, ground (AG)</i> . This address shall be the ground DTE address (5.2.3.1.3.1) in the range of 0 to 255. The address shall be extracted from the calling DTE address contained in the ISO 8208 packet and converted to binary representation.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.2.1.8 Standard	<i>Address, mobile (AM)</i> . This address shall be the mobile DTE sub-address (5.2.3.1.3.2) in the range of 0 to 15. The address shall be extracted from the two least significant digits of the called DTE address contained in the ISO 8208 packet and converted to binary representation.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.2.2.1 Standard	5.2.5.2.2.2 <i>Translation into ISO 8208 packets</i> <i>Translation.</i> Reception by the ADLP reformatting process of a Mode S CALL REQUEST by GDLP packet (or an S-bit sequence of packets) from the ADCE shall result in the generation of a corresponding ISO 8208 CALL REQUEST packet to the local DCE. The translation from the Mode S packet to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.2.1 with the exceptions as specified in 5.2.5.2.2.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.2.2.2 Standard	<i>Called DTE, calling DTE address and length fields.</i> The called DTE address shall be composed of the aircraft address and the value contained in the AM field of the Mode S packet, converted to BCD (5.2.3.1.3.2). The calling DTE address shall be the ground DTE address contained in the AG field of the Mode S packet, converted to BCD. The length field shall be as defined in ISO 8208.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.3.1.1 Standard	5.2.5.2.3 <i>CALL ACCEPT BY ADLP</i> 5.2.5.2.3.1 <i>Translation into Mode S packets</i> <i>Translated packet format.</i> Reception by the ADLP reformatting process of an ISO 8208 CALL ACCEPT packet from the local DCE shall result in the generation of corresponding Mode S CALL ACCEPT by ADLP packet(s) (as determined by S-bit processing (5.2.5.1.4.2)) as follows: DP:1 MP:1 SP:2 ST:2 FILL2:0 or 2 TC:2 SN:6 CH:4 AM:4 AG:8 S:1 FILL:2 F:1 LV:4 UD:v Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.3.1.2 Standard	<i>Data packet type (DP)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.3.1.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.3.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.3.1.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.3.1.6 Standard	<i>Temporary channel number (TC)</i> . The TC value in the originating Mode S CALL REQUEST by GDLP packet shall be returned to the GDLP along with the channel number (CH) assigned by the ADLP.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.3.1.7 Standard	<i>Channel number (CH)</i> . The field shall be set equal to the channel number assigned by the ADLP as determined during the CALL REQUEST procedures for the Mode S connection.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.3.1.8 Standard	<i>Address, mobile and address, ground</i> . The AM and AG values in the originating Mode S CALL REQUEST by GDLP packet shall be returned in these fields. When present, DTE addresses in the ISO 8208 CALL ACCEPT packet shall be ignored.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.3.2.1 Standard	5.2.5.2.3.2 <i>Translation into ISO 8208 packets</i> <i>Translation</i> . Reception by the GDLP reformatting process of a Mode S CALL ACCEPT by ADLP packet (or an S-bit sequence of packets) from the GDCE shall result in the generation of a corresponding ISO 8208 CALL ACCEPT packet to the local DCE. The translation from the Mode S packet to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.3.1 with the exceptions as specified in 5.2.5.2.3.2.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.3.2.2 Standard	<p><i>Called DTE, calling DTE address and length fields.</i> Where present, the called DTE address shall be composed of the aircraft address and the value contained in the AM field of the Mode S packet, converted to BCD (5.2.3.1.3.2). Where present, the calling DTE address shall be the ground DTE address contained in the AG field of the Mode S packet, converted to BCD. The length field shall be as defined in ISO 8208.</p> <p><i>Note.— The called and calling DTE addresses are optional in the corresponding ISO 8208 packet and are not required for correct operation of the Mode S subnetwork.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.4.1.1 Standard	<p>5.2.5.2.4 CALL ACCEPT BY GDLP</p> <p>5.2.5.2.4.1 Translation into Mode S packets</p> <p><i>Translated packet format.</i> Reception by the GDLP reformatting process of an ISO 8208 CALL ACCEPT packet from the local DCE shall result in the generation of corresponding Mode S CALL ACCEPT by GDLP packet(s) (as determined by S-bit processing (5.2.5.1.4.2)) as follows:</p> <p>DP:1 MP:1 SP:2 ST:2 FILL:2 FILL:2 SN:6 CH:4 AM:4 AG:8 S:1 FILL:2 F:1 LV:4 UD:v</p> <p>Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.4.1.2 Standard	<p><i>Data packet type (DP).</i> This field shall be set to 0.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.4.1.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	No Difference		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.4.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.4.1.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.4.1.6 Standard	<i>Address, mobile and address, ground</i> . The AM and AG values in the originating Mode S CALL REQUEST by ADLP packet shall be returned in these fields. When present, DTE addresses in the ISO 8208 CALL ACCEPT packet shall be ignored.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.4.2.1 Standard	5.2.5.2.4.2 <i>Translation into ISO 8208 packets</i> <i>Translation.</i> Reception by the ADLP reformatting process of a Mode S CALL ACCEPT by GDLP packet (or an S-bit sequence of packets) from the ADCE shall result in the generation of a corresponding ISO 8208 CALL ACCEPT packet to the local DCE. The translation from the Mode S packet to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.4.1 with the exceptions as specified in 5.2.5.2.4.2.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.4.2.2 Standard	<i>Called DTE, calling DTE address and length fields.</i> Where present, the calling DTE address shall be composed of the aircraft address and the value contained in the AM field of the Mode S packet, converted to BCD (5.2.3.1.3.2). Where present, the called DTE address shall be the ground DTE address contained in the AG field of the Mode S packet, converted to BCD. The length field shall be as defined in ISO 8208. <i>Note.— The called and calling DTE addresses are optional in the corresponding ISO 8208 packet and are not required for correct operation of the Mode S subnetwork.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.5.1.1 Standard	<p>5.2.5.2.5 CLEAR REQUEST BY ADLP</p> <p>5.2.5.2.5.1 Translation into Mode S packets</p> <p><i>Translated packet format.</i> Reception by the ADLP reformatting process of an ISO 8208 CLEAR REQUEST packet from the local DCE shall result in the generation of a corresponding Mode S CLEAR REQUEST by ADLP packet(s) (as determined by S-bit processing (5.2.5.1.4.2)) as follows: DP:1 MP:1 SP:2 ST:2 FILL2:0 or 2 TC:2 SN:6 CH:4 AM:4 AG:8 CC:8 DC:8 S:1 FILL:2 F:1 LV:4 UD:v</p> <p>Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1 and 5.2.5.2.2.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.5.1.2 Standard	<i>Data packet type (DP).</i> This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.5.1.3 Standard	<i>MSP packet type (MP).</i> This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.5.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.5.1.5 Standard	<i>Channel number (CH)</i> : If a channel number has been allocated during the call acceptance phase, then CH shall be set to that value, otherwise it shall be set to zero.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		
Chapter 5 Reference 5.2.5.2.5.1.6 Standard	<i>Temporary channel (TC)</i> : If a channel number has been allocated during the call acceptance phase, then TC shall be set to zero, otherwise it shall be set to the value used in the CALL REQUEST by GDLP.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.5.1.7 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.5.1.8 Standard	<i>Address, ground or address, mobile</i> . The AG and AM values in the originating Mode S CALL REQUEST by ADLP or CALL REQUEST by GDLP packets shall be returned in these fields. When present, DTE addresses in the ISO 8208 CLEAR REQUEST packet shall be ignored.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.5.1.9 Standard	<i>Clearing cause (CC) and diagnostic code (DC) fields.</i> These fields shall be transferred without modification from the ISO 8208 packet to the Mode S packet when the DTE has initiated the clear procedure. If the XDLP has initiated the clear procedure, the clearing cause field and diagnostic field shall be as defined in the state tables for the DCE and XDCE (see also 5.2.6.3.3). The coding and definition of these fields shall be as specified in ISO 8208.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.5.2.1 Standard	5.2.5.2.5.2 <i>Translation into ISO 8208 packets</i> <i>Translation.</i> Reception by the GDLP reformatting process of a Mode S CLEAR REQUEST by ADLP packet (or an S-bit sequence of packets) from the local GDCE shall result in the generation of a corresponding ISO 8208 CLEAR REQUEST packet to the local DCE. The translation from the Mode S packet to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.5.1 with the exceptions specified in 5.2.5.2.5.2.2 and 5.2.5.2.5.2.3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.5.2.2 Standard	<i>Called DTE, calling DTE and length fields.</i> These fields shall be omitted in the ISO 8208 CLEAR REQUEST packet.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.5.2.3 Standard	<i>Clearing Cause Field.</i> This field shall be set taking account of 5.2.6.3.3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.6.1.1 Standard	<p>5.2.5.2.6 CLEAR REQUEST BY GDLP</p> <p>5.2.5.2.6.1 Translation into Mode S packets</p> <p>Translated packet format. Reception by the GDLP reformatting process of an ISO 8208 CLEAR REQUEST packet from the local DCE shall result in the generation of corresponding Mode S CLEAR REQUEST by GDLP packet(s) (as determined by S-bit processing (5.2.5.1.4.2)) as follows: DP:1 MP:1 SP:2 ST:2 FILL:2 TC:2 SN:6 CH:4 AM:4 AG:8 CC:8 DC:8 S:1 FILL:2 F:1 LV:4 UD:v</p> <p>Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1, 5.2.5.2.2 and 5.2.5.2.5.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.6.1.2 Standard	<i>Data packet type (DP)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.6.1.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.6.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.6.1.5 Standard	<i>Channel number (CH)</i> : If a channel number has been allocated during the call acceptance phase, then CH shall be set to that value, otherwise it shall be set to zero.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.6.1.6 Standard	<i>Temporary channel (TC)</i> : If a channel number has been allocated during the call acceptance phase, then TC shall be set to zero, otherwise it shall be set to the value used in the CALL REQUEST by GDLP.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.6.1.7 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.6.2.1 Standard	5.2.5.2.6.2 <i>Translation into ISO 8208 packets</i> <i>Translation.</i> Reception by the ADLP reformatting process of a Mode S CLEAR REQUEST by GDLP packet (or an S-bit sequence of packets) from the local ADCE shall result in the generation of a corresponding ISO 8208 CLEAR REQUEST packet to the local DCE. The translation from the Mode S packet to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.6.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.6.2.2 Standard	<i>Called DTE, calling DTE and length fields.</i> These fields shall be omitted in the ISO 8208 CLEAR REQUEST packet.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.7.1.1 Standard	5.2.5.2.7 <i>DATA</i> 5.2.5.2.7.1 <i>Translation into Mode S packets</i> <i>Translated packet format.</i> Reception by the XDLP reformatting process of ISO 8208 DATA packet(s) from the local DCE shall result in the generation of corresponding Mode S DATA packet(s) as determined by M-bit processing (5.2.5.1.4.1), as follows: DP:1 M:1 SN:6 FILL1:0 OR 6 PS:4 PR:4 CH:4 LV:4 UD:v	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.7.1.2 Standard	<i>Data packet type (DP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.7.1.3 Standard	<i>M field (M)</i> . A value of 1 shall indicate that the packet is part of an M-bit sequence with more packets in the sequence to follow. A value of 0 shall indicate that the sequence ends with this packet. The appropriate value shall be placed in the M-bit field of the Mode S packet. <i>Note.— See 5.2.5.1.4 and ISO 8208 for a complete explanation.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.7.1.4 Standard	<i>Sequence number (SN)</i> . The sequence number field shall be set as specified in 5.2.5.2.1.1.7.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.7.1.5 Standard	<i>Packet send sequence number (PS)</i> . The packet send sequence number field shall be set as specified in 5.2.6.4.4.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.7.1.6 Standard	<i>Packet receive sequence number (PR)</i> . The packet receive sequence number field shall be set as specified in 5.2.6.4.4.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.7.1.7 Standard	<i>Channel number (CH)</i> . The channel number field shall contain the Mode S channel number that corresponds to the incoming ISO 8208 DATA packet channel number.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.7.1.8 Standard	<i>User data length (LV)</i> . This field shall indicate the number of full bytes used in the last SLM or ELM segment as defined in 5.2.2.3.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.7.1.9 Standard	<i>Fill (FILL1)</i> . This field shall be set as specified in 5.2.5.2.1.1.11.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.7.1.10 Standard	<i>User data (UD)</i> . The user data shall be transferred from the ISO 8208 packet to the Mode S packet utilizing the M-bit packet assembly processing as required.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.7.2 Standard	<i>Translation into ISO 8208 packets.</i> Reception by the XDLP reformatting process of Mode S DATA packet(s) from the local XDCE shall result in the generation of corresponding ISO 8208 DATA packet(s) to the local DCE. The translation from Mode S packet(s) to the ISO 8208 packet(s) shall be the inverse of the processing defined in 5.2.5.2.7.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.8.1.1 Standard	5.2.5.2.8 <i>INTERRUPT</i> 5.2.5.2.8.1 <i>Translation into Mode S packets</i> <i>Translated packet format.</i> Reception by the XDLP reformatting process of an ISO 8208 INTERRUPT packet from the local DCE shall result in the generation of corresponding Mode S INTERRUPT packet(s) (as determined by S-bit processing (5.2.5.1.4.2)) as follows: DP:1 MP:1 SP:2 ST:2 FILL2:0 or 2 S:1 F:1 SN:6 CH:4 LV:4 UD:v Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.8.1.2 Standard	<i>Data packet type (DP).</i> This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.8.1.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.8.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.8.1.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.8.1.6 Standard	<i>User data length (LV)</i> . This field shall be set as specified in 5.2.2.3.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.8.1.7 Standard	<i>User data (UD)</i> . The user data shall be transferred from the ISO 8208 packet to the Mode S packet using the S-bit packet reassembly processing as required. The maximum size of the user data field for an INTERRUPT packet shall be 32 bytes.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.8.2 Standard	<i>Translation into ISO 8208 packets.</i> Reception by the XDLP reformatting process of Mode S INTERRUPT packet(s) from the local XDCE shall result in the generation of a corresponding ISO 8208 INTERRUPT packet to the local DCE. The translation from the Mode S packet(s) to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.8.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.9.1.1 Standard	5.2.5.2.9 INTERRUPT CONFIRMATION 5.2.5.2.9.1 Translation into Mode S packets <i>Translated packet format.</i> Reception by the XDLP reformatting process of an ISO 8208 INTERRUPT CONFIRMATION packet from the local DCE shall result in the generation of a corresponding Mode S INTERRUPT CONFIRMATION packet as follows: DP:1 MP:1 SP:2 ST:2 SS:2 FILL2:0 or 2 SN:6 CH:4 FILL:4 Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.9.1.2 Standard	<i>Data packet type (DP).</i> This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.9.1.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.9.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.9.1.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.9.1.6 Standard	<i>Supervisory subset (SS)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.9.2 Standard	<i>Translation into ISO 8208 packets.</i> Reception by the XDLP reformatting process of a Mode S INTERRUPT CONFIRMATION packet from the local XDCE shall result in the generation of a corresponding ISO 8208 INTERRUPT CONFIRMATION packet to the local DCE. The translation from the Mode S packet to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.9.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.10.1.1 Standard	5.2.5.2.10 RESET REQUEST 5.2.5.2.10.1 Translation into Mode S packets <i>Translated packet format.</i> Reception by the XDLP reformatting process of an ISO 8208 RESET REQUEST packet from the local DCE shall result in the generation of a corresponding Mode S RESET REQUEST packet as follows: DP:1 MP:1 SP:2 ST:2 FILL2:0 or 2 FILL:2 SN:6 CH:4 FILL:4 RC:8 DC:8 Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.10.1.2 Standard	<i>Data packet type (DP).</i> This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.10.1.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.10.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.10.1.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.10.1.6 Standard	<i>Reset cause code (RC) and diagnostic code (DC)</i> . The reset cause and diagnostic codes used in the Mode S RESET REQUEST packet shall be as specified in the ISO 8208 packet when the reset procedure is initiated by the DTE. If the reset procedure originates with the DCE, the DCE state tables shall specify the diagnostic fields coding. In this case, bit 8 of the reset cause field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.2.10.2 Standard	<i>Translation into ISO 8208 packets.</i> Reception by the XDLP reformatting process of a Mode S RESET packet from the local XDCE shall result in the generation of a corresponding ISO 8208 RESET packet to the local DCE. The translation from the Mode S packet to the ISO 8208 packet shall be the inverse of the processing defined in 5.2.5.2.10.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.2.11 Standard	<i>ISO 8208 RESTART REQUEST to Mode S CLEAR REQUEST.</i> The receipt of an ISO 8208 RESTART REQUEST from the local DCE shall result in the reformatting process generating a Mode S CLEAR REQUEST by ADLP or Mode S CLEAR REQUEST by GDLP for all SVCs associated with the requesting DTE. The fields of the Mode S CLEAR REQUEST packets shall be set as specified in 5.2.5.2.5 and 5.2.5.2.6. <i>Note.— There are no restart states in the Mode S packet layer protocol.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.1.1 Standard	5.2.5.3 PACKETS LOCAL TO THE MODE S SUBNETWORK <i>Note.— Packets defined in this section do not result in the generation of an ISO 8208 packet.</i> 5.2.5.3.1 MODE S RECEIVE READY <i>Packet format.</i> The Mode S RECEIVE READY packet arriving from an XDLP is not related to the control of the DTE/DCE interface and shall not cause the generation of an ISO 8208 packet. The format of the packet shall be as follows: DP:1 MP:1 SP:2 ST:2 FILL2:0 or 2 FILL:2 SN:6 CH:4 PR:4 Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1. The packet shall be processed as specified in 5.2.6.5.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.1.2 Standard	<i>Data packet type (DP)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.1.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.1.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.1.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.1.6 Standard	<i>Packet receive sequence number (PR)</i> . This field shall be set as specified in 5.2.6.4.4.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
Chapter 5 Reference 5.2.5.3.2.1 Standard	<p>5.2.5.3.2 <i>MODE S RECEIVE NOT READY</i></p> <p><i>Packet format.</i> The Mode S RECEIVE NOT READY packet arriving from an XDLP is not related to the control of the DTE/DCE interface and shall not cause the generation of an ISO 8208 packet. The format of the packet shall be as follows:</p> <table border="0" style="margin-left: 40px;"> <tr> <td>DP:1</td> <td>MP:1</td> <td>SP:2</td> <td>ST:2</td> <td>FILL2:0 or 2</td> </tr> <tr> <td></td> <td>FILL:2</td> <td>SN:6</td> <td>CH:4</td> <td>PR:4</td> </tr> </table> <p>Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1. The packet shall be processed as specified in 5.2.6.6.</p>	DP:1	MP:1	SP:2	ST:2	FILL2:0 or 2		FILL:2	SN:6	CH:4	PR:4	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
DP:1	MP:1	SP:2	ST:2	FILL2:0 or 2											
	FILL:2	SN:6	CH:4	PR:4											
Chapter 5 Reference 5.2.5.3.2.2 Standard	<i>Data packet type (DP).</i> This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde										
Chapter 5 Reference 5.2.5.3.2.3 Standard	<i>MSP packet type (MP).</i> This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde										
Chapter 5 Reference 5.2.5.3.2.4 Standard	<i>Supervisory packet (SP).</i> This field shall be set to 2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.2.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.2.6 Standard	<i>Packet receive sequence number (PR)</i> . This field shall be set as specified in 5.2.6.4.4.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.1 Standard	5.2.5.3.3 <i>MODE S ROUTE</i> <i>Packet format</i> . The format for the packet shall be as follows: DP:1 MP:1 SP:2 ST:2 OF:1 IN:1 RTL:8 RT:v ODL:0 or 8 OD:v Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1. The packet shall only be generated by the GDLP. It shall be processed by the ADLP as specified in 5.2.8.1.2 and shall have a maximum size as specified in 5.2.6.4.2.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.2 Standard	<i>Data packet type (DP)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.3.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.6 Standard	<i>Option flag (OF)</i> . This field shall indicate the presence of the optional data length (ODL) and optional data (OD) fields. OF shall be set to 1 if ODL and OD are present. Otherwise it shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.3.9.3 Standard	<i>Interrogator identifier (II)</i> . This field shall contain the 4-bit II code.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.9.4 Standard	<i>Add/delete flag (AD)</i> . This field shall indicate whether the II code-DTE pairs shall be added (<i>AD</i> = 1) or deleted (<i>AD</i> = 0) from the II code-DTE cross-reference table.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.9.5 Standard	<i>Number of DTE addresses (ND)</i> . This field shall be expressed in binary in the range from 0 to 7 and shall indicate the number of DTE addresses present in DAL minus 1 (in order to allow from 1 to 8 DTE addresses).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.9.6 Standard	<i>DTE address list (DAL)</i> . This list shall consist of up to 8 DTE addresses, expressed in 8-bit binary representation.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.3.10 Standard	<i>Optional data length (ODL)</i> . This field shall contain the length in bytes of the following OD field.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.3.11 Standard	<i>Optional data (OD)</i> . This variable length field shall contain optional data.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.4.1 Standard	<p>5.2.5.3.4 MODE S CLEAR CONFIRMATION BY ADLP</p> <p><i>Packet format</i>. The format for this packet shall be as follows:</p> <p style="padding-left: 40px;">DP:1 MP:1 SP:2 ST:2 FILL2:0 or 2 TC:2 SN:6 CH:4 AM:4 AG:8</p> <p>Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1 and 5.2.5.2.5. This packet shall be processed as specified in 5.2.6.3.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.4.2 Standard	<i>Data packet type (DP)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.4.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.4.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.4.5 Standard	<i>Channel number (CH)</i> : If a channel number has been allocated during the call acceptance phase, then CH shall be set to that value, otherwise it shall be set to zero.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.4.6 Standard	<i>Temporary channel (TC)</i> : If a channel number has been allocated during the call acceptance phase, then TC shall be set to zero, otherwise it shall be set to the value used in the CALL REQUEST by GDLP.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.4.7 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.5.1 Standard	<p>5.2.5.3.5 MODE S CLEAR CONFIRMATION BY GDLP</p> <p><i>Packet format.</i> The format for this packet shall be as follows:</p> <p style="text-align: center;">DP:1 MP:1 SP:2 ST:2 FILL: 2 TC:2 SN:6 CH:4 AM:4 AG:8</p> <p>Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1 and 5.2.5.2.6. This packet shall be processed as specified in 5.2.6.3.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.5.2 Standard	<i>Data packet type (DP).</i> This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.5.3 Standard	<i>MSP packet type (MP).</i> This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.5.4 Standard	<i>Supervisory packet (SP).</i> This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.5.5 Standard	<i>Channel number (CH)</i> : If a channel number has been allocated during the call acceptance phase, then CH shall be set to that value, otherwise it shall be set to zero.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.5.6 Standard	<i>Temporary channel (TC)</i> : If a channel number has been allocated during the call acceptance phase, then TC shall be set to zero, otherwise it shall be set to the value used in the CALL REQUEST by GDLP.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.5.7 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.6.1 Standard	5.2.5.3.6 <i>MODE S RESET CONFIRMATION</i> <i>Packet format</i> . The format for this packet shall be as follows: DP:1 MP:1 SP:2 ST:2 FILL2:0 or 2 FILL:2 SN:6 CH:4 FILL:4 Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1. This packet shall be processed as specified in Table 5-14.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.6.2 Standard	<i>Data packet type (DP)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.6.3 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.6.4 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.6.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.7.1 Standard	<p>5.2.5.3.7 <i>MODE S REJECT</i></p> <p><i>Packet format.</i> The format for this packet shall be as follows:</p> <p style="text-align: center;">DP:1 MP:1 SP:2 ST:2 SS:2 FILL2:0 or 2 SN:6 CH:4 PR:4</p> <p>Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1. This packet shall be processed as specified in 5.2.6.8.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.7.2 Standard	<p><i>Data packet type (DP).</i> This field shall be set to 0.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.7.3 Standard	<p><i>MSP packet type (MP).</i> This field shall be set to 1.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.7.4 Standard	<p><i>Supervisory packet (SP).</i> This field shall be set to 3.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.5.3.7.5 Standard	<i>Supervisory type (ST)</i> . This field shall be set to 3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.7.6 Standard	<i>Supervisory subset (SS)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.5.3.7.7 Standard	<i>Packet receive sequence number (PR)</i> . This field shall be set as specified in 5.2.6.4.4.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.1 Standard	<p style="text-align: center;">5.2.6 XDCE operation</p> <p><i>Note.— The ADCE process within the ADLP acts as a peer process to the GDCE process in the GDLP.</i></p> <p><i>State transitions.</i> The XDCE shall operate as a state machine. Upon entering a state, the XDCE shall perform the actions specified in Table 5-14. State transition and additional action(s) shall be as specified in Table 5-15 through Table 5-22.</p> <p><i>N1.</i>The next state transition (if any) that occurs when the XDCE receives a packet from the peer XDCE is specified by Table 5-15 through Table 5-19. The same transitions are defined in Table 5-20 through Table 5-22 when the XDCE receives a packet from the DCE (via the reformatting process).</p> <p><i>N2.</i>The XDCE state hierarchy is the same as for the DCE as presented in Figure 5-2, except that states r2, r3 and p5 are omitted.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.2.1 Standard	<p style="text-align: center;">5.2.6.2 DISPOSITION OF PACKETS</p> <p>Upon receipt of a packet from the peer XDCE, the packet shall be forwarded or not forwarded to the DCE (via the reformatting process) according to the parenthetical instructions contained in Tables 5-15 to 5-19. If no parenthetical instruction is listed or if the parenthetical instruction indicates “do not forward” the packet shall be discarded.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.2.2 Standard	Upon receipt of a packet from the DCE (via the reformatting process), the packet shall be forwarded or not forwarded to the peer XDCE according to the parenthetical instructions contained in Tables 5-20 to 5-22. If no parenthetical instruction is listed or if the parenthetical instruction indicates "do not forward" the packet shall be discarded.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.3.1 Standard	5.2.6.3 SVC CALL SETUP AND CLEAR PROCEDURE <i>Setup procedures.</i> Upon receipt of a CALL REQUEST from the DCE or peer XDCE, the XDLP shall determine if sufficient resources exist to operate the SVC. This shall include: sufficient buffer space (refer to 5.2.5.1.1 for buffer requirements) and an available p1 state SVC. Upon acceptance of the CALL REQUEST from the DCE (via the reformatting process), the Mode S CALL REQUEST packet shall be forwarded to frame processing. Upon acceptance of a Mode S CALL REQUEST from the peer XDCE (via frame processing), the Mode S CALL REQUEST shall be sent to the reformatting process.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.3.2 Standard	<i>Aborting a call request.</i> If the DTE and/or the peer XDCE abort a call before they have received a CALL ACCEPT packet, they shall indicate this condition by issuing a CLEAR REQUEST packet. Procedures for handling these cases shall be as specified in Table 5-16 and Table 5-20.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.3.3.1 Standard	5.2.6.3.3 <i>VIRTUAL CALL CLEARING</i> If the XDCE receives a Mode S CALL REQUEST from the reformatting process that it cannot support, it shall initiate a Mode S CLEAR REQUEST packet that is sent to the DCE (via the reformatting process) for transfer to the DTE (the DCE thus enters the DCE CLEAR REQUEST to DTE state, p7).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.3.3.2 Standard	If the XDCE receives a Mode S CALL REQUEST packet from the peer XDCE (via frame processing) which it cannot support, it shall enter the state p7.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.3.3.3 Standard	A means shall be provided to advise the DTE whether an SVC has been cleared due to the action of the peer DTE or due to a problem within the subnetwork itself.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.3.3.4 Recommendation	Recommendation. — <i>The requirement of 5.2.6.3.3.3 should be satisfied by setting bit 8 of the cause field to 1 to indicate that the problem originated in the Mode S subnetwork and not in the DTE. The diagnostic and cause codes should be set as follows:</i> a) <i>no channel number available, DC = 71, CC = 133;</i> b) <i>buffer space not available, DC = 71, CC = 133;</i> c) <i>DTE not operational, DC = 162, CC = 141; and</i> d) <i>link failure, DC = 225, CC = 137.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.3.3.5 Standard	<p>If the ADLP receives a Mode S ROUTE packet with the IN bit set to ONE, the ADLP shall perform local initialization by clearing Mode S SVCs associated with the DTE addresses contained in the ROUTE packet. If the GDLP receives a search request (Table 5-23) from an ADLP, the GDLP shall perform local initialization by clearing Mode S SVCs associated with that ADLP. Local initialization shall be accomplished by:</p> <ul style="list-style-type: none"> a) releasing all allocated resources associated with these SVCs (including the resequencing buffers); b) returning these SVCs to the ADCE ready state (p1); and c) sending Mode S CLEAR REQUEST packets for these SVCs to the DCE (via the reformatting process) for transfer to the DTE. <p><i>Note.— This action will allow all ISO 8208 SVCs attached to the Mode S SVCs to be cleared and return to their ready states (p1).</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.3.4 Standard	<p><i>Clear confirmation.</i> When the XDCE receives a Mode S CLEAR CONFIRMATION packet, the remaining allocated resources to manage the SVC shall be released (including the resequencing buffers) and the SVC shall be returned to the p1 state. Mode S CLEAR CONFIRMATION packets shall not be transferred to the reformatting process.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.3.5 Standard	<p><i>Clear collision.</i> A clear collision occurs at the XDCE when it receives a Mode S CLEAR REQUEST packet from the DCE (via the reformatting process) and then receives a Mode S CLEAR REQUEST packet from the peer XDCE (or vice versa). In this event, the XDCE does not expect to receive a Mode S CLEAR CONFIRMATION packet for this SVC and shall consider the clearing complete.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.3.6 Standard	<i>Packet processing.</i> The XDCE shall treat an S-bit sequence of Mode S CALL REQUEST, CALL ACCEPT and CLEAR REQUEST packets as a single entity.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.1.1 Standard	5.2.6.4 DATA TRANSFER AND INTERRUPT PROCEDURES 5.2.6.4.1 GENERAL PROVISIONS Data transfer and interrupt procedures shall apply independently to each SVC. The contents of the user data field shall be passed transparently to the DCE or to the peer XDCE. Data shall be transferred in the order dictated by the sequence numbers assigned to the data packets.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.1.2 Standard	To transfer DATA packets, the SVC shall be in a FLOW CONTROL READY state (d1).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.4.2.1 Standard	5.2.6.4.2 <i>MODE S PACKET SIZE</i> The maximum size of Mode S packets shall be 152 bytes in the uplink direction and 160 bytes in the downlink direction for installations that have full uplink and downlink ELM capability. The maximum downlink packet size for level four transponders with less than 16 segment downlink ELM capability shall be 10 bytes times the maximum number of downlink ELM segments that the transponder specifies in its data link capability report. If there is no ELM capability, the maximum Mode S packet size shall be 28 bytes.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.2.2 Standard	The Mode S subnetwork shall allow packets of less than the maximum size to be transferred.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.3.1 Standard	5.2.6.4.3 <i>FLOW CONTROL WINDOW SIZE</i> The flow control window size of the Mode S subnetwork shall be independent of that used on the DTE/DCE interface. The Mode S subnetwork window size shall be 15 packets in the uplink and downlink directions.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.4.4.1 Standard	<p><i>5.2.6.4.4 SVC FLOW CONTROL</i></p> <p>Flow control shall be managed by means of a sequence number for received packets (PR) and one for packets that have been sent (PS). A sequence number (PS) shall be assigned for each Mode S DATA packet generated by the XDLP for each SVC. The first Mode S DATA packet transferred by the XDCE to frame processing when the SVC has just entered the flow control ready state shall be numbered zero. The first Mode S packet received from the peer XDCE after an SVC has just entered the flow control ready state shall be numbered zero. Subsequent packets shall be numbered consecutively.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.4.2 Standard	A source of Mode S DATA packets (the ADCE or GDCE) shall not send (without permission from the receiver) more Mode S DATA packets than would fill the flow control window. The receiver shall give explicit permission to send more packets.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.4.3 Standard	The permission information shall be in the form of the next expected packet sequence number and shall be denoted PR. If a receiver wishes to update the window and it has data to transmit to the sender, a Mode S DATA packet shall be used for information transfer. If the window must be updated and no data are to be sent, a Mode S RECEIVE READY (RR) or Mode S RECEIVE NOT READY (RNR) packet shall be sent. At this point, the "sliding window" shall be moved to begin at the new PR value. The XDCE shall now be authorized to transfer more packets without acknowledgement up to the window limit.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.4.4.4 Standard	When the sequence number (PS) of the next Mode S DATA packet to be sent is in the range $PR \leq PS \leq PR + 14$ (modulo 16), the sequence number shall be defined to be "in the window" and the XDCE shall be authorized to transmit the packet. Otherwise, the sequence number (PS) of the packet shall be defined to be "outside the window" and the XDCE shall not transmit the packet to the peer XDCE.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.4.5 Standard	When the sequence number (PS) of the packet received is next in sequence and within the window, the XDCE shall accept this packet. Receipt of a packet with a PS: a) outside the window; or b) out of sequence; or c) not equal to 0 for the first data packet after entering FLOW CONTROL READY state (<i>d1</i>); shall be considered an error (5.2.6.8).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.4.6 Standard	The receipt of a Mode S DATA packet with a valid PS number (i.e. the next PS in sequence) shall cause the lower window PR to be changed to that PS value plus 1. The packet receive sequence number (PR) shall be conveyed to the originating XDLP by a Mode S DATA, RECEIVE READY, RECEIVE NOT READY, or REJECT packet. A valid PR value shall be transmitted by the XDCE to the peer XDCE after the receipt of 8 packets provided that sufficient buffer space exists to store 15 packets. Incrementing the PR and PS fields shall be performed using modulo 16 arithmetic. <i>Note.— The loss of a packet which contains the PR value may cause the ADLP/GDLP operations for that SVC to cease.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.4.4.7 Standard	A copy of a packet shall be retained until the user data has been successfully transferred. Following successful transfer, the PS value shall be updated.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.4.8 Standard	The PR value for user data shall be updated as soon as the required buffer space for the window (as determined by flow control management) is available within the DCE.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.4.9 Standard	Flow control management shall be provided between the DCE and XDCE.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.4.5.1 Standard	<p>5.2.6.4.5 INTERRUPT PROCEDURES FOR SWITCHED VIRTUAL CIRCUITS</p> <p>If user data is to be sent via the Mode S subnetwork without following the flow control procedures, the interrupt procedures shall be used. The interrupt procedure shall have no effect on the normal data packet and flow control procedures. An interrupt packet shall be delivered to the DTE (or the transponder or interrogator interface) at or before the point in the stream of data at which the interrupt was generated. The processing of a Mode S INTERRUPT packet shall occur as soon as it is received by the XDCE.</p> <p><i>Note.— The use of clear, reset, and restart procedures can cause interrupt data to be lost.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.5.2 Standard	The XDCE shall treat an S-bit sequence of Mode S INTERRUPT packets as a single entity.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.4.5.3 Standard	Interrupt processing shall have precedence over any other processing for the SVC occurring at the time of the interrupt.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.4.5.4 Standard	The reception of a Mode S INTERRUPT packet before the previous interrupt of the SVC has been confirmed (by the receipt of a Mode S INTERRUPT CONFIRMATION packet) shall be defined as an error. The error results in a reset (see Table 5-18).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.5.1 Standard	5.2.6.5 RECEIVE READY PROCEDURE The Mode S RECEIVE READY packet shall be sent if no Mode S DATA packets (that normally contain the updated PR value) are available for transmittal and it is necessary to transfer the latest PR value. It also shall be sent to terminate a receiver not ready condition.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.5.2 Standard	Receipt of the Mode S RECEIVE READY packet by the XDCE shall cause the XDCE to update its value of PR for the outgoing SVC. It shall not be taken as a demand for retransmission of packets that have already been transmitted and are still in the window.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.5.3 Standard	Upon receipt of the Mode S RECEIVE READY packet, the XDCE shall go into the ADLP(GDLP) RECEIVE READY state (g1).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.6.1 Standard	5.2.6.6 RECEIVE NOT READY PROCEDURE The Mode S RECEIVE NOT READY packet shall be used to indicate a temporary inability to accept additional DATA packets for the given SVC. The Mode S RNR condition shall be cleared by the receipt of a Mode S RR packet or a Mode S REJECT packet.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.6.2 Standard	When the XDCE receives a Mode S RECEIVE NOT READY packet from the peer XDCE, it shall update its value of PR for the SVC and stop transmitting Mode S DATA packets on the SVC to the XDLP. The XDCE shall go into the ADLP(GDLP) RECEIVE NOT READY state (g2).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.6.3 Standard	The XDCE shall transmit a Mode S RECEIVE NOT READY packet to the peer XDCE if it is unable to receive from the peer XDCE any more Mode S DATA packets on the indicated SVC. Under these conditions, the XDCE shall go into the ADCE(GDCE) RECEIVE NOT READY state (f2).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.7.1 Standard	<p style="text-align: center;">5.2.6.7 RESET PROCEDURE</p> <p>When the XDCE receives a Mode S RESET REQUEST packet from either the peer XDCE or the DCE (via the reformatting process) or due to an error condition performs its own reset, the following actions shall be taken:</p> <ul style="list-style-type: none"> a) those Mode S DATA packets that have been transmitted to the peer XDCE shall be removed from the window; b) those Mode S DATA packets that are not transmitted to the peer XDCE but are contained in an M-bit sequence for which some packets have been transmitted shall be deleted from the queue of DATA packets awaiting transmission; c) those Mode S DATA packets received from the peer XDCE that are part of an incomplete M-bit sequence shall be discarded; d) the lower window edge shall be set to 0 and the next packet sent shall have a sequence number (PS) of 0; e) any outstanding Mode S INTERRUPT packets to or from the peer XDCE shall be left unconfirmed; f) any Mode S INTERRUPT packet awaiting transfer shall be discarded; g) data packets awaiting transfer shall not be discarded (unless they are part of a partially transferred M-bit sequence); and h) the transition to <i>d1</i> shall also include a transition to <i>i1, j1, f1</i> and <i>g1</i>. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.7.2 Standard	The reset procedure shall apply to the DATA TRANSFER state (<i>p4</i>). The error procedure in Table 5-16 shall be followed. In any other state the reset procedure shall be abandoned.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.8.1 Standard	5.2.6.8 REJECT PROCEDURE When the XDCE receives a Mode S DATA packet from the peer XDCE with incorrect format or whose packet sequence number (PS) is not within the defined window (Table 5-19) or is out of sequence, it shall discard the received packet and send a Mode S REJECT packet to the peer XDCE via frame processing. The Mode S REJECT packet shall indicate a value of PR for which retransmission of the Mode S DATA packets is to begin. The XDCE shall discard subsequent out-of-sequence Mode S DATA packets whose receipt occurs while the Mode S REJECT packet response is still outstanding.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.8.2 Standard	When the XDCE receives a Mode S REJECT packet from the peer XDCE, it shall update its lower window value with the new value of PR and begin to (re)transmit packets with a sequence number of PR.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.8.3 Standard	Reject indications shall not be transferred to the DCE. If the ISO 8208 interface supports the reject procedures, the reject indications occurring on the ISO 8208 interface shall not be transferred between the DCE and the XDCE.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.9.1 Standard	<p>5.2.6.9 PACKET RESEQUENCING AND DUPLICATE SUPPRESSION</p> <p><i>N1.If the frames for an SVC include both types (SLM and ELM), the sequence of packets may be lost due to the different delivery times. The order may also be lost if multiple interrogators are used to deliver frames for the same SVC to a given XDLP. The following procedure will correct for a limited amount of desequencing.</i></p> <p><i>N2.This process serves as an interface between frame processing and the XDCE function.</i></p> <p><i>Resequencing.</i> Resequencing shall be performed independently for the uplink and downlink transfers of each Mode S SVC. The following variables and parameters shall be used:</p> <p><i>SNRA</i> 6-bit variable indicating the sequence number of a received packet on a specific SVC. It is contained in the SN field of the packet (5.2.5.2.1.1.7).</p> <p><i>NESN</i> The next expected sequence number following a series of consecutive sequence numbers.</p> <p><i>HSNR</i> The highest value of SNR in the resequencing window.</p> <p><i>Tq</i> Resequencing timers (see Tables 5-1 and 5-13) associated with a specific SVC.</p> <p>All operations involving the sequence number (SN) shall be performed modulo 64.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.9.2 Standard	<p><i>Duplication window.</i> The range of <i>SNR</i> values between <i>NESN</i> – 32 and <i>NESN</i> – 1 inclusive shall be denoted the duplication window.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.9.3 Standard	<i>Resequencing window.</i> The range of <i>SNR</i> values between <i>NESN</i> + 1 and <i>NESN</i> + 31 inclusive shall be denoted the resequencing window. Received packets with a sequence number value in this range shall be stored in the resequencing window in sequence number order.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.9.4.1 Standard	<i>5.2.6.9.4 TRANSMISSION FUNCTIONS</i> For each SVC, the first packet sent to establish a connection (the first Mode S CALL REQUEST or first Mode S CALL ACCEPT packet) shall cause the value of the <i>SN</i> field to be initialized to zero. The value of the <i>SN</i> field shall be incremented after the transmission (or retransmission) of each packet.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.9.4.2 Standard	The maximum number of unacknowledged sequence numbers shall be 32 consecutive <i>SN</i> numbers. Should this condition be reached, then it shall be treated as an error and the channel cleared. <i>Note.— A limit on the number of unacknowledged packets is required since the SN field is six bits long and therefore has a maximum of 64 different values before the values repeat.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.9.5.1 Standard	<i>5.2.6.9.5 RECEIVE FUNCTIONS</i> <i>Resequencing.</i> The resequencing algorithm shall maintain the variables <i>HSNR</i> and <i>NESN</i> for each SVC. <i>NESN</i> shall be initialized to 0 for all SVCs and shall be reset to 0 when the SVC re-enters the channel number pool (5.2.5.1.2).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.9.5.2 Standard	<i>Processing of packets within the duplication window.</i> If a packet is received with a sequence number value within the duplication window, the packet shall be discarded.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.9.5.3 Standard	<i>Processing of packets within the resequencing window.</i> If a packet is received with a sequence number within the resequencing window, it shall be discarded as a duplicate if a packet with the same sequence number has already been received and stored in the resequencing window. Otherwise, the packet shall be stored in the resequencing window. Then, if no <i>Tq</i> timers are running, <i>HSNR</i> shall be set to the value of <i>SNR</i> for this packet and a <i>Tq</i> timer shall be started with its initial value (Tables 5-1 and 5-13). If at least one <i>Tq</i> timer is running, and <i>SNR</i> is not in the window between <i>NESN</i> and <i>HSNR</i> + 1 inclusive, a new <i>Tq</i> timer shall be started and the value of <i>HSNR</i> shall be updated. If at least one <i>Tq</i> timer is running, and <i>SNR</i> for this packet is equal to <i>HSNR</i> + 1, the value of <i>HSNR</i> shall be updated.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.6.9.5.4 Standard	<i>Release of packets to the XDCE.</i> If a packet is received with a sequence number equal to <i>NESN</i> , the following procedure shall be applied: a) the packet and any packets already stored in the resequencing window up to the next missing sequence number shall be passed to the XDCE; b) <i>NESN</i> shall be set to 1 + the value of the sequence number of the last packet passed to the XDCE; and c) the <i>Tq</i> timer associated with any of the released packets shall be stopped.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.6.9.6 Standard	<p><i>Tq</i> timer expiration. If a <i>Tq</i> timer expires, the following procedure shall be applied:</p> <ul style="list-style-type: none"> a) <i>NESN</i> shall be incremented until the next missing sequence number is detected after that of the packet associated with the <i>Tq</i> timer that has expired; b) any stored packets with sequence numbers that are no longer in the resequencing window shall be forwarded to the XDCE except that an incomplete S-bit sequence shall be discarded; and c) the <i>Tq</i> timer associated with any released packets shall be stopped. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7 Standard	<p style="text-align: center;">Mode S specific services processing</p> <p>Mode S specific services shall be processed by an entity in the XDLP termed the Mode S specific services entity (SSE). Transponder registers shall be used to convey the information specified in Table 5-24. The data structuring of the registers in Table 5-24 shall be implemented in such a way that interoperability is ensured.</p> <p><i>N1. The data formats and protocols for messages transferred via Mode S specific services are specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871) (in preparation).</i></p> <p><i>N2. Uniform implementation of the data formats and protocols for messages transferred via Mode S specific services will ensure interoperability.</i></p> <p><i>N3. This section describes the processing of control and message data received from the Mode S specific services interface.</i></p> <p><i>N4. Control data consists of information permitting the determination of, for example, message length, BDS code used to access the data format for a particular register, and aircraft address.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.1.1.1 Standard	<p align="center">5.2.7.1 ADLP PROCESSING</p> <p><i>5.2.7.1.1 DOWNLINK PROCESSING</i></p> <p><i>Specific services capability.</i> The ADLP shall be capable of receiving control and message data from the Mode S specific services interface(s) and sending delivery notices to this interface. The control data shall be processed to determine the protocol type and the length of the message data. When the message or control data provided at this interface are erroneous (i.e. incomplete, invalid or inconsistent), the ADLP shall discard the message and deliver an error report at the interface.</p> <p><i>Note.— The diagnostic content and error reporting mechanism are a local issue.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.1.1.2 Standard	<i>Broadcast processing.</i> The control and message data shall be used to format the Comm-B broadcast message as specified in 5.2.7.5 and transferred to the transponder.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.1.1.3 Standard	<p><i>GICB processing.</i> The 8-bit BDS code shall be determined from the control data. The 7-byte register content shall be extracted from the received message data. The register content shall be transferred to the transponder, along with an indication of the specified register number. A request to address one of the air-initiated Comm-B registers or the airborne collision avoidance system (ACAS) active resolution advisories register shall be discarded. The assignment of registers shall be as specified in Table 5-24.</p> <p><i>Note.— Provision of the data available in transponder registers 40, 50 and 60 {HEX} has been mandated in some ICAO Regions in support of ATM applications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.1.1.4.1 Standard	<p>5.2.7.1.1.4 MSP processing</p> <p>The MSP message length, channel number (M/CH) (5.2.7.3.1.3) and optionally the interrogator identifier (II) code shall be determined from the control data. The MSP message content shall be extracted from the received message data. If the message length is 26 bytes or less, the SSE shall format an air-initiated Comm-B message (5.2.7.1.1.4.2) for transfer to the transponder using the short form MSP packet (5.2.7.3.1). If the message length is 27 to 159 bytes and the transponder has adequate downlink ELM capability, the SSE shall format an ELM message for transfer using the short form MSP packet. If the message length is 27 to 159 bytes and the transponder has a limited downlink ELM capability, the SSE shall format multiple long form MSP packets (5.2.7.3.2) using ELM messages, as required utilizing the L-bit and M/SN fields for association of the packets. If the message length is 27 to 159 bytes and the transponder does not have downlink ELM capability, the SSE shall format multiple long form MSP packets (5.2.7.3.2) using air initiated Comm-B messages, as required utilizing the L-bit and M/SN fields for association of the packets. Different frame types shall never be used in the delivery of an MSP message. Messages longer than 159 bytes shall be discarded. The assignment of downlink MSP channel numbers shall be as specified in Table 5-25.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.1.1.4.2 Standard	For an MSP, a request to send a packet shall cause the packet to be multisite-directed to the interrogator which II code is specified in control data. If no II code is specified, the packet shall be downlinked using the air-initiated protocol. A message delivery notice for this packet shall be provided to the Mode S specific interface when the corresponding close-out(s) have been received from the transponder. If a close-out has not been received from the transponder in T_z seconds, as specified in Table 5-1, the MSP packet shall be discarded. This shall include the cancellation in the transponder of any frames associated with this packet. A delivery failure notice for this message shall be provided to the Mode S specific services interface.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.1.2.1 Standard	<p><i>5.2.7.1.2 UPLINK PROCESSING</i></p> <p><i>Note.— This section describes the processing of Mode S specific services messages received from the transponder.</i></p> <p><i>Specific services capability.</i> The ADLP shall be capable of receiving Mode S specific services messages from the transponder via frame processing. The ADLP shall be capable of delivering the messages and the associated control data at the specific services interface. When the resources allocated at this interface are insufficient to accommodate the output data, the ADLP shall discard the message and deliver an error report at this interface.</p> <p><i>Note.— The diagnostic content and the error reporting mechanism are a local issue.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.1.2.2 Standard	<i>Broadcast processing.</i> If the received message is a broadcast Comm-A, as indicated by control data received over the transponder/ADLP interface, the broadcast ID and user data (5.2.7.5) shall be forwarded to the Mode S specific services interface (5.2.3.2.1) along with the control data that identifies this as a broadcast message. The assignment of uplink broadcast identifier numbers shall be as specified in Table 5-23.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.1.2.3 Standard	<i>MSP processing.</i> If the received message is an MSP, as indicated by the packet format header (5.2.7.3), the user data field of the received MSP packet shall be forwarded to the Mode S specific services interface (5.2.3.2.1) together with the MSP channel number (M/CH), the IIS subfield (5.2.2.1.1.1) together with control data that identifies this as an MSP message. L-bit processing shall be performed as specified in 5.2.7.4. The assignment of uplink MSP channel numbers shall be as specified in Table 5-25.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.2.1.1 Standard	<p style="text-align: center;">5.2.7.2 GDLP PROCESSING</p> <p>5.2.7.2.1 UPLINK PROCESSING</p> <p><i>Specific services capability.</i> The GDLP shall be capable of receiving control and message data from the Mode S specific services interface(s) (5.2.3.2.2) and sending delivery notices to the interface(s). The control data shall be processed to determine the protocol type and the length of the message data.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.2.1.2 Standard	<i>Broadcast processing.</i> The GDLP shall determine the interrogator(s), broadcast azimuths and scan times from the control data and format the broadcast message for transfer to the interrogator(s) as specified in 5.2.7.5.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.2.1.3 Standard	<i>GICB processing.</i> The GDLP shall determine the register number and the aircraft address from the control data. The aircraft address and BDS code shall be passed to the interrogator as a request for a ground-initiated Comm-B.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.2.1.4 Standard	<i>MSP processing.</i> The GDLP shall extract from the control data the message length, the MSP channel number (M/CH) and the aircraft address, and obtain the message content from the message data. If the message length is 27 bytes or less, the SSE shall format a Comm-A message for transfer to the interrogator using the short form MSP packet (5.2.7.3.1). If the message length is 28 to 151 bytes and the transponder has uplink ELM capability, the SSE shall format an ELM message for transfer to the interrogator using the short form MSP packet. If the message length is 28 to 151 bytes and the transponder does not have uplink ELM capability, the SSE shall format multiple long form MSP packets (5.2.7.3.2) utilizing the L-bit and the M/SN fields for association of the packets. Messages longer than 151 bytes shall be discarded. The interrogator shall provide a delivery notice to the Mode S specific services interface(s) indicating successful or unsuccessful delivery, for each uplinked packet.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.2.2.1 Standard	5.2.7.2.2 <i>DOWNLINK PROCESSING</i> <i>Specific services capability.</i> The GDLP shall be capable of receiving Mode S specific services messages from the interrogator via frame processing.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.2.2.2 Standard	<i>Broadcast processing.</i> If the received message is a broadcast Comm-B, as indicated by the interrogator/GDLP interface, the GDLP shall: a) generate control data indicating the presence of a broadcast message and the 24-bit address of the aircraft from which the message was received; b) append the 7-byte MB field of the broadcast Comm-B; and c) forward this data to the Mode S specific services interface(s) (5.2.3.2.2).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.2.2.3 Standard	<i>GICB processing.</i> If the received message is a GICB, as indicated by the interrogator/GDLP interface, the GDLP shall: a) generate control data indicating the presence of a GICB message, the register number and the 24-bit address of the aircraft from which the message was received; b) append the 7-byte MB field of the GICB; and c) forward this data to the Mode S specific services interface(s) (5.2.3.2.2).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.2.2.4 Standard	<p><i>MSP processing.</i> If the received message is an MSP as indicated by the packet format header (5.2.7.3), the GDLP shall:</p> <ul style="list-style-type: none"> a) generate control data indicating the transfer of an MSP, the length of the message, the MSP channel number (M/CH) and the 24-bit address of the aircraft from which the message was received; b) append the user data field of the received MSP packet; and c) forward this data to the Mode S specific services interface(s) (5.2.3.2.2). <p>L-bit processing shall be performed as specified in 5.2.7.4.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.1 Standard	<p style="text-align: center;">5.2.7.3 MSP PACKET FORMATS</p> <p><i>Short form MSP packet.</i> The format for this packet shall be as follows:</p> <p style="text-align: center;">DP:1 MP:1 M/CH:6 FILL:0 or 6 UD:v</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.1.1 Standard	<p><i>Data packet type (DP).</i> This field shall be set to 0.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.1.2 Standard	<p><i>MSP packet type (MP).</i> This field shall be set to 0.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.3.1.3 Standard	<i>MSP channel number (M/CH)</i> . The field shall be set to the channel number derived from the SSE control data.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.1.4 Standard	<i>Fill field (FILL1:0 or 6)</i> . The fill length shall be 6 bits for a downlink SLM frame. Otherwise the fill length shall be 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.1.5 Standard	<i>User data (UD)</i> . The user data field shall contain message data received from the Mode S specific services interface (5.2.3.2.2).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.2 Standard	<i>Long form MSP packet</i> . The format for this packet shall be as follows: DP:1 MP:1 SP:2 L:1 M/SN:3 FILL2:0 or 2 M/CH:6 UD:v Fields shown in the packet format and not specified in the following paragraphs shall be set as specified in 5.2.5.2.1 and 5.2.7.3.1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.3.3 Standard	<i>Data packet type (DP)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.3.1 Standard	<i>MSP packet type (MP)</i> . This field shall be set to 1.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.3.2 Standard	<i>Supervisory packet (SP)</i> . This field shall be set to 0.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.3.3 Standard	<i>L field (L)</i> . A value of 1 shall indicate that the packet is part of an L-bit sequence with more packets in the sequence to follow. A value of 0 shall indicate that the sequence ends with this packet.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.3.3.4 Standard	<i>MSP sequence number field (M/SN)</i> . This field shall be used to detect duplication in the delivery of L-bit sequences. The first packet in an L-bit sequence shall be assigned a sequence number of 0. Subsequent packets shall be numbered sequentially. A packet received with the same sequence number as the previously received packet shall be discarded.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.4 Standard	<i>L-bit processing.</i> L-bit processing shall be performed only on the long form MSP packet and shall be performed as specified for M-bit processing (5.2.5.1.4.1) except as specified in the following paragraphs.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.4.1 Standard	Upon receipt of a long form MSP packet, the XDLP shall construct the user data field by: <ul style="list-style-type: none"> a) verifying that the packet order is correct using the M/SN field (5.2.7.3.2); b) assuming that the user data field in the MSP packet is the largest number of integral bytes that is contained within the frame; c) associating each user data field in an MSP packet received with a previous user data field in an MSP packet that has an L-bit value of 1; and <p style="margin-left: 20px;"><i>Note.— Truncation of the user data field is not permitted as this is treated as an error condition.</i></p> d) if an error is detected in the processing of an MSP packet, the packet shall be discarded. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.4.2 Standard	In the processing of an L-bit sequence, the XDLP shall discard any MSP packets that have duplicate M/SN values. The XDLP shall discard the entire L-bit sequence if a long form MSP packet is determined to be missing by use of the M/SN field.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.7.4.3 Standard	The packets associated with any L-bit sequence whose reassembly is not completed in <i>T_m</i> seconds (Tables 5-1 and 5-13) shall be discarded.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.5.1 Standard	5.2.7.5 BROADCAST FORMAT <i>Uplink Broadcast.</i> The format of the broadcast Comm-A shall be as follows: The 83-bit uplink broadcast shall be inserted in an uplink Comm-A frame. The MA field of the Comm-A frame shall contain the broadcast identifier specified in Table 5-23 in the first 8 bits, followed by the first 48 user data bits of the broadcast message. The last 27 user data bits of the broadcast message shall be placed in the 27 bits immediately following the UF field of the Comm-A frame.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.7.5.2 Standard	<i>Downlink broadcast.</i> The format of broadcast Comm-B shall be as follows: The 56-bit downlink broadcast message shall be inserted in the MB field of the broadcast Comm-B. The MB field shall contain the broadcast identifier specified in Table 5-23 in the first 8 bits, followed by the 48 user data bits.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.8.1.1 Standard	<p style="text-align: center;">5.2.8 Mode S subnetwork management</p> <p style="text-align: center;">5.2.8.1 INTERROGATOR LINK DETERMINATION FUNCTION</p> <p><i>Note.— The ADLP interrogator link determination function selects the II code of the Mode S interrogator through which a Mode S subnetwork packet may be routed to the desired destination ground DTE.</i></p> <p><i>II code-DTE address correlation.</i> The ADLP shall construct and manage a Mode S interrogator-data terminal equipment (DTE) cross-reference table whose entries are Mode S interrogator identifier (II) codes and ground DTE addresses associated with the ground ATN routers or other ground DTEs. Each entry of the II code-DTE cross-reference table shall consist of the 4-bit Mode S II code and the 8-bit binary representation of the ground DTE.</p> <p><i>N1.Due to the requirement for non-ambiguous addresses, a DTE address also uniquely identifies a GDLP.</i></p> <p><i>N2.An ATN router may have more than one ground DTE address.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.8.1.2 Standard	<p><i>Protocol.</i> The following procedures shall be used:</p> <ul style="list-style-type: none"> a) when the GDLP initially detects the presence of an aircraft, or detects contact with a currently acquired aircraft through an interrogator with a new II code, the appropriate fields of the DATA LINK CAPABILITY report shall be examined to determine if, and to what level, the aircraft has the capability to participate in a data exchange. After positive determination of data link capability, the GDLP shall uplink one or more Mode S ROUTE packets as specified in 5.2.5.3.3. This information shall relate the Mode S II code with the ground DTE addresses accessible through that interrogator. The ADLP shall update the II code-DTE cross-reference table and then discard the Mode S ROUTE packet(s); b) a II code-DTE cross-reference table entry shall be deleted when commanded by a Mode S ROUTE packet or when the ADLP recognizes that the transponder has not been selectively interrogated by a Mode S interrogator with a given II code for <i>T</i>_s seconds by monitoring the IIS subfield in Mode S surveillance or Comm-A interrogations (Table 5-1); c) when the GDLP determines that modification is required to the Mode S interrogator assignment, it shall transfer one or more Mode S ROUTE packets to the ADLP. The update information contained in the Mode S ROUTE packet shall be used by the ADLP to modify its cross-reference table. Additions shall be processed before deletions; d) when the GDLP sends the initial ROUTE packet after acquisition of a Mode S data link-equipped aircraft, the IN bit shall be set to ONE. This value shall cause the ADLP to perform the procedures as specified in 5.2.6.3.3.3. Otherwise, the IN bit shall be set to ZERO; e) when the ADLP is initialized (e.g. after a power-up procedure), the ADLP shall issue a search request by sending a broadcast Comm-B message with 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>broadcast identifier equal to 255 (FF16, as specified in Table 5-23) and the remaining 6 bytes unused. On receipt of a search request, a GDLP shall respond with one or more Mode S ROUTE packets, clear all SVCs associated with the ADLP, as specified in 5.2.6.3.3, and discard the search request. This shall cause the ADLP to initialize the II code-DTE cross-reference table; and</p> <p>f) on receipt of an update request (Table 5-23), a GDLP shall respond with one or more Mode S ROUTE packets and discard the update request. This shall cause the ADLP to update the II code-DTE cross-reference table.</p> <p><i>Note.— The update request may be used by the ADLP under exceptional circumstances (e.g. changeover to standby unit) to verify the contents of its II code-DTE cross-reference table.</i></p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 5 Reference 5.2.8.1.3.1</p> <p>Standard</p>	<p>5.2.8.1.3 PROCEDURES FOR DOWNLINKING MODE S PACKETS</p> <p>When the ADLP has a packet to downlink, the following procedures shall apply:</p> <p>a) <i>CALL REQUEST packet.</i> If the packet to be transferred is a Mode S CALL REQUEST, the ground DTE address field shall be examined and shall be associated with a connected Mode S interrogator using the II code-DTE cross-reference table. The packet shall be downlinked using the multisite-directed protocol. A request to transfer a packet to a DTE address not in the cross-reference table shall result in the action specified in 5.2.6.3.3.1.</p> <p>b) <i>Other SVC packets.</i> For an SVC, a request to send a packet to a ground DTE shall cause the packet to be multisite-directed to the last Mode S interrogator used to successfully transfer (uplink or downlink) a packet to that DTE, provided that this Mode S interrogator is currently in the II code-DTE cross-reference table. Otherwise, an SVC packet shall be downlinked using the multisite-directed protocol to any other Mode S interrogator associated with the specified ground DTE address.</p> <p>Level 5 transponders shall be permitted to use additional interrogators for downlink transfer as indicated in the II code-DTE cross-reference table.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>Less protective or partially implemented or not implemented</p>		<p>Not used in Cabo Verde</p>



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.8.1.3.2 Standard	A downlink frame transfer shall be defined to be successful if its Comm-B or ELM close-out is received from the transponder within T_z seconds as specified in Table 5-1. If the attempt is not successful and an SVC packet is to be sent, the II code-DTE cross-reference table shall be examined for another entry with the same called ground DTE address and a different Mode S II code. The procedure shall be retried using the multisite-directed protocol with the new Mode S interrogator. If there are no entries for the required called DTE, or all entries result in a failed attempt, a link failure shall be declared (5.2.8.3.1).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.8.2.1 Standard	5.2.8.2 SUPPORT FOR THE DTE(S) <i>GDLP connectivity reporting.</i> The GDLP shall notify the ground DTE(s) of the availability of a Mode S data link-equipped aircraft ("join event"). The GDLP shall also inform the ground DTEs when such an aircraft is no longer in contact via that GDLP ("leave event"). The GDLP shall provide for notification (on request) of all Mode S data link-equipped aircraft currently in contact with that GDLP. The notifications shall provide the ground ATN router with the subnetwork point of attachment (SNPA) address of the mobile ATN router, with the position of the aircraft and quality of service as optional parameters. The SNPA of the mobile ATN router shall be the DTE address formed by the aircraft address and a sub-address of 0 (5.2.3.1.3.2).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.8.2.2 Standard	<i>ADLP connectivity reporting.</i> The ADLP shall notify all aircraft DTEs whenever the last remaining entry for a ground DTE is deleted from the II code-DTE cross-reference table (5.2.8.1.1). This notification shall include the address of this DTE.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.8.2.3 Standard	<i>Communications requirements.</i> The mechanism for communication of changes in subnetwork connectivity shall be a confirmed service, such as the join/leave events that allow notification of the connectivity status.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.8.3.1 Standard	5.2.8.3 ERROR PROCEDURES <i>Link failure.</i> The failure to deliver a packet to the referenced XDLP after an attempt has been made to deliver this packet via all available interrogators shall be declared to be a link level failure. For an SVC, the XDCE shall enter the state <i>p1</i> , and release all resources associated with that channel. This shall include the cancellation in the transponder of any frames associated with this SVC. A Mode S CLEAR REQUEST packet shall be sent to the DCE via the reformatting process and shall be forwarded by the DCE as an ISO 8208 packet to the local DTE as described in 5.2.6.3.3. On the aircraft side, the channel shall not be returned to the ADCE channel pool, i.e. does not return to the state <i>p1</i> , until <i>Tr</i> seconds after the link failure has been declared (Table 5-1).	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.8.3.2.1 Standard	5.2.8.3.2 <i>ACTIVE CHANNEL DETERMINATION</i> <i>Procedure for d1 state.</i> The XDLP shall monitor the activity of all SVCs, not in a READY state (p1). If an SVC is in the (XDCE) FLOW CONTROL READY state (d1) for more than Tx seconds (the active channel timer, Tables 5-1 and 5-13) without sending a Mode S RR, RNR, DATA, or REJECT packet, then: a) if the last packet sent was a Mode S REJECT packet to which a response has not been received, then the XDLP shall resend that packet; b) otherwise, the XDLP shall send a Mode S RR or RNR packet as appropriate to the peer XDLP.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.8.3.2.2 Standard	<i>Procedure for other states.</i> If an XDCE SVC is in the p2, p3, p6, p7, d2 or d3 state for more than Tx seconds, the link failure procedure of 5.2.8.3.1 shall be performed.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.8.3.2.3 Standard	Link failure shall be declared if either a failure to deliver, or a failure to receive, keep-alive packets has occurred. In which case the channel shall be cleared.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.9 Standard	The data link capability report The data link capability report shall be as specified in Annex 10, Volume IV, 3.1.2.6.10.2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.10.1 Standard	<p style="text-align: center;">5.2.10 System timers</p> <p>The values for timers shall conform to the values given in Tables 5-1 and 5-13.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.10.2 Standard	Tolerance for all timers shall be plus or minus one percent.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.10.3 Standard	Resolution for all timers shall be one second.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.11.1 Standard	<p style="text-align: center;">5.2.11 System requirements</p> <p><i>Data integrity.</i> The maximum bit error rates for data presented at the ADLP/transponder interface or the GDLP/interrogator interface measured at the local DTE/XDLP interface (and vice versa) shall not exceed 10^{-9} for undetected errors and 10^{-7} for detected errors.</p> <p><i>Note.— The maximum error rate includes all errors resulting from data transfers across the interfaces and from XDLP internal operation.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.11.2.1 Standard	<p style="text-align: center;">5.2.11.2 TIMING</p> <p><i>ADLP timing.</i> ADLP operations shall not take longer than 0.25 seconds for regular traffic and 0.125 seconds for interrupt traffic. This interval shall be defined as follows:</p> <ul style="list-style-type: none"> a) <i>Transponders with downlink ELM capability.</i> The time that the final bit of a 128-byte data packet is presented to the DCE for downlink transfer to the time that the final bit of the first encapsulating frame is available for delivery to the transponder. b) <i>Transponders with Comm-B capability.</i> The time that the final bit of a user data field of 24 bytes is presented to the DCE for downlink transfer to the time that the final bit of the last of the four Comm-B segments that forms the frame encapsulating the user data is available for delivery to the transponder. c) <i>Transponders with uplink ELM capability.</i> The time that the final bit of the last segment of an ELM of 14 Comm-C segments that contains a user data field of 128 bytes is received by the ADLP to the time that the final bit of the corresponding packet is available for delivery to the DTE. d) <i>Transponders with Comm-A capability.</i> The time that the final bit of the last segment of four linked Comm-A segments that contains a user data field of 25 bytes is received by the ADLP to the time that the final bit of the corresponding packet is available for delivery to the DTE. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.2.11.2.2 Recommendation	<p>GDLP TIMING</p> <p>Recommendation.— <i>The total time delay across the GDLP, exclusive of transmission delay, should not be greater than 0.125 seconds.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.11.3 Standard	<i>Interface rate.</i> The physical interface between the ADLP and the transponder shall have a minimum bit rate of 100 kilobits per second.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Chapter 5 Reference 5.3.1 Standard	<p style="text-align: center;">5.3 DCE AND XDCE STATE TABLES</p> <p><i>State table requirements.</i> The DCE and XDCE shall function as specified in state Tables 5-3 to 5-22. State Tables 5-15 through 5-22 shall be applied to:</p> <ul style="list-style-type: none"> a) ADLP state transitions when the XDCE or XDLP terms in parenthesis are omitted; and b) GDLP state transitions when the terms in parenthesis are used and the XDCE or XDLP preceding them are omitted. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.2 Standard	<p><i>Diagnostic and cause codes.</i> The table entries for certain conditions indicate a diagnostic code that shall be included in the packet generated when entering the state indicated. The term, “D = ,” shall define the diagnostic code. When “A = DIAG,” the action taken shall be to generate an ISO 8208 DIAGNOSTIC packet and transfer it to the DTE; the diagnostic code indicated shall define the entry in the diagnostic field of the packet. The cause field shall be set as specified in 5.2.6.3.3. The reset cause field shall be set as specified in ISO 8208.</p> <p>N1.<i>The tables provided below specify state requirements in the following order:</i></p> <p>5-3 <i>DCE special cases</i></p> <p>5-4 <i>DTE effect on DCE restart states</i></p> <p>5-5 <i>DTE effect on DCE call setup and clearing states</i></p> <p>5-6 <i>DTE effect on DCE reset states</i></p> <p>5-7 <i>DTE effect on DCE interrupt transfer states</i></p> <p>5-8 <i>DTE effect on DCE flow control transfer states</i></p> <p>5-9 <i>XDCE effect on DCE restart states</i></p> <p>5-10 <i>XDCE effect on DCE all setup and clearing states</i></p> <p>5-11 <i>XDCE effect on DCE reset states</i></p> <p>5-12 <i>XDCE effect on DCE interrupt transfer states</i></p> <p>5-15 <i>GDLP (ADLP) effect on ADCE (GDCE) packet layer ready states</i></p> <p>5-16 <i>GDLP (ADLP) effect on ADCE (GDCE) call setup and clearing states</i></p> <p>5-17 <i>GDLP (ADLP) effect on ADCE (GDCE) reset states</i></p> <p>5-19 <i>GDLP (ADLP) effect on ADCE (GDCE) interrupt transfer states</i></p> <p>5-19 <i>GDLP (ADLP) effect on ADCE (GDCE) flow control transfer states</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>5-20 DCE effect on ADCE (GDCE) call setup and clearing states</p> <p>5-21 DCE effect on ADCE (GDCE) reset states</p> <p>5-22 DCE effect on ADCE (GDCE) interrupt transfer states</p> <p>N2. All tables specify both ADLP and GDLP actions.</p> <p>N3. Within the Mode S subnetwork, states p6 and d2 are transient states.</p> <p>N4. References to "notes" in the state tables refer to table-specific notes that follow each state table.</p> <p>N5. All diagnostic and cause codes are interpreted as decimal numbers.</p> <p>N6. An SVC between an ADCE and a GDCE may be identified by a temporary and/or permanent channel number, as defined in 5.2.5.1.2.</p>				
<p>Chapter 5 Reference 5.4.1 Standard</p>	<p>5.4 MODE S PACKET FORMATS</p> <p><i>Formats.</i> The Mode S packet formats shall be as specified in Figures 5-3 to 5-22.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>Less protective or partially implemented or not implemented</p>		<p>Not used in Cabo Verde</p>



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																						
Chapter 5 Reference 5.4.2 Standard	<p><i>Significance of control fields.</i> The structure of the format control fields used in Mode S packets shall be as specified in Figure 5-23. The significance of all control fields used in these packet formats shall be as follows:</p> <table border="0"> <tr> <td><i>Field symbol</i></td> <td><i>Definition</i></td> </tr> <tr> <td>AG</td> <td>Address, Ground; the 8-bit binary representation of the ground DTE address (5.2.3.1.3.1)</td> </tr> <tr> <td>AM</td> <td>Address, Mobile; the 4-bit binary representation of the last two BCD digits of the mobile DTE address (5.2.3.1.3.2)</td> </tr> <tr> <td>CC</td> <td>Clearing cause as defined in ISO 8208</td> </tr> <tr> <td>CH</td> <td>channel number (1 to 15)</td> </tr> <tr> <td>DC</td> <td>Diagnostic code as defined in ISO 8208</td> </tr> <tr> <td>DP</td> <td>Data packet type (Figure 5-23)</td> </tr> <tr> <td>F</td> <td>S-bit sequence, first packet flag</td> </tr> <tr> <td>FILL</td> <td>Fill field</td> </tr> <tr> <td>FILL1</td> <td>Has a length of 6 bits for a non-multiplexed packet in a downlink SLM frame; otherwise it is 0 bit</td> </tr> <tr> <td>FILL2</td> <td>Has a length of 0 bit for a non-multiplexed packet in a downlink SLM frame and fro a multiplexing header; otherwise it is 2 bits</td> </tr> <tr> <td>FIRST PACKET</td> <td>The contents of the first of the multiplexed packets</td> </tr> <tr> <td>FS</td> <td>Fast select present</td> </tr> <tr> <td>IN</td> <td>Initialization bit</td> </tr> <tr> <td>L</td> <td>“More bit” for long-form MSP packets as specified in 5.2.7.4</td> </tr> <tr> <td>LAST PACKET</td> <td>The contents of the last of the multiplexed packets</td> </tr> <tr> <td>LENGTH</td> <td>The length of a multiplexed packet in bytes expressed as an unsigned binary number</td> </tr> <tr> <td>LV</td> <td>User data field length; number of user bytes as specified in 5.2.2.3.1</td> </tr> <tr> <td>M</td> <td>“More bit” for SVC DATA packets as</td> </tr> </table>	<i>Field symbol</i>	<i>Definition</i>	AG	Address, Ground; the 8-bit binary representation of the ground DTE address (5.2.3.1.3.1)	AM	Address, Mobile; the 4-bit binary representation of the last two BCD digits of the mobile DTE address (5.2.3.1.3.2)	CC	Clearing cause as defined in ISO 8208	CH	channel number (1 to 15)	DC	Diagnostic code as defined in ISO 8208	DP	Data packet type (Figure 5-23)	F	S-bit sequence, first packet flag	FILL	Fill field	FILL1	Has a length of 6 bits for a non-multiplexed packet in a downlink SLM frame; otherwise it is 0 bit	FILL2	Has a length of 0 bit for a non-multiplexed packet in a downlink SLM frame and fro a multiplexing header; otherwise it is 2 bits	FIRST PACKET	The contents of the first of the multiplexed packets	FS	Fast select present	IN	Initialization bit	L	“More bit” for long-form MSP packets as specified in 5.2.7.4	LAST PACKET	The contents of the last of the multiplexed packets	LENGTH	The length of a multiplexed packet in bytes expressed as an unsigned binary number	LV	User data field length; number of user bytes as specified in 5.2.2.3.1	M	“More bit” for SVC DATA packets as	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
<i>Field symbol</i>	<i>Definition</i>																																										
AG	Address, Ground; the 8-bit binary representation of the ground DTE address (5.2.3.1.3.1)																																										
AM	Address, Mobile; the 4-bit binary representation of the last two BCD digits of the mobile DTE address (5.2.3.1.3.2)																																										
CC	Clearing cause as defined in ISO 8208																																										
CH	channel number (1 to 15)																																										
DC	Diagnostic code as defined in ISO 8208																																										
DP	Data packet type (Figure 5-23)																																										
F	S-bit sequence, first packet flag																																										
FILL	Fill field																																										
FILL1	Has a length of 6 bits for a non-multiplexed packet in a downlink SLM frame; otherwise it is 0 bit																																										
FILL2	Has a length of 0 bit for a non-multiplexed packet in a downlink SLM frame and fro a multiplexing header; otherwise it is 2 bits																																										
FIRST PACKET	The contents of the first of the multiplexed packets																																										
FS	Fast select present																																										
IN	Initialization bit																																										
L	“More bit” for long-form MSP packets as specified in 5.2.7.4																																										
LAST PACKET	The contents of the last of the multiplexed packets																																										
LENGTH	The length of a multiplexed packet in bytes expressed as an unsigned binary number																																										
LV	User data field length; number of user bytes as specified in 5.2.2.3.1																																										
M	“More bit” for SVC DATA packets as																																										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	specified in 5.2.5.1.4.1 M/CH MSP channel number MP MSP packet type (Figure 5-23) M/SN Sequence number; the sequence number for the long form MSP packet OD Optional data ODL Optional data length OF Option flag P Priority field PR Packet receive sequence number PS Packet send sequence number RC Resetting cause code as defined in ISO 8208 RT Route table as defined in 5.2.5.3.3.8 RTL Route table length expressed in bytes S "More bit" for CALL REQUEST, CALL ACCEPT, CLEAR REQUEST and INTERRUPT packets as specified in 5.2.5.1.4.2 SN Sequence number; the sequence number for this packet type SP Supervisory packet (Figure 5-23) SS Supervisory subset number (Figure 5- 23) ST Supervisory type (Figure 5-23) TC Temporary channel number (1 to 3) UD User data field				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 6 Reference</p> <p>Definition</p>	<p style="text-align: center;">CHAPTER 6. VHF AIR-GROUND DIGITAL LINK (VDL)</p> <p style="text-align: center;">6.1 DEFINITIONS AND SYSTEM CAPABILITIES</p> <p><i>N1.The very high frequency (VHF) digital link (VDL) Mode 2 and the VDL Mode 4 provide data service capabilities. The VDL Mode 3 provides both voice and data service capabilities. The data capability is a constituent mobile subnetwork of the aeronautical telecommunication network (ATN). In addition, the VDL may provide non-ATN functions. Standards and Recommended Practices (SARPs) for the VDL are defined and referenced below.</i></p> <p><i>N2.Additional information on VDL is contained in the Manuals on VHF VDL Mode 2, VDL Mode 3 and VDL Mode 4 Technical Specifications (Docs 9776, 9805 and 9816).</i></p> <p><i>N3.Sections 6.1.2 to 6.8.2 contain Standards and Recommended Practices for VDL Modes 2 and 3. Section 6.9 contains Standards and Recommended Practices for VDL Node 4.</i></p> <p style="text-align: center;">6.1.1 Definitions</p> <p><i>Automatic dependent surveillance-broadcast (ADS-B). A means by which aircraft, aerodrome vehicles and other objects can automatically transmit and/or receive data such as identification, position and additional data, as appropriate, in a broadcast mode via a data link.</i></p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	Broadcast. A transmission of information relating to air navigation that is not addressed to a specific station or stations.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Burst. A time-defined, contiguous set of one or more related signal units which may convey user information and protocols, signalling, and any necessary preamble.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Current slot. The slot in which a received transmission begins.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Data circuit-terminating equipment (DCE). A DCE is a network provider equipment used to facilitate communications between DTEs.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Data link entity (DLE). A protocol state machine capable of setting up and managing a single data link connection.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	Data link service (DLS) sublayer. The sublayer that resides above the MAC sublayer. For VDL Mode 4, the DLS sublayer resides above the VSS sublayer. The DLS manages the transmit queue, creates and destroys DLEs for connection-oriented communications, provides facilities for the LME to manage the DLS, and provides facilities for connectionless communications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Data terminal equipment (DTE). A DTE is an endpoint of a subnetwork connection.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Extended Golay Code. An error correction code capable of correcting multiple bit errors.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Frame. The link layer frame is composed of a sequence of address, control, FCS and information fields. For VDL Mode 2, these fields are bracketed by opening and closing flag sequences, and a frame may or may not include a variable-length information field.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	Gaussian filtered frequency shift keying (GFSK). A continuous-phase, frequency shift keying technique using two tones and a Gaussian pulse shape filter.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Global signalling channel (GSC). A channel available on a worldwide basis which provides for communication control.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Link. A link connects an aircraft DLE and a ground DLE and is uniquely specified by the combination of aircraft DLS address and the ground DLS address. A different subnetwork entity resides above every link endpoint.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Link layer. The layer that lies immediately above the physical layer in the Open Systems Interconnection protocol model. The link layer provides for the reliable transfer of information across the physical media. It is subdivided into the data link sublayer and the media access control sublayer.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	Link management entity (LME). A protocol state machine capable of acquiring, establishing and maintaining a connection to a single peer system. An LME establishes data link and subnetwork connections, “hands-off” those connections, and manages the media access control sublayer and physical layer. An aircraft LME tracks how well it can communicate with the ground stations of a single ground system. An aircraft VME instantiates an LME for each ground station that it monitors. Similarly, the ground VME instantiates an LME for each aircraft that it monitors. An LME is deleted when communication with the peer system is no longer viable.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	M burst. A management channel data block of bits used in VDL Mode 3. This burst contains signalling information needed for media access and link status monitoring.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Media access control (MAC). The sublayer that acquires the data path and controls the movement of bits over the data path.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Mode 2. A data-only VDL mode that uses D8PSK modulation and a carrier sense multiple access (CSMA) control scheme.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	Mode 3. A voice and data VDL mode that uses D8PSK modulation and a TDMA media access control scheme.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Mode 4. A data-only VDL mode using a GFSK modulation scheme and self-organizing time division multiple access (STDMA).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Physical layer. The lowest level layer in the Open Systems Interconnection protocol model. The physical layer is concerned with the transmission of binary information over the physical medium (e.g. VHF radio).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Quality of service. The information relating to data transfer characteristics used by various communication protocols to achieve various levels of performance for network users.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Reed-Solomon code. An error correction code capable of correcting symbol errors. Since symbol errors are collections of bits, these codes provide good burst error correction capabilities.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	Self-organizing time division multiple access (STDMA). A multiple access scheme based on time-shared use of a radio frequency (RF) channel employing: (1) discrete contiguous time slots as the fundamental shared resource; and (2) a set of operating protocols that allows users to mediate access to these time slots without reliance on a master control station.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Slot. One of a series of consecutive time intervals of equal duration. Each burst transmission starts at the beginning of a slot.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Subnetwork connection. A long-term association between an aircraft DTE and a ground DTE using successive virtual calls to maintain context across link handoff.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Subnetwork dependent convergence function (SND CF). A function that matches the characteristics and services of a particular subnetwork to those characteristics and services required by the internetwork facility.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	Subnetwork entity. In this document, the phrase “ground DCE” will be used for the subnetwork entity in a ground station communicating with an aircraft; the phrase “ground DTE” will be used for the subnetwork entity in a ground router communicating with an aircraft station; and, the phrase “aircraft DTE” will be used for the subnetwork entity in an aircraft communicating with the station. A subnetwork entity is a packet layer entity as defined in ISO 8208.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Subnetwork layer. The layer that establishes, manages and terminates connections across a subnetwork.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	System. A VDL-capable entity. A system comprises one or more stations and the associated VDL management entity. A system may either be an aircraft system or a ground system.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Time division multiple access (TDMA). A multiple access scheme based on time-shared use of an RF channel employing: (1) discrete contiguous time slots as the fundamental shared resource; and (2) a set of operating protocols that allows users to interact with a master control station to mediate access to the channel.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	User group. A group of ground and/or aircraft stations which share voice and/or data connectivity. For voice communications, all members of a user group can access all communications. For data, communications include point-to-point connectivity for air-to-ground messages, and point-to-point and broadcast connectivity for ground-to-air messages.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	VDL management entity (VME). A VDL-specific entity that provides the quality of service requested by the ATN-defined SN_SME. A VME uses the LMEs (that it creates and destroys) to enquire the quality of service available from peer systems.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	VDL Mode 4 burst. A VHF digital link (VDL) Mode 4 burst is composed of a sequence of source address, burst ID, information, slot reservation and frame check sequence (FCS) fields, bracketed by opening and closing flag sequences. <i>Note.— The start of a burst may occur only at quantized time intervals and this constraint allows the propagation delay between the transmission and reception to be derived.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	VDL Mode 4 DLS system. A VDL system that implements the VDL Mode 4 DLS and subnetwork protocols to carry ATN packets or other packets.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference Definition	VDL Mode 4 specific services (VSS) sublayer. The sublayer that resides above the MAC sublayer and provides VDL Mode 4 specific access protocols including reserved, random and fixed protocols.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	VDL station. An aircraft-based or ground-based physical entity, capable of VDL Mode 2, 3 or 4. <i>Note.— In the context of this chapter, a VDL station is also referred to as a “station”.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Vocoder. A low bit rate voice encoder/decoder.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	Voice unit. A device that provides a simplex audio and signalling interface between the user and VDL.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference Definition	VSS user. A user of the VDL Mode 4 specific services. The VSS user could be higher layers in the VDL Mode 4 SARPs or an external application using VDL Mode 4.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.1.2.1 Standard	<p align="center">6.1.2 Radio channels and functional channels</p> <p><i>Aircraft station radio frequency range.</i> An aircraft station shall be capable of tuning to any of the channels in the range specified in Section 6.1.4.1 within 100 milliseconds after the receipt of an autotune command. In addition, for VDL Mode 3, an aircraft station shall be able to tune to any channel in the range specified in Section 6.1.4.1 within 100 milliseconds after the receipt of any tuning command.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.1.2.2 Standard	<i>Ground station radio frequency range.</i> A ground station shall be capable of operating on its assigned channel within the radio frequency range detailed in 6.1.4.1.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.1.2.3 Standard	<i>Common signalling channel.</i> Frequency 136.975MHz shall be reserved as a worldwide common signalling channel (CSC) for VDL Mode 2.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.1.3.1 Standard	<p align="center">6.1.3 System capabilities</p> <p><i>Data transparency.</i> The VDL system shall provide code-independent, byte-independent transfer of data.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.1.3.2 Standard	<i>Broadcast.</i> The VDL system shall provide link layer data broadcast services (Mode 2) and/or voice and data broadcast services (Mode 3). For VDL Mode 3, the data broadcast service shall support network multicasting capability originating from the ground.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.1.3.3 Standard	<i>Connection management.</i> The VDL system shall establish and maintain a reliable communications path between the aircraft and the ground system while allowing but not requiring manual intervention. <i>Note.— In this context “reliable” is defined by the BER requirement specified in 6.3.5.1.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.1.3.4 Standard	<i>Ground network transition.</i> A VDL-equipped aircraft shall transition from one ground station to another when circumstances dictate.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.1.3.5 Standard	<i>Voice capability.</i> The VDL Mode 3 system shall support a transparent, simplex voice operation based on a “Listen-Before-Push-To-Talk” channel access.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.1.4.1 Standard	<p>6.1.4 Air-ground VHF digital link communications system characteristics</p> <p>The radio frequencies used shall be selected from the radio frequencies in the band 117.975 – 137 MHz. The lowest assignable frequency shall be 118.000 MHz, and the highest assignable frequency shall be 136.975 MHz. The separation between assignable frequencies (channel spacing) shall be 25 kHz.</p> <p><i>Note.— Volume V specifies that the block of frequencies from 136.9 – 136.975 MHz inclusive is reserved for VHF air-ground digital communications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.1.4.2 Standard	The design polarization of emissions shall be vertical.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.1.1 Standard	<p>6.2 SYSTEM CHARACTERISTICS OF THE GROUND INSTALLATION</p> <p>6.2.1 Ground station transmitting function</p> <p><i>Frequency stability.</i> The radio frequency of VDL ground station equipment operation shall not vary more than plus or minus 0.0002 per cent (2 parts per million) from the assigned frequency.</p> <p><i>Note.— The frequency stability for VDL ground stations using DSB-AM modulation is specified in Part II, Chapter 2 for 25 kHz channel spacing.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.2 Recommendation	<p style="text-align: center;">Power</p> <p>Recommendation.— <i>The effective radiated power should be such as to provide a field strength of at least 75 microvolts per metre (minus 109 dBW/m²) within the defined operational coverage of the facility, on the basis of free-space propagation.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.3.1 Standard	<p style="text-align: center;">6.2.3 Spurious emissions</p> <p>Spurious emissions shall be kept at the lowest value which the state of the technique and the nature of the service permit. <i>Note.— Appendix S3 to the Radio Regulations specifies the levels of spurious emissions to which transmitters must conform.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.4.1 Standard	<p style="text-align: center;">6.2.4 Adjacent channel emissions</p> <p>The amount of power from a VDL ground transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the first adjacent channel shall not exceed 0 dBm.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.4.1.1 Standard	<p>After 1 January 2002, the amount of power from all new installations of a VDL ground transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the first adjacent channel shall not exceed 2 dBm.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.4.2 Standard	The amount of power from a VDL ground transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the second adjacent channel shall be less than minus 25 dBm and from thereon it shall monotonically decrease at the minimum rate of 5 dB per octave to a maximum value of minus 52 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.4.2.1 Standard	After 1 January 2002, the amount of power from all new installations of a VDL ground transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the second adjacent channel shall be less than minus 28 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.4.2.2 Standard	After 1 January 2002, the amount of power from all new installations of a VDL ground transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the fourth adjacent channel shall be less than minus 38 dBm, and from thereon it shall monotonically decrease at the minimum rate of 5 dB per octave to a maximum value of minus 53 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.4.3 Standard	The amount of power from a VDL ground transmitter under all operating conditions when measured over a 16 kHz channel bandwidth centered on the first adjacent channel shall not exceed minus 20 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.4.3.1 Standard	After 1 January 2002, the amount of power from all new installations of a VDL ground transmitter under all operating conditions when measured over a 16 kHz channel bandwidth centred on the first adjacent channel shall not exceed minus 18 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.4.4 Standard	After 1 January 2005, all VDL ground transmitters shall meet the provisions of 6.2.4.1.1, 6.2.4.2.1, 6.2.4.2.2 and 6.2.4.3.1, subject to the conditions of 6.2.4.5.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.2.4.5 Standard	Requirements of mandatory compliance of the provisions of 6.2.4.4 shall be made on the basis of regional air navigation agreements which specify the airspace of operation and the implementation timescales. The agreements shall provide at least two years' notice of mandatory compliance of ground systems.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.1 Standard	<p style="text-align: center;">6.3 SYSTEM CHARACTERISTICS OF THE AIRCRAFT INSTALLATION</p> <p><i>Frequency stability.</i> The radio frequency of VDL aircraft equipment shall not vary more than plus or minus 0.0005 per cent (5 parts per million) from the assigned frequency.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.2 Standard	<i>Power.</i> The effective radiated power shall be such as to provide a field strength of at least 20 microvolts per metre (minus 120 dBW/m ²) on the basis of free-space propagation, at ranges and altitudes appropriate to the operational conditions pertaining to the areas over which the aircraft is operated.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.3.1 Standard	6.3.3 Spurious emissions Spurious emissions shall be kept at the lowest value which the state of the technique and the nature of service permit. <i>Note.— Appendix S3 to the Radio Regulations specifies the levels of spurious emissions to which transmitters must conform.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.4.1 Standard	6.3.4 Adjacent channel emissions The amount of power from a VDL aircraft transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the first adjacent channel shall not exceed 0 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.4.1.1 Standard	After 1 January 2002, the amount of power from all new installations of a VDL aircraft transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the first adjacent channel shall not exceed 2 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.4.2 Standard	The amount of power from a VDL aircraft transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the second adjacent channel shall be less than minus 25 dBm and from thereon it shall monotonically decrease at the minimum rate of 5 dB per octave to a maximum value of minus 52 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.4.2.1 Standard	After 1 January 2002, the amount of power from all new installations of a VDL aircraft transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the second adjacent channel shall be less than minus 28 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.4.2.2 Standard	After 1 January 2002, the amount of power from all new installations of a VDL aircraft transmitter under all operating conditions when measured over the 25 kHz channel bandwidth of the fourth adjacent channel shall be less than minus 38 dBm, and from thereon it shall monotonically decrease at the minimum rate of 5 dB per octave to a maximum value of minus 53 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.4.3 Standard	The amount of power from a VDL aircraft transmitter under all operating conditions when measured over a 16 kHz channel bandwidth centred on the first adjacent channel shall not exceed minus 20 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.4.3.1 Standard	After 1 January 2002, the amount of power from all new installations of a VDL aircraft transmitter under all operating conditions when measured over a 16 kHz channel bandwidth centred on the first adjacent channel shall not exceed minus 18 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.4.4 Standard	After 1 January 2005, all VDL aircraft transmitters shall meet the provisions of 6.3.4.1.1, 6.3.4.2.1, 6.3.4.2.2 and 6.3.4.3.1, subject to the conditions of 6.3.4.5.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.4.5 Standard	Requirements of mandatory compliance of the provisions of 6.3.4.4 shall be made on the basis of regional air navigation agreements which specify the airspace of operation and the implementation timescales. The agreements shall provide at least two years' notice of mandatory compliance of aircraft systems.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.5.1 Standard	<p style="text-align: center;">6.3.5 Receiving function</p> <p><i>Specified error rate.</i> The specified error rate for Mode 2 operation shall be the maximum corrected Bit Error Rate (BER) of 1 in 10⁴. The specified error rate for Mode 3 operation shall be the maximum uncorrected BER of 1 in 10³. The specified error rate for Mode 4 operation shall be the maximum uncorrected BER of 1 in 10⁴.</p> <p><i>Note.— The above physical layer BER requirements are derived from the BER requirement imposed by ATN at the subnetwork interface.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.5.2 Standard	<p><i>Sensitivity.</i> The receiving function shall satisfy the specified error rate with a desired signal strength of not more than 20 microvolts per metre (minus 120 dBW/m²).</p> <p><i>Note.— The required signal strength at the edge of the service volume takes into account the requirements of the system and signal losses within the system, and considers environmental noise sources.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.5.3 Standard	<p><i>Out-of-band immunity performance.</i> The receiving function shall satisfy the specified error rate with a desired signal field strength of not more than 40 microvolts per metre (minus 114 dBW/m²) and with an undesired DSB-AM D8PSK or GFSK signal on the adjacent or any other assignable channel being at least 40 dB higher than the desired signal.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.5.3.1 Standard	<p>After 1 January 2002, the receiving function of all new installations of VDL shall satisfy the specified error rate with a desired signal field strength of not more than 40 microvolts per metre (minus 114 dBW/m²) and with an undesired VHF DSB-AM, D8PSK or GFSK signal at least 60 dB higher than the desired signal on any assignable channel 100 kHz or more away from the assigned channel of the desired signal.</p> <p><i>Note.— This level of interference immunity performance provides a receiver performance consistent with the influence of the VDL RF spectrum mask as specified in 6.3.4 with an effective isolation transmitter/receiver isolation of 69 dB. Better transmitter and receiver performance could result in less isolation required. Guidance material on the measurement technique is included in the Handbook on Radio Frequency Spectrum Requirements for Civil Aviation including statement of approved ICAO policies (Doc 9718).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.5.3.2 Standard	After 1 January 2005, the receiving function of all installations of VDL shall meet the provisions of 6.3.5.3.1, subject to the conditions of 6.3.5.3.3.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.5.3.3 Standard	Requirements of mandatory compliance of the provisions of 6.3.5.3.2 shall be made on the basis of regional air navigation agreements which specify the airspace of operation and the implementation timescales. The agreement shall provide for at least two years' notice of mandatory compliance of aircraft systems.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.5.4.1 Standard	<p style="text-align: center;">6.3.5.4 INTERFERENCE IMMUNITY PERFORMANCE</p> <p>The receiving function shall satisfy the specified error rate with a desired field strength of not more than 40 microvolts per metre, and with one or more out-of-band signals, except for VHF FM broadcast signals, having a total level at the receiver input of minus 33 dBm.</p> <p><i>Note.— In areas where the adjacent higher band signal interference exceeds this specification, a higher immunity requirement will apply.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.3.5.4.2 Standard	The receiving function shall satisfy the specified error rate with a desired field strength of not more than 40 microvolts per metre, and with one or more VHF FM broadcast signals having a total level at the receiver input of minus 5 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4 Standard	PHYSICAL LAYER PROTOCOLS AND SERVICES The aircraft and ground stations shall access the physical medium operating in simplex mode.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.1.1 Standard	6.4.1 Functions The physical layer shall provide the following functions: a) transmitter and receiver frequency control; b) digital reception by the receiver; c) digital transmission by the transmitter; and d) notification services.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.1.1.1 Standard	<i>Transmitter/receiver frequency control.</i> The VDL physical layer shall set the transmitter or receiver frequency as commanded by the link management entity (LME). <i>Note.— The LME is a link layer entity as contained in the Manuals on VDL Mode 2 and VDL Mode 3 Technical Specifications.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.1.1.2 Standard	<i>Digital reception by the receiver.</i> The receiver shall decode input signals and forward them to the higher layers for processing.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.1.1.3 Standard	<i>Digital transmission.</i> The VDL physical layer shall appropriately encode and transmit information received from higher layers over the RF channel.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.2.1 Standard	6.4.2 Modes 2 and 3 common physical layer <i>Modulation scheme.</i> Modes 2 and 3 shall use differentially encoded 8 phase shift keying (D8PSK), using a raised cosine filter with $\alpha = 0.6$ (nominal value). The information to be transmitted shall be differentially encoded with 3 bits per symbol (baud) transmitted as changes in phase rather than absolute phase. The data stream to be transmitted shall be divided into groups of 3 consecutive data bits, least significant bit first. Zeros shall be padded to the end of the transmissions if needed for the final channel symbol.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.2.1.1 Standard	<i>Data encoding.</i> A binary data stream entering a differential data encoder shall be converted into three separate binary streams X, Y, and Z so that bits $3n$ form X, bits $3n + 1$ form Y, and bits $3n + 2$ form Z. The triplet at time k (X_k, Y_k, Z_k) shall be converted to a change in phase as shown in Table 6-1*, and the absolute phase ϕ_k is the accumulated series of $\Delta\phi_k$, that is: $\phi_k = \phi_{k-1} + \Delta\phi_k$ * All tables are located at the end of this chapter.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.2.1.2 Standard	<p><i>Transmitted signal form.</i> The phase-modulated baseband signal as defined in 6.4.2.1.1 shall excite the pulse shape filter.</p> <p>where:</p> <p>h is the complex impulse response of the pulse shape filter;</p> <p>k is defined in 6.4.2.1.1;</p> <p>ϕ is defined by the equation in 6.4.2.1.1;</p> <p>t is time;</p> <p>T_s is time duration of each symbol.</p> <p>The output (function of time) of the pulse shape filter ($s(t)$) shall modulate the carrier frequency. The pulse shape filter shall have a nominal complex frequency response of a raised-cosine filter with $\alpha=0.6$.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.2.2 Standard	<p><i>Modulation rate.</i> The symbol rate shall be 10 500 symbols/second, resulting in a nominal bit rate of 31 500 bits/s. The modulation stability requirements for Modes 2 and 3 are provided in Table 6-2.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.1 Standard	<p>6.4.3 Mode 2 specific physical layer</p> <p><i>Note.— The Mode 2 specific physical layer specification includes a description of the Mode 2 training sequence, forward error correction (FEC), interleaving, bit scrambling, channel sensing, and physical layer system parameters.</i></p> <p>To transmit a sequence of frames, a station shall insert the bit numbers and flags (per the data link service description for Mode 2 as contained in the Manual on VDL Mode 2 Technical Specifications), compute the FEC (per 6.4.3.1.2), interleave (per 6.4.3.1.3), prepend the training sequence (per 6.4.3.1.1), carry out bit scrambling (per 6.4.3.1.4) and finally encode and modulate the RF signal (per 6.4.2.1).</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.1 Standard	<p><i>Training sequence.</i> Data transmission shall begin with a demodulator training sequence consisting of five segments:</p> <ul style="list-style-type: none"> a) transmitter ramp-up and power stabilization; b) synchronization and ambiguity resolution; c) reserved symbol; d) transmission length; and e) header FEC. <p><i>Note.— Immediately after these segments follows an AVLC frame with the format as contained in the data link service description in the Manual on VDL Mode 2 Technical Specifications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.1.1.1 Standard	<p><i>Transmitter ramp-up and power stabilization.</i> The purpose of the first segment of the training sequence, called the ramp-up, is to provide for transmitter power stabilization and receiver AGC settling, and it shall immediately precede the first symbol of the unique word. The duration of the ramp-up shall be five symbol periods. The time reference point (t), for the following specification is the centre of the first unique word symbol, a point that occurs half a symbol period after the end of the ramp-up. Conversely stated, the beginning of the ramp-up starts at $t = -5.5$ symbol periods. The transmitted power shall be less than -40 dBc prior to time $t = -5.5$ symbol periods. The ramp-up shall provide that at time $t = -3.0$ symbol periods the transmitted power is 90 per cent of the manufacturer's stated output power or greater (see Figure 6-1*). Regardless of the method used to implement (or truncate) the raised cosine filter, the output of the transmitter between times $t = -3.0$ and $t = -0.5$ will appear as if '000' symbols were transmitted during the ramp-up period.</p> <p><i>N1.For Mode 3, the timing reference point is the same as the "power reference point".</i></p> <p><i>N2.It is desirable to maximize the time allowed for the AGC settling time. Efforts should be made to have power above 90 per cent of nominal output power at $t - 3.5$ symbol periods.</i></p> <p>_____</p> <p>* All figures are located at the end of this chapter.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.1.2 Standard	<p><i>Synchronization and ambiguity resolution.</i> The second segment of the training sequence shall consist of the unique word:</p> <p style="padding-left: 40px;">000 010 011 110 000 001 101 110 001 100 011 111 101 111 100 010</p> <p>and shall be transmitted from left to right.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.1.1.3 Standard	<i>Reserved symbol.</i> The third segment of the training sequence shall consist of the single symbol representing 000. <i>Note.— This field is reserved for future definition.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.1.4 Standard	<i>Transmission length.</i> To allow the receiver to determine the length of the final Reed-Solomon block, the transmitter shall send a 17-bit word, from least significant bit (lsb) to most significant bit (msb), indicating the total number of data bits that follow the header FEC. <i>Note.— The length does not include those bits transmitted for: the Reed Solomon FEC, extra bits padded to ensure that the interleaver generates an integral number of 8-bit words, or the extra bits padded to ensure that the data encoder generates an integral number of 3-bit symbols.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.1.1.5 Standard	<p><i>Header FEC.</i> To correct bit errors in the header, a (25, 20) block code shall be computed over the reserved symbol and the transmission length segments. The block code shall be transmitted as the fifth segment. The encoder shall accept the header in the bit sequence that is being transmitted. The five parity bits to be transmitted shall be generated using the following equation:</p> $[P_1, \dots, P_5] = [R_1, \dots, R_3, TL_1, \dots, TL_{17}] H^T$ <p>where:</p> <ul style="list-style-type: none"> P is the parity symbol (P₁ shall be transmitted first); R is the reserved symbol; TL is the transmission Length symbol; T is the matrix transpose function; and H is the parity matrix defined below: $H = \begin{matrix} 00 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 1 \\ 11 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & \\ 00 & 1 & 1 & 1 & 1 & 1 & 1 & 0 & 0 & 0 \\ 01 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & \\ 11 & 0 & 0 & 0 & 0 & 1 & 1 & 1 & 0 & 0 & 1 \\ 10 & 0 & 0 & 0 & 0 & 1 & 1 & 1 & 1 & \\ 11 & 0 & 1 & 1 & 0 & 1 & 1 & 0 & 1 & 0 & \\ 10 & 0 & 1 & 1 & 0 & 0 & 1 & 1 & \\ 01 & 1 & 0 & 1 & 0 & 0 & 1 & 1 & 1 & 1 & \\ 00 & 1 & 0 & 1 & 0 & 1 & 0 & 1 & \end{matrix}$	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.1.6 Standard	<p><i>Bit transmission order.</i> The five parity bits of the resultant vector product shall be transmitted from the left bit first.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.1.2 Standard	<i>Forward error correction.</i> In order to improve the effective channel throughput by reducing the number of required retransmissions, FEC shall be applied after the training sequence, regardless of frame boundaries.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.2.1 Standard	<p><i>FEC calculation.</i> The FEC coding shall be accomplished by means of a systematic fixed-length Reed-Solomon (RS) (255,249) 28-ary code.</p> <p><i>N1.</i> This code is capable of correcting up to three octets for data blocks of 249 octets (1992 bits). Longer transmissions must be divided up into 1992 bit transmissions and shorter transmissions must be extended by virtual fill with trailing zeros. Six RS-check octets are appended for a total block of 255 octets.</p> <p>The field defining the primitive polynomial of the code shall be as follows:</p> $p(x) = (x^8 + x^7 + x^2 + x + 1)$ <p>The generator polynomial shall be as follows:</p> <p>where:</p> <ul style="list-style-type: none"> α is a primitive element of GF(256) GF(256) is a Galois field (GF) of size 256. <p><i>N2.</i> The Reed-Solomon codes are described in the Recommendation for Space Data System Standards Telemetry Channel Coding, by the Consultative Committee for Space Data Systems (see the Appendix to this chapter).</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.1.2.2 Standard	<i>Block lengths.</i> The six RS-check octets shall be calculated on blocks of 249 octets. Longer transmissions shall be split into blocks of 249 octets, per 6.4.3.1.3. Blocks of shorter length shall be extended to 249 octets by a virtual fill of trailing zeros. The virtual fill shall not be transmitted. Blocks shall be coded according to 6.4.3.1.2.3 through 6.4.3.1.2.3.3.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.2.3 Standard	<i>No error correction.</i> For blocks with 2 or fewer non-fill octets, no error correction shall be used.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.2.3.1 Standard	<i>Single-byte error correction.</i> For blocks with 3 to 30 non-fill octets, all six RS-check octets shall be generated, but only the first two shall be transmitted. The last four RS-check octets shall be treated as erasures at the decoder.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.2.3.2 Standard	<i>Two-byte error correction.</i> For blocks with 31 to 67 non-fill octets, all six RS-check octets shall be generated, but only the first four shall be transmitted. The last two RS-check octets shall be treated as erasures at the decoder.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.1.2.3.3 Standard	<i>Three-byte error correction.</i> For blocks with 68 or more non-fill octets, all six RS-check octets shall be generated and transmitted.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 6 Reference 6.4.3.1.3</p> <p>Standard</p>	<p><i>Interleaving.</i> To improve the performance of the FEC, an octet-based table-driven interleaver shall be used. The interleaver shall create a table having 255 octets per row and c rows, where</p> $c = \text{transmission length (bits)} / 1992 \text{ (bits)}$ <p>where:</p> <ul style="list-style-type: none"> a) the transmission length is as defined in 6.4.3.1.1.5; and b) c = the smallest integer greater than or equal to the value of the fraction. <p>After extending the data to an even multiple of 1992 bits, the interleaver shall write the transmission stream into the first 249 octets of each row by taking each consecutive group of eight bits and storing them from the first column to the 249th. The first bit in each group of eight bits shall be stored in the eighth bit position; the first group of 1992 bits shall be stored in the first row, the second group of 1992 bits in the second row, etc. After the FEC is computed on each row, the FEC data (or erasures) shall be stored in columns 250 through 255. The interleaver shall then pass the data to the scrambler by reading out column by column, skipping any octet which contains erasures or all fill bits. All of the bits in an octet shall be transmitted from bit 8 to bit 1.</p> <p>On reception, the de-interleaver shall calculate the number of rows and size of the last (potentially partial) row from the length field in the header. It shall only pass valid data bytes to the higher layer.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.1.4 Standard	<p><i>Bit scrambling.</i> To aid clock recovery and to stabilize the shape of the transmitted spectrum, bit scrambling shall be applied. The pseudo noise (PN) sequence shall be a 15-stage generator (see Figure 6-2) with the characteristic polynomial:</p> $X^{15} + X + 1$ <p>The PN-sequence shall start after the frame synchronization pattern with the initial value 1101 0010 1011 001 with the left-most bit in the first stage of the register as per Figure 6-2. After processing each bit, the register shall be shifted one bit to the right. For possible encryption in the future this initial value shall be programmed. The sequence shall be added (modulo 2) to the data at the transmit side (scrambling) and to the scrambled data at the receive side (descrambling) per Table 6-3.</p> <p><i>Note.— The concept of a PN scrambler is explained in ITU-R Recommendation S.446-4, Annex 1, Section 4.3.1, Method 1 (see the Appendix to this chapter).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.2.1 Standard	<p>6.4.3.2 MODE 2 CHANNEL SENSING</p> <p><i>Channel busy to idle detection.</i> When a station receives on-channel power of at least -87 dBm for at least 5 milliseconds, then:</p> <p>a) with a likelihood of 0.9, it shall continue to consider the channel occupied if the signal level is attenuated to below -92 dBm for less than 1 millisecond; and</p> <p>b) with a likelihood of 0.9, it shall consider the channel unoccupied if the signal level is attenuated to below -92 dBm for at least 1.5 milliseconds.</p> <p><i>Note.— the maximum link throughput available to all users is highly sensitive to the RF channel sense delay (from the time when the channel actually changes state until a station detects and acts on that change) and RF channel seizure delay (from the time when a station decides to transmit until the transmitter is sufficiently ramped up to lock out other stations). Accordingly, it is imperative that all efforts are made to reduce those times as the state-of-the-art advances.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.2.2 Standard	<p><i>Channel idle to busy detection.</i> With a likelihood of at least 0.9, a station shall consider the channel occupied within 1 millisecond after on-channel power rises to at least -90 dBm.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.2.3 Recommendation	<p>Recommendation.— <i>The detection of an occupied channel should occur within 0.5 milliseconds.</i></p> <p><i>Note.— A higher probability of false alarm is acceptable on the idle to busy detection than the busy to idle detection because of the effects of the two different errors.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.3.1 Standard	<p align="center">6.4.3.3 MODE 2 RECEIVER/TRANSMITTER INTERACTION</p> <p><i>Receiver to transmitter turnaround time.</i> A station shall transmit the training sequence such that the centre of the first symbol of the unique word will be transmitted within 1.25 milliseconds after the result of an access attempt is successful (see Figure 6-3). The total frequency change during the transmission of the unique word shall be less than 10 Hz. After transmission of the unique word, the phase acceleration shall be less than 500 Hz per second.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.3.2 Standard	<p><i>Transmitter to receiver turnaround time.</i> The transmitter power shall be -20 dBc within 2.5 symbol periods of the middle of the final symbol of the burst. The transmitter power leakage when the transmitter is in the "off" state shall be less than -83 dBm. A station shall be capable of receiving and demodulating with nominal performance, an incoming signal within 1.5 milliseconds after transmission of the final information symbol.</p> <p><i>Note.— Reference DO-160D section 21, category H for antenna radiated signals.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.3.4.1 Standard	<p align="center">6.4.3.4 MODE 2 PHYSICAL LAYER SYSTEM PARAMETERS</p> <p>The physical layer shall implement the system parameters as defined in Table 6-4.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.3.4.1.1 Standard	<i>Parameter P1 (minimum transmission length).</i> Parameter P1 defines the minimum transmission length that a receiver shall be capable of demodulating without degradation of BER.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.1 Standard	<p style="text-align: center;">6.4.4 Mode 3 specific physical layer</p> <p><i>Note.— The Mode 3 specific physical layer specification includes a description of Mode 3 management (M) burst and handoff check message (H) burst uplink, M burst downlink, voice/data (V/D) burst, and bit scrambling.</i></p> <p><i>Management (M) burst and handoff check message (H) burst uplink.</i> The M uplink burst (as contained in the Manual on VDL Mode 3 Technical Specifications) shall consist of three segments, the training sequence followed by the system data and the transmitter ramp down. The H uplink burst (as contained in the Manual on VDL Mode 3 Technical Specifications) shall consist of three segments, the training sequence followed by the handoff check message and the transmitter ramp down.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.1.1 Standard	<i>Training sequence.</i> Uplink M burst and H burst training sequences shall consist of two components as follows: a) transmitter ramp up and power stabilization; and b) synchronization and ambiguity resolution.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.4.1.1.1 Standard	<i>Transmitter ramp-up and power stabilization.</i> This shall be as defined in Section 6.4.3.1.1.1.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.1.1.2 Standard	<i>Synchronization and ambiguity resolution.</i> The second component of the training sequence shall consist of the synchronization sequence, known as S ₂ [*] , as follows: 000 001 101 100 110 010 111 100 010 011 101 000 111 000 011 001 and shall be transmitted from left to right. <i>Note.— The sequence S₂[*] is very closely related to the sequence S₂ (Section 6.4.4.3.1.2). The 15 phase changes between the 16 symbols of S₂[*] are each exactly 180° out of phase from the 15 phase changes associated with S₂. This relationship can be used to simplify the process of simultaneously searching for both sequences.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.4.1.2 Standard	<p><i>System data and handoff check message.</i> The non-3T configuration (as contained in the Manual on VDL Mode 3 Technical Specifications) system data shall consist of 32 transmitted symbols. The 96 transmitted bits shall include 48 bits of information and 48 parity bits, generated as 4 Golay (24, 12) code words. The 3T configuration as contained in the Manual on VDL Mode 3 Technical Specifications shall consist of 128 transmitted symbols. The 384 transmitted bits shall include 192 bits of information and 192 parity bits, generated as 16 Golay (24, 12) code words. The 3T configuration handoff check message shall consist of 40 transmitted symbols. The 120 transmitted bits shall include 60 bits of information and 60 parity bits, generated as 5 Golay (24,12) code words. The specific definition of the Golay encoder shall be as follows: If the 12 bit input bit sequence is written as a row vector x, then the 24 bit output sequence can be written as the row vector y, where $y = x G$, and the matrix G shall be given by</p> $G = \begin{bmatrix} 1 & 1 & 0 & 1 & 0 & 1 & 1 & 1 & 0 & 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 1 & 1 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 & 0 & 0 & 1 & 1 & 1 & 0 & 1 & 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 0 & 0 & 1 & 1 & 0 & 1 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 1 & 0 & 0 & 1 & 1 & 0 & 1 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 1 & 1 & 0 & 0 & 1 & 1 & 0 & 1 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 1 & 1 & 0 & 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 1 & 1 & 0 & 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 1 & 1 & 0 & 1 & 1 & 1 & 1 & 0 & 0 & 0 \end{bmatrix}$	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>0 0 0 0 0 0 1 0 0 1 1 0 1 1 1 0 0 0 1 1 0 0 0 0 0 0 0 0 0 0 0 1 0 1 0 1 0 1 1 1 0 0 0 1 1 0 0 0 0 0 0 0 0 0 0 0 1</p> <p><i>Note.— The extended Golay code allows for the correction of any error pattern with 3 or fewer bit errors and the detection of any 4-bit error pattern.</i></p>				
<p>Chapter 6 Reference 6.4.4.1.3 Standard</p>	<p><i>Transmitter ramp-down.</i> The transmitter power shall be –20 dBc within 2.5 symbol periods of the middle of the final symbol of the burst. The transmitter power leakage when the transmitter is in the “off” state shall be less than – 83 dBm. <i>Note.— Reference RTCA/DO-160D section 21, category H for antenna radiated signals.</i></p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		
<p>Chapter 6 Reference 6.4.4.2 Standard</p>	<p><i>Management (M) burst downlink.</i> The M downlink burst (as contained in the Manual on VDL Mode 3 Technical Specifications) shall consist of three segments, the training sequence followed by the system data and the transmitter ramp down.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		
<p>Chapter 6 Reference 6.4.4.2.1 Standard</p>	<p><i>Training sequence.</i> The M downlink burst training sequence shall consist of two components as follows: a) transmitter ramp up and power stabilization; and b) synchronization and ambiguity resolution.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.4.2.1.1 Standard	<i>Transmitter ramp-up and power stabilization.</i> This shall be as defined in 6.4.4.1.1.1.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.2.1.2 Standard	<i>Synchronization and ambiguity resolution.</i> Three separate synchronization sequences shall be used for this burst type. The standard sequence, known as S_1 , shall be as follows: 000 111 001 001 010 110 000 011 100 110 011 111 010 101 100 101 and shall be transmitted from left to right. The special sequence used to identify poll responses shall be as defined in 6.4.4.1.1.2. The special sequence used to identify net entry requests (S_1^*) shall use the following sequence: 000 001 111 111 100 000 110 101 010 000 101 001 100 011 010 011 and shall be transmitted from left to right. <i>Note.— The sequence S_1^* is very closely related to the sequence S_1. The 15 phase changes between the 16 symbols of S_1^* are each exactly 180° out of phase from the 15 phase changes associated with S_1. This relationship can be used to simplify the process of simultaneously searching for both sequences.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.2.2 Standard	<i>System data.</i> The system data segment shall consist of 16 transmitted symbols. The 48 transmitted bits shall be encoded as 24 bits of system data and 24 bits of parity bits generated as two consecutive (24, 12) Golay code words. The encoding of the (24, 12) Golay code words should be as defined in 6.4.4.1.2.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.4.2.3 Standard	<i>Transmitter ramp-down.</i> This shall be as defined in 6.4.4.1.3.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.3 Standard	<i>Voice or data (V/D) burst.</i> The V/D burst (as contained in the Manual on VDL Mode 3 Technical Specifications) shall consist of four segments: the training sequence followed by the header, the user information segment and the transmitter ramp down. The same V/D burst format shall be used for both uplink and downlink.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.3.1 Standard	<i>Training sequence.</i> V/D burst training sequence shall consist of two components as follows: a) transmitter ramp-up and power stabilization; and b) synchronization and ambiguity resolution.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.3.1.1 Standard	<i>Transmitter ramp-up and power stabilization.</i> This shall be as specified in 6.4.4.1.1.1.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.3.1.2 Standard	<i>Synchronization and ambiguity resolution.</i> The second component of the training sequence shall consist of the synchronization sequence, known as S2, as follows: 000 111 011 010 000 100 001 010 100 101 011 110 001 110 101 111 and shall be transmitted from left to right.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.4.3.2 Standard	<i>Header.</i> The header segment shall consist of 8 transmitted symbols. The 24 transmitted bits shall be encoded as 12 bits of header information and 12 parity bits, generated as a single (24, 12) Golay code word. The encoding of the (24, 12) Golay code word shall be as defined in 6.4.4.1.2.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.3.3 Standard	<i>User information.</i> The user information segment shall consist of 192 3-bit symbols. When transmitting voice, FEC shall be applied to the analysis output of the vocoder specified in 6.8. The vocoder shall provide satisfactory performance in a BER environment of 10^{-3} (with a design goal of 10^{-2}). The overall bit rate of the vocoder <i>including</i> FEC is 4 800 bits/s (except when in the truncated mode in which the bit rate is 4 000 bits/s).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.3.3.1 Standard	When transmitting user data, the 576 bits shall be encoded as a single Reed-Solomon (72, 62) 2s-ary code word. For user data input to the Reed-Solomon encoder of length less than 496 bits, input data shall be padded with zeroes at the end to a full length of 496 bits. The field defining the primitive polynomial of the code shall be as described in 6.4.3.1.2.1. The generator polynomial shall be as follows: <i>Note.— The Reed-Solomon (72, 62) code is capable of correcting up to five 2s-ary (code word) symbol errors in the received word.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.4.3.4 Standard	<i>Transmitter ramp-down.</i> This shall be as defined in 6.4.4.1.3.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.4 Standard	<i>Interleaving.</i> There shall be no interleaving in Mode 3 operation.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.5 Standard	<i>Bit scrambling.</i> Under Mode 3 operation, bit scrambling, as specified in 6.4.3.1.4 shall be performed on each burst, starting after the training sequence. The scrambling sequence shall be reinitialized on each burst effectively providing a constant overlay for each of the Mode 3 fixed length bursts.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.6 Standard	<i>Receiver/transmitter interaction.</i> The switching times in this subsection will be defined as the time between the middle of the last information symbol of one burst and the middle of the first symbol of the synchronization sequence of the subsequent burst. <i>Note.— This nominal time will be shortened by considerations such as the finite width of each symbol due to Nyquist filtering and the ramp up and power stabilization sequence. Such alternative definitions could yield switching times up to 8 symbol periods shorter.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.4.4.6.1 Standard	<p><i>Receiver to transmitter switching time.</i> An aircraft radio shall be capable of switching from reception to transmission within 17 symbol periods. This time can be relaxed to 33 symbol periods for aircraft radios which do not implement functions requiring discrete addressing.</p> <p>N1.<i>The shortest R/T switching time for an aircraft radio occurs when the reception of an uplink M channel beacon is followed by a V/D transmission in the same slot. In certain instances where aircraft radios do not implement functions requiring discrete addressing, the R/T switching time can be increased since the last two Golay words of the uplink M channel beacon need not be read.</i></p> <p>N2.<i>The minimum turnaround time assumes that in configurations 3VID, 2VID, and 3T (as contained in Section 5.5.2.4 of the Manual on VDL Mode 3 Technical Specifications), the aircraft radios will be provided with software that will prevent them from transmitting a downlink m channel message in a slot following the reception of a voice message from another aircraft with a long time delay.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.6.2 Standard	<p><i>Transmitter to receiver switching time.</i> An aircraft radio shall be capable of switching from transmission to reception within 32 symbol periods.</p> <p><i>Note.— The worst case T/R switching time for an aircraft radio occurs when it transmits a downlink M channel message and receives a V/D message in the same slot.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.4.4.7.1 Recommendation	<p>6.4.4.7 <i>Fringe coverage indication.</i></p> <p>Recommendation.— <i>Indication of near edge-of-coverage should be provided to the VDL Mode 3 aircraft.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.5.1.1 Standard	<p align="center">6.5 LINK LAYER PROTOCOLS AND SERVICES</p> <p align="center">6.5.1 General information</p> <p><i>Functionality.</i> The VDL link layer shall provide the following sublayer functions:</p> <ul style="list-style-type: none"> a) media access control (MAC) sublayer, which requires the use of the carrier sense multiple access (CSMA) algorithm for Mode 2 or TDMA for Mode 3; b) a data link service (DLS) sublayer: <ul style="list-style-type: none"> 1) for Mode 2, the DLS sublayer provides connection-oriented point-to-point links using data link entities (DLE) and connectionless broadcast link over the MAC sublayer; and 2) for Mode 3, the DLS sublayer provides acknowledged connectionless point-to-point and point-to-multipoint links over a MAC sublayer that guarantees sequencing; and c) a VDL management entity (VME), which establishes and maintains DLEs between the aircraft and the ground-based systems using link management entities (LME). 	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.5.1.2.1 Standard	<p align="center">6.5.1.2 SERVICE</p> <p><i>Connection-oriented.</i> The VDL Mode 2 link layer shall provide a reliable point-to-point service using a connection-oriented DLS sublayer.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.5.1.2.2 Standard	<i>Connectionless.</i> The VDL Mode 2 and 3 link layers shall provide an unacknowledged broadcast service using a connectionless DLS sublayer.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.5.1.2.3 Standard	<i>Acknowledged connectionless.</i> The VDL Mode 3 link layer shall provide an acknowledged point-to-point service using a connectionless DLS sublayer that relies upon the MAC sublayer to guarantee sequencing.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.5.2.1 Standard	6.5.2 MAC sublayer The MAC sublayer shall provide for the transparent acquisition of the shared communications path. It makes invisible to the DLS sublayer the way in which supporting communications resources are utilized to achieve this. <i>Note.— Specific MAC services and procedures for VDL Modes 2 and 3 are contained in the Manuals on VDL Mode 2 and VDL Mode 3 Technical Specifications.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.5.3.1 Standard	6.5.3 Data link service sublayer For Mode 2, the DLS shall support bit-oriented simplex air-ground communications using the aviation VHF link control (AVLC) protocol. <i>Note.— Specific data link services, parameters and protocol definitions for VDL Mode 2 are contained in the Manual on VDL Mode 2 Technical Specifications.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.5.3.2 Standard	For Mode 3, the DLS shall support bit-oriented, priority based, simplex air-ground communications using the acknowledged connectionless data link (A-CLDL) protocol. <i>Note.— Specific data link services, parameters and protocol definitions for VDL Mode 3 are contained in the Manual on VDL Mode 3 Technical Specifications.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.5.4.1 Standard	<p style="text-align: center;">6.5.4 VDL management entity</p> <i>Services.</i> The VME shall provide link establishment, maintenance and disconnection services as well as support parameter modification. Specific VME services, parameter formats and procedures for Modes 2 and 3 are contained in the Manuals on VDL Mode 2 and Mode 3 Technical Specifications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.6.1.1 Standard	<p style="text-align: center;">6.6 SUBNETWORK LAYER PROTOCOLS AND SERVICES</p> <p style="text-align: center;">6.6.1 Architecture for Mode 2</p> <p>The subnetwork layer protocol used across the VHF air-ground subnetwork for VDL Mode 2 is referred to formally as a subnetwork access protocol (SNAcP) and shall conform to ISO 8208, except as contained in the Manual on VDL Mode 2 Technical Specifications. The SNAcP is contained within the Manual on VDL Mode 2 Technical Specifications as the subnetwork protocol. If there are any differences between the Manual on VDL Mode 2 Technical Specifications and the cited specifications, the Manual on VDL Mode 2 Technical Specifications shall have precedence. On the air-ground interface, the aircraft subnetwork entity shall act as a DTE and the ground subnetwork entity shall act as a DCE.</p> <p><i>Note.— Specific subnetwork layer protocol access points, services, packet formats, parameters and procedures for VDL Mode 2 are contained in the Manual on VDL Mode 2 Technical Specifications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.6.2.1 Standard	<p align="center">6.6.2 Architecture for Mode 3</p> <p>The subnetwork layer used across the VHF air-ground subnetwork for VDL Mode 3 provides the flexibility to simultaneously support multiple subnetwork protocols. The currently defined options are to support ISO 8473 connectionless network protocol and to support ISO 8208, both as contained in the Manual on VDL Mode 3 Technical Specifications. The Manual on VDL Mode 3 Technical Specifications shall have precedence with respect to any differences with the cited specifications. For the ISO 8208 interface, both the air and ground subnetwork entities shall act as DCEs.</p> <p><i>Note.— Specific subnetwork layer protocol access points, services, packet formats, parameters and procedures for VDL Mode 3 are contained in the Manual on VDL Mode 3 Technical Specifications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.7.1.1 Standard	<p align="center">6.7 THE VDL MOBILE SUBNETWORK DEPENDENT CONVERGENCE FUNCTION (SNDCF)</p> <p align="center">6.7.1 VDL Mode 2 SNDCF</p> <p><i>Introduction.</i> The VDL Mode 2 mobile SNDCF shall be the standard mobile SNDCF.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.7.1.2 Standard	<p><i>New function.</i> The VDL Mode 2 mobile SNDCF shall support maintaining context (e.g. compression tables) across subnetwork calls. The SNDCF shall use the same context (e.g. compression tables) across all SVCs negotiated to a DTE, when negotiated with the same parameters. The SNDCF shall support at least 2 SVCs sharing a context.</p> <p><i>N1.Because handoffs can be expected to reorder packets, certain compression algorithms do not lend themselves to use over VDL Mode 2. Further, implementors of dictionary-based compression algorithms must be sensitive to the problem of updates arriving on either the old or newly established call.</i></p> <p><i>N2.The encoding of the Call User Data field is described in Doc 9705 except with modifications as contained in the Manual on VDL Mode 2 Technical Specifications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.7.2.1 Standard	<p style="text-align: center;">6.7.2 VDL Mode 3 SNDCF</p> <p>The VDL Mode 3 shall support one or more of the defined SNDCFs. The first is the standard ISO 8208 SNDCF as defined in Doc 9705. This is a connection-oriented SNDCF. The second type of SNDCF supported by VDL Mode 3 is denoted frame-based SNDCF. The details of this connectionless oriented SNDCF are contained in the Manual on VDL Mode 3 Technical Specifications, including network layer interface, support for broadcast and unicast network packets, and ATN router support.</p> <p><i>Note.— The framed-based SNDCF is termed such because it uses the VDL Mode 3 frames without the need for an additional protocol (viz. ISO 8208 SNDCF) to transfer network packets. The frame-based SNDCF achieves independence from the network protocol by identifying the payload of each frame. Upon receipt of a frame, the payload is examined and control is passed to the protocol identified.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.8.1.1 Standard	<p style="text-align: center;">6.8 VOICE UNIT FOR MODE 3</p> <p style="text-align: center;">6.8.1 Services</p> <p>The voice unit shall provide for a simplex, “push-to-talk” audio and signalling interface between the user and the VDL. Two separate mutually exclusive voice circuit types shall be supported:</p> <p>a) Dedicated circuits: This shall provide service to a specific user group on an exclusive basis with no sharing of the circuit with other users outside the group. Access shall be based on a “listen-before-push-to-talk” discipline.</p> <p>b) Demand assigned circuits: This shall provide voice circuit access which is arbitrated by the ground station in response to an access request received from the aircraft station. This type of operation shall allow dynamic sharing of the channel resource increasing trunking efficiency.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.8.1.2 Standard	<i>Priority access.</i> The voice unit operation shall support a priority override access for authorized ground users.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.8.1.3 Standard	<i>Message source identification.</i> The voice unit operation shall support notification to the user of the source of a received message (i.e. whether the message originated from an air or ground station).	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.8.1.4 Standard	<i>Coded squelch.</i> The voice unit shall support a coded squelch operation that offers some degree of rejection of undesired co-channel voice messages based on the burst time of arrival.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.8.2.1 Standard	<p align="center">6.8.2 Speech encoding, parameters and procedures</p> <p>The VDL Mode 3 shall use the advanced multiband excitation (AMBE) 4.8 kbits/s encoding/decoding algorithm, version number AMBE-ATC-10, developed by Digital Voice Systems, Incorporated (DVSI) for voice communications.</p> <p><i>N1. Information on technical characteristics of the 4.8 kbits/s AMBE algorithm is contained in AMBE-ATC-10 Low Level Description, obtainable from DVSI.</i></p> <p><i>N2. The 4.8 kbits/s AMBE encoding/decoding technology described in the document is subject to DVSI patent rights and copyrights. Manufacturers must enter into a license agreement with DVSI prior to obtaining a detailed description of the algorithm before incorporation in equipment operating in the VDL Mode 3 service. By letter to ICAO dated 29 October 1999, DVSI confirmed its commitment to license the technology for the manufacture and sale of aeronautical equipment under reasonable terms and conditions, negotiated on a non-discriminatory basis.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.8.2.2 Standard	Speech encoding definition, voice unit parameters, and procedure descriptions for VDL Mode 3 Voice Unit operation are contained in the Manual on VDL Mode 3 Technical Specifications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.1 Standard	<p style="text-align: center;">6.9 VDL MODE 4</p> <p>A Mode 4 station shall conform to the requirements defined in 6.1.2.3, 6.1.4.2, 6.2.1.1, 6.2.3.1, 6.2.4, 6.3.1, 6.3.3.1, 6.3.4, 6.3.5.1, 6.3.5.2, 6.3.5.3, 6.3.5.4.1 and 6.9.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.2.1.1 Standard	<p style="text-align: center;">6.9.2 VDL Mode 4 radio channels</p> <p style="text-align: center;">6.9.2.1 VDL MODE 4 STATION FREQUENCY RANGE</p> <p><i>Transmitter/receiver tuning range.</i> A VDL Mode 4 transmitter/receiver shall be capable of tuning to any of the 25 kHz channels from 112 MHz to 137 MHz.</p> <p><i>Note.— Operational conditions or certain applications may require the equipment to be operated in a narrower frequency range.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.2.1.2 Standard	<i>Simultaneous reception.</i> A VDL Mode 4 station shall be capable of receiving two channels simultaneously.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.2.1.3 Recommendation	Recommendation.— <i>A VDL Mode 4 station should be capable of receiving additional channels simultaneously as required by operational services.</i>	CV CAR 19, 19.B.230, (1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.2.2.1 Standard	<p align="center">6.9.2.2 GLOBAL SIGNALLING CHANNELS</p> <p>VDL Mode 4 stations shall use two assigned frequencies as global signalling channels (GSC), to support user communications and link management functions.</p> <p><i>Note.— Additional channels may be defined in a local domain and notified to mobile users by broadcast from ground stations on the GSCs defined above.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.3.1 Standard	<p align="center">6.9.3 System capabilities</p> <p><i>ATN compatibility.</i> The VDL Mode 4 system shall support ATN/IPS-compliant subnetwork services.</p> <p><i>Note.— VDL Mode 4 provides a seamless transfer of data between ATN/IPS ground networks and ATN/IPS aircraft networks. Interoperability with ATN/OSI networks, where required, is expected to be arranged prior to implementation. VDL Modes 2 and 3 provide ATN/OSI-compliant subnetworks.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.3.2 Standard	<i>Data transparency.</i> The VDL Mode 4 system shall provide code-independent, byte-independent transfer of data.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.3.3 Standard	<i>Broadcast.</i> The VDL Mode 4 system shall provide link layer broadcast services.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.3.4 Standard	<i>Point-to-point.</i> The VDL Mode 4 system shall provide link layer point-to-point services.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.3.5 Standard	<i>Air-air communications.</i> The VDL Mode 4 system shall provide air-air communications, without ground support, as well as air-ground communications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.3.6 Standard	<i>Connection management.</i> When supporting air-ground operations, the VDL Mode 4 system shall establish and maintain a reliable communications path between the aircraft and the ground system while allowing, but not requiring, manual intervention.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.3.7 Standard	<i>Ground network transition.</i> A mobile VDL Mode 4 DLS station shall transition from one ground VDL Mode 4 DLS station to another as required.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.3.8 Standard	<i>Derived time capability.</i> VDL Mode 4 shall provide the capability for deriving time from time-of-arrival measurements of received VDL Mode 4 transmissions whenever externally derived estimates of time are unavailable.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.3.9 Standard	<i>Simplex operations.</i> Mobile and ground VDL Mode 4 stations shall access the physical medium operating in simplex mode.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.4.1 Standard	6.9.4 Coordination of channel utilization On a regional basis, transmissions shall be scheduled relative to UTC, to ensure efficient use of shared channels and to avoid unintentional slot re-use.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.1.1.1 Standard	6.9.5 Physical layer protocols and services <i>Note.— Unless otherwise stated, the requirements defined in this section apply to both mobile and ground stations.</i> 6.9.5.1 FUNCTIONS 6.9.5.1.1 TRANSMITTED POWER <i>Airborne installation.</i> The effective radiated power shall be such as to provide a field strength of at least 35 microvolts per metre (minus 114.5 dBW/m ²) on the basis of free space propagation, at ranges and altitudes appropriate to the conditions pertaining to the areas over which the aircraft is operated.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.5.1.1.2 Recommendation	<i>Ground installation.</i> Recommendation. — <i>The effective radiated power should be such as to provide a field strength of at least 75 microvolts per metre (minus 109 dBW/m²) within the defined operational coverage of the facility, on the basis of free-space propagation.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.1.2.1 Standard	<i>6.9.5.1.2 TRANSMITTER AND RECEIVER FREQUENCY CONTROL</i> The VDL Mode 4 physical layer shall set the transmitter or receiver frequency as commanded by the link management entity (LME). Channel selection time shall be less than 13 ms after the receipt of a command from a VSS user.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.1.3.1 Standard	<i>6.9.5.1.3 DATA RECEPTION BY RECEIVER</i> The receiver shall decode input signals and forward them to the higher layers for processing.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.1.4.1 Standard	<i>6.9.5.1.4 DATA TRANSMISSION BY TRANSMITTER</i> <i>Data encoding and transmission.</i> The physical layer shall encode the data received from the data link layer and transmit it over the RF channel. RF transmission shall take place only when permitted by the MAC.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.5.1.4.2 Standard	<p><i>Order of transmission.</i> The transmission shall consist of the following stages in the following order:</p> <ul style="list-style-type: none"> a) transmitter power stabilization; b) bit synchronization; c) ambiguity resolution and data transmission; and d) transmitter decay. <p><i>Note.— The definitions of the stages are given in Sections 6.9.5.2.3.1 to 6.9.5.2.3.4.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.1.4.3 Standard	<p><i>Automatic transmitter shutdown.</i> A VDL Mode 4 station shall automatically shut-down power to any final stage amplifier in the event that output power from that amplifier exceeds -30 dBm for more than 1 second. Reset to an operational mode for the affected amplifier shall require a manual operation.</p> <p><i>Note.— This is intended to protect the shared channel resource against so-called “stuck transmitters”.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.1.5.1 Standard	<p>6.9.5.1.5 NOTIFICATION SERVICES</p> <p><i>Signal quality.</i> The operational parameters of the equipment shall be monitored at the physical layer. Signal quality analysis shall be performed in the demodulator process and in the receive process.</p> <p><i>Note.— Processes that may be evaluated in the demodulator include bit error rate (BER), signal to noise ratio (SNR) and timing jitter. Processes that may be evaluated in the receiver include received signal level and group delay.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.5.1.5.2 Standard	<i>Arrival time.</i> The arrival time of each received transmission shall be measured with a two-sigma error of 5 microseconds.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.1.5.3 Recommendation	Recommendation. — <i>The receiver should be capable of measuring the arrival time within a two-sigma error of 1 microsecond.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.2.1 Standard	6.9.5.2 PROTOCOL DEFINITION FOR GFSK <i>Modulation scheme.</i> The modulation scheme shall be GFSK. The first bit transmitted (in the training sequence) shall be a high tone and the transmitted tone shall be toggled before transmitting a 0 (i.e. non-return to zero inverted encoding).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.2.2 Standard	<i>Modulation rate.</i> Binary ones and binary zeros shall be generated with a modulation index of 0.25 ± 0.03 and a BT product of 0.28 ± 0.03 , producing data transmission at a bit rate of $19\,200 \text{ bits/s} \pm 50 \text{ ppm}$.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.5.2.3.1 Standard	6.9.5.2.3 STAGES OF TRANSMISSION <i>Transmitter power stabilization.</i> The first segment of the training sequence is the transmitter power stabilization, which shall have a duration of 16 symbol periods. The transmitter power level shall be no less than 90 per cent of the steady state power level at the end of the transmitter power stabilization segment.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.2.3.2 Standard	<i>Bit synchronization.</i> The second segment of the training sequence shall be the 24-bit binary sequence 0101 0101 0101 0101 0101 0101, transmitted from left to right immediately before the start of the data segment.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.2.3.3 Standard	<i>Ambiguity resolution and data transmission.</i> The transmission of the first bit of data shall start 40 bit intervals (approximately 2083.3 microseconds) \pm 1 microsecond after the nominal start of transmission. <i>N1.This is referenced to emissions at the output of the antenna.</i> <i>N2.Ambiguity resolution is performed by the link layer.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.2.3.4 Standard	<i>Transmitter decay.</i> The transmitted power level shall decay at least by 20 dB within 300 microseconds after completing a transmission. The transmitter power level shall be less than -90 dBm within 832 microseconds after completing a transmission.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.5.3.1 Standard	6.9.5.3 CHANNEL SENSING <i>Estimation of noise floor.</i> A VDL Mode 4 station shall estimate the noise floor based on power measurements of the channel whenever a valid training sequence has not been detected.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.3.2 Standard	The algorithm used to estimate the noise floor shall be such that the estimated noise floor shall be lower than the maximum power value measured on the channel over the last minute when the channel is regarded as idle. <i>Note.— The VDL Mode 4 receiver uses an energy sensing algorithm as one of the means to determine the state of the channel (idle or busy). One algorithm that can be used to estimate the noise floor is described in the Manual on VDL Mode 4 Technical Specifications.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.3.3 Standard	<i>Channel idle to busy detection.</i> A VDL Mode 4 station shall employ the following means to determine the channel idle to busy transition at the physical layer.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.3.3.1 Standard	<i>Detection of a training sequence.</i> The channel shall be declared busy if a VDL Mode 4 station detects a valid training sequence followed by a frame flag.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.5.3.3.2 Standard	<i>Measurement of channel power.</i> Regardless of the ability of the demodulator to detect a valid training sequence, a VDL Mode 4 station shall consider the channel busy with at least a 95 per cent probability within 1 ms after on-channel power rises to the equivalent of at least four times the estimated noise floor for at least 0.5 milliseconds.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.3.4.1 Standard	6.9.5.3.4 CHANNEL BUSY TO IDLE DETECTION A VDL Mode 4 station shall employ the following means to determine the channel busy to idle transition.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.3.4.2 Standard	<i>Measurement of transmission length.</i> When the training sequence has been detected, the channel busy state shall be held for a period of time at least equal to 5 milliseconds, and subsequently allowed to transition to the idle state based on measurement of channel power.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.3.4.3 Standard	<i>Measurement of channel power.</i> When not otherwise held in the channel busy state, a VDL Mode 4 station shall consider the channel idle with at least a 95 per cent probability if on-channel power falls below the equivalent of twice the estimated noise floor for at least 0.9 milliseconds.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.4.1 Standard	6.9.5.4 RECEIVER/TRANSMITTER INTERACTION <i>Receiver to transmitter turnaround time.</i> A VDL Mode 4 station shall be capable of beginning the transmission of the transmitter power stabilization sequence within 16 microseconds after terminating the receiver function.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.5.4.2 Standard	<i>Frequency change during transmission.</i> The phase acceleration of the carrier from the start of the synchronization sequence to the data end flag shall be less than 300 Hz per second.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.4.3 Standard	<i>Transmitter to receiver turnaround time.</i> A VDL Mode 4 station shall be capable of receiving and demodulating with nominal performance an incoming signal within 1 ms after completing a transmission. <i>Note.— Nominal performance is defined as a bit error rate (BER) of 10⁻⁴.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.5.1.1 Standard	6.9.5.5 PHYSICAL LAYER SYSTEM PARAMETERS 6.9.5.5.1 PARAMETER P1 (MINIMUM TRANSMISSION LENGTH) A receiver shall be capable of demodulating a transmission of minimum length P1 without degradation of BER.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.5.1.2 Standard	The value of P1 shall be 19 200 bits.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.5.5.2.1 Standard	6.9.5.5.2 PARAMETER P2 (NOMINAL CO-CHANNEL INTERFERENCE PERFORMANCE) The parameter P2 shall be the nominal co-channel interference at which a receiver shall be capable of demodulating without degradation in BER.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.5.2.2 Standard	The value of P2 shall be 12 dB.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.6.1 Standard	6.9.5.6 FM BROADCAST INTERFERENCE IMMUNITY PERFORMANCE FOR VDL MODE 4 RECEIVING SYSTEMS A VDL Mode 4 station shall conform to the requirements defined in section 6.3.5.4 when operating in the band 117.975–137 MHz.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.5.6.2 Standard	A VDL Mode 4 station shall conform to the requirements defined below when operating in the band 108-117.975 MHz.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 6 Reference 6.9.5.6.2.1</p> <p>Standard</p>	<p>The VDL Mode 4 receiving system shall meet the requirements specified in 6.3.5.1 in the presence of two-signal, third-order intermodulation products caused by VHF FM broadcast signals having levels in accordance with the following:</p> $2N_1 + N_2 + 72 \leq 0$ <p>for VHF FM sound broadcasting signals in the range 107.7–108.0 MHz and</p> <p>for VHF FM sound broadcasting signals below 107.7 MHz, where the frequencies of the two VHF FM sound broadcasting signals produce, within the receiver, a two-signal, third-order intermodulation product on the desired VDL Mode 4 frequency.</p> <p>N_1 and N_2 are the levels (dBm) of the two VHF FM sound broadcasting signals at the VDL Mode 4 receiver input. Neither level shall exceed the desensitization criteria set forth in 6.9.5.6.2.2.</p> <p>$\Delta f = 108.1 - f_1$, where f_1 is the frequency of N_1, the VHF FM sound broadcasting signal closer to 108.1 MHz.</p> <p><i>Note.— The FM intermodulation immunity requirements are not applied to a VDL Mode 4 channel operating below 108.1 MHz, and hence frequencies below 108.1 MHz are not intended for general assignments.</i></p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		
<p>Chapter 6 Reference 6.9.5.6.2.2</p> <p>Standard</p>	<p>The VDL Mode 4 receiving system shall not be desensitized in the presence of VHF FM broadcast signals having levels in accordance with Tables 6-5 and 6-6.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.9.6 Note	<p style="text-align: center;">Link layer</p> <p><i>Note.— Details on link layer functions are contained in the Manual on VDL Mode 4 Technical Specifications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.7 Note	<p style="text-align: center;">Subnetwork layer and SNDCF</p> <p><i>Note.— Details on subnetwork layer functions and SNDCF are contained in the Manual on VDL Mode 4 Technical Specifications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 6 Reference 6.9.8 Note	<p style="text-align: center;">ADS-B applications</p> <p><i>Note.— Details on ADS-B application functions are contained in the Manual on VDL Mode 4 Technical Specifications.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	<p style="text-align: center;">CHAPTER 7. AERONAUTICAL MOBILE AIRPORT COMMUNICATIONS SYSTEM (AEROMACS)</p> <p style="text-align: center;">7.1 DEFINITIONS</p> <p><i>Adaptive modulation.</i> A system's ability to communicate with another system using multiple burst profiles and a system's ability to subsequently communicate with multiple systems using different burst profiles.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference Definition	<i>Aerodrome.</i> A defined area on land or water (including any buildings, installations and equipment) intended to be used either wholly or in part for the arrival, departure and surface movement of aircraft.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	<i>AeroMACS downlink (DL).</i> The transmission direction from the base station (BS) to the mobile station (MS).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	<i>AeroMACS handover.</i> The process in which a mobile station (MS) migrates from the air-interface provided by one base station (BS) to the air-interface provided by another BS. A break-before-make AeroMACS handover is where service with the target BS starts after a disconnection of service with the previous serving BS.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	<i>AeroMACS uplink (UL).</i> The transmission direction from the mobile station (MS) to the base station (BS).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	<i>Aeronautical Mobile Airport Communications System (AeroMACS).</i> A high-capacity data link supporting mobile and fixed communications on the aerodrome surface.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference Definition	Base station (BS). A generalized equipment set providing connectivity, management and control of the mobile station (MS).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Bit error rate (BER). The number of bit errors in a sample divided by the total number of bits in the sample, generally averaged over many such samples.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Burst profile. Set of parameters that describe the uplink or downlink transmission properties associated with an interval usage code. Each profile contains parameters such as modulation type, forward error correction (FEC) type, preamble length, guard times, etc.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Convolutional turbo codes (CTC). Type of forward error correction (FEC) code.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Data transit delay. In accordance with ISO 8348, the average value of the statistical distribution of data delays. This delay represents the subnetwork delay and does not include the connection establishment delay.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference Definition	Domain. A set of end systems and intermediate systems that operate according to the same routing procedures and that is wholly contained within a single administrative domain.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Forward error correction. The process of adding redundant information to the transmitted signal in a manner which allows correction, at the receiver, of errors incurred in the transmission.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Frequency assignment. A logical assignment of centre frequency and channel bandwidth programmed to the base station (BS).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Frequency assignment. A logical assignment of centre frequency and channel bandwidth programmed to the base station (BS).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Mobile station (MS). A station in the mobile service intended to be used while in motion or during halts at unspecified points. An MS is always a subscriber station (SS).	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference Definition	Partial usage sub-channelization (PUSC). A technique in which the orthogonal frequency division multiplexing (OFDM) symbol subcarriers are divided and permuted among a subset of sub-channels for transmission, providing partial frequency diversity.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Residual error rate. The ratio of incorrect, lost and duplicate subnetwork service data units (SNSDUs) to the total number of SNSDUs that were sent.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Service data unit (SDU). A unit of data transferred between adjacent layer entities, which is encapsulated within a protocol data unit (PDU) for transfer to a peer layer.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Service flow. A unidirectional flow of media access control layer (MAC) service data units (SDUs) on a connection that is providing a particular quality of service (QoS).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Subnetwork entry time. The time from when the mobile station starts the scanning for BS transmission, until the network link establishes the connection, and the first network user "protocol data unit" can be sent.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference Definition	Subnetwork service data unit (SNSDU). An amount of subnetwork user data, the identity of which is preserved from one end of a subnetwork connection to the other.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Subscriber station (SS). A generalized equipment set providing connectivity between subscriber equipment and a base station (BS).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference Definition	Time division duplex (TDD). A duplex scheme where uplink and downlink transmissions occur at different times but may share the same frequency.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.3.1 Standard	<p style="text-align: center;">7.2 INTRODUCTION</p> <p><i>N1. Aeronautical mobile airport communications system (AeroMACS) is a high-capacity data link supporting mobile and fixed communications, related to the safety and regularity of flight, on the aerodrome surface.</i></p> <p><i>N2. AeroMACS is derived from the IEEE 802.16-2009 mobile standards. AeroMACS profile document (RTCA DO345 and EUROCAE ED 222) lists all features from these standards which are mandatory, not applicable or optional. AeroMACS profile differentiates between base station and mobile station functionality and contains, for each feature, a reference to the applicable standards.</i></p> <p><i>N3.</i></p> <p style="text-align: center;">7.3 GENERAL</p> <p>AeroMACS shall conform to the requirements of this and the following chapters.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.2 Standard	AeroMACS shall only transmit when on the surface of an aerodrome.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.3 Standard	AeroMACS shall support aeronautical mobile (route) service (AM(R) S) communications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.3.4 Standard	AeroMACS shall process messages according to their associated priority.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.5 Standard	AeroMACS shall support multiple levels of message priority.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.6 Standard	AeroMACS shall support point to point communication.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.7 Standard	AeroMACS shall support multicast and broadcast communication services.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.8 Standard	AeroMACS shall support internet protocol (IP) packet data services.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.3.9 Standard	AeroMACS shall provide mechanisms to transport ATN/IPS and ATN/OSI (over IP) based messaging.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.10 Recommendation	Recommendation. — <i>AeroMACS should support voice services.</i> <i>Note.</i> — <i>The Manual on the Aeronautical Telecommunication Network (ATN) using Internet Protocol Suite (IPS) Standards and Protocols (Doc 9896) provides information on voice service over IP.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.11 Standard	AeroMACS shall support multiple service flows simultaneously.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.12 Standard	AeroMACS shall support adaptive modulation and coding.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.13 Standard	AeroMACS shall support handover between different AeroMACS BSs during aircraft movement or on degradation of connection with current BS.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.3.14 Standard	AeroMACS shall keep total accumulated interference levels with limits defined by the International Telecommunication Union — Radiocommunication Sector (ITU-R) as required by national/international rules on frequency assignment planning and implementation.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.3.15 Standard	AeroMACS shall support a flexible implementation architecture to permit link and network layer functions to be located in different or same physical entities.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.1.1 Standard	<p align="center">7.4 RADIO FREQUENCY (RF) CHARACTERISTICS</p> <p align="center">7.4.1 General radio characteristics</p> <p>AeroMACS shall operate in time division duplex (TDD) mode.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.1.2 Standard	AeroMACS shall operate with a 5 MHz channel bandwidth.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.4.1.3 Standard	AeroMACS MS antenna polarization shall be vertical.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.1.4 Standard	AeroMACS BS antenna polarization shall have a vertical component.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.1.5 Standard	AeroMACS shall operate without guard bands between adjacent AeroMACS channels.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.1.6 Standard	AeroMACS shall operate according to the orthogonal frequency division multiple access method.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.1.7 Standard	AeroMACS shall support both segmented partial usage sub-channelization (PUSC) and PUSC with all carriers as subcarrier permutation methods.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.4.2.1 Standard	<p align="center">7.4.2 Frequency bands</p> <p>AeroMACS equipment shall operate in the band from 5 030 MHz to 5 150 MHz in channels of 5 MHz bandwidth.</p> <p><i>N1. Some States may, on the basis of national regulations, have additional allocations to support AeroMACS. Information on the technical characteristics and operational performance of AeroMACS is contained in the AeroMACS Minimum Operational Performance Specification (MOPS) (EUROCAE ED-223 / RTCA DO-346) and AeroMACS Minimum Aviation System Performance Standard (MASPS) (EUROCAE ED-227).</i></p> <p><i>N2. The last centre frequency of 5 145 MHz is selected as the reference frequency for the numbering of AeroMACS channels. AeroMACS nominal centre frequencies are numbered downward from the reference frequency in 5 MHz steps.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.2.2 Standard	<p>The mobile equipment shall operate at centre frequencies offset from the preferred frequencies, with an offset of 250 kHz step size.</p> <p><i>Note.— The nominal centre frequencies are the preferred centre frequencies for AeroMACS operations. However, the base stations should have the capability to deviate from the preferred centre frequencies to satisfy potential national spectrum authority implementation issues (i.e. to allow AeroMACS operations without receiving or causing interference to other systems operating in the band such as MLS and AMT).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.4.3.1 Standard	<p align="center">7.4.3 Radiated power</p> <p>The maximum mobile station equivalent isotropic radiated power (EIRP) shall not exceed 30 dBm.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.3.2 Standard	The maximum base station EIRP in a sector shall not exceed 39.4 dBm.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.3.3 Standard	<p>Recommendation.— <i>In order to meet ITU requirements, the total base station EIRP in a sector should be decreased from that peak, considering the antenna characteristics, at elevations above the horizon. Further information is provided in the guidance material.</i></p> <p>N1.<i>EIRP - defined as antenna gain in a specified elevation direction plus the average AeroMACS transmitter power. While the instantaneous peak power from a given transmitter may exceed that level when all of the subcarriers randomly align in phase, when the large number of transmitters assumed in the analysis is taken into account, average power is the appropriate metric.</i></p> <p>N2.<i>If a sector contains multiple transmit antennas (e.g., multiple input multiple output (MIMO) antenna), the specified power limit is the sum of the powers from each antenna.</i></p> <p>N3.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.4.4.1 Standard	<p align="center">7.4.4 Minimum receiver sensitivity</p> <p>AeroMACS receiver sensitivity shall comply with Table 7-1, AeroMACS receiver sensitivity values.</p> <p><i>N1.The computation of the sensitivity level for AeroMACS is described in the Aeronautical Mobile Airport Communications System (AeroMACS) Manual (Doc 10044).</i></p> <p><i>N2.AeroMACS receiver would be 2 dB more sensitive than indicated if Convolutional Turbo Codes (CTC) is used.</i></p> <p><i>N3.The sensitivity level is defined as the power level measured at the receiver input when the bit error rate (BER) is equal to 1×10^{-6} and all active subcarriers are transmitted in the channel. In general the requisite input power depends on the number of active subcarriers of the transmission.</i></p> <p><i>N4.The values in Table 7-1 assume a receiver noise figure of 8 dB.</i></p> <p><i>N5.The sensitivity values in Table 7-1 assume absence of any source of interference except for thermal and receiver noise.</i></p> <p><i>N6.</i></p>	CV CAR 19, 19.B.230, (1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.4.5.1 Standard	<p align="center">7.4.5 Spectral mask and emissions</p> <p>The power spectral density of the emissions when all active subcarriers are transmitted in the channel shall be attenuated below the maximum power spectral density as follows:</p> <ul style="list-style-type: none"> a) on any frequency removed from the assigned frequency between 50 and 55 per cent of the authorized bandwidth: 26 + 145 log (per cent of BW/50) dB; b) on any frequency removed from the assigned frequency between 55 and 100 per cent of the authorized bandwidth: 32 + 31 log (per cent of (BW)/55) dB; c) on any frequency removed from the assigned frequency between 100 and 150 per cent of the authorized bandwidth: 40 + 57 log (per cent of (BW)/100) dB; and d) on any frequency removed from the assigned frequency beyond 150 per cent of the authorized bandwidth: 50 dB. <p><i>Note.— The power spectral density at a given frequency is the power within a bandwidth equal to 100 kHz centred at this frequency, divided by this measurement bandwidth. It is made clear that the measurement of the power spectral density should encompass the energy over at least one frame period.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.5.2 Standard	AeroMACS shall implement power control.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.4.5.3 Standard	AeroMACS minimum rejection for adjacent (+/-5MHz) channel, measured at BER=10 ⁻⁶ level for a victim signal power 3 dB higher than the receiver sensitivity, shall be 10 dB for 16 QAM 3/4.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.5.4 Standard	AeroMACS minimum rejection for adjacent (+/-5MHz) channel, measured at BER=10 ⁻⁶ level for a victim signal power 3 dB higher than the receiver sensitivity, shall be 4 dB for 64 QAM 3/4.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.5.5 Standard	AeroMACS minimum rejection for second adjacent (+/-10MHz) channel and beyond, measured at BER=10 ⁻⁶ level for a victim signal power 3 dB higher than the receiver sensitivity, shall be 29 dB for 16 QAM 3/4.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.5.6 Standard	AeroMACS minimum rejection for second adjacent (+/-10MHz) channel and beyond, measured at BER=10 ⁻⁶ level for a victim signal power 3 dB higher than the receiver sensitivity, shall be 23 dB for 64 QAM 3/4. <i>Note.— For additional clarification to the requirements stated in 7.4.5.3, 7.4.5.4, 7.4.5.5 and 7.4.5.6, refer to IEEE 802.16-2009 section 8.4.14.2.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.4.6.1 Standard	<p style="text-align: center;">7.4.6 Frequency tolerance</p> <p>AeroMACS BS transmitter frequency tolerance shall be better than $\pm 2 \times 10^{-6}$ of nominal channel frequency.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.6.2 Standard	AeroMACS MS transmitter centre frequency shall be locked to that of the BS transmission centre frequency with a tolerance better than 2 per cent of the subcarrier spacing.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.4.6.3 Standard	AeroMACS MS shall track the frequency of the BS and shall defer any transmission if synchronization is lost or exceeds the tolerances given above.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.1.1 Standard	<p style="text-align: center;">7.5 PERFORMANCE REQUIREMENTS</p> <p style="text-align: center;">7.5.1 AeroMACS communications service provider</p> <p>The maximum unplanned service outage duration on a per aerodrome basis shall be 6 minutes.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.5.1.2 Standard	The maximum accumulated unplanned service outage time on a per aerodrome basis shall be 240 minutes/year.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.1.3 Standard	The maximum number of unplanned service outages shall not exceed 40 per year per aerodrome. <i>Note.— The requirements given in 7.5.1.1 to 7.5.1.3 refer to the overall service provision by the AeroMACS communication service provider on the aerodrome surface. This may include other media which can provide alternate communication paths in the event of an AeroMACS failure.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.1.4 Standard	Connection resilience. The probability that a transaction will be completed once started shall be at least 0.999 for AeroMACS over any one-hour interval. <i>Note.— Connection releases resulting from AeroMACS handover between base stations, log-off or circuit pre-emption are excluded from this specification.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.2.1 Standard	7.5.2 Doppler shift AeroMACS shall operate with a Doppler shift induced by the movement of the MS up to a radial speed of 92.6 km (50 NM) per hour, relative to the BS.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.5.3.1 Standard	<p style="text-align: center;">7.5.3 Delay</p> <p>Subnetwork entry time shall be less than 90 seconds.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.3.2 Recommendation	<p>Recommendation.— <i>Subnetwork entry time should be less than 20 seconds.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.3.3 Standard	The from-MS data transit delay (95th percentile) for the highest priority data service, shall be less than or equal to 1.4 seconds over a window of 1 hour or 600 SDUs, whichever is longer.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.3.4 Standard	The to-MS data transit delay (95th percentile) for the highest priority data service, shall be less than or equal to 1.4 seconds over a window of 1 hour or 600 SDUs, whichever is longer.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.4.1 Standard	<p style="text-align: center;">7.5.4 Integrity</p> <p>AeroMACS BS and MS shall support mechanisms to detect and correct corrupt SNSDUs.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.5.4.2 Standard	AeroMACS BS and MS shall only process SNSDUs addressed to themselves.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.4.3 Recommendation	Recommendation. — <i>The residual error rate, to/from MS should be less than or equal to 5×10^{-8} per SNSDU.</i> <i>Note.</i> — <i>There are no integrity requirements for SNSDU residual rate to the BS and MS as the requirement is entirely satisfied by the end-to-end systems in the aircraft and air traffic service provider.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.4.4 Standard	The maximum bit error rate shall not exceed 10^{-6} after CTC-FEC, if the received signal is equal to or greater than the minimum sensitivity level for the modulations scheme used, as given in Table 7-1.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.5.1 Standard	7.5.5 Security AeroMACS shall provide a capability to protect the integrity of messages in transit. <i>Note.</i> — <i>The capability includes cryptographic mechanisms to provide integrity of messages in transit.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.5.5.2 Standard	AeroMACS shall provide a capability to protect the availability of the system. <i>Note.— The capability includes measures to ensure that the system and its capacity are available for authorized uses during unauthorized events.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.5.3 Standard	AeroMACS shall provide a capability to protect the confidentiality of messages in transit. <i>Note.— The capability includes cryptographic mechanisms to provide encryption/decryption of messages.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.5.4 Standard	AeroMACS shall provide an authentication capability. <i>Note.— The capability includes cryptographic mechanisms to provide peer entity authentication, mutual peer entity authentication, and data origin authentication.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.5.5 Standard	AeroMACS shall provide a capability to ensure the authenticity of messages in transit. <i>Note.— The capability includes cryptographic mechanisms to provide authenticity of messages in transit.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.5.5.6 Standard	AeroMACS shall provide a capability to authorize the permitted actions of users of the system. <i>Note.— The capability includes mechanisms to explicitly authorize the actions of authenticated users. Actions that are not explicitly authorized are denied.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.5.5.7 Standard	If AeroMACS provide interfaces to multiple domains, AeroMACS shall provide capability to prevent intrusion from lower integrity domain to higher integrity domain.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.6.1 Standard	7.6 SYSTEM INTERFACES AeroMACS shall provide data service interface to the system users.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.6.2 Standard	AeroMACS shall support notification of the status of communications. <i>Note.— This requirement could support notification of the loss of communications (such as join and leave events).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.7.1 Standard	7.7 APPLICATION REQUIREMENTS AeroMACS shall support multiple classes of services to provide appropriate service levels to applications.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 7 Reference 7.7.2 Standard	If there is a resource contention, AeroMACS shall pre-empt services with a lower priority than those given in Annex 10, Volume II, 5.1.8.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 8 Reference</p> <p>Definition</p>	<p style="text-align: center;">CHAPTER 8. AFTN NETWORK</p> <p style="text-align: center;">8.1 DEFINITIONS</p> <p>Data signalling rate. Data signalling rate refers to the passage of information per unit of time, and is expressed in bits/ second. Data signalling rate is given by the formula:</p> <p>where m is the number of parallel channels, T_i is the minimum interval for the ith channel expressed in seconds, n_i is the number of significant conditions of the modulation in the ith channel.</p> <p>N1.</p> <p>a) For a single channel (serial transmission) it reduces to $(1/T)\log_2 n$; with a two-condition modulation ($n = 2$), it is $1/T$.</p> <p>b) For a parallel transmission with equal minimum intervals and equal number of significant conditions on each channel, it is $m(1/T)\log_2 n$ ($m(1/T)$ in case of a two-condition modulation.)</p> <p>N2. In the above definition, the term "parallel channels" is interpreted to mean: channels, each of which carries an integral part of an information unit, e.g. the parallel transmission of bits forming a character. In the case of a circuit comprising a number of channels, each of which carries information "independently", with the sole purpose of increasing the traffic handling capacity, these channels are not to be regarded as parallel channels in the context of this definition.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference Definition	Degree of standardized test distortion. The degree of distortion of the restitution measured during a specific period of time when the modulation is perfect and corresponds to a specific text.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference Definition	Effective margin. That margin of an individual apparatus which could be measured under actual operating conditions.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference Definition	Low modulation rates. Modulation rates up to and including 300 bauds.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference Definition	Margin. The maximum degree of distortion of the circuit at the end of which the apparatus is situated which is compatible with the correct translation of all the signals which it may possibly receive.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference Definition	Medium modulation rates. Modulation rates above 300 and up to and including 3 000 bauds.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference Definition	<p>Modulation rate. The reciprocal of the unit interval measured in seconds. This rate is expressed in bauds.</p> <p><i>Note.— Telegraph signals are characterized by intervals of time of duration equal to or longer than the shortest or unit interval. The modulation rate (formerly telegraph speed) is therefore expressed as the inverse of the value of this unit interval. If, for example, the unit interval is 20 milliseconds, the modulation rate is 50 bauds.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference Definition	<p>Synchronous operation. Operation in which the time interval between code units is a constant.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.1 Standard	<p align="center">8.2 TECHNICAL PROVISIONS RELATING TO TELETYPEWRITER APPARATUS AND CIRCUITS USED IN THE AFTN</p> <p>In international teletypewriter circuits of the AFTN, using a 5-unit code, the International Telegraph Alphabet No 2 (see Table 8-1*) shall be used only to the extent prescribed in 4.1.2 of Volume II.</p> <hr/> <p>* All tables and figures are located at the end of this chapter.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.2 Recommendation	Recommendation. — <i>The modulation rate should be determined by bilateral or multilateral agreement between administrations concerned, taking into account primarily traffic volume.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.3 Recommendation	Recommendation. — <i>The nominal duration of the transmitting cycle should be at least 7.4 units (preferably 7.5), the stop element lasting for at least 1.4 units (preferably 1.5).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.3.1 Recommendation	Recommendation. — <i>The receiver should be able to translate correctly in service the signals coming from a transmitter with a nominal transmitting cycle of 7 units.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.4 Recommendation	Recommendation. — <i>Apparatus in service should be maintained and adjusted in such a manner that its net effective margin is never less than 35 per cent.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.5 Recommendation	Recommendation. — <i>The number of characters which the textual line of the page-printing apparatus may contain should be fixed at 69.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.6 Recommendation	Recommendation. — <i>In start-stop apparatus fitted with automatic time delay switches, the disconnection of the power supply to the motor should not take place before the lapse of at least 45 seconds after the reception of the last signal.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.7 Recommendation	Recommendation. — <i>Arrangements should be made to avoid the mutilation of signals transmitted at the head of a message and received on start-stop reperforating apparatus.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.7.1 Recommendation	Recommendation. — <i>If the reperforating apparatus is provided with local means for feeding the paper, not more than one mutilated signal should be tolerated.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.8 Recommendation	Recommendation. — <i>Complete circuits should be so engineered and maintained that their degree of standardized test distortion does not exceed 28 per cent on the standardized text:</i> THE QUICK BROWN FOX JUMPS OVER THE LAZY DOG <i>or</i> VOYEZ LE BRICK GEANT QUE JEXAMINE PRES DU WHARF	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.9 Recommendation	Recommendation. — <i>The degree of isochronous distortion on the standardized text of each of the parts of a complete circuit should be as low as possible, and in any case should not exceed 10 per cent.</i>	CV CAR 19, 19.B.230, (1) CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.10 Recommendation	Recommendation. — <i>The overall distortion in transmitting equipment used on teletypewriter channels should not exceed 5 per cent.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.2.11 Recommendation	Recommendation. — <i>AFTN circuits should be equipped with a system of continuous check of channel condition. Additionally, controlled circuit protocols should be applied.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.3.1.1 Recommendation	<p align="center">8.3 TERMINAL EQUIPMENT ASSOCIATED WITH AERONAUTICAL RADIOTELETYPEWRITER CHANNELS OPERATING IN THE BAND 2.5 – 30 MHz</p> <p align="center">8.3.1 Selection of type of modulation and code</p> <p>Recommendation.— <i>Frequency shift modulation (F1B) should be employed in radioteletypewriter systems used in the aeronautical fixed service (AFS), except where the characteristics of the independent sideband (ISB) method of operation are of advantage.</i></p> <p><i>Note.</i>— <i>F1B type of modulation is accomplished by shifting a radio frequency carrier between two frequencies representing “position A” (start signal polarity) and “position Z” (stop signal polarity) of the start-stop 5-unit telegraphic code.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.3.2.1 Recommendation	<p align="center">8.3.2 System characteristics</p> <p>Recommendation.— <i>The characteristics of signals from radioteletypewriter transmitters utilizing F1B modulation should be as follows:</i></p> <ul style="list-style-type: none"> a) <i>Frequency shift: the lowest possible value.</i> b) <i>Frequency shift tolerance: within plus or minus 3 per cent of the nominal value of the frequency shift.</i> c) <i>Polarity: single channel circuits: the higher frequency corresponds to “position A” (start signal polarity).</i> 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.3.2.2 Recommendation	Recommendation. — <i>The variation of the mean between the radio frequencies representing respectively “position A” and “position Z” should not exceed 100 Hz during any two-hour period.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.3.2.3 Recommendation	Recommendation. — <i>The over-all distortion of the teletypewriter signal, as monitored at the output of the radio transmitter or in its immediate vicinity, should not exceed 10 per cent.</i> <i>Note.</i> — <i>Such distortion means the displacement in time of the transitions between elements from their proper positions, expressed as a percentage of unit element time.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.3.2.4 Recommendation	Recommendation. — <i>Radioteletypewriter receivers concerned with F1B modulation should be capable of operating satisfactorily on signals having the characteristics set out in 8.3.2.1 and 8.3.2.2 above.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.3.2.5 Recommendation	Recommendation. — <i>The characteristics of multichannel transmission of teletypewriter signals over a radio circuit should be established by agreement between the Administrations concerned.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.4.1 Recommendation	<p>8.4 CHARACTERISTICS OF INTERREGIONAL AFS CIRCUITS</p> <p>Recommendation.— <i>Interregional AFS circuits being implemented or upgraded should employ high quality telecommunications service. Modulation rate should take into account traffic volumes expected under both normal and alternate route conditions.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.5.1.1 Recommendation	<p>8.5 TECHNICAL PROVISIONS RELATING TO ATS MESSAGE TRANSMISSION</p> <p><i>8.5.1 Interconnection by direct or omnibus channels — low modulation rates — 5-unit code.</i></p> <p><i>Note.— See 8.6 for medium modulation rates.</i></p> <p>Recommendation.— <i>AFTN techniques (cf. 8.2) should be used.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.1.1 Recommendation	<p align="center">8.6 TECHNICAL PROVISIONS RELATING TO INTERNATIONAL GROUND-GROUND DATA INTERCHANGE AT MEDIUM AND HIGHER SIGNALLING RATES</p> <p align="center"><i>Note.— Throughout this section in the context of coded character sets, the term “unit” means the unit of selective information and is essentially equivalent to the term “bit”.</i></p> <p align="center">8.6.1 General</p> <p>Recommendation.— <i>In international data interchange of characters, a 7-unit coded character set providing a repertoire of 128 characters and designated as International Alphabet No. 5 (IA-5) should be used. Compatibility with the 5-unit coded character set of International Telegraph Alphabet No. 2 (ITA-2) should be ensured where applicable.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.1.2 Standard	When the provisions of 8.6.1.1 are applied, International Alphabet No. 5 (IA-5) contained in Table 8-2 shall be used.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.1.2.1 Standard	The serial transmission of units comprising an individual character of IA-5 shall be with the low order unit (b ₁) transmitted first.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.1.2.2 Recommendation	Recommendation. — <i>When IA-5 is used, each character should include an additional unit for parity in the eighth level position.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.1.2.3 Standard	When the provisions of 8.6.1.2.2 are applied, the sense of the character parity bit shall produce even parity in links which operate on the start-stop principle, and odd parity in links using end-to-end synchronous operations.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.1.2.4 Standard	Character-for-character conversion shall be as listed in Tables 8-3 and 8-4 for all characters which are authorized in the AFTN format for transmission on the AFS in both IA-5 and ITA-2.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.1.2.5 Standard	Characters which appear in only one code set, or which are not authorized for transmission on the AFS shall be as depicted in the code conversion tables.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																	
Chapter 8 Reference 8.6.2.1 Recommendation	<p>8.6.2 Data transmission characteristics</p> <p>Recommendation.— <i>The data signalling rate should be chosen from among the following:</i></p> <p>600 bits/s 4 800 bits/s 1 200 bits/s 9 600 bits/s 2 400 bits/s</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference																																			
Chapter 8 Reference 8.6.2.2 Recommendation	<p>Recommendation.— <i>The type of transmission for each data signalling rate should be chosen as follows:</i></p> <table border="0"> <tr> <td>Data transmission</td> <td>signalling rate</td> <td>Type of</td> </tr> <tr> <td>600 bits/s</td> <td></td> <td>Synchronous</td> </tr> <tr> <td colspan="3"><i>or asynchronous serial transmission</i></td> </tr> <tr> <td>1 200 bits/s</td> <td></td> <td>Synchronous</td> </tr> <tr> <td colspan="3"><i>or asynchronous serial transmission</i></td> </tr> <tr> <td>2 400 bits/s</td> <td></td> <td>Synchronous</td> </tr> <tr> <td colspan="3"><i>serial transmission</i></td> </tr> <tr> <td>4 800 bits/s</td> <td></td> <td>Synchronous</td> </tr> <tr> <td colspan="3"><i>serial transmission</i></td> </tr> <tr> <td>9 600 bits/s</td> <td></td> <td>Synchronous</td> </tr> <tr> <td colspan="3"><i>serial transmission</i></td> </tr> </table>	Data transmission	signalling rate	Type of	600 bits/s		Synchronous	<i>or asynchronous serial transmission</i>			1 200 bits/s		Synchronous	<i>or asynchronous serial transmission</i>			2 400 bits/s		Synchronous	<i>serial transmission</i>			4 800 bits/s		Synchronous	<i>serial transmission</i>			9 600 bits/s		Synchronous	<i>serial transmission</i>			CV CAR 19, 19.B.230, (a),(1)	No Difference		
Data transmission	signalling rate	Type of																																				
600 bits/s		Synchronous																																				
<i>or asynchronous serial transmission</i>																																						
1 200 bits/s		Synchronous																																				
<i>or asynchronous serial transmission</i>																																						
2 400 bits/s		Synchronous																																				
<i>serial transmission</i>																																						
4 800 bits/s		Synchronous																																				
<i>serial transmission</i>																																						
9 600 bits/s		Synchronous																																				
<i>serial transmission</i>																																						



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																								
Chapter 8 Reference 8.6.2.3 Recommendation	<p>Recommendation.— <i>The type of modulation for each data signalling rate should be chosen as follows:</i></p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%; text-align: center;">Data</td> <td style="width: 20%; text-align: center;">signalling rate</td> <td style="width: 20%; text-align: center;">Type of</td> <td style="width: 40%;"></td> </tr> <tr> <td style="text-align: center;">600</td> <td style="text-align: center;">bits/s</td> <td style="text-align: center;">Frequency</td> <td></td> </tr> <tr> <td style="text-align: center;">1 200</td> <td style="text-align: center;">bits/s</td> <td style="text-align: center;">Frequency</td> <td></td> </tr> <tr> <td style="text-align: center;">2 400</td> <td style="text-align: center;">bits/s</td> <td style="text-align: center;">Phase</td> <td></td> </tr> <tr> <td style="text-align: center;">4 800</td> <td style="text-align: center;">bits/s</td> <td style="text-align: center;">Phase</td> <td></td> </tr> <tr> <td style="text-align: center;">9 600</td> <td style="text-align: center;">bits/s</td> <td style="text-align: center;">Phase-amplitude</td> <td></td> </tr> </table> <p><i>Note.</i>— <i>This recommendation does not necessarily apply to ground-ground extensions of air-ground links used exclusively for the transfer of air-ground data, inasmuch as such circuits may be considered as part of the air-ground link.</i></p>	Data	signalling rate	Type of		600	bits/s	Frequency		1 200	bits/s	Frequency		2 400	bits/s	Phase		4 800	bits/s	Phase		9 600	bits/s	Phase-amplitude		CV CAR 19, 19.B.230, (a),(1)	No Difference		
Data	signalling rate	Type of																											
600	bits/s	Frequency																											
1 200	bits/s	Frequency																											
2 400	bits/s	Phase																											
4 800	bits/s	Phase																											
9 600	bits/s	Phase-amplitude																											
Chapter 8 Reference 8.6.2.4.1 Standard	<p>8.6.2.4 CHARACTER STRUCTURE ON DATA LINKS</p> <p>Character parity shall not be used for error checking on CIDIN links. Parity appended to IA-5 coded characters per 8.6.1.2.2, prior to entry to the CIDIN shall be ignored. For messages exiting the CIDIN, parity shall be generated in accordance with 8.6.1.2.3.</p>	CV CAR 19, 19.B.230, (a),(1)	Not Applicable																										
Chapter 8 Reference 8.6.2.4.2 Standard	<p>Characters of less than eight bits in length shall be padded out to eight bits in length before transmission over any octet based or bit-oriented communications network. The padding bits shall occupy the higher order end of the octet, i.e. bit 8, bit 7 as required, and shall have the binary values 0.</p>	CV CAR 19, 19.B.230, (a),(1)	Not Applicable																										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.2.5 Standard	When exchanging data over CIDIN links using bit-oriented procedures, the entry centre address, exit centre addresses and destination addresses in the Transport and CIDIN Packet Headers shall be in the IA-5 character set contained in Table 8-2.	CV CAR 19, 19.B.230, (a),(1)	Not Applicable		
Chapter 8 Reference 8.6.2.6 Recommendation	Recommendation. — <i>When transmitting messages in AFTN format over CIDIN links using bit-oriented procedures, the messages should be in the IA-5 character set contained in Table 8-2.</i>	CV CAR 19, 19.B.230, (a),(1)	Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.1 Standard	<p>8.6.3 Ground-ground character-oriented data link control procedures</p> <p><i>Note.— The provisions of this section pertain to ground-ground data interchange applications using IA-5 prescribed by 8.6.1 and which employ the ten transmission control characters (SOH, STX, ETX, EOT, ENQ, ACK, DLE, NAK, SYN, and ETB) for data link control, over synchronous or asynchronous transmission facilities.</i></p> <p><i>Descriptions.</i> The following descriptions shall apply to data link applications contained in this section:</p> <ul style="list-style-type: none"> a) A master station is that station which has control of the data link at a given instant. b) A slave station is one that has been selected to receive a transmission from the master station. c) A control station is the single station on a multipoint link that is permitted to assume master status and deliver messages to one or more individually selected (non-control) tributary stations, or it is permitted to assign temporary master status to any of the other tributary stations. 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.3 Standard	Three system categories are specified in terms of their respective circuit characteristics, terminal configurations, and message transfer procedures as follows: System category A: two-way alternate, multipoint allowing either centralized or non-centralized operation and single or multiple message-oriented information transfers without replies (but with delivery verification). System category B: two-way simultaneous, point-to-point employing message associated blocking and modulo 8 numbering of blocks and acknowledgements. System category C: two-way alternate, multipoint allowing only centralized (computer-to-terminal) operation, single or multiple message transfers with replies.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.3.1 Standard	<p>In addition to the characteristics prescribed in the paragraphs that follow for both system categories A and B, other parameters that shall be accounted for in order to ensure viable, operationally reliable communications include:</p> <p>a) the number of SYN characters required to establish and maintain synchronization; <i>Note.— Normally the transmitting station sends three contiguous SYN characters and the receiving station detects at least two before any action is taken.</i></p> <p>b) the values of system time-outs for such functions as “idle line” and “no response” as well as the number of automatic retries that are to be attempted before manual intervention is signalled;</p> <p>c) the composition of prefixes within a 15 character maximum. <i>Note.— By agreement between the administrations concerned, it is permissible for supervisory signals to contain a station identification prefix using characters selected from columns 4 through 7 of IA-5.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.3.2 Recommendation	Recommendation.— <i>For multipoint implementations designed to permit only centralized (computer-to-terminal) operations, the provisions of 8.6.3.7 should be employed.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.4.1 Standard	<p style="text-align: center;">8.6.3.4 BLOCK CHECK CHARACTER</p> <p>Both system category A and B shall utilize a block check character to determine the validity of a transmission.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.4.2 Standard	The block check character shall be composed of 7 bits plus a parity bit.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.4.3 Standard	Each of the first 7 bits of the block check character shall be the modulo 2 binary sum of every element in the same bit 1 to bit 7 column of the successive characters of the transmitted block.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.4.4 Standard	The longitudinal parity of each column of the block, including the block check character, shall be even.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.4.5 Standard	The sense of the parity bit of the block check character shall be the same as for the information characters (see 8.6.1.2.3).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.4.6.1 Standard	<i>8.6.3.4.6 SUMMATION</i> The summation to obtain the block check character shall be started by the first appearance of either SOH (start of heading) or STX (start of text).	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.4.6.2 Standard	The starting character shall not be included in the summation.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.4.6.3 Standard	If an STX character appears after the summation has been started by SOH, then the STX character shall be included in the summation as if it were a text character.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.4.6.4 Standard	With the exception of SYN (synchronous idle), all the characters which are transmitted after the start of the block check summation shall be included in the summation, including the ETB (end of transmission/block) or ETX (end of text) control character which signals that the following character is the block check character.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.4.7 Standard	No character, SYN or otherwise, shall be inserted between the ETB or ETX character and the block check character.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5 Standard	DESCRIPTION OF SYSTEM CATEGORY A System category A is one in which a number of stations are connected by a multipoint link and one station is permanently designated as the control station which monitors the link at all times to ensure orderly operation.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.5.1.1 Standard	8.6.3.5.1 LINK ESTABLISHMENT PROCEDURE To establish the link for transmission, the control station shall either: a) poll one of the tributary stations to assign it master status; or b) assume master status and select one or more tributary (slave) stations to receive a transmission.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.1.2 Standard	Polling shall be accomplished by the control station sending a polling supervisory sequence consisting of a prefix identifying a single tributary station and ending in ENQ.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.1.3 Standard	A tributary station detecting its assigned polling supervisory sequence shall assume master status and respond in one of two ways: a) if the station has a message to send, it shall initiate a selection supervisory sequence as described in 8.6.3.5.1.5; b) if the station has no message to send, it shall send EOT, and master status shall revert to the control station.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.1.4 Standard	If the control station detects an invalid or no response resulting from a poll, it shall terminate by sending EOT prior to resuming polling or selection.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.5.1.5 Standard	Selection shall be accomplished by the designated master station sending a selection supervisory sequence consisting of a prefix identifying a single station and ending in ENQ.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.1.6 Standard	A station detecting its assigned selection supervisory sequence shall assume slave status and send one of two replies: a) if the station is ready to receive, it shall send a prefix followed by ACK. Upon detecting this reply, the master station shall either select another station or proceed with message transfer; b) if the station is not ready to receive, it shall send a prefix followed by NAK and thereby relinquish slave status. If the master station receives NAK, or no reply, it shall either select another or the same tributary station or terminate; c) it shall be permissible for N retries ($N \geq 0$) to be made to select a station for which NAK, an invalid reply, or no response has been received.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.1.7 Standard	If one or more stations have been selected and have properly responded with ACK, the master station shall proceed with message transfer.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.5.2.1 Standard	8.6.3.5.2 MESSAGE TRANSFER PROCEDURE The master station shall send a message or series of messages, with or without headings to the selected slave station(s).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.2.2 Standard	The transmission of a message shall: a) begin with: SOH if the message has a heading, STX if the message has no heading; b) be continuous, ending with ETX, immediately followed by a block check character (BCC).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.2.3 Standard	After transmitting one or more messages, the master station shall verify successful delivery at each selected slave station.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.3.1 Standard	8.6.3.5.3 DELIVERY VERIFICATION PROCEDURE The master station shall send a delivery verification supervisory sequence consisting of a prefix identifying a single slave station and ending in ENQ.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.5.3.2 Standard	A slave station detecting its assigned delivery verification supervisory sequence shall send one of two replies: a) if the slave station properly received all of the transmission, it shall send an optional prefix followed by ACK; b) if the slave station did not receive all of the transmission properly, it shall send an optional prefix followed by NAK.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.3.3 Standard	If the master station receives no reply or an invalid reply, it shall request a reply from the same or another slave station until all selected stations have been properly accounted for.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.3.4 Standard	If the master station receives a negative reply (NAK) or, after $N \geq 0$ repeat attempts, no reply, it shall repeat that transmission to the appropriate slave stations at a later opportunity.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.5.3.5 Standard	After all messages have been sent and delivery verified, the master station shall proceed with link termination.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.5.4.1 Standard	8.6.3.5.4 LINK TERMINATION PROCEDURE The terminate function, negating the master or slave status of all stations and returning master status to the control station, shall be accomplished by the master station transmitting EOT.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6 Standard	DESCRIPTION OF SYSTEM CATEGORY B System category B is one in which two stations are on a point-to-point, full-duplex link and each station has the capability to maintain concurrent master and slave status, i.e. master status on its transmit side and slave status on its receive side and both stations can transmit simultaneously.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6.1.1 Standard	8.6.3.6.1 LINK ESTABLISHMENT PROCEDURE To establish the link for message transfers (from the calling to the called station), the calling station shall request the identity of the called station by sending an identification supervisory sequence consisting of a DLE character followed by a colon character, an optional prefix, and ENQ.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6.1.2 Standard	The called station, upon detecting ENQ, shall send one of two replies: a) if ready to receive, it shall send a sequence consisting of a DLE followed by a colon, a prefix which includes its identity and ended by ACK0 (see 8.6.3.6.2.5). This establishes the link for message transfers from the calling to the called station; b) if not ready to receive, it shall send the above sequence with the ACK0 replaced by NAK.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.6.1.3 Standard	Establishment of the link for message transfers in the opposite direction can be initiated at any time following circuit connection in a similar manner to that described above.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6.2.1 Standard	8.6.3.6.2 MESSAGE TRANSFER PROCEDURE System category B message transfer provides for message associated blocking with longitudinal checking and modulo 8 numbered acknowledgements.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6.2.2 Standard	It is permissible for a transmission block to be a complete message or a portion of a message. The sending station shall initiate the transmission with SOTB N followed by: <ul style="list-style-type: none"> a) SOH if it is the beginning of a message that contains a heading; b) STX if it is the beginning of a message that has no heading; c) SOH if it is an intermediate block that continues a heading; d) STX if it is an intermediate block that continues a text. <i>Note.— SOTB N is the two-character transmission control sequence DLE = (characters 1/0, and 3/13) followed by the block number, N, where N is one of the IA-5 characters 0, 1 ... 7 (characters 3/0, 3/1 ... 3/7).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.6.2.3 Standard	A block which ends at an intermediate point within a message shall be ended with ETB; a block which ends at the end of a message shall be ended with ETX.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6.2.4 Standard	It shall be permissible for each station to initiate and continue to send messages to the other concurrently according to the following sequence. a) It shall be permissible for the sending station (master side) to send blocks, containing messages or parts of messages, continuously to the receiving station (slave side) without waiting for a reply. b) It shall be permissible for replies, in the form of slave responses, to be transmitted by the receiving station while the sending station is sending subsequent blocks. <i>Note.— By use of modulo 8 numbering of blocks and replies, it shall be permissible for the sending station to send as many as seven blocks ahead of the received replies before being required to stop transmission until six or less blocks are outstanding.</i> c) If a negative reply is received, the sending station (master side) shall start retransmission with the block following the last block for which the proper affirmative acknowledgement was received.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.6.2.5 Standard	Slave responses shall be according to one of the following: a) if a transmission block is received without error and the station is ready to receive another block, it shall send DLE, a colon, an optional prefix, and the appropriate acknowledgement ACKN (referring to the received block beginning with SOTB N, e.g. ACK0, transmitted as DLE0 is used as the affirmative reply to the block numbered SOTB0, DLE1 for SOTB1, etc.); b) if a transmission block is not acceptable, the receiving station shall send DLE, a colon, an optional prefix, and NAK.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6.2.6 Recommendation	Recommendation. — <i>Slave responses should be interleaved between message blocks and transmitted at the earliest possible time.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6.3.1 Standard	8.6.3.6.3 LINK TERMINATION PROCEDURE If the link has been established for message transfers in either or both directions, the sending of EOT by a station shall signal the end of message transfers in that direction. To resume message transfers after sending EOT, the link shall be re-established in that direction.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.6.3.2 Standard	EOT shall only be transmitted by a station after all outstanding slave responses have been received or otherwise accounted for.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.6.4.1 Standard	<p>8.6.3.6.4 <i>CIRCUIT DISCONNECTION</i></p> <p>On switched connections, the data links in both directions shall be terminated before the connection is cleared. In addition, the station initiating clearing of the connection shall first announce its intention to do so by transmitting the two-character sequence DLE EOT, followed by any other signals required to clear the connection.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7 Standard	<p>DESCRIPTION OF SYSTEM CATEGORY C (CENTRALIZED)</p> <p>System category C (centralized) is one (like system category A) in which a number of stations are connected by a multipoint link and one station is designated as the control station but (unlike system category A) provides only for centralized (computer-to-terminal) operations where message interchange (with replies) shall be constrained to occur only between the control and a selected tributary station.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.1.1 Standard	<p>8.6.3.7.1 <i>LINK ESTABLISHMENT PROCEDURE</i></p> <p>To establish the link for transmission the control station shall either:</p> <ul style="list-style-type: none"> a) poll one of the tributary stations to assign it master status; or b) assume master status and select a tributary station to assume slave status and receive a transmission according to either of two prescribed selection procedures: <ul style="list-style-type: none"> 1) selection with response (see 8.6.3.7.1.5); or 2) fast select (see 8.6.3.7.1.7). 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.7.1.2 Standard	Polling is accomplished by the control station sending a polling supervisory sequence consisting of a prefix identifying a single tributary station and ending in ENQ.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.1.3 Standard	A tributary station detecting its assigned polling supervisory sequence shall assume master status and respond in one of two ways: a) if the station has a message to send, it shall initiate message transfer. The control station assumes slave status; b) if the station has no message to send, it shall send EOT and master status shall revert to the control station.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.1.4 Standard	If the control station detects an invalid or no response resulting from a poll, it shall terminate by sending EOT prior to resuming polling or selection.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.1.5 Standard	Selection with response is accomplished by the control station assuming master status and sending a selection supervisory sequence consisting of a prefix identifying a single tributary station and ending in ENQ.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.7.1.6 Standard	<p>A tributary station detecting its assigned selection supervisory sequence shall assume slave status and send one of two replies:</p> <ul style="list-style-type: none"> a) if the station is ready to receive, it shall send an optional prefix followed by ACK. Upon detecting this reply, the master station shall proceed with message transfer; b) if the station is not ready to receive, it shall send an optional prefix followed by NAK. Upon detecting NAK, it shall be permissible for the master station to again attempt selecting the same tributary station or initiate termination by sending EOT. <p><i>Note.— If the control station receives an invalid or no reply, it is permitted to attempt again to select the same tributary or after N retries (N ≥ 0) either to exit to a recovery procedure or to initiate termination by sending EOT.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.1.7 Standard	Fast select is accomplished by the control station assuming master status and sending a selection supervisory sequence, and without ending this transmission with ENQ or waiting for the selected tributary to respond, proceeding directly to message transfer.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.2.1 Standard	<p><i>MESSAGE TRANSFER PROCEDURE</i></p> <p>The station with master status shall send a single message to the station with slave status and wait for a reply.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.7.2.2 Standard	The message transmission shall: a) begin with: SOH if the message has a heading, STX if the message has no heading; and b) be continuous, ending with ETX, immediately followed by BCC.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.2.3 Standard	The slave station, upon detecting ETX followed by BCC, shall send one of two replies: a) if the messages were accepted and the slave station is ready to receive another message, it shall send an optional prefix followed by ACK. Upon detecting ACK, the master station shall be permitted either to transmit the next message or initiate termination; b) if the message was not accepted and the slave station is ready to receive another message, it shall send an optional prefix followed by NAK. Upon detecting NAK, the master station may either transmit another message or initiate termination. Following the NAK reply, the next message transmitted need not be a retransmission of the message that was not accepted.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.2.4 Standard	If the master station receives an invalid or no reply to a message, it shall be permitted to send a delivery verification supervisory sequence consisting of an optional prefix followed by ENQ. Upon receipt of a delivery verification supervisory sequence, the slave station repeats its last reply.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.3.7.2.5 Standard	<i>N</i> retries ($N \geq 0$) may be made by the master station in order to get a valid slave reply. If a valid reply is not received after <i>N</i> retries, the master station exits to a recovery procedure.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.3.7.3.1 Standard	<i>8.6.3.7.3 LINK TERMINATION PROCEDURE</i> The station with master status shall transmit EOT to indicate that it has no more messages to transmit. EOT shall negate the master/slave status of both stations and return master status to the control station.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.1 Standard	<p>8.6.4 Ground-ground bit-oriented data link control procedures</p> <p><i>Note.— The provisions of this section pertain to ground-ground data interchange applications using bit-oriented data link control procedures enabling transparent, synchronous transmission that is independent of any encoding; data link control functions are accomplished by interpreting designated bit positions in the transmission envelope of a frame.</i></p> <p>The following descriptions shall apply to data link applications contained in this section:</p> <ul style="list-style-type: none"> a) Bit-oriented data link control procedures enable transparent transmission that is independent of any encoding. b) A data link is the logical association of two interconnected stations, including the communication control capability of the interconnected stations. c) A station is a configuration of logical elements, from or to which messages are transmitted on a data link, including those elements which control the message flow on the link via communication control procedures. d) A combined station sends and receives both commands and responses and is responsible for control of the data link. e) Data communication control procedures are the means used to control and protect the orderly interchange of information between stations on a data link. f) A component is defined as a number of bits in a prescribed order within a sequence for the control and supervision of the data link. g) An octet is a group of 8 consecutive bits. h) A sequence is one or more components in prescribed 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>order comprising an integral number of octets.</p> <p>i) A field is a series of a specified number of bits or specified maximum number of bits which performs the functions of data link or communications control or constitutes data to be transferred.</p> <p>j) A frame is a unit of data to be transferred over the data link, comprising one or more fields in a prescribed order.</p> <p>k) A common ICAO data interchange network (CIDIN) switching centre is that part of an automatic AFTN switching centre which provides for the entry, relay, and exit centre functions using the bit-oriented link and CIDIN network procedures specified in this section and includes the appropriate interface(s) with other parts of the AFTN and with other networks.</p>				
<p>Chapter 8 Reference 8.6.4.2.1 Standard</p>	<p>8.6.4.2 BIT-ORIENTED DATA LINK CONTROL PROCEDURES FOR POINT-TO-POINT, GROUND-GROUND DATA INTERCHANGE APPLICATIONS EMPLOYING SYNCHRONOUS TRANSMISSION FACILITIES</p> <p><i>Note.— The following link level procedures are the same as the LAPB link level procedures described in ITU CCITT Recommendation X.25, Section 2, Yellow Book (1981 version). Later versions of Recommendation X.25 will be reviewed as they are released to ascertain whether or not they should be adopted.</i></p> <p><i>Frame format.</i> Frames shall contain not less than 32 bits, excluding the opening and closing flags, and shall conform to the following format:</p> <p style="text-align: center;">FLAG F ADDRESS A CONTROL C INFORMATION I FCS FLAG F</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.1.1 Standard	A frame shall consist of an opening flag (F), an address field (A), a control field (C), an optional information field (I), a frame check sequence (FCS), and a closing flag sequence (F), and shall be transmitted in that order. <i>Note.— In relation to CIDIN, the opening flag, the fields A and C, the FCS and the closing flag form together the Data Link Control Field (DLCF). The field 1 is denoted as the Link Data Field (LDF).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.1.1.1 Standard	The flag (F) shall be the 8-bit sequence 01111110 which delimits the beginning and ending of each frame. It shall be permissible for the closing flag of a frame to also serve as the opening flag of the next frame.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.1.1.2 Standard	The address (A) field shall consist of one octet, excluding 0 bits added to achieve transparent transmission, which shall contain the link address of the combined station.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.1.1.3 Standard	The control (C) field shall consist of one octet, excluding 0 bits added to achieve transparent transmission, and shall contain the commands, responses, and frame sequence number components for the control of the data link.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.1.1.4 Standard	The information (I) field shall contain digital data which may be presented in any code or sequence but shall not exceed a maximum of 259 octets, excluding 0 bits added to achieve transparent transmission. The I field shall always be a multiple of 8 bits in length.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.1.1.5 Standard	The frame check sequence (FCS) shall consist of two octets, excluding 0 bits added to achieve transparent transmission, and shall contain the error detecting bits.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.2 Standard	A frame check sequence (FCS) shall be included in each frame for the purpose of error checking.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.2.1 Standard	The error checking algorithm shall be a cyclic redundancy check (CRC).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.2.2 Standard	The CRC polynomial ($P(x)$) shall be $x^{16} + x^{12} + x^5 + 1.$	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.2.3 Standard	<p>The FCS shall be a 16-bit sequence. This FCS shall be the ones' complement of the remainder, $R(x)$, obtained from the modulo 2 division of</p> $x^{16}[G(x)] + x^k(x^{15} + x^{14} + x^{13} + \dots + x^2 + x + 1)$ <p>by the CRC polynomial, $P(x)$.</p> <p>$G(x)$ shall be the contents of the frame existing between, but including neither, the final bit of the opening flag nor the first bit of the FCS, excluding bits inserted for transparent transmission.</p> <p>K shall be the length of $G(x)$ (number of bits).</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference												
Chapter 8 Reference 8.6.4.2.2.4 Standard	<p>The generation and checking of the FCS accumulation shall be as follows:</p> <p>a) the transmitting station shall initiate the FCS accumulation with the first (least significant) bit of the address (A) field and shall include all bits up to and including the last bit preceding the FCS sequence, but shall exclude all 0 bits (if any) inserted to achieve transparent transmission;</p> <p>b) upon completion of the accumulation the FCS shall be transmitted, starting with bit b1 (highest order coefficient) and proceeding in sequence to bit b16 (lowest order coefficient) as shown below;</p> <div style="text-align: center;"> <p><i>trans</i></p> <p>↓</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">b16</td> <td style="padding: 0 10px;"><i>First bit mitted</i> b15</td> <td style="padding: 0 10px;">b14</td> <td style="padding: 0 10px;">b3</td> <td style="padding: 0 10px;">b2</td> <td style="padding: 0 10px;">b1</td> </tr> <tr> <td style="padding: 0 10px;">x0</td> <td style="padding: 0 10px;">x1</td> <td style="padding: 0 10px;">x2</td> <td style="padding: 0 10px;">x13</td> <td style="padding: 0 10px;">x14</td> <td style="padding: 0 10px;">x15</td> </tr> </table> </div> <p>c) the receiving station shall carry out the cyclic redundancy check (CRC) on the content of the frame commencing with the first bit received following the opening flag, and shall include all bits up to and including the last bit preceding the closing flag, but shall exclude all 0 bits (if any) deleted according to the rules for achievement of transparency;</p> <p>d) upon completion of the FCS accumulation, the receiving station shall examine the remainder. In the absence of transmission error, the remainder shall be 1111000010111000 (x0 through x15, respectively).</p>	b16	<i>First bit mitted</i> b15	b14	b3	b2	b1	x0	x1	x2	x13	x14	x15	CV CAR 19, 19.B.230, (a),(1)	No Difference		
b16	<i>First bit mitted</i> b15	b14	b3	b2	b1												
x0	x1	x2	x13	x14	x15												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.3 Standard	<i>Achievement of transparency.</i> The frame format contents (A, C, link data field, and FCS) shall be capable of containing any bit configuration.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.3.1 Standard	The following rules shall apply to all frame contents, except flag sequences: a) the transmitting station shall examine the frame contents before transmission, and shall insert a single 0 bit immediately following each sequence of 5 consecutive 1 bits; b) the receiving station shall examine the received frame contents for patterns consisting of 5 consecutive 1 bits immediately followed by one (or more) 0 bit(s) and shall remove the 0 bit which directly follows 5 consecutive 1 bits.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.4 Standard	<p><i>Special transmission sequences and related link states.</i> In addition to employing the prescribed repertoire of commands and responses to manage the interchange of data and control information, stations shall use the following conventions to signal the indicated conditions:</p> <ul style="list-style-type: none"> a) <i>Abort</i> is the procedure by which a station in the process of sending a frame ends the frame in an unusual manner such that the receiving station shall ignore the frame. The conventions for aborting a frame shall be: <ul style="list-style-type: none"> 1) transmitting at least seven, but less than fifteen, one bits (with no inserted zeros); 2) receiving seven one bits. b) <i>Active link state.</i> A link is in an active state when a station is transmitting a frame, an abort sequence, or interframe time fill. When the link is in the active state, the right of the transmitting station to continue transmission shall be reserved. c) <i>Interframe time fill.</i> Interframe time fill shall be accomplished by transmitting continuous flags between frames. There is no provision for time fill within a frame. d) <i>Idle link state.</i> A link is in an idle state when a continuous one condition is detected that persists for 15 bit times, or longer. Idle link time fill shall be a continuous one condition on the link. e) <i>Invalid frame.</i> An invalid frame is one that is not properly bounded by two flags or one which is shorter than 32 bits between flags. 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.5.1 Standard	8.6.4.2.5 MODES <i>Operational mode.</i> The operational mode shall be the asynchronous balanced mode (ABM).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.5.1.1 Standard	It shall be permissible for a combined station in ABM to transmit without invitation from the associated station.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.5.1.2 Standard	A combined station in ABM shall be permitted to transmit any command or response type frame except DM.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.5.2 Standard	<i>Non-operational mode.</i> The non-operational mode shall be the asynchronous disconnected mode (ADM) in which a combined station is logically disconnected from the data link.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.5.2.1 Standard	It shall be permissible for a combined station in ADM to transmit without invitation from the associated station.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.5.2.2 Standard	A combined station in ADM shall transmit only SABM, DISC, UA and DM frames. (See 8.6.4.2.7 for a description of the commands and responses to which these frame types refer.)	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.5.2.3 Standard	A combined station in ADM shall transmit a DM when a DISC is received, and shall discard all other received command frames except SABM. If a discarded command frame has the P bit set to "1", the combined station shall transmit a DM with the F bit set to "1".	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.6 Standard	<i>Control field functions and parameters.</i> Control fields contain a command or a response and sequence numbers where applicable. Three types of control fields shall be used to perform: a) numbered information transfer (I-frames); b) numbered supervisory functions (S-frames); and c) unnumbered control functions (U-frames). The control field formats shall be as shown in Table 8-5. The functional frame designation associated with each type control field as well as the control field parameters employed in performing these functions shall be described in the following paragraphs.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.6.1 Standard	The I-frame type is used to perform information transfers. Except for some special cases it is the only format which shall be permitted to contain an information field.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.6.2 Standard	The S-frame type is used for supervisory commands and responses that perform link supervisory control functions such as acknowledge information frames, request transmission or retransmission of information frames, and to request a temporary suspension of transmission of I-frames. No information field shall be contained in the S-frame.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.6.3 Standard	The U-frame type is used for unnumbered commands and responses that provide additional link control functions. One of the U-frame responses, the frame reject (FRMR) response, shall contain an information field; all other frames of the U-frame type shall not contain an information field.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.6.4 Standard	The station parameters associated with the three control field types shall be as follows: a) <i>Modulus</i> . Each I-frame shall be sequentially numbered with a send sequence count, $N(S)$, having value 0 through modulus minus one (where modulus is the modulus of the sequence numbers). The modulus shall be 8. The maximum number of sequentially numbered I-frames that a station shall have outstanding (i.e. unacknowledged) at any given time shall never exceed one less than the modulus of the sequence numbers. This restriction on the number of outstanding frames is to prevent any ambiguity in the association of transmission frames with sequence numbers during normal operation and/or error recovery. b) The send state variable $V(S)$ shall denote the sequence number of the next in-sequence I-frame to be transmitted. 1) The send state variable shall take on the value 0 through modulus minus one (modulus is the modulus of the sequence numbering and the numbers cycle through the entire range). 2) The value of $V(S)$ shall be incremented by one with each successive in-sequence I-frame transmission, but shall not exceed the value of $N(R)$ contained in the last received frame by more than the maximum permissible number of outstanding I-frames (k). See i) below for the definition of k . c) Prior to transmission of an in-sequence I-frame, the value of $N(S)$ shall be updated to equal the value of $V(S)$. d) The receive state variable $V(R)$ shall denote the sequence number of the next in-sequence I-frame to be received. 3) $V(R)$ shall take on the values 0 through modulus minus one.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	<p>AERONAUTICAL TELECOMMUNICATIONS</p> <p>Standard or Recommended Practice</p>	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>4) The value of $V(R)$ shall be incremented by one after the receipt of an error-free, in-sequence I-frame whose send sequence number $N(S)$, equals $V(R)$.</p> <p>e) All I-frames and S-frames shall contain $N(R)$, the expected sequence number of the next received frame. Prior to transmission of either an I or an S type frame, the value of $N(R)$ shall be updated to equal the current value of the receive state variable. $N(R)$ indicates that the station transmitting the $N(R)$ has correctly received all I-frames numbered up to and including $N(R) - 1$.</p> <p>f) Each station shall maintain an independent send state variable, $V(S)$, and receive state variable, $V(R)$, on the I-frames it sends and receives. That is, each combined station shall maintain a $V(S)$ count on the I-frames it transmits and a $V(R)$ count on the I-frames it has correctly received from the remote combined station.</p> <p>g) The poll (P/F) bit shall be used by a combined station to solicit (poll) a response or sequence of responses from the remote combined station.</p> <p>h) The final (P/F) bit shall be used by the remote combined station to indicate the response frame transmitted as the result of a soliciting (poll) command.</p> <p>i) The maximum number (k) of sequentially numbered I-frames that a station may have outstanding (i.e. unacknowledged) at any given time is a station parameter which shall never exceed the modulus.</p> <p><i>Note.— k is determined by station buffering limitations and should be the subject of bilateral agreement at the time of circuit establishment.</i></p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.7 Standard	<i>Commands and responses.</i> It shall be permissible for a combined station to generate either commands or responses. A command shall contain the remote station address while a response shall contain the sending station address. The mnemonics associated with all of the commands and responses prescribed for each of the three frame types (I, S, and U) and the corresponding encoding of the control field are as shown in Table 8-6.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.7.1 Standard	The I-frame command provides the means for transmitting sequentially numbered frames, each of which shall be permitted to contain an information field.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.7.2 Standard	The S-frame commands and responses shall be used to perform numbered supervisory functions (such as acknowledgement, polling, temporary suspension of information transfer, or error recovery).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.7.2.1 Standard	The receive ready command or response (RR) shall be used by a station to: <ul style="list-style-type: none"> a) indicate that it is ready to receive an I-frame; b) acknowledge previously received I-frames numbered up to and including $N(R) - 1$; c) clear a busy condition that was initiated by the transmission of RNR. <i>Note.— It is permissible for a combined station to use the RR command to solicit a response from the remote combined station with the poll bit set to "1".</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.7.2.2 Standard	It shall be permissible to issue a reject command or response (REJ) to request retransmission of frames starting with the I-frame numbered $N(R)$ where: a) I-frames numbered $N(R) - 1$ and below are acknowledged; b) additional I-frames pending initial transmission are to be transmitted following the retransmitted I-frame(s); c) only one REJ exception condition, from one given station to another station, shall be established at any given time: another REJ shall not be issued until the first REJ exception condition has been cleared; d) the REJ exception condition is cleared (reset) upon the receipt of an I-frame with an $N(S)$ count equal to the $N(R)$ of the REJ command/response.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.7.2.3 Standard	The receive not ready command or response (RNR) shall be used to indicate a busy condition, i.e. temporary inability to accept additional incoming I-frames, where: a) frames numbered up to and including $N(R) - 1$ are acknowledged; b) frame $N(R)$ and any subsequent I-frames received, if any, are not acknowledged (the acceptance status of these frames shall be indicated in subsequent exchanges); c) the clearing of a busy condition shall be indicated by the transmission of an RR, REJ, SABM, or UA with or without the P/F bit set to "1".	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.7.2.3.1 Recommendation	<p>Recommendation.—</p> <p>a) <i>A station receiving an RNR frame when in the process of transmitting should stop transmitting I-frames at the earliest possible time.</i></p> <p>b) <i>Any REJ command or response which was received prior to the RNR should be actioned before the termination of transmission.</i></p> <p>c) <i>It should be permissible for a combined station to use the RNR command with the poll bit set to "1" to obtain a supervisory frame with the final bit set to "1" from the remote combined station.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.2.7.2.4 Standard	<p>It shall be permissible for the selective reject command or response (SREJ) to be used to request retransmission of the single I-frame numbered $N(R)$ where:</p> <p>a) frames numbered up to $N(R) - 1$ are acknowledged; frame $N(R)$ is not accepted; the only I-frames accepted are those received correctly and in sequence following the I-frame requested; the specific I-frame to be retransmitted is indicated by the $N(R)$ in the SREJ command/response;</p> <p>b) the SREJ exception condition is cleared (reset) upon receipt of an I-frame with an $N(S)$ count equal to the $N(R)$ of the SREJ;</p> <p>c) after a station transmits a SREJ it is not permitted to transmit SREJ or REJ for an additional sequence error until the first SREJ error condition has been cleared;</p> <p>d) I-frames that have been permitted to be transmitted following the I-frame indicated by the SREJ are not retransmitted as the result of receiving a SREJ; and</p> <p>e) it is permissible for additional I-frames pending initial transmission to be transmitted following the retransmission of the specific I-frame requested by the SREJ.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.2.7.3 Standard	<p>The U-frame commands and responses shall be used to extend the number of link control functions. Transmitted U-frames do not increment the sequence counts at either the transmitting or receiving station.</p> <p>a) The U-frame mode-setting commands (SABM, and DISC) shall be used to place the addressed station in the appropriate response mode (ABM or ADM) where:</p> <ol style="list-style-type: none"> 1) upon acceptance of the command, the station send and receive state variables, $V(S)$ and $V(R)$, are set to zero; 2) the addressed station confirms acceptance at the earliest possible time by transmission of a single unnumbered acknowledgement, UA; 3) previously transmitted frames that are unacknowledged when the command is actioned remain unacknowledged; 4) the DISC command is used to perform a logical disconnect, i.e. to inform the addressed combined station that the transmitting combined station is suspending operation. No information field shall be permitted with the DISC command. <p>b) The unnumbered acknowledge response (UA) shall be used by a combined station to acknowledge the receipt and acceptance of an unnumbered command. Received unnumbered commands are not actioned until the UA response is transmitted. No information field shall be permitted with the UA response.</p> <p>c) The frame reject response (FRMR), employing the information field described below, shall be used by a combined station in the operational mode (ABM) to report that one of the following conditions resulted from the receipt of a frame without an FCS error:</p> <ol style="list-style-type: none"> 5) a command/response that is invalid or not implemented; 6) a frame with an information field that exceeds the size of the buffer available; 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>7) a frame having an invalid $N(R)$ count. <i>Note.— An invalid $N(R)$ is a count which points to an I-frame which has previously been transmitted and acknowledged or to an I-frame which has not been transmitted and is not the next sequential I-frame pending transmission.</i></p> <p>d) The disconnected mode response (DM) shall be used to report a non-operational status where the station is logically disconnected from the link. No information field shall be permitted with the DM response. <i>Note.— The DM response shall be sent to request the remote combined station to issue a mode-setting command or, if sent in response to the reception of a mode-setting command, to inform the remote combined station that the transmitting station is still in ADM and cannot action the mode-setting command.</i></p>				
<p>Chapter 8 Reference 8.6.4.3 Standard</p>	<p>EXCEPTION CONDITION REPORTING AND RECOVERY This section specifies the procedures that shall be employed to effect recovery following the detection or occurrence of an exception condition at the link level. Exception conditions described are those situations that may occur as the result of transmission errors, station malfunction, or operational situations.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.3.1 Standard	<p><i>Busy condition.</i> A busy condition occurs when a station temporarily cannot receive or continue to receive I-frames due to internal constraints, e.g. due to buffering limitations. The busy condition shall be reported to the remote combined station by the transmission of an RNR frame with the $N(R)$ number of the next I-frame that is expected. It shall be permissible for traffic pending transmission at the busy station to be transmitted prior to or following the RNR.</p> <p><i>Note.— The continued existence of a busy condition must be reported by retransmission of RNR at each P/F frame exchange.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.3.1.1 Standard	Upon receipt of an RNR, a combined station in ABM shall cease transmitting I-frames at the earliest possible time by completing or aborting the frame in process. The combined station receiving an RNR shall perform a time-out operation before resuming asynchronous transmission of I-frames unless the busy condition is reported as cleared by the remote combined station. If the RNR was received as a command with the P bit set to “1”, the receiving station shall respond with an S-frame with the F bit set to “1”.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.3.1.2 Standard	The busy condition shall be cleared at the station which transmitted the RNR when the internal constraint ceases. Clearance of the busy condition shall be reported to the remote station by transmission of an RR, REJ, SABM, or UA frame (with or without the P/F bit set to “1”).	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.3.2 Standard	N(S) <i>sequence error</i> . An N(S) sequence exception shall be established in the receiving station when an I-frame that is received error free (no FCS error) contains an N(S) sequence number that is not equal to the receive variable V(R) at the receiving station. The receiving station shall not acknowledge (shall not increment its receive variable V(R)) the frame causing the sequence error, or any I-frames which may follow, until an I-frame with the correct N(S) number is received. A station that receives one or more I-frames having sequence errors, but which are otherwise error free, shall accept the control information contained in the N(R) field and the P/F bit to perform link control functions, e.g. to receive acknowledgement of previously transmitted I-frames (via the N(R)), to cause the station to respond (P bit set to "1").	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.3.2.1 Standard	The means specified in 8.6.4.3.2.1.1 and 8.6.4.3.2.1.2 shall be available for initiating the retransmission of lost or errored I-frames following the occurrence of a sequence error.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.3.2.1.1 Standard	Where the REJ command/response is used to initiate an exception recovery following the detection of a sequence error, only one "sent REJ" exception condition, from one station to another station, shall be established at a time. A "sent REJ" exception shall be cleared when the requested I-frame is received. A station receiving REJ shall initiate sequential (re)transmission of I-frames starting with the I-frame indicated by the N(R) contained in the REJ frame.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																									
Chapter 8 Reference 8.6.4.3.2.1.2 Standard	<p>In the event a receiving station, due to a transmission error, does not receive (or receives and discards) a single I-frame or the last I-frame(s) in a sequence of I-frames, it shall not detect an out-of-sequence exception and, therefore, shall not transmit REJ. The station which transmitted the unacknowledged I-frame(s) shall, following the completion of a system-specified time-out period, take appropriate recovery action to determine the sequence number at which retransmission must begin.</p> <p style="text-align: center;">FRMR INFORMATION FIELD BITS FOR BASIC (SABM) OPERATION</p> <p style="text-align: center;"><i>First bit transmitted</i></p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">1</td> <td style="padding: 0 10px;">8</td> <td style="padding: 0 10px;">9</td> <td style="padding: 0 10px;">10</td> <td style="padding: 0 10px;">12</td> <td style="padding: 0 10px;">13</td> <td style="padding: 0 10px;">14</td> <td style="padding: 0 10px;">16</td> <td style="padding: 0 10px;">17</td> <td style="padding: 0 10px;">18</td> <td style="padding: 0 10px;">19</td> <td style="padding: 0 10px;">20</td> <td style="padding: 0 10px;">21</td> <td style="padding: 0 10px;">24</td> </tr> <tr> <td>rejected</td> <td>basic</td> <td>control</td> <td>field</td> <td></td> <td>0</td> <td>V(S)</td> <td>v</td> <td>V(R)</td> <td></td> <td>w</td> <td>x</td> <td></td> <td></td> </tr> <tr> <td>y</td> <td>z</td> <td colspan="11">set to zero</td> </tr> </table> <p>where: rejected basic control field is the control field of the received frame which caused the frame reject; V(S) is the current value of the send state variable at the remote combined station reporting the error condition (bit 10 = low order bit); V(R) is the current value of the receive state variable at the remote combined station reporting the error condition (bit 14 = low order bit); v set to "1" indicates that the received frame which caused rejection was a response; w set to "1" indicates that the control field received and returned in bits 1 through 8 are invalid or not implemented; x set to "1" indicates that the control field received and returned in bits 1 through 8 was considered invalid because the frame contained an information field which is not permitted with this command. Bit w must be set to "1" in conjunction with this bit; y set to "1" indicates that the information field received exceeded the maximum information field length which can be accommodated by the station reporting the error condition. This bit is mutually exclusive with bits w and x above; z set to "1" indicates that the control field received and returned in bits 1 through 8 contained an invalid N(R) count. This bit is mutually exclusive with bit w.</p>	1	8	9	10	12	13	14	16	17	18	19	20	21	24	rejected	basic	control	field		0	V(S)	v	V(R)		w	x			y	z	set to zero											CV CAR 19, 19.B.230, (a),(1)	No Difference		
1	8	9	10	12	13	14	16	17	18	19	20	21	24																																	
rejected	basic	control	field		0	V(S)	v	V(R)		w	x																																			
y	z	set to zero																																												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.3.2.1.3 Recommendation	<p>Recommendation.— <i>A combined station which has timed out waiting for a response should not retransmit all unacknowledged frames immediately. The station may enquire about status with a supervisory frame.</i></p> <p><i>N1.If a station does retransmit all unacknowledged I-frames after a time-out, it must be prepared to receive a subsequent REJ frame with an N(R) greater than its send variable V(S).</i></p> <p><i>N2.Since contention may occur in the case of two-way alternate communications in ABM or ADM, the time-out interval employed by one combined station must be greater than that employed by the other combined station so as to permit contention to be resolved.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 8 Reference 8.6.4.3.3 Standard	<p><i>FCS error.</i> Any frame with an FCS error shall not be accepted by the receiving station and will be discarded. No action shall be taken by the receiving station as the result of that frame.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.3.4 Standard	<p><i>Frame reject exception condition.</i> A frame reject exception condition shall be established upon the receipt of an error-free frame which contains an invalid or unimplemented control field, an invalid <i>N(R)</i>, or an information field which has exceeded the maximum established storage capability. If a frame reject exception condition occurs in a combined station, the station shall either:</p> <ul style="list-style-type: none"> a) take recovery action without reporting the condition to the remote combined station; or b) report the condition to the remote combined station with a FRMR response. The remote station will then be expected to take recovery action; if, after waiting an appropriate time, no recovery action appears to have been taken, the combined station reporting the frame reject exception condition may take recovery action. <p>Recovery action for balanced operation includes the transmission of an implemented mode-setting command. Higher level functions may also be involved in the recovery.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.3.5 Standard	<p><i>Mode-setting contention.</i> A mode-setting contention situation exists when a combined station issues a mode-setting command and, before receiving an appropriate response (UA or DM), receives a mode-setting command from the remote combined station. Contention situations shall be resolved in the following manner:</p> <ul style="list-style-type: none"> a) when the send and receive mode-setting commands are the same, each combined station shall send a UA response at the earliest respond opportunity. Each combined station shall either enter the indicated mode immediately or defer entering the indicated mode until receiving a UA response. In the latter case, if the UA response is not received: <ul style="list-style-type: none"> 1) the mode may be entered when the response timer expires; or 2) the mode-setting command may be reissued; b) when the mode-setting commands are different, each combined station shall enter ADM and issue a DM response at the earliest respond opportunity. In the case of DISC contention with a different mode-setting command, no further action is required. 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.4.3.6 Standard	<p><i>Time-out functions.</i> Time-out functions shall be used to detect that a required or expected acknowledging action or response to a previously transmitted frame has not been received. Expiration of the time-out function shall initiate appropriate action, e.g. error recovery or reissuance of the P bit. The duration of the following time-out functions is system dependent and subject to bilateral agreement:</p> <ul style="list-style-type: none"> a) combined stations shall provide a time-out function to determine that a response frame with F bit set to “1” to a command frame with the P bit set to “1” has not been received. The time-out function shall automatically cease upon receipt of a valid frame with the F bit set to “1”; b) a combined station which has no P bit outstanding, and which has transmitted one or more frames for which responses are anticipated shall start a time-out function to detect the no-response condition. The time-out function shall cease when an I- or S-frame is received with the <i>N(R)</i> higher than the last received <i>N(R)</i> (actually acknowledging one or more I-frames). 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.5.1.1 Standard	<p>8.6.5 Common ICAO data interchange network (CIDIN)</p> <p>8.6.5.1 INTRODUCTION</p> <p>N1. <i>The common ICAO data interchange network (CIDIN) is an element of the aeronautical fixed service (AFS) which uses bit-oriented procedures, store and forward techniques and packet switching techniques based on CCITT Recommendation X.25 to carry messages of specific applications of the AFS such as AFTN and operational meteorological information (OPMET).</i></p> <p>N2. <i>The CIDIN provides a reliable common network service for the conveyance of application messages in binary to text form to air traffic service providers and aircraft operating agencies.</i></p> <p>CIDIN entry and exit centres or stations shall be used to connect application entities to the CIDIN.</p> <p><i>Note.— The interfacing between CIDIN and application entities is a matter for local implementation.</i></p>		Not Applicable		
Chapter 8 Reference 8.6.5.1.2 Standard	CIDIN relay centres shall be used to forward packets between CIDIN entry and exit centres or stations which are not directly connected.		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.5.2.1 Standard	<p style="text-align: center;">8.6.5.2 GENERAL</p> <p>There shall be four protocol levels defined to control the transfer of messages between CIDIN switching centres: the data link protocol level the X.25 packet protocol level the CIDIN packet protocol level the CIDIN transport protocol level N1. <i>The relationship of the terms used is shown in Figures 8-1 and 8-2.</i> N2. <i>The details of CIDIN communication procedures and system specifications, as implemented in Europe, are shown in the EUR CIDIN Manual (EUR Doc 005).</i></p>		Not Applicable		
Chapter 8 Reference 8.6.5.2.2.1 Standard	<p style="text-align: center;"><i>8.6.5.2.2 THE DATA LINK PROTOCOL LEVEL</i></p> <p>X.25 packets to be transferred between two CIDIN switching centres or a CIDIN switching centre and a packet switched data network, shall be formatted into data link frames.</p>		Not Applicable		
Chapter 8 Reference 8.6.5.2.2.2 Standard	<p>Each data link frame shall consist of a data link control field (DLCF), possibly followed by a link data field, and shall be terminated by a frame check sequence and flag (being the second part of the DLCF). If a link data field is present, the frame shall be denoted as an information frame.</p>		Not Applicable		
Chapter 8 Reference 8.6.5.2.2.3 Standard	<p>X.25 packets shall be transmitted within the link data field of information frames. Only one packet shall be contained in the link data field.</p>		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.5.2.3.1 Standard	8.6.5.2.3 THE X.25 PACKET PROTOCOL LEVEL Each CIDIN packet to be transferred on CIDIN circuits between CIDIN switching centres shall be formatted into one X.25 packet. When a packet switched data network is used, it shall be permissible to format the CIDIN packet into more than one X.25 packet.		Not Applicable		
Chapter 8 Reference 8.6.5.2.3.2 Standard	The integrity of each CIDIN packet shall be preserved by the X.25 packet protocol by mapping each CIDIN packet onto one complete X.25 packet sequence, as defined in CCITT Recommendation X.25.		Not Applicable		
Chapter 8 Reference 8.6.5.2.3.3 Standard	Each X.25 packet shall consist of an X.25 packet header, possibly followed by a user data field (UDF).		Not Applicable		
Chapter 8 Reference 8.6.5.2.3.4 Standard	The X.25 packet protocol is based on the application of virtual circuit procedures. A virtual circuit shall be defined as a logical path between two CIDIN switching centres. If a packet switched data network is used to interconnect two CIDIN switching centres, the procedure shall provide full compatibility with the procedures to be followed for virtual circuits according to CCITT Recommendation X.25.		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.5.2.4.1 Standard	<p><i>8.6.5.2.4 THE CIDIN PACKET PROTOCOL LEVEL</i></p> <p>Each transport header and the associated segment shall be preceded by a CIDIN packet header. No further segmentation of the CIDIN message shall be used between transport protocol level and CIDIN packet protocol level. Both headers, therefore, shall be used in combination. Together they shall be referred to as the communications control field (CCF). Together with the message segment they form CIDIN packets that shall be transmitted from entry centre to exit centre(s), when necessary through one or more relay centres, as an entity.</p>		Not Applicable		
Chapter 8 Reference 8.6.5.2.4.2 Standard	<p>CIDIN packets of one CIDIN message shall be relayed independently via predetermined routes through the network thus allowing alternative routing on a CIDIN packet basis as necessary.</p>		Not Applicable		
Chapter 8 Reference 8.6.5.2.4.3 Standard	<p>The CIDIN packet header shall contain information to enable relay centres to handle CIDIN packets in the order of priority, to transmit the CIDIN packets on the proper outgoing circuit(s) and to duplicate or multiply CIDIN packets when required for multiple dissemination purposes. The information shall be sufficient to apply address stripping on the exit addresses as well as on the addressee indicators of messages in AFTN format.</p>		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.5.2.5.1 Standard	8.6.5.2.5 THE TRANSPORT PROTOCOL LEVEL Information exchanged over the CIDIN shall be transmitted as CIDIN messages.		Not Applicable		
Chapter 8 Reference 8.6.5.2.5.2 Standard	The length of a CIDIN message shall be defined by the CIDIN packet sequence number (CPSN). The maximum permissible length is 215 packets which in effect results in no practical limitation.		Not Applicable		
Chapter 8 Reference 8.6.5.2.5.3 Standard	If the length of a CIDIN message and its transport and packet headers (as defined below) exceeds 256 octets, the message shall be divided into segments and placed in the CIDIN user data field of CIDIN packets. Each segment shall be preceded by a transport header containing information to enable the re-assembly of the CIDIN message at the exit centre(s) from individually received segments and to determine further handling of the received complete CIDIN message.		Not Applicable		
Chapter 8 Reference 8.6.5.2.5.4 Standard	All segments of one CIDIN message shall be provided with the same message identification information in the transport header. Only the CPSN and final CIDIN packet (FCP) indicator shall be different.		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.6.5.2.5.5 Standard	Recovery of messages shall be performed at the transport level.		Not Applicable		
Chapter 9 Reference 9.1 Standard	CHAPTER 9. AIRCRAFT ADDRESSING SYSTEM The aircraft address shall be one of 16 777 214 twenty-four-bit aircraft addresses allocated by ICAO to the State of Registry or common mark registering authority and assigned as prescribed in the Appendix to this Chapter.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 9 Reference 9.1.1 Standard	Non-aircraft transponders that are installed on aerodrome surface vehicles, obstacles or fixed Mode S target detection devices for surveillance and/or radar monitoring purposes shall be assigned 24-bit aircraft addresses. <i>Note.— Under such specific conditions, the term “aircraft” can be understood as “aircraft (or pseudo-aircraft) or vehicle (A/V)” where a limited set of data is generally sufficient for operational purposes.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 9 Reference 9.1.1.1 Recommendation	Recommendation.— Mode S transponders used under specific conditions stated in 9.1.1 should not have any negative impact on the performance of existing ATS surveillance systems and ACAS.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 10.1.1 Standard	<p style="text-align: center;">CHAPTER 10. POINT-TO-MULTIPOINT COMMUNICATIONS</p> <p style="text-align: center;">10.1 SERVICE VIA SATELLITE FOR THE DISSEMINATION OF AERONAUTICAL INFORMATION</p> <p>Point-to-multipoint telecommunication service via satellite to support the dissemination of aeronautical information shall be based on full-time, non pre-emptible, protected services as defined in the relevant CCITT Recommendations.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 10.2.1 Recommendation	<p style="text-align: center;">10.2 SERVICE VIA SATELLITE FOR THE DISSEMINATION OF WAFS PRODUCTS</p> <p>Recommendation.— <i>System characteristics should include the following:</i></p> <ul style="list-style-type: none"> a) <i>frequency — C-band, earth-to-satellite, 6 GHz band, satellite-to-earth, 4 GHz band;</i> b) <i>capacity with effective signalling rate of not less than 9 600 bits/s;</i> c) <i>bit error rates — better than 1 in 10⁷;</i> d) <i>forward error correction; and</i> e) <i>availability 99.95 per cent.</i> 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference Definition	<p align="center">CHAPTER 11. HF DATA LINK</p> <p align="center">11.1 DEFINITIONS AND SYSTEM CAPABILITIES</p> <p><i>Note.— The following Standards and Recommended Practices are specific to the high frequency data link (HF DL) and are in addition to the requirements specified in the ITU Radio Regulations (Appendix 27). The HF DL is a constituent mobile subnetwork of the aeronautical telecommunication network (ATN), operating in the aeronautical mobile (R) high frequency bands. In addition, the HF DL may provide non-ATN functions, such as direct link service (DLS). The HF DL system must enable aircraft to exchange data with ground-based users.</i></p> <p align="center">11.1.1 Definitions</p> <p>Coded chip. A “1” or “0” output of the rate ½ or ¼ convolutional code encoder.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	<p>Designated operational coverage (DOC) area. The area in which a particular service is provided and in which the service is afforded frequency protection.</p> <p><i>Note.— This area may, after proper coordination to ensure frequency protection, extend to areas outside the allotment areas contained in Appendix S27 to the Radio Regulations.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	<p>Direct link service (DLS). A data communications service which makes no attempt to automatically correct errors, detected or undetected, at the link layer of the air-ground communications path. (Error control may be effected by end-user systems.)</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference Definition	<i>High frequency network protocol data unit (HFNPDU).</i> User data packet.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	<i>Link protocol data unit (LPDU).</i> Data unit which encapsulates a segment of an HFNPDU.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	<i>M-ary phase shift keying (M-PSK) modulation.</i> A digital phase modulation that causes the phase of the carrier waveform to take on one of a set of M values.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	<i>Media access protocol data unit (MPDU).</i> Data unit which encapsulates one or more LPDUs.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	<i>M-PSK symbol.</i> One of the M possible phase shifts of the M-PSK modulated carrier representing a group of $\log_2 M$ coded chips.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference Definition	Peak envelope power (PEP). The peak power of the modulated signal supplied by the transmitter to the antenna transmission line.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	Physical layer protocol data unit (PPDU). Data unit passed to the physical layer for transmission, or decoded by the physical layer after reception.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	Quality of service (QOS). The information relating to data transfer characteristics used by various communications protocols to achieve various levels of performance for network users.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	Reliable link service (RLS). A data communications service provided by the subnetwork which automatically provides for error control over its link through error detection and requested retransmission of signal units found to be in error.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference Definition	Squitter protocol data unit (SPDU). Data packet which is broadcast every 32 seconds by an HF DL ground station on each of its operating frequencies, and which contains link management information.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.2.1 Standard	<p align="center">11.2 HF DATA LINK SYSTEM</p> <p align="center">System architecture</p> <p>The HF DL system shall consist of one or more ground and aircraft station subsystems, which implement the HF DL protocol (see 11.3). The HF DL system shall also include a ground management subsystem (see 11.4).</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.2.1.1 Standard	<p align="center">AIRCRAFT AND GROUND STATION SUBSYSTEMS</p> <p>The HF DL aircraft station subsystem and the HF DL ground station subsystem shall include the following functions:</p> <ul style="list-style-type: none"> a) HF transmission and reception; b) data modulation and demodulation; and c) HF DL protocol implementation and frequency selection. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.2.2 Standard	<p align="center">Operational coverage</p> <p>Frequency assignments for HF DL shall be protected throughout their designated operational coverage (DOC) area.</p> <p><i>N1.DOC areas may be different from current MWARAs or RDARAs as defined in Appendix 27 to the ITU Radio Regulations.</i></p> <p><i>N2.Additional coordination with ITU is required in cases where DOC areas are not in conformity with the allotment areas specified in the ITU Radio Regulations.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.2.3 Standard	<p align="center">Requirements for carriage of HF DL equipment</p> <p>Requirements for mandatory carriage of HF DL equipment shall be made on the basis of regional air navigation agreements that specify the airspace of operation and the implementation timescale.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.2.3.1 Standard	<p style="text-align: center;">NOTICE</p> <p>The agreement above shall provide advance notice of at least two years for the mandatory carriage of airborne systems.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.2.4.1 Recommendation	<p style="text-align: center;">11.2.4 Ground station networking</p> <p>Recommendation.— <i>HFDL ground station subsystems should interconnect through a common ground management subsystem.</i></p> <p><i>Note.</i>— <i>This provides a distributed subnetwork, with a subnetwork point of attachment (SNPA), depending on the method of implementation, which allows for the maintenance of virtual circuit connections as aircraft stations transition between designated operational coverage areas. The distribution may be multi-regional or worldwide.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.2.5 Standard	<p style="text-align: center;">Ground station synchronization</p> <p>Synchronization of HFDL ground station subsystems shall be to within ± 25 ms of UTC. For any station not operating within ± 25 ms of UTC, appropriate notification shall be made to all aircraft and ground station subsystems to allow for continued system operation.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.2.6.1 Standard	<p style="text-align: center;">11.2.6 Quality of service</p> <p style="text-align: center;">RESIDUAL PACKET ERROR RATE</p> <p>The undetected error rate for a network user packet which contains between 1 and 128 octets of user data shall be equal to or less than 1 in 10⁶.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.2.6.2 Standard	<p style="text-align: center;">SPEED OF SERVICE</p> <p>Transit and transfer delays for network user packets (128 octets) with priorities defined in Part I, Chapter 4, Table 4-26 for message priorities 7 through 14, shall not exceed the values of Table 11-1.*</p> <hr style="width: 20%; margin-left: 0;"/> <p>* All tables and figures are located at the end of this chapter.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3 Standard	<p style="text-align: center;">HF DATA LINK PROTOCOL</p> <p>The HF DL protocol shall consist of a physical layer, a link layer, and a subnetwork layer, as specified below.</p> <p><i>Note.— The HF DL protocol is a layered protocol and is compatible with the open systems interconnection (OSI) reference model. It permits the HF DL to function as an aeronautical telecommunication network (ATN)-compatible subnetwork. The details of the protocol are described in the Manual on HF Data Link (Doc 9741).</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1 Standard	<p style="text-align: center;">Physical layer RF characteristics</p> <p>The aircraft and ground stations shall access the physical medium operating in simplex mode.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.1 Standard	<p style="text-align: center;">FREQUENCY BANDS</p> <p>HF DL installations shall be capable of operating at any single sideband (SSB) carrier (reference) frequency available to the aeronautical mobile (R) service in the band 2.8 to 22 MHz, and in compliance with the relevant provisions of the Radio Regulations.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.1.2 Standard	CHANNELS Channel utilization shall be in conformity with the table of carrier (reference) frequencies of Appendix 27 to the ITU Radio Regulations.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.3 Standard	TUNING The equipment shall be capable of operating on integral multiples of 1 kHz.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.4 Standard	SIDEBAND The sideband used for transmission shall be on the higher side of its carrier (reference) frequency.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.5 Standard	MODULATION HF DL shall employ M-ary phase shift keying (M-PSK) to modulate the radio frequency carrier at the assigned frequency. The symbol rate shall be 1 800 symbols per second ± 10 parts per million (i.e. 0.018 symbols per second). The value of M and the information data rate shall be as specified in Table 11-2.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.1.5.1 Standard	<p><i>M-PSK CARRIER</i></p> <p>The M-PSK carrier expressed mathematically shall be defined as:</p> $s(t) = A \cdot p(t-kT) \cos[2\pi f_0 t + \phi(k)], \quad k = 0, 1, \dots, N-1$ <p>where:</p> <p>N = number of M-PSK symbols in transmitted physical layer protocol data unit (PPDU)</p> <p>s(t) = analog waveform or signal at time t</p> <p>A = peak amplitude</p> <p>f₀ = SSB carrier (reference) + 1 440 Hz</p> <p>T = M-PSK symbol period (1/1 800 s)</p> <p>φ (k) = phase of kth M-PSK symbol</p> <p>p(t-kT) = pulse shape of kth M-PSK symbol at time t.</p> <p><i>Note.— the number of M-PSK symbols sent, N, defines the length (duration = NT seconds) of the PPDU. These parameters are defined in the Manual on HF Data Link (Doc 9741).</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.5.2 Standard	<p><i>PULSE SHAPE</i></p> <p>The pulse shape, p(t), shall determine the spectral distribution of the transmitted signal. The Fourier transform of the pulse shape, P(f), shall be defined by:</p> $P(f) = 1, \quad \text{if } 0 < f < (1 - b)/2T$ $P(f) = \cos \{ \pi(2 f T - 1 + b)/4b \}, \quad \text{if } (1 - b)/2T < f < (1 + b)/2T$ $P(f) = 0, \quad \text{if } f > (1 + b)/2T$ <p>where the spectral roll-off parameter, b = 0.31, has been chosen so that the -20 dB points of the signal are at SSB carrier (reference) + 290 Hz and SSB carrier (reference) + 2 590 Hz and the peak-to-average power ratio of the waveform is less than 5 dB.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.1.6 Standard	<p style="text-align: center;">TRANSMITTER STABILITY</p> <p>The basic frequency stability of the transmitting function shall be better than:</p> <ul style="list-style-type: none"> a) ± 20 Hz for HF DL aircraft station subsystems; and b) ± 10 Hz for HF DL ground station subsystems. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.7 Standard	<p style="text-align: center;">RECEIVER STABILITY</p> <p>The basic frequency stability of the receiving function shall be such that, with the transmitting function stability specified in 11.3.1.6, the overall frequency difference between ground and airborne functions achieved in service does not exceed 70 Hz.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.8 Standard	<p style="text-align: center;">PROTECTION</p> <p>A 15 dB desired to undesired (D/U) signal ratio shall apply for the protection of co-channel assignments for HF DL as follows:</p> <ul style="list-style-type: none"> a) data versus data; b) data versus voice; and c) voice versus data. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.9 Standard	<p style="text-align: center;">CLASS OF EMISSION</p> <p>The class of emission shall be 2K80J2DEN.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.1.10 Standard	<p style="text-align: center;">ASSIGNED FREQUENCY</p> <p>The HF DL assigned frequency shall be 1 400 Hz higher than the SSB carrier (reference) frequency.</p> <p><i>Note.— By convention, the HF DL assigned frequency is offset from the SSB carrier (reference) frequency by 1 400 Hz. The HF DL M-PSK carrier of the digital modulation is offset from the SSB carrier (reference) frequency by 1 440 Hz. The digital modulation is fully contained within the same overall channel bandwidth as the voice signal and complies with the provisions of Appendix 27 to the ITU Radio Regulations.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.11 Standard	<p style="text-align: center;">EMISSION LIMITS</p> <p>For HF DL aircraft and ground station transmitters, the peak envelope power (P_p) of any emission on any discrete frequency shall be less than the peak envelope power (P_p) of the transmitter in accordance with the following (see Figure 11-1):</p> <ol style="list-style-type: none"> a) on any frequency between 1.5 kHz and 4.5 kHz lower than the HF DL assigned frequency, and on any frequency between 1.5 kHz and 4.5 kHz higher than the HF DL assigned frequency: at least 30 dB; b) on any frequency between 4.5 kHz and 7.5 kHz lower than the HF DL assigned frequency, and on any frequency between 4.5 kHz and 7.5 kHz higher than the HF DL assigned frequency; at least 38 dB; and c) on any frequency lower than 7.5 kHz below the HF DL assigned frequency and on any frequency higher than 7.5 kHz above the HF DL assigned frequency: <ol style="list-style-type: none"> 1) HF DL aircraft station transmitters; 43 dB; 2) HF DL ground station transmitters up to and including 50 W: [43 + 10 log₁₀P_p(W)] dB; and 3) HF DL ground station transmitters more than 50 W: 60dB. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.1.12.1 Standard	11.3.1.12 POWER <i>Ground station installations.</i> The peak envelope power (P_p) supplied to the antenna transmission line shall not exceed a maximum value of 6 kW as provided for in Appendix 27 of the Radio Regulations.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.12.2 Standard	<i>Aircraft station installations.</i> The peak envelope power supplied to the antenna transmission line shall not exceed 400 W, except as provided for in Appendix 27/62 of the Radio Regulations.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.13 Standard	UNDESIRE SIGNAL REJECTION For HF DL aircraft and ground station receivers, undesired input signals shall be attenuated in accordance with the following: a) on any frequency between f_c and $(f_c - 300 \text{ Hz})$, or between $(f_c + 2\,900 \text{ Hz})$ and $(f_c + 3\,300 \text{ Hz})$; at least 35 dB below the peak of the desired signal level; and b) on any frequency below $(f_c - 300 \text{ Hz})$, or above $(f_c + 3\,300 \text{ Hz})$: at least 60 dB below the peak of the desired signal level, where f_c is the carrier (reference) frequency.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.1.14 Recommendation	Recommendation. — <i>The receiving function should recover from an instantaneous increase in RF power at the antenna terminal of 60 dB within 10 milliseconds. The receiving function should recover from an instantaneous decrease in RF power at the antenna terminal of 60 dB within 25 milliseconds.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.2.1 Standard	<p align="center">11.3.2 Physical layer functions</p> <p align="center">FUNCTIONS</p> <p>The functions provided by the physical layer shall include the following:</p> <ul style="list-style-type: none"> a) transmitter and receiver control; b) transmission of data; and c) reception of data. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.2 Standard	<p align="center">TRANSMITTER AND RECEIVER CONTROL</p> <p>The HF DL physical layer shall implement the transmitter/receiver switching and frequency tuning as commanded by the link layer. The physical layer shall perform transmitter keying on demand from the link layer to transmit a packet.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.2.1 Standard	<p><i>TRANSMITTER TO RECEIVER TURNAROUND TIME</i></p> <p>The transmitted power level shall decay at least by 10 dB within 100 milliseconds after completing a transmission. An HF DL station subsystem shall be capable of receiving and demodulating, with nominal performance, an incoming signal within 200 milliseconds of the start of the subsequent receive slot.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.2.2 Standard	<p><i>RECEIVER TO TRANSMITTER TURNAROUND TIME</i></p> <p>An HF DL station subsystem shall provide nominal output power within plus or minus 1 dB to the antenna transmission line within 200 milliseconds of the start of the transmit slot.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.2.3 Standard	<p style="text-align: center;">TRANSMISSION OF DATA</p> <p>Transmission of data shall be accomplished using a time division multiple access (TDMA) technique. The HF DL data link ground station subsystems shall maintain TDMA frame and slot synchronization for the HF DL system. To ensure that slot synchronization is maintained, each HF data link modulator shall begin outputting a pre-key segment at the beginning of a time slot plus or minus 10 milliseconds.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.3.1 Standard	<p><i>TDMA STRUCTURE</i></p> <p>Each TDMA frame shall be 32 seconds. Each TDMA frame shall be divided into thirteen equal duration slots as follows:</p> <ul style="list-style-type: none"> a) the first slot of each TDMA frame shall be reserved for use by the HF DL ground station subsystem to broadcast link management data in SPDU packets; and b) the remaining slots shall be designated either as uplink slots, downlink slots reserved for specific HF DL aircraft station subsystems, or as downlink random access slots for use by all HF DL aircraft station subsystems on a contention basis. These TDMA slots shall be assigned on a dynamic basis using a combination of reservation, polling and random access assignments. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.3.2 Standard	<p><i>BROADCAST</i></p> <p>The HF DL ground station subsystem shall broadcast a squitter protocol data unit (SPDU) every 32 seconds on each of its operating frequencies.</p> <p><i>Note.— Details on the TDMA frame and slot structures, pre-key segment, data structure, including the SPDU, are contained in the Manual on HF Data Link (Doc 9741).</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.2.4.1 Standard	<p align="center"><i>11.3.2.4 RECEPTION OF DATA</i></p> <p><i>FREQUENCY SEARCH</i></p> <p>Each HF DL aircraft station shall automatically search the assigned frequencies until it detects an operating frequency.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.4.2 Standard	<p><i>RECEPTION OF PPDU's</i></p> <p>The HF data link receiver shall provide the means to detect, synchronize, demodulate and decode PPDU's modulated according to the waveform defined in 11.3.1.5, subject to the following distortion:</p> <ul style="list-style-type: none"> a) the 1 440 Hz audio carrier offset by plus or minus 70 Hz; b) discrete and/or diffuse multipath distortion with up to 5 ms multipath spread; c) multipath amplitude fading with up to 2 Hz two-sided RMS Doppler spread and Rayleigh statistics; and d) additive Gaussian and broadband impulsive noise with varying amplitude and random arrival times. <p><i>Note.— Reference CCIR Report 549-2.</i></p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.4.3 Standard	<p><i>DECODING OF PPDU's</i></p> <p>Upon receipt of the preamble segment the receiver shall:</p> <ul style="list-style-type: none"> a) detect the beginning of a burst of data; b) measure and correct the frequency offset between the transmitter and receiver due to Doppler shift and transmitter/receiver frequency offsets; c) determine the data rate and interleaver settings to use during data demodulation; d) achieve M-PSK symbol synchronization; and e) train the equalizer. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.2.4.4 Standard	SYNCHRONIZATION Each HF DL aircraft station subsystem shall synchronize its slot timing to that of its corresponding ground station with respect to the reception time of the last received SPDU.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.4.5.1 Standard	SPECIFIED PACKET ERROR RATE PERFORMANCE The number of HF DL media access protocol data units (MPDUs) received with one or more bit errors shall not exceed 5 per cent of the total number of MPDUs received, when using a 1.8 second interleaver and under the signal-in-space conditions shown in Table 11-3.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.2.4.5.2 Recommendation	Recommendation. — <i>The number of HF DL MPDUs received with one or more bit errors should not exceed 5 percent of the total number of MPDUs received, when using a 1.8 second interleaver under the conditions shown in Table 11-3a.</i>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.3 Standard	Link layer <i>Note.— Details on link layer functions are contained in the Manual on HF Data Link (Doc 9741).</i> The link layer shall provide control functions for the physical layer, link management and data service protocols.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.3.1 Standard	CONTROL FUNCTIONS The link layer shall pass commands for frequency tuning, transmitter keying and transmitter/receiver switching to the physical layer.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.3.2 Standard	LINK MANAGEMENT The link layer shall manage TDMA slot assignments, log-on and log-off procedures, ground station and aircraft station TDMA synchronization, and other functions necessary, taking into account message priority, for the establishment and maintenance of communications.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.3.3 Standard	DATA SERVICE PROTOCOLS The link layer shall support a reliable link service (RLS) protocol and a direct link service (DLS) protocol.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.3.3.1 Standard	<i>RLS</i> The RLS protocol shall be used to exchange acknowledged user data packets between aircraft and ground peer link layers.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.3.3.2 Standard	<i>DLS</i> The DLS protocol shall be used to broadcast unsegmented uplink high frequency network protocol data units (HFNPDU) and other HFNPDU not requiring automatic retransmission by the link layer.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.4.1 Standard	<p>11.3.4 Subnetwork layer</p> <p><i>Note.— Details on subnetwork layer protocols and services are contained in the Manual on HF Data Link (Doc 9741).</i></p> <p>PACKET DATA</p> <p>The HFDL subnetwork layer in the HFDL aircraft station subsystem and HFDL ground station subsystem shall provide connection-oriented packet data service by establishing subnetwork connections between subnetwork service users.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.4.2 Standard	<p>CONNECTIVITY NOTIFICATION SERVICE</p> <p>The HFDL subnetwork layer in the HFDL aircraft station subsystem shall provide the additional connectivity notification service by sending connectivity notification event messages to the attached ATN router.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.4.2.1 Standard	<p>CONNECTIVITY NOTIFICATION EVENT MESSAGES</p> <p>The connectivity notification service shall send connectivity notification event messages to the attached ATN router through the subnetwork access function.</p>	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.4.3 Standard	<p>HFDL SUBNETWORK LAYER FUNCTIONS</p> <p>The HFDL subnetwork layer in both the HFDL aircraft station subsystem and HFDL ground station subsystem shall include the following three functions:</p> <ul style="list-style-type: none"> a) HFDL subnetwork dependent (HFSND) function; b) subnetwork access function; and c) interworking function. 	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 11.3.4.3.1 Standard	<i>HFSND FUNCTION</i> The HFSND function shall perform the HFSND protocol between each pair of HF DL aircraft station subsystems and HF DL ground station subsystems by exchanging HFNPDU's. It shall perform the HFSND protocol aircraft function in the HF DL aircraft station subsystem and the HFSND protocol ground function in the HF DL ground station subsystem.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.4.3.2 Standard	<i>SUBNETWORK ACCESS FUNCTION</i> The subnetwork access function shall perform the ISO 8208 protocol between the HF DL aircraft station subsystem or HF DL ground station subsystem and the attached routers by exchanging ISO 8208 packets. It shall perform the ISO 8208 DCE function in the HF DL aircraft station subsystem and the HF DL ground station subsystem.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.3.4.3.3 Standard	<i>INTERWORKING FUNCTION</i> The interworking function shall provide the necessary harmonization functions between the HFSND, the subnetwork access and the connectivity notification functions.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
Reference 11.4.1 Standard	11.4 GROUND MANAGEMENT SUBSYSTEM <i>Note.— Details on the ground management subsystem functions and interfaces are contained in the Manual on HF Data Link (Doc 9741).</i> Management functions The ground management subsystem shall perform the functions necessary to establish and maintain communications channels between the HF DL ground and aircraft station subsystems.	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																		
Reference 11.4.2 Standard	<p style="text-align: center;">Management/control information exchange</p> <p>The ground management subsystem shall interface with the ground station subsystem in order to exchange control information required for frequency management, system table management, log status management, channel management, and quality of service (QOS) data collection.</p> <p style="text-align: center;">TABLES FOR CHAPTER 11</p> <p style="text-align: center;">Table 11-1. Transfer delays</p> <table style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th style="text-align: center;"><i>Direction</i></th> <th style="text-align: center;"><i>Priority</i></th> <th style="text-align: center;"><i>Delay</i></th> </tr> </thead> <tbody> <tr> <td>To-aircraft</td> <td>7 through 14</td> <td>45 s</td> <td></td> </tr> <tr> <td><i>Transit delay</i></td> <td>From-aircraft</td> <td>7 through 14</td> <td>60 s</td> </tr> <tr> <td>To-aircraft</td> <td>11 through 14</td> <td>90 s</td> <td></td> </tr> <tr> <td><i>Transfer delay (95 percentile)</i></td> <td></td> <td>7 through 10</td> <td>120 s</td> </tr> <tr> <td></td> <td>From-aircraft</td> <td>11 through 14</td> <td>150 s</td> </tr> <tr> <td></td> <td></td> <td>7 through 10</td> <td>250 s</td> </tr> </tbody> </table> <p style="text-align: center;">Table 11-2. Value of M and information data rate</p> <table style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: center;"><i>M</i></th> <th style="text-align: center;"><i>Information data rate (bits per second)</i></th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">300 or 600</td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">1 200</td> </tr> <tr> <td style="text-align: center;">8</td> <td style="text-align: center;">1 800</td> </tr> </tbody> </table> <p><i>Note.— When M equals the value 2, the data rate may be 300 or 600 bits per second as determined by the channel coding rate. The value of M may change from one data transmission to another depending on the data rate selected. The channel coding rate is described in the Manual on HF Data Link (Doc 9741).</i></p> <p style="text-align: center;">Table 11-3. HF signal-in-space conditions</p> <table style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: center;"><i>Data rate (bits per second)</i></th> <th style="text-align: center;"><i>Number of channel paths</i></th> <th style="text-align: center;"><i>Multipath spread (milliseconds)</i></th> <th style="text-align: center;"><i>Fading bandwidth (Hz) per CCIR Report 5492</i></th> <th style="text-align: center;"><i>Frequency offset (Hz)</i></th> <th style="text-align: center;"><i>Signal to noise ratio (dB) in a 3 kHz bandwidth</i></th> <th style="text-align: center;"><i>MPDU size (octets)</i></th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1 200</td> <td style="text-align: center;">1 fixed</td> <td style="text-align: center;">—</td> <td style="text-align: center;">—</td> <td style="text-align: center;">—</td> <td style="text-align: center;">—</td> <td style="text-align: center;">40</td> </tr> </tbody> </table>		<i>Direction</i>	<i>Priority</i>	<i>Delay</i>	To-aircraft	7 through 14	45 s		<i>Transit delay</i>	From-aircraft	7 through 14	60 s	To-aircraft	11 through 14	90 s		<i>Transfer delay (95 percentile)</i>		7 through 10	120 s		From-aircraft	11 through 14	150 s			7 through 10	250 s	<i>M</i>	<i>Information data rate (bits per second)</i>	2	300 or 600	4	1 200	8	1 800	<i>Data rate (bits per second)</i>	<i>Number of channel paths</i>	<i>Multipath spread (milliseconds)</i>	<i>Fading bandwidth (Hz) per CCIR Report 5492</i>	<i>Frequency offset (Hz)</i>	<i>Signal to noise ratio (dB) in a 3 kHz bandwidth</i>	<i>MPDU size (octets)</i>	1 200	1 fixed	—	—	—	—	40	CV CAR 19, 19.B.230, (a),(1)	Less protective or partially implemented or not implemented		Not used in Cabo Verde
	<i>Direction</i>	<i>Priority</i>	<i>Delay</i>																																																				
To-aircraft	7 through 14	45 s																																																					
<i>Transit delay</i>	From-aircraft	7 through 14	60 s																																																				
To-aircraft	11 through 14	90 s																																																					
<i>Transfer delay (95 percentile)</i>		7 through 10	120 s																																																				
	From-aircraft	11 through 14	150 s																																																				
		7 through 10	250 s																																																				
<i>M</i>	<i>Information data rate (bits per second)</i>																																																						
2	300 or 600																																																						
4	1 200																																																						
8	1 800																																																						
<i>Data rate (bits per second)</i>	<i>Number of channel paths</i>	<i>Multipath spread (milliseconds)</i>	<i>Fading bandwidth (Hz) per CCIR Report 5492</i>	<i>Frequency offset (Hz)</i>	<i>Signal to noise ratio (dB) in a 3 kHz bandwidth</i>	<i>MPDU size (octets)</i>																																																	
1 200	1 fixed	—	—	—	—	40																																																	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																				
	<table border="0"> <tr> <td></td> <td>4</td> <td>256</td> <td></td> </tr> <tr> <td>1 800</td> <td>2 fading</td> <td>2</td> <td>1 40</td> </tr> <tr> <td></td> <td>16</td> <td>400</td> <td></td> </tr> <tr> <td>1 200</td> <td>2 fading</td> <td>2</td> <td>1 40</td> </tr> <tr> <td></td> <td>11.5</td> <td>256</td> <td></td> </tr> <tr> <td>600</td> <td>2 fading</td> <td>2</td> <td>1 40</td> </tr> <tr> <td></td> <td>8</td> <td>128</td> <td></td> </tr> <tr> <td>300</td> <td>2 fading</td> <td>2</td> <td>1 40</td> </tr> <tr> <td></td> <td>5</td> <td>64</td> <td></td> </tr> </table> <p>Table 11-3a. HF signal-in-space conditions</p> <p><i>Data rate (bits per second) Number of channel paths</i> <i>Multipath spread (milliseconds) Fading bandwidth (Hz) per</i> <i>CCIR Report 5492 Frequency offset (Hz) Signal to noise ratio</i> <i>(dB) in a 3 kHz bandwidth MPDU size (octets)</i></p> <table border="0"> <tr> <td>1 200</td> <td>2 fading</td> <td>4</td> <td>1 40</td> </tr> <tr> <td></td> <td>13</td> <td>256</td> <td></td> </tr> <tr> <td>1 800</td> <td>2 fading</td> <td>2</td> <td>2 40</td> </tr> <tr> <td></td> <td>11.5</td> <td>256</td> <td></td> </tr> </table>		4	256		1 800	2 fading	2	1 40		16	400		1 200	2 fading	2	1 40		11.5	256		600	2 fading	2	1 40		8	128		300	2 fading	2	1 40		5	64		1 200	2 fading	4	1 40		13	256		1 800	2 fading	2	2 40		11.5	256					
	4	256																																																							
1 800	2 fading	2	1 40																																																						
	16	400																																																							
1 200	2 fading	2	1 40																																																						
	11.5	256																																																							
600	2 fading	2	1 40																																																						
	8	128																																																							
300	2 fading	2	1 40																																																						
	5	64																																																							
1 200	2 fading	4	1 40																																																						
	13	256																																																							
1 800	2 fading	2	2 40																																																						
	11.5	256																																																							



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference Definition	<p align="center">CHAPTER 12. UNIVERSAL ACCESS TRANSCEIVER (UAT)</p> <p align="center">12.1 DEFINITIONS AND OVERALL SYSTEM CHARACTERISTICS</p> <p align="center">12.1.1 Definitions</p> <p><i>High performance receiver.</i> A UAT receiver with enhanced selectivity to further improve the rejection of adjacent frequency DME interference (see 12.3.2.2 for further details).</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference Definition	<p><i>Optimum sampling point.</i> The optimum sampling point of a received UAT bit stream is at the nominal centre of each bit period, when the frequency offset is either plus or minus 312.5 kHz.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference Definition	<p><i>Power measurement point (PMP).</i> A cable connects the antenna to the UAT equipment. The PMP is the end of that cable that attaches to the antenna. All power measurements are considered as being made at the PMP unless otherwise specified. The cable connecting the UAT equipment to the antenna is assumed to have 3 dB of loss.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference Definition	Pseudorandom message data block. Several UAT requirements state that performance will be tested using pseudorandom message data blocks. Pseudorandom message data blocks should have statistical properties that are nearly indistinguishable from those of a true random selection of bits. For instance, each bit should have (nearly) equal probability of being a ONE or a ZERO, independent of its neighbouring bits. There should be a large number of such pseudorandom message data blocks for each message type (Basic ADS-B, Long ADS-B or Ground Uplink) to provide sufficient independent data for statistical performance measurements. See Section 2.3 of Part I of the <i>Manual on the Universal Access Transceiver (UAT)</i> (Doc 9861) for an example of how to provide suitable pseudorandom message data blocks.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference Definition	Service volume. A part of the facility coverage where the facility provides a particular service in accordance with relevant SARPs and within which the facility is afforded frequency protection.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference Definition	Standard UAT receiver. A general purpose UAT receiver satisfying the minimum rejection requirements of interference from adjacent frequency distance measuring equipment (DME) (see 12.3.2.2 for further details).	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference Definition	Successful message reception (SMR). The function within the UAT receiver for declaring a received message as valid for passing to an application that uses received UAT messages. See Section 4 of Part I of the <i>Manual on the Universal Access Transceiver (UAT)</i> (Doc 9861) for a detailed description of the procedure to be used by the UAT receiver for declaring successful message reception.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference Definition	UAT ADS-B message. A message broadcasted once per second by each aircraft to convey state vector and other information. UAT ADS-B messages can be in one of two forms depending on the amount of information to be transmitted in a given second: the <i>Basic UAT ADS-B Message</i> or the <i>Long UAT ADS-B Message</i> (see 12.4.4.1 for definition of each). UAT ground stations can support traffic information service-broadcast (TIS-B) through transmission of individual ADS-B messages in the ADS-B segment of the UAT frame.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference Definition	UAT ground uplink message. A message broadcasted by ground stations, within the ground segment of the UAT frame, to convey flight information such as text and graphical weather data, advisories, and other aeronautical information, to aircraft that are in the service volume of the ground station (see 12.4.4.2 for further details).	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference Definition	Universal access transceiver (UAT). A broadcast data link operating on 978 MHz, with a modulation rate of 1.041667 Mbps.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.1.2.1 Standard	<p>12.1.2 UAT overall system characteristics of aircraft and ground stations</p> <p><i>Note.— Details on technical requirements related to the implementation of UAT SARPs are contained in Part I of the Manual on the Universal Access Transceiver (UAT) (Doc 9861). Part II of the Manual on the Universal Access Transceiver (UAT) (Doc 9861)(in preparation) will provide additional guidance material.</i></p> <p>TRANSMISSION FREQUENCY The transmission frequency shall be 978 MHz.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.1.2.2 Standard	<p>FREQUENCY STABILITY The radio frequency of the UAT equipment shall not vary more than ± 0.002 per cent (20 ppm) from the assigned frequency.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.1.2.3.1 Standard	<p>12.1.2.3 TRANSMIT POWER</p> <p>TRANSMIT POWER LEVELS UAT equipment shall operate at one of the power levels shown in Table 12-1*.</p> <hr/> <p>* All tables and figures are located at the end of the chapter.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.1.2.3.2 Standard	<p><i>MAXIMUM POWER</i></p> <p>The maximum equivalent isotropically radiated power (EIRP) for a UAT aircraft or ground station shall not exceed +58 dBm.</p> <p><i>Note.— For example, the maximum EIRP listed above could result from the maximum allowable aircraft transmitter power shown in Table 12-1 with a maximum antenna gain of 4 dBi.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.1.2.3.3 Standard	<p><i>TRANSIT MASK</i></p> <p>The spectrum of a UAT ADS-B message transmission modulated with pseudorandom message data blocks (MDB) shall fall within the limits specified in Table 12-2 when measured in a 100 kHz bandwidth.</p> <p><i>Note.— Figure 12-1* is a graphical representation of Table 12-2.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.1.2.4 Standard	<p>SPURIOUS EMISSIONS</p> <p>Spurious emissions shall be kept at the lowest value which the state of the technique and the nature of the service permit.</p> <p><i>Note.— Appendix 3 of the ITU Radio Regulations requires that transmitting stations shall conform to the maximum permitted power levels for spurious emissions or for unwanted emissions in the spurious domain.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.1.2.5 Standard	<p>POLARIZATION</p> <p>The design polarization of emissions shall be vertical.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.1.2.6 Standard	<p style="text-align: center;">TIME/AMPLITUDE PROFILE OF UAT MESSAGE TRANSMISSION</p> <p>The time/amplitude profile of a UAT message transmission shall meet the following requirements, in which the <i>reference time</i> is defined as the beginning of the first bit of the synchronization sequence (see 12.4.4.1.1, 12.4.4.2.1) appearing at the output port of the equipment.</p> <p><i>Notes.—</i></p> <p>1. All power requirements for subparagraphs “a” through “f” below apply to the PMP. for installations that support transmitter diversity, the RF power output on the non-selected antenna port should be at least 20 dB below the level on the selected port.</p> <p>2. All power requirements for subparagraphs “a” through “f” assume a 300 kHz measurement bandwidth. All power requirements for subparagraphs “b”, “c”, “d” and “e” assume a 2 MHz measurement bandwidth.</p> <p>3. The beginning of a bit is 1/2 bit period prior to the optimum sample point.</p> <p>4. These requirements are depicted graphically in Figure 12-2.</p> <p>a) Prior to 8 bit periods before the reference time, the RF output power at the PMP shall not exceed -dBm.</p> <p><i>Note.— This unwanted radiated power restriction is necessary to ensure that the UAT transmitting subsystem does not prevent closely located UAT receiving equipment on the same aircraft from meeting its requirements. It assumes that the isolation between transmitter and receiver equipment at the PMP exceeds 20 dB.</i></p> <p>b) Between 8 and 6 bit periods prior to the reference time, the RF output power at the PMP shall remain at least 20 dB below the minimum power requirement for the UAT equipment class.</p> <p><i>Note.— Guidance on definition of UAT equipment classes will be provided in Part II of the Manual on the Universal Access Transceiver (UAT)</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p><i>(Doc 9861) (in preparation).</i></p> <p>c) During the Active state, defined as beginning at the reference time and continuing for the duration of the message, the RF output power at the PMP shall be greater than or equal to the minimum power requirement for the UAT equipment class.</p> <p>d) The RF output power at the PMP shall not exceed the maximum power for the UAT equipment class at any time during the Active state.</p> <p>e) Within 6 bit periods after the end of the Active state, the RF output power at the PMP shall be at a level at least 20 dB below the minimum power requirement for the UAT equipment class.</p> <p>f) Within 8 bit periods after the end of the Active state, the RF output power at the PMP shall fall to a level not to exceed -80 dBm.</p> <p><i>Note.— This unwanted radiated power restriction is necessary to ensure that the transmitting subsystem does not prevent closely located UAT receiving equipment on the same aircraft from meeting its requirements. It assumes that the isolation between transmitter and receiver equipment at the PMP exceeds 20 dB.</i></p>				
Reference 12.1.3 Standard	<p>Mandatory carriage requirements</p> <p>Requirements for mandatory carriage of UAT equipment shall be made on the basis of regional air navigation agreements which specify the airspace of operation and the implementation timescales for the carriage of equipment, including the appropriate lead time.</p> <p><i>Note.— No changes will be required to aircraft systems or ground systems operating solely in regions not using UAT.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.2.1.1.1 Standard	<p>12.2 SYSTEM CHARACTERISTICS OF THE GROUND INSTALLATION</p> <p>12.2.1 Ground station transmitting function</p> <p>12.2.1.1 GROUND STATION TRANSMITTER POWER</p> <p>Recommendation.— <i>The effective radiated power should be such as to provide a field strength of at least 280 microvolts per metre (minus 97 dBW/m²) within the service volume of the facility on the basis of free-space propagation.</i></p> <p><i>Note.</i>— <i>This is determined on the basis of delivering a -91 dBm (corresponds to 200 microvolts per metre) signal level at the PMP (assuming an omnidirectional antenna). The 280 µV/m recommendation corresponds to the delivery of a -88 dBm signal level at the PMP of the receiving equipment. The 3 dB difference between -88 dBm and -91 dBm provides margin for excess path loss over free-space propagation.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.2.2 Note	<p>Ground station receiving function</p> <p><i>Note.</i>— <i>An example ground station receiver is discussed in Section 2.5 of Part II of the Manual on the Universal Access Transceiver (UAT) (Doc 9861), with UAT air-to-ground performance estimates consistent with use of that receiver provided in Appendix B of that manual.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.3.1.1 Standard	<p align="center">12.3 SYSTEM CHARACTERISTICS OF THE AIRCRAFT INSTALLATION</p> <p align="center">12.3.1 Aircraft transmitting function</p> <p align="center">AIRCRAFT TRANSMITTER POWER</p> <p>The effective radiated power shall be such as to provide a field strength of at least 225 microvolts per metre (minus 99 dBW/m²) on the basis of free-space propagation, at ranges and altitudes appropriate to the operational conditions pertaining to the areas over which the aircraft is operated. Transmitter power shall not exceed 54 dBm at the PMP.</p> <p><i>N1. The above field strength is determined on the basis of delivering a -93 dBm (corresponds to 160 microvolts per metre) signal level at the PMP (assuming an omnidirectional antenna). The 3 dB difference between 225 μV/m and 160 μV/m provides margin for excess path loss over free-space propagation when receiving a long UAT ADS-B message. A 4 dB margin is provided when receiving a basic UAT ADS-B message.</i></p> <p><i>N2. Various aircraft operations may have difference air-air range requirements depending on the intended ADS-B function of the UAT equipment. Therefore different installations may operate at different power levels (see 12.1.2.3.1).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.3.2.1.1 Standard	<p style="text-align: center;">12.3.2 Receiving function</p> <p style="text-align: center;">12.3.2.1 RECEIVER SENSITIVITY</p> <p><i>LONG UAT ADS-B MESSAGE AS DESIRED SIGNAL</i></p> <p>A desired signal level of -93 dBm applied at the PMP shall produce a rate of successful message reception (SMR) of 90 per cent or better under the following conditions:</p> <ul style="list-style-type: none"> a) When the desired signal is of nominal modulation (i.e. FM deviation is 625 kHz) and at the maximum signal frequency offsets, and subject to relative Doppler shift at ± 1 200 knots. b) When the desired signal is of maximum modulation distortion allowed in 12.4.3, at the nominal transmission frequency ± 1 parts per million (ppm), and subject to relative Doppler shift at ± 1 200 knots. <p><i>Note.— The receiver criteria for successful message reception of UAT ADS-B messages are provided in Section 4 of Part I of the Manual on the Universal Access Transceiver (UAT) (Doc 9861).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.3.2.1.2 Standard	<p><i>BASIC UAT ADS-B MESSAGE AS DESIRED SIGNAL</i></p> <p>A desired signal level of -94dBm applied at the PMP shall produce a rate of SMR of 90 per cent or better under the following conditions:</p> <ul style="list-style-type: none"> a) When the desired signal is of nominal modulation (i.e. FM deviation is 625 kHz) and at the maximum signal frequency offsets, and subject to relative Doppler shift at ± 1 200 knots; b) When the desired signal is of maximum modulation distortion allowed in 12.4.3, at the nominal transmission frequency ± 1 ppm, and subject to relative Doppler shift at ± 1 200 knots. <p><i>Note.— The receiver criteria for successful message reception of UAT ADS-B messages are provided in Section 4 of Part I of the Manual on the Universal Access Transceiver (UAT) (Doc 9861).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.3.2.1.3 Standard	<p><i>UAT GROUND UPLINK MESSAGE AS DESIRED SIGNAL</i></p> <p>A desired signal level of -91 dBm applied at the PMP shall produce a rate of an SMR of 90 per cent or better under the following conditions:</p> <ul style="list-style-type: none"> a) When the desired signal is of nominal modulation (i.e. FM deviation is 625 kHz) and at the maximum signal frequency offsets, and subject to relative Doppler shift at ±850 knots; b) When the desired signal is of maximum modulation distortion allowed in Section 12.4.3, at the nominal transmission frequency ±1 ppm, and subject to relative Doppler shift at ±850 knots. <p><i>N1.The receiver criteria for successful message reception of UAT ground uplink messages are provided in Section 4 of Part I of the Manual on the Universal Access Transceiver (UAT) (Doc 9861) (in preparation).</i></p> <p><i>N2.This requirement ensures the bit rate accuracy supporting demodulation in the UAT equipment is adequate to properly receive the longer UAT ground uplink message.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.3.2.2 Standard	<p style="text-align: center;">RECEIVER SELECTIVITY</p> <p>N1. <i>The undesired signal used is an unmodulated carrier applied at the frequency offset.</i></p> <p>N2. <i>This requirement establishes the receiver's rejection of the off-channel energy.</i></p> <p>N3. <i>It is assumed that ratios in between the specified offsets will fall near the interpolated value.</i></p> <p>N4. <i>The desired signal used is a UAT ADS-B long message at -90 dBm at the PMP, to be received with a 90 per cent successful message reception rate.</i></p> <p>N5. <i>The tolerable co-channel continuous wave interference power level for aircraft UAT receivers is assumed to be -101 dBm or less at the PMP.</i></p> <p>N6. <i>See Section 2.4.2 of Part II of the Manual on the Universal Access Transceiver (UAT) (Doc 9861) for a discussion of when a high-performance receiver is desirable.</i></p> <p>a) <i>Standard UAT receivers shall meet the selectivity characteristics given in Table 12-3.</i></p> <p>b) <i>High-performance receivers shall meet the more stringent selectivity characteristics given in Table 12-4.</i></p> <p><i>Note.— See Section 2.4.2 of Part II of the Manual on the Universal Access Transceiver (UAT) (Doc 9861) for guidance material on the implementation of high-performance receivers.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.3.2.3 Standard	<p style="text-align: center;">Receiver desired signal dynamic range</p> <p>The receiver shall achieve a successful message reception rate for long ADS-B messages of 99 per cent or better when the desired signal level is between -90 dBm and -10 dBm at the PMP in the absence of any interfering signals.</p> <p><i>Note.— The value of -10 dBm represents 120-foot separation from an aircraft transmitter transmitting at maximum allowed power.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.3.2.4 Standard	<p>RECEIVER TOLERANCE TO PULSED INTERFERENCE</p> <p><i>Note.— All power level requirements in this section are referenced to the PMP.</i></p> <p>a) For Standard and High-Performance receivers the following requirements shall apply:</p> <ol style="list-style-type: none"> 1) The receiver shall be capable of achieving 99 per cent SMR of long UAT ADS-B messages when the desired signal level is between -90 dBm and -10 dBm when subjected to DME interference under the following conditions: DME pulse pairs at a nominal rate of 3 600 pulse pairs per second at either 12 or 30 microseconds pulse spacing at a level of -36 dBm for any 1 MHz DME channel frequency between 980 MHz and 1 213 MHz inclusive. 2) Following a 21 microsecond pulse at a level of ZERO (0) dBm and at a frequency of 1 090 MHz, the receiver shall return to within 3 dB of the specified sensitivity level (see 12.3.2.1) within 12 microseconds. <p>b) For the standard UAT receiver the following additional requirements shall apply:</p> <ol style="list-style-type: none"> 3) The receiver shall be capable of achieving 90 per cent SMR of long UAT ADS-B messages when the desired signal level is between -87 dBm and -10 dBm when subjected to DME interference under the following conditions: DME pulse pairs at a nominal rate of 3 600 pulse pairs per second at a 12 microseconds pulse spacing at a level of -56 dBm and a frequency of 979 MHz. 4) The receiver shall be capable of achieving 90 per cent SMR of long UAT ADS-B messages when the desired signal level is between -87 dBm and -10 dBm when subjected to DME interference under the following conditions: DME pulse pairs at a nominal rate of 3 600 pulse pairs per second at a 12 microseconds pulse spacing at a level of 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>–70 dBm and a frequency of 978 MHz.</p> <p>c) For the high-performance receiver the following additional requirements shall apply:</p> <p>5) The receiver shall be capable of achieving 90 per cent SMR of long UAT ADS-B messages when the desired signal level is between –87 dBm and –10 dBm when subjected to DME interference under the following conditions: DME pulse pairs at a nominal rate of 3 600 pulse pairs per second at a 12 microseconds pulse spacing at a level of –43 dBm and a frequency of 979 MHz.</p> <p>6) The receiver shall be capable of achieving 90 per cent SMR of long UAT ADS-B messages when the desired signal level is between –87 dBm and –10 dBm when subjected to DME interference under the following conditions: DME pulse pairs at a nominal rate of 3 600 pulse pairs per second at a 12 microseconds pulse spacing at a level of –79 dBm and a frequency of 978 MHz.</p>				
Reference 12.4.1	<p>12.4 PHYSICAL LAYER CHARACTERISTICS</p> <p>Modulation rate</p> <p>The modulation rate shall be 1.041 667 Mbps with a tolerance for aircraft transmitters of ±20 ppm and a tolerance for ground transmitters of ±2 ppm.</p> <p><i>Note.— The tolerance on the modulation rate is consistent with the requirement on modulation distortion (see 12.4.3).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Reference 12.4.2</p> <p>Standard</p>	<p style="text-align: center;">Modulation type</p> <p>a) Data shall be modulated onto the carrier using binary continuous phase frequency shift keying. The modulation index, <i>h</i>, shall be no less than 0.6;</p> <p>b) A binary ONE (1) shall be indicated by a shift up in frequency from the nominal carrier frequency and a binary ZERO (0) by a shift down from the nominal carrier frequency.</p> <p><i>N1. Filtering of the transmitted signal (at base band and/or after frequency modulation) will be required to meet the spectral containment requirement of 12.1.2.3.3. This filtering may cause the deviation to exceed these values at points other than the optimum sampling points.</i></p> <p><i>N2. Because of the filtering of the transmitted signal, the received frequency offset varies continuously between the nominal values of ±312.5 kHz (and beyond), and the optimal sampling point may not be easily identified. This point can be defined in terms of the so-called “eye diagram” of the received signal. The ideal eye diagram is a superposition of samples of the (undistorted) post detection waveform shifted by multiples of the bit period (0.96 microseconds). The optimum sampling point is the point during the bit period at which the opening of the eye diagram (i.e. the minimum separation between positive and negative frequency offsets at very high signal-to-noise ratios) is maximized. An example “eye diagram” can be seen in Figure 12-3. The timing of the points where the lines converge defines the “optimum sampling point”. Figure 12-4 shows an eye pattern that has been partially closed by modulation distortion.</i></p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.4.3 Standard	<p style="text-align: center;">Modulation distortion</p> <p>a) For aircraft transmitters, the minimum vertical opening of the eye diagram of the transmitted signal (measured at the optimum sampling points) shall be no less than 560 kHz when measured over an entire long UAT ADS-B message containing pseudorandom message data blocks.</p> <p>b) For ground transmitters, the minimum vertical opening of the eye diagram of the transmitted signal (measured at the optimum sampling points) shall be no less than 560 kHz when measured over an entire UAT ground uplink message containing pseudorandom message data blocks.</p> <p>c) For aircraft transmitters, the minimum horizontal opening of the eye diagram of the transmitted signal (measured at 978 MHz) shall be no less than 0.624 microseconds (0.65 symbol periods) when measured over an entire long UAT ADS-B message containing pseudorandom message data blocks.</p> <p>d) For ground transmitters, the minimum horizontal opening of the eye diagram of the transmitted signal (measured at 978 MHz) shall be no less than 0.624 microseconds (0.65 symbol periods) when measured over an entire UAT ground uplink message containing pseudorandom message data blocks.</p> <p><i>N1. Section 12.4.4 defines the UAT ADS-B message types.</i></p> <p><i>N2. The ideal eye diagram is a superposition of samples of the (undistorted) post detection waveform shifted by multiples of the bit period (0.96 microseconds).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.4.4 Standard	<p align="center">Broadcast message characteristics</p> <p>The UAT system shall support two different message types: the UAT ADS-B message and the UAT ground uplink message.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.4.4.1 Standard	<p align="center">UAT ADS-B MESSAGE</p> <p>The Active portion (see 12.1.2.6) of a UAT ADS-B message shall contain the following elements, in the following order:</p> <ul style="list-style-type: none"> Bit synchronization Message data bloc FEC parity. 	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.4.4.1.1 Standard	<p><i>BIT SYNCHRONIZATION</i></p> <p>The first element of the Active portion of the UAT ADS-B message shall be a 36-bit synchronization sequence. For the UAT ADS-B messages the sequence shall be:</p> <p align="center">111010101100110111011010010011100010</p> <p>with the left-most bit transmitted first.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.4.4.1.2 Standard	<p><i>THE MESSAGE DATA BLOCK</i></p> <p>The second element of the Active portion of the UAT ADS-B message shall be the message data block. There shall be two lengths of UAT ADS-B message data blocks supported. The basic UAT ADS-B message shall have a 144-bit message data block and the long UAT ADS-B message shall have a 272-bit message data block.</p> <p><i>Note.— The format, encoding and transmission order of the message data block element is provided in Section 2.1 of Part I of the Manual on the Universal Access Transceiver (UAT) (Doc 9861).</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.4.4.1.3 Standard	<i>FEC PARITY</i> The third and final element of the Active portion of the UAT ADS-B message shall be the FEC parity.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.4.4.1.3.1 Standard	<p><i>Code type</i></p> <p>The FEC parity generation shall be based on a systematic Reed-Solomon (RS) 256-ary code with 8-bit code word symbols. FEC parity generation shall be per the following code:</p> <p>a) Basic UAT ADS-B Message: parity shall be a RS (30, 18) code;</p> <p><i>Note.— This results in 12 bytes (code symbols) of parity capable of correcting up to 6 symbol errors per block.</i></p> <p>b) Long UAT ADS-B Message: Parity shall be a RS (48, 34) code.</p> <p><i>Note.— This results in 14 bytes (code symbols) of parity capable of correcting up to 7 symbol errors per block.</i></p> <p>For either message length the primitive polynomial of the code shall be as follows:</p> $p(x) = x^8 + x^7 + x^2 + x + 1$ <p>The generator polynomial shall be as follows:</p> <p>where:</p> <p>P = 131 for RS (30, 18) code, P = 133 for RS (48, 34) code, and α is a primitive element of a Galois field of size 256 (i.e. GF(256)).</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Reference 12.4.4.1.3.2 Standard	<i>Transmission order of FEC parity</i> FEC parity bytes shall be ordered most significant to least significant in terms of the polynomial coefficients they represent. The ordering of bits within each byte shall be most significant to least significant. FEC parity bytes shall follow the message data block.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.4.4.2 Standard	UAT GROUND UPLINK MESSAGE The Active portion of a UAT ground uplink message shall contain the following elements, in the following order: Bit synchronization Interleaved message data block and FEC parity.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.4.4.2.1 Standard	<i>BIT SYNCHRONIZATION</i> The first element of the Active portion of the UAT ground uplink message shall be a 36-bit synchronization sequence. For the UAT ground uplink message the sequence shall be: 000101010011001000100101101100011101 with the left-most bit transmitted first.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Reference 12.4.4.2.2.1 Standard	<i>12.4.4.2.2 INTERLEAVED MESSAGE DATA BLOCK AND FEC PARITY</i> <i>Message data block (before interleaving and after de-interleaving)</i> The UAT ground uplink message shall have 3 456 bits of message data block. These bits are divided into 6 groups of 576 bits. FEC is applied to each group as described in 12.4.4.2.2.2. <i>Note.— Further details on the format, encoding and transmission order of the UAT ground uplink message data block are provided in Section 2.2. of Part I of the Manual on the Universal Access Transceiver (UAT) (Doc 9861).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Reference 12.4.4.2.2.1</p> <p>Standard</p>	<p><i>12.4.4.2.2.2 FEC parity (before interleaving and after de-interleaving)</i></p> <p><i>Code type</i> The FEC parity generation shall be based on a systematic RS 256-ary code with 8 bit code word symbols. FEC parity generation for each of the six blocks shall be a RS (92,72) code.</p> <p><i>N1. Section 12.4.4.2.2.3 provides details on the interleaving procedure.</i></p> <p><i>N2. This results in 20 bytes (symbols) of parity capable of correcting up to 10 symbol errors per block. The additional use of interleaving for the UAT ground uplink message allows additional robustness against burst errors.</i></p> <p>The primitive polynomial of the code is as follows: $p(x) = x^8 + x^7 + x^2 + x + 1$ The generator polynomial is as follows:</p> <p>where: P = 139, and α is a primitive element of a Galois field of size 256 (i.e. GF(256)).</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		
<p>Reference 12.4.4.2.2.2</p> <p>Standard</p>	<p><i>Transmission order of FEC parity</i> FEC parity bytes are ordered most significant to least significant in terms of the polynomial coefficients they represent. The ordering of bits within each byte will be most significant to least significant. FEC parity bytes shall follow the message data block.</p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Reference 12.4.4.2.2.3</p> <p>Standard</p>	<p><i>Interleaving procedure</i> UAT ground uplink messages shall be interleaved and transmitted by the ground station, as listed below:</p> <p>a) Interleaving procedure: The interleaved message data block and FEC parity consists of 6 interleaved Reed-Solomon blocks. The interleaver is represented by a 6×92 matrix, where each entry is a RS 8-bit symbol. Each row comprises a single RS (92,72) block as shown in Table 12-5. In this table, block numbers prior to interleaving are represented as “A” through “F.” The information is ordered for transmission column by column, starting at the upper left corner of the matrix.</p> <p>b) Transmission order: The bytes are then transmitted in the following order: 1,73,145,217,289,361,2,74,146,218,290,362,3, . . .,C/20,D/20,E/20,F/20.</p> <p><i>Note.— On reception these bytes need to be de-interleaved so that the RS blocks can be reassembled prior to error correction decoding.</i></p>	<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																								
<p>Reference 12.5</p> <p>Note</p>	<p style="text-align: center;">GUIDANCE MATERIAL</p> <p>N1.<i>The Manual on the Universal Access Transceiver (UAT) (Doc 9861), Part I, provides detailed technical specifications on UAT, including ADS-B message data blocks and formats, procedures for operation of UAT transmitting subsystems, and avionics interface requirements with other aircraft systems.</i></p> <p>N2.<i>The Manual on the Universal Access Transceiver (UAT) (Doc 9861), Part II, provides information on UAT system operation, description of a range of example avionics equipment classes and their applications, guidance on UAT aircraft and ground station installation aspects, and detailed information on UAT system performance simulation.</i></p> <hr/> <p style="text-align: center;">TABLES FOR CHAPTER 12</p> <p style="text-align: center;">Table 12-1. Transmitter power levels</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><i>Transmitter type</i></th> <th style="text-align: left;"><i>Minimum power at PMP</i></th> <th style="text-align: left;"><i>Maximum power at PMP</i></th> <th style="text-align: left;"><i>Intended minimum</i></th> </tr> </thead> <tbody> <tr> <td colspan="4"><i>air-to-air ranges</i></td> </tr> <tr> <td>Aircraft (Low)</td> <td>7 watts (+38.5 dBm)</td> <td>18</td> <td></td> </tr> <tr> <td>watts (+42.5 dBm)</td> <td>20 NM</td> <td></td> <td></td> </tr> <tr> <td>Aircraft (Medium)</td> <td>16 watts (+42 dBm)</td> <td>40</td> <td></td> </tr> <tr> <td>watts (+46 dBm)</td> <td>40 NM</td> <td></td> <td></td> </tr> <tr> <td>Aircraft (High)</td> <td>100 watts (+50 dBm)</td> <td>250</td> <td></td> </tr> <tr> <td>watts (+54 dBm)</td> <td>120 NM</td> <td></td> <td></td> </tr> <tr> <td>Ground Station</td> <td colspan="3">Specified by the service provider to meet local requirements</td> </tr> <tr> <td>within the constraint of 12.1.2.3.2.</td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>N3.<i>The three levels listed for the avionics are available to support applications with varying range requirements. See the discussion of UAT aircraft Equipage Classes in Section 2.4.2 of Part II of the Manual on the Universal</i></p>	<i>Transmitter type</i>	<i>Minimum power at PMP</i>	<i>Maximum power at PMP</i>	<i>Intended minimum</i>	<i>air-to-air ranges</i>				Aircraft (Low)	7 watts (+38.5 dBm)	18		watts (+42.5 dBm)	20 NM			Aircraft (Medium)	16 watts (+42 dBm)	40		watts (+46 dBm)	40 NM			Aircraft (High)	100 watts (+50 dBm)	250		watts (+54 dBm)	120 NM			Ground Station	Specified by the service provider to meet local requirements			within the constraint of 12.1.2.3.2.				<p>CV CAR 19, 19.B.230, (a),(1)</p>	<p>No Difference</p>		
<i>Transmitter type</i>	<i>Minimum power at PMP</i>	<i>Maximum power at PMP</i>	<i>Intended minimum</i>																																										
<i>air-to-air ranges</i>																																													
Aircraft (Low)	7 watts (+38.5 dBm)	18																																											
watts (+42.5 dBm)	20 NM																																												
Aircraft (Medium)	16 watts (+42 dBm)	40																																											
watts (+46 dBm)	40 NM																																												
Aircraft (High)	100 watts (+50 dBm)	250																																											
watts (+54 dBm)	120 NM																																												
Ground Station	Specified by the service provider to meet local requirements																																												
within the constraint of 12.1.2.3.2.																																													



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																														
	<p>Access Transceiver (UAT) (Doc 9861) (in preparation).</p> <p><i>N4. The intended minimum air-to-air ranges are for high-density air traffic environments. Larger air-to-air ranges will be achieved in low-density air traffic environments.</i></p> <p>Table 12-2. UAT transmit spectrum</p> <table border="0"> <tr> <td><i>Frequency offset from centre</i></td> <td><i>Required attenuation from maximum power level (dB as measured at the PMP)</i></td> </tr> <tr> <td>All frequencies in the range 0 – 0.5 MHz</td> <td>0</td> </tr> <tr> <td>All frequencies in the range 0.5 – 1.0 MHz</td> <td>Base</td> </tr> <tr> <td> d on linear* interpolation between these points</td> <td></td> </tr> <tr> <td> 1.0 MHz</td> <td>18</td> </tr> <tr> <td>All frequencies in the range 1.0 – 2.25 MHz</td> <td>Base</td> </tr> <tr> <td> d on linear* interpolation between these points</td> <td></td> </tr> <tr> <td> 2.25 MHz</td> <td>50</td> </tr> <tr> <td>All frequencies in the range 2.25 – 3.25 MHz</td> <td>Base</td> </tr> <tr> <td> d on linear* interpolation between these points</td> <td></td> </tr> <tr> <td> 3.25 MHz</td> <td>60</td> </tr> </table> <p><i>* based on attenuation in dB and a linear frequency scale</i></p> <p>Table 12-3. Standard UAT receiver rejection ratios</p> <table border="0"> <tr> <td><i>Frequency offset from centre</i></td> <td><i>Minimum rejection ratio</i></td> </tr> <tr> <td><i>(Undesired/desired level in dB)</i></td> <td></td> </tr> <tr> <td>-1.0 MHz</td> <td>10</td> </tr> <tr> <td>+1.0 MHz</td> <td>15</td> </tr> </table>	<i>Frequency offset from centre</i>	<i>Required attenuation from maximum power level (dB as measured at the PMP)</i>	All frequencies in the range 0 – 0.5 MHz	0	All frequencies in the range 0.5 – 1.0 MHz	Base	d on linear* interpolation between these points		1.0 MHz	18	All frequencies in the range 1.0 – 2.25 MHz	Base	d on linear* interpolation between these points		2.25 MHz	50	All frequencies in the range 2.25 – 3.25 MHz	Base	d on linear* interpolation between these points		3.25 MHz	60	<i>Frequency offset from centre</i>	<i>Minimum rejection ratio</i>	<i>(Undesired/desired level in dB)</i>		-1.0 MHz	10	+1.0 MHz	15				
<i>Frequency offset from centre</i>	<i>Required attenuation from maximum power level (dB as measured at the PMP)</i>																																		
All frequencies in the range 0 – 0.5 MHz	0																																		
All frequencies in the range 0.5 – 1.0 MHz	Base																																		
d on linear* interpolation between these points																																			
1.0 MHz	18																																		
All frequencies in the range 1.0 – 2.25 MHz	Base																																		
d on linear* interpolation between these points																																			
2.25 MHz	50																																		
All frequencies in the range 2.25 – 3.25 MHz	Base																																		
d on linear* interpolation between these points																																			
3.25 MHz	60																																		
<i>Frequency offset from centre</i>	<i>Minimum rejection ratio</i>																																		
<i>(Undesired/desired level in dB)</i>																																			
-1.0 MHz	10																																		
+1.0 MHz	15																																		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																						
	<p>(±) 2.0 MHz 50 (±) 10.0 MHz 60</p> <p><i>Note.— It is assumed that ratios in between the specified offsets will fall near the interpolated value.</i></p> <p>Table 12-4. High-performance receiver rejection ratios</p> <p><i>Frequency offset from centre</i> <i>Minimum rejection ratio</i> <i>(Undesired/desired level in dB)</i></p> <p>-1.0 MHz 30 +1.0 MHz 40 (±) 2.0 MHz 50 (±) 10.0 MHz 60</p> <p>Table 12-5. Ground uplink interleaver matrix</p> <table border="1" data-bbox="415 852 924 1291"> <thead> <tr> <th>RS Block</th> <th colspan="2">MDB</th> <th colspan="2">Byte #</th> </tr> <tr> <th></th> <th>FEC</th> <th>Parity</th> <th>(Block/B</th> <th>yte #)</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>1</td> <td>2 3 ...</td> <td>71</td> <td>72 A/1 ...</td> </tr> <tr> <td></td> <td>A/19</td> <td>A/20</td> <td></td> <td></td> </tr> <tr> <td>B</td> <td>73</td> <td>74 75 ...</td> <td>143</td> <td>144 B/1 ...</td> </tr> <tr> <td></td> <td>B/19</td> <td>B/20</td> <td></td> <td></td> </tr> <tr> <td>C</td> <td>145</td> <td>146 147 ...</td> <td>215</td> <td>216 C/1 ...</td> </tr> <tr> <td></td> <td>C/19</td> <td>C/20</td> <td></td> <td></td> </tr> <tr> <td>D</td> <td>217</td> <td>218 219 ...</td> <td>287</td> <td>288 D/1 ...</td> </tr> <tr> <td></td> <td>D/19</td> <td>D/20</td> <td></td> <td></td> </tr> <tr> <td>E</td> <td>289</td> <td>290 291 ...</td> <td>359</td> <td>360 E/1 ...</td> </tr> <tr> <td></td> <td>E/19</td> <td>E/20</td> <td></td> <td></td> </tr> <tr> <td>F</td> <td>361</td> <td>362 363 ...</td> <td>431</td> <td>432 F/1 ...</td> </tr> <tr> <td></td> <td>F/19</td> <td>F/20</td> <td></td> <td></td> </tr> </tbody> </table> <p><i>Note.— In Table 12-5, message data block Byte #1 through #72 are the 72 bytes (8 bits each) of message data block information carried in the first RS (92,72) block. FEC parity A/1 through A/20 are the 20 bytes of FEC parity associated with that block (A).</i></p>	RS Block	MDB		Byte #			FEC	Parity	(Block/B	yte #)	A	1	2 3 ...	71	72 A/1 ...		A/19	A/20			B	73	74 75 ...	143	144 B/1 ...		B/19	B/20			C	145	146 147 ...	215	216 C/1 ...		C/19	C/20			D	217	218 219 ...	287	288 D/1 ...		D/19	D/20			E	289	290 291 ...	359	360 E/1 ...		E/19	E/20			F	361	362 363 ...	431	432 F/1 ...		F/19	F/20						
RS Block	MDB		Byte #																																																																								
	FEC	Parity	(Block/B	yte #)																																																																							
A	1	2 3 ...	71	72 A/1 ...																																																																							
	A/19	A/20																																																																									
B	73	74 75 ...	143	144 B/1 ...																																																																							
	B/19	B/20																																																																									
C	145	146 147 ...	215	216 C/1 ...																																																																							
	C/19	C/20																																																																									
D	217	218 219 ...	287	288 D/1 ...																																																																							
	D/19	D/20																																																																									
E	289	290 291 ...	359	360 E/1 ...																																																																							
	E/19	E/20																																																																									
F	361	362 363 ...	431	432 F/1 ...																																																																							
	F/19	F/20																																																																									



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference 1.0.1 Note	<p style="text-align: center;">PART II — VOICE COMMUNICATION SYSTEMS CHAPTER 1. DEFINITIONS</p> <p><i>Note.— Material on secondary power supply and guidance material concerning reliability and availability for communication systems is contained in Annex 10, Volume I, 2.9 and Volume I, Attachment F, respectively.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.1.1 Standard	<p style="text-align: center;">CHAPTER 2. AERONAUTICAL MOBILE SERVICE</p> <p style="text-align: center;">2.1 AIR-GROUND VHF COMMUNICATION SYSTEM CHARACTERISTICS</p> <p><i>Note.— In the following text the channel spacing for 8.33 kHz channel assignments is defined as 25 kHz divided by 3 which is 8.3333 ... kHz.</i></p> <p>The characteristics of the air-ground VHF communication system used in the International Aeronautical Mobile Service shall be in conformity with the following specifications:</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.1.1.1 Standard	Radiotelephone emissions shall be double sideband (DSB) amplitude modulated (AM) carriers. The designation of emission is A3E, as specified in the ITU Radio Regulations.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.1.2 Standard	Spurious emissions shall be kept at the lowest value which the state of technique and the nature of the service permit. <i>Note.— Appendix S3 to the ITU Radio Regulations specifies the levels of spurious emissions to which transmitters must conform.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.1.1.3 Standard	The radio frequencies used shall be selected from the radio frequencies in the band 117.975 – 137 MHz. The separation between assignable frequencies (channel spacing) and frequency tolerances applicable to elements of the system shall be as specified in Volume V. <i>Note.— The band 117.975 – 132 MHz was allocated to the Aeronautical Mobile (R) Service in the ITU Radio Regulations (1947). By subsequent revisions at ITU World Administrative Radio Conferences the bands 132 – 136 MHz and 136 – 137 MHz were added under conditions which differ for ITU Regions, or for specified countries or combinations of countries (see RRs S5.203, S5.203A and S5.203B for additional allocations in the band 136 – 137 MHz and S5.201 for the band 132 – 136 MHz).</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.1.1.4 Standard	The design polarization of emissions shall be vertical.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.2.1.1 Standard	<p align="center">2.2 SYSTEM CHARACTERISTICS OF THE GROUND INSTALLATION</p> <p align="center">2.2.1 Transmitting function</p> <p><i>Frequency stability.</i> The radio frequency of operation shall not vary more than plus or minus 0.005 per cent from the assigned frequency. Where 25 kHz channel spacing is introduced in accordance with Volume V, the radio frequency of operation shall not vary more than plus or minus 0.002 per cent from the assigned frequency. Where 8.33 kHz channel spacing is introduced in accordance with Volume V, the radio frequency of operation shall not vary more than plus or minus 0.0001 per cent from the assigned frequency.</p> <p><i>Note.— The above frequency stability requirements will not be sufficient for offset carrier systems using 25 kHz channel spacing or higher.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.2.1.1.1 Standard	<p><i>Offset carrier systems in 8.33 kHz, 25 kHz, 50 kHz and 100 kHz channel spaced environments.</i> The stability of individual carriers of an offset carrier system shall be such as to prevent first-order heterodyne frequencies of less than 4 kHz and, additionally, the maximum frequency excursion of the outer carrier frequencies from the assigned carrier frequency shall not exceed 8 kHz. Offset carrier systems for 8.33 kHz channel spacing shall be limited to two-carrier systems using a carrier offset of plus and minus 2.5 kHz.</p> <p><i>Note.— Examples of the required stability of the individual carriers of offset carrier systems may be found at the Attachment to Part II.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.2.1.2 Recommendation	POWER Recommendation. — <i>On a high percentage of occasions, the effective radiated power should be such as to provide a field strength of a least 75 microvolts per metre (minus 109 dBW/m²) within the defined operational coverage of the facility, on the basis of free space propagation.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.2.1.3 Standard	<i>Modulation.</i> A peak modulation factor of at least 0.85 shall be achievable.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.2.1.4 Recommendation	Recommendation. — <i>Means should be provided to maintain the average modulation factor at the highest practicable value without overmodulation.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.2.2.1 Standard	2.2.2 Receiving function <i>Frequency stability.</i> Where 8.33 kHz channel spacing is introduced in accordance with Volume V, the radio frequency of operation shall not vary more than plus or minus 0.0001 per cent from the assigned frequency.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.2.2.2 Standard	<i>Sensitivity.</i> After due allowance has been made for feeder loss and antenna polar diagram variation, the sensitivity of the receiving function shall be such as to provide on a high percentage of occasions an audio output signal with a wanted/unwanted ratio of 15 dB, with a 50 per cent amplitude modulated (A3E) radio signal having a field strength of 20 microvolts per metre (minus 120 dBW/m ²) or more.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.2.2.3 Standard	<i>Effective acceptance bandwidth.</i> When tuned to a channel having a width of 25 kHz, 50 kHz or 100 kHz, the receiving system shall provide an adequate and intelligible audio output when the signal specified at 2.2.2.2 has a carrier frequency within plus or minus 0.005 per cent of the assigned frequency. When tuned to a channel having a width of 8.33 kHz, the receiving system shall provide an adequate and intelligible audio output when the signal specified at 2.2.2.2 has a carrier frequency within plus or minus 0.0005 per cent of the assigned frequency. Further information on the effective acceptance bandwidth is contained in the Attachment to Part II. <i>Note.— The effective acceptance bandwidth includes Doppler shift.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.2.2.4 Standard	<i>Adjacent channel rejection.</i> The receiving system shall ensure an effective rejection of 60 dB or more at the next assignable channel. <i>Note.— The next assignable frequency will normally be plus or minus 50 kHz. Where this channel spacing will not suffice, the next assignable frequency will be plus or minus 25 kHz, or plus or minus 8.33 kHz, implemented in accordance with the provisions of Volume V. It is recognized that in certain areas of the world receivers designed for 25 kHz, 50 kHz or 100 kHz channel spacing may continue to be used.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.1.1 Standard	<p align="center">2.3 SYSTEM CHARACTERISTICS OF THE AIRBORNE INSTALLATION</p> <p align="center">2.3.1 Transmitting function</p> <p><i>Frequency stability.</i> The radio frequency of operation shall not vary more than plus or minus 0.005 per cent from the assigned frequency. Where 25 kHz channel spacing is introduced, the radio frequency of operation shall not vary more than plus or minus 0.003 per cent from the assigned frequency. Where 8.33 kHz channel spacing is introduced, the radio frequency of operation shall not vary more than plus or minus 0.0005 per cent from the assigned frequency.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.1.2 Standard	<i>Power.</i> On a high percentage of occasions, the effective radiated power shall be such as to provide a field strength of at least 20 microvolts per metre (minus 120 dBW/m ²) on the basis of free space propagation, at ranges and altitudes appropriate to the operational conditions pertaining to the areas over which the aircraft is operated.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.1.3 Standard	<p><i>Adjacent channel power.</i> The amount of power from a 8.33 kHz airborne transmitter under all operating conditions when measured over a 7 kHz channel bandwidth centred on the first 8.33 kHz adjacent channel shall not exceed -45 dB below the transmitter carrier power. The above adjacent channel power shall take into account the typical voice spectrum.</p> <p><i>Note.— The voice spectrum is assumed to be a constant level between 300 and 800 Hz and attenuated by 10 dB per octave above 800 Hz.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.1.4 Standard	<i>Modulation.</i> A peak modulation factor of at least 0.85 shall be achievable.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.1.5 Recommendation	Recommendation. — <i>Means should be provided to maintain the average modulation factor at the highest practicable value without overmodulation.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.2.1 Standard	2.3.2 Receiving function <i>Frequency stability.</i> Where 8.33 kHz channel spacing is introduced in accordance with Volume V, the radio frequency of operation shall not vary more than plus or minus 0.0005 per cent from the assigned frequency.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.2.2.1 Recommendation	2.3.2.2 SENSITIVITY Recommendation. — <i>After due allowance has been made for aircraft feeder mismatch, attenuation loss and antenna polar diagram variation, the sensitivity of the receiving function should be such as to provide on a high percentage of occasions an audio output signal with a wanted/unwanted ratio of 15 dB, with a 50 per cent amplitude modulated (A3E) radio signal having a field strength of 75 microvolts per metre (minus 109 dBW/m²).</i> <i>Note.</i> — <i>For planning extended range VHF facilities, an airborne receiving function sensitivity of 30 microvolts per metre may be assumed.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.2.3 Standard	<p><i>Effective acceptance bandwidth for 100 kHz, 50 kHz and 25 kHz channel spacing receiving installations.</i> When tuned to a channel designated in Volume V as having a width of 25 kHz, 50 kHz or 100 kHz, the receiving function shall ensure an effective acceptance bandwidth as follows:</p> <ul style="list-style-type: none"> a) in areas where offset carrier systems are employed, the receiving function shall provide an adequate audio output when the signal specified at 2.3.2.2 has a carrier frequency within 8 kHz of the assigned frequency; b) in areas where offset carrier systems are not employed, the receiving function shall provide an adequate audio output when the signal specified at 2.3.2.2 has a carrier frequency of plus or minus 0.005 per cent of the assigned frequency. 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.2.4 Standard	<p><i>Effective acceptance bandwidth for 8.33 kHz channel spacing receiving installations.</i> When tuned to a channel designated in Volume V, as having a width of 8.33 kHz, the receiving function shall ensure an effective acceptance bandwidth as follows:</p> <ul style="list-style-type: none"> a) in areas where offset carrier systems are employed, the receiving function shall provide an adequate audio output when the signal specified in 2.3.2.2 has a carrier frequency of plus or minus 2.5 kHz of the assigned frequency; and b) in areas where offset carrier systems are not employed, the receiving function shall provide an adequate audio output when the signal specified in 2.3.2.2 has a carrier frequency within plus or minus 0.0005 per cent of the assigned frequency. Further information on the effective acceptance bandwidth is contained in Part II, Attachment A. <p><i>N1.The effective acceptance bandwidth includes Doppler shift.</i></p> <p><i>N2.When using offset carrier systems (ref. 2.3.2.3 and 2.3.2.4), receiver performance may become degraded when receiving two or more similar strength offset carrier signals. Caution is therefore advised with the implementation of offset carrier systems.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.2.5 Standard	<p><i>Adjacent channel rejection.</i> The receiving function shall ensure an effective adjacent channel rejection as follows:</p> <ul style="list-style-type: none"> a) <i>8.33 kHz channels:</i> 60 dB or more at plus or minus 8.33 kHz with respect to the assigned frequency, and 40 dB or more at plus or minus 6.5 kHz; <p><i>Note.— The receiver local oscillator phase noise should be sufficiently low to avoid any degradation of the receiver capability to reject off carrier signals. A phase noise level better than minus 99 dBc/Hz 8.33 kHz away from the carrier is necessary to comply with 45 dB adjacent channel rejection under all operating conditions.</i></p> <ul style="list-style-type: none"> b) <i>25 kHz channel spacing environment:</i> 50 dB or more at plus or minus 25 kHz with respect to the assigned frequency and 40 dB or more at plus or minus 17 kHz; c) <i>50 kHz channel spacing environment:</i> 50 dB or more at plus or minus 50 kHz with respect to the assigned frequency and 40 dB or more at plus or minus 35 kHz; d) <i>100 kHz channel spacing environment:</i> 50 dB or more at plus or minus 100 kHz with respect to the assigned frequency. 	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.2.6 Recommendation	<p>Recommendation.— <i>Whenever practicable, the receiving system should ensure an effective adjacent channel rejection characteristic of 60 dB or more at plus or minus 25 kHz, 50 kHz and 100 kHz from the assigned frequency for receiving systems intended to operate in channel spacing environments of 25 kHz, 50 kHz and 100 kHz, respectively.</i></p> <p><i>Note.— Frequency planning is normally based on an assumption of 60 dB effective adjacent channel rejection at plus or minus 25 kHz, 50 kHz or 100 kHz from the assigned frequency as appropriate to the channel spacing environment.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.2.7 Recommendation	<p>Recommendation.— <i>In the case of receivers complying with 2.3.2.3 or 2.3.2.4 used in areas where offset carrier systems are in force, the characteristics of the receiver should be such that:</i></p> <ul style="list-style-type: none"> a) <i>the audio frequency response precludes harmful levels of audio heterodynes resulting from the reception of two or more offset carrier frequencies;</i> b) <i>the receiver muting circuits, if provided, operate satisfactorily in the presence of audio heterodynes resulting from the reception of two or more offset carrier frequencies.</i> 	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.2.8.1 Standard	<p>2.3.2.8 VDL — INTERFERENCE IMMUNITY PERFORMANCE</p> <p>For equipment intended to be used in independent operations of services applying DSB-AM and VDL technology on board the same aircraft, the receiving function shall provide an adequate and intelligible audio output with a desired signal field strength of not more than 150 microvolts per metre (minus 102 dBW/m²) and with an undesired VDL signal field strength of at least 50 dB above the desired field strength on any assignable channel 100 kHz or more away from the assigned channel of the desired signal.</p> <p><i>Note.— This level of VDL interference immunity performance provides a receiver performance consistent with the influence of the VDL RF spectrum mask as specified in Volume III, Part I, 6.3.4 with an effective transmitter/receiver isolation of 68 dB. Better transmitter and receiver performance could result in less isolation required.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.2.8.2 Standard	After 1 January 2002, the receiving function of all new installations intended to be used in independent operations of services applying DSB-AM and VDL technology on board the same aircraft shall meet the provisions of 2.3.2.8.1.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.2.8.3 Standard	After 1 January 2005, the receiving function of all installations intended to be used in independent operations of services applying DSB-AM and VDL technology on board the same aircraft shall meet the provisions of 2.3.2.8.1, subject to the conditions of 2.3.2.8.4.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.2.8.4 Standard	Requirements for mandatory compliance of the provisions of 2.3.2.8.3 shall be made on the basis of regional air navigation agreements which specify the airspace of operation and the implementation timescales.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.2.8.4.1 Standard	The agreement indicated in 2.3.2.8.4 shall provide at least two years' notice of mandatory compliance of airborne systems.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.3.1 Standard	<p align="center">2.3.3 Interference immunity performance</p> <p>After 1 January 1998, the VHF communications receiving system shall provide satisfactory performance in the presence of two signal, third-order intermodulation products caused by VHF FM broadcast signals having levels at the receiver input of minus 5 dBm.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.3.2 Standard	<p>After 1 January 1998, the VHF communications receiving system shall not be desensitized in the presence of VHF FM broadcast signals having levels at the receiver input of minus 5 dBm.</p> <p><i>Note.— Guidance material on immunity criteria to be used for the performance quoted in 2.3.3.1 and 2.3.3.2 is contained in the Attachment Part II, 1.3.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.3.3 Standard	<p>After 1 January 1995, all new installations of airborne VHF communications receiving systems shall meet the provisions of 2.3.3.1 and 2.3.3.2.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.3.3.4 Recommendation	<p>Recommendation.— <i>Airborne VHF communications receiving systems meeting the immunity performance Standards of 2.3.3.1 and 2.3.3.2 should be placed into operation at the earliest possible date.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.1 Standard	<p align="center">2.4 SINGLE SIDEBAND (SSB) HF COMMUNICATION SYSTEM CHARACTERISTICS FOR USE IN THE AERONAUTICAL MOBILE SERVICE</p> <p>The characteristics of the air-ground HF SSB system, where used in the Aeronautical Mobile Service, shall be in conformity with the following specifications.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.1.1 Standard	<p align="center">2.4.1.1 FREQUENCY RANGE</p> <p>HF SSB installations shall be capable of operation at any SSB carrier (reference) frequency available to the Aeronautical Mobile (R) Service in the band 2.8 MHz to 22 MHz and necessary to meet the approved assignment plan for the region(s) in which the system is intended to operate, and in compliance with the relevant provisions of the Radio Regulations.</p> <p>N1. See <i>Introduction to Volume V, Chapter 3, and Figures 2-1 and 2-2*</i>.</p> <p>N2. The <i>ITU World Administrative Radio Conference, Aeronautical Mobile (R) Service, Geneva, 1978, established a new Allotment Plan (Appendix 27, Aer to the Radio Regulations) based on single sideband replacing the earlier double sideband Allotment Plan. The World Radiocommunication Conference 1995 redesignated it as Appendix S27. Minor editorial changes were made at the World Radiocommunication Conference 1997.</i></p> <p>* All tables and figures are located at the end of this chapter.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.1.1.2 Standard	The equipment shall be capable of operating on integral multiples of 1 kHz.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.2.1 Standard	2.4.1.2 SIDEBAND SELECTION The sideband transmitted shall be that on the higher frequency side of its carrier (reference) frequency.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.3.1 Standard	2.4.1.3 CARRIER (REFERENCE) FREQUENCY Channel utilization shall be in conformity with the table of carrier (reference) frequencies at 27/16 and the Allotment Plan at 27/186 to 27/207 inclusive (or frequencies established on the basis of 27/21, as may be appropriate) of Appendix S27. <i>Note.— It is intended that only the carrier (reference) frequency be promulgated in Regional Plans and Aeronautical Publications.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.4.1 Standard	2.4.1.4 CLASSES OF EMISSION AND CARRIER SUPPRESSION The system shall utilize the suppressed carrier class of emission J3E (also J7B and J9B as applicable). When SELCAL is employed as specified in Chapter 3 of Part II, the installation shall utilize class H2B emission.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.1.4.2 Standard	By 1 February 1982 aeronautical stations and aircraft stations shall have introduced the appropriate class(es) of emission prescribed in 2.4.1.4.1. Effective this date the use of class A3E emission shall be discontinued except as provided in 2.4.1.4.4.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.4.3 Standard	Until 1 February 1982 aeronautical stations and aircraft stations equipped for single sideband operations shall also be equipped to transmit class H3E emission where required to be compatible with reception by double sideband equipment. Effective this date the use of class H3E emission shall be discontinued except as provided in 2.4.1.4.4.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.4.4 Recommendation	Recommendation. — <i>For stations directly involved in coordinated search and rescue operations using the frequencies 3 023 kHz and 5 680 kHz, the class of emission J3E should be used; however, since maritime mobile and land mobile services may be involved, A3E and H3E classes of emission may be used.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.4.5 Standard	After 1 April 1981 no new DSB equipment shall be installed.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.4.6 Standard	Aircraft station transmitters shall be capable of at least 26 dB carrier suppression with respect to peak envelope power (P_p) for classes of emission J3E, J7B or J9B.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.1.4.7 Standard	Aeronautical station transmitters shall be capable of 40 dB carrier suppression with respect to peak envelope power (P_p) for classes of emission J3E, J7B or J9B.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.5.1 Standard	<p style="text-align: center;">2.4.1.5 AUDIO FREQUENCY BANDWIDTH</p> <p>For radiotelephone emissions the audio frequencies shall be limited to between 300 and 2 700 Hz and the occupied bandwidth of other authorized emissions shall not exceed the upper limit of J3E emissions. In specifying these limits, however, no restriction in their extension shall be implied in so far as emissions other than J3E are concerned, provided that the limits of unwanted emissions are met (see 2.4.1.7).</p> <p><i>Note.— For aircraft and aeronautical station transmitter types first installed before 1 February 1983 the audio frequencies will be limited to 3 000 Hz.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.5.2 Standard	For other authorized classes of emission the modulation frequencies shall be such that the required spectrum limits of 2.4.1.7 will be met.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.1.6.1 Standard	<p style="text-align: center;">2.4.1.6 FREQUENCY TOLERANCE</p> <p>The basic frequency stability of the transmitting function for classes of emission J3E, J7B or J9B shall be such that the difference between the actual carrier of the transmission and the carrier (reference) frequency shall not exceed: 20 Hz for airborne installations; 10 Hz for ground installations.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.6.2 Standard	<p>The basic frequency stability of the receiving function shall be such that, with the transmitting function stabilities specified in 2.4.1.6.1, the overall frequency difference between ground and airborne functions achieved in service and including Doppler shift, does not exceed 45 Hz. However, a greater frequency difference shall be permitted in the case of supersonic aircraft.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.7.1 Standard	<p style="text-align: center;">2.4.1.7 SPECTRUM LIMITS</p> <p>For aircraft station transmitter types and for aeronautical station transmitters first installed before 1 February 1983 and using single sideband classes of emission H2B, H3E, J3E, J7B or J9B the mean power of any emission on any discrete frequency shall be less than the mean power (P_m) of the transmitter in accordance with the following:</p> <ul style="list-style-type: none"> on any frequency removed by 2 kHz or more up to 6 kHz from the assigned frequency: at least 25 dB; on any frequency removed by 6 kHz or more up to 10 kHz from the assigned frequency: at least 35 dB; on any frequency removed from the assigned frequency by 10 kHz or more: <ul style="list-style-type: none"> a) aircraft station transmitters: 40 dB; b) aeronautical station transmitters: [43 + 10 log₁₀P_m(W)] dB 	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.1.7.2 Standard	<p>For aircraft station transmitters first installed after 1 February 1983 and for aeronautical station transmitters in use as of 1 February 1983 and using single sideband classes of emission H2B, H3E, J3E, J7B or J9B, the peak envelope power (P_p) of any emission on any discrete frequency shall be less than the peak envelope power (P_p) of the transmitter in accordance with the following:</p> <ul style="list-style-type: none"> on any frequency removed by 1.5 kHz or more up to 4.5 kHz from the assigned frequency: at least 30 dB; on any frequency removed by 4.5 kHz or more up to 7.5 kHz from the assigned frequency: at least 38 dB; on any frequency removed from the assigned frequency by 7.5 kHz or more: <ul style="list-style-type: none"> a) aircraft station transmitters: 43 dB; b) aeronautical station transmitters: for transmitter power up to and including 50 W: $[43 + 10 \log_{10} P_p(W)] \text{ dB}$ <p>For transmitter power more than 50 W: 60 dB.</p> <p><i>Note.— See Figures 2-1 and 2-2.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.4.1.8.1 Standard	<p style="text-align: center;">2.4.1.8 POWER</p> <p><i>Aeronautical station installations.</i> Except as permitted by the relevant provisions of Appendix S27 to the ITU Radio Regulations, the peak envelope power (P_p) supplied to the antenna transmission line for H2B, H3E, J3E, J7B or J9B classes of emissions shall not exceed a maximum value of 6 kW.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
Chapter 2 Reference 2.4.1.8.2 Standard	<p><i>Aircraft station installations.</i> The peak envelope power supplied to the antenna transmission line for H2B, H3E, J3E, J7B or J9B classes of emission shall not exceed 400 W except as provided for in Appendix S27 of the ITU Radio Regulations as follows:</p> <p>S27/68 It is recognized that the power employed by aircraft transmitters may, in practice, exceed the limits specified in No. 27/60. However, the use of such increased power (which normally should not exceed 600 W P_p) shall not cause harmful interference to stations using frequencies in accordance with the technical principles on which the Allotment Plan is based.</p> <p>S27/60 Unless otherwise specified in Part II of this Appendix, the peak envelope powers supplied to the antenna transmission line shall not exceed the maximum values indicated in the table below; the corresponding peak effective radiated powers being assumed to be equal to two-thirds of these values:</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: left;"><i>Class of emission</i></th> <th style="text-align: left;"><i>Stations</i></th> </tr> <tr> <th></th> <th style="text-align: center;"><i>Max. peak</i></th> </tr> </thead> <tbody> <tr> <td colspan="2"><i>envelope power (P_p)</i></td> </tr> <tr> <td>H2B, 3E, J7B, J9B, A3E*, H3E* (100% modulation)</td> <td style="text-align: center;">Aeronautical 6 kW 400 W</td> </tr> <tr> <td>Other emission such as A1A, F1B</td> <td style="text-align: center;">Aeronautical 1.5 kW 100 W</td> </tr> </tbody> </table> <p>* A3E and H3E to be used only on 3 023 kHz and 5 680 kHz.</p>	<i>Class of emission</i>	<i>Stations</i>		<i>Max. peak</i>	<i>envelope power (P_p)</i>		H2B, 3E, J7B, J9B, A3E*, H3E* (100% modulation)	Aeronautical 6 kW 400 W	Other emission such as A1A, F1B	Aeronautical 1.5 kW 100 W	CV CAR 19, 19.B.230, (a),(1)	No Difference		
<i>Class of emission</i>	<i>Stations</i>														
	<i>Max. peak</i>														
<i>envelope power (P_p)</i>															
H2B, 3E, J7B, J9B, A3E*, H3E* (100% modulation)	Aeronautical 6 kW 400 W														
Other emission such as A1A, F1B	Aeronautical 1.5 kW 100 W														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.1.9 Standard	<i>Method of operation.</i> Single channel simplex shall be employed.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.5.1 Standard	<p align="center">2.5 Satellite voice communication (SATVOICE) system characteristics</p> <p><i>Note.— Guidance material for the implementation of the aeronautical mobile satellite service is contained in the Manual on the Aeronautical Mobile Satellite (Route) Service (Doc 9925). Additional guidance for SATVOICE systems is contained in the Satellite Voice Operations Manual (Doc 10038), and the Performance-based Communication and Surveillance (PBCS) Manual (Doc 9869).</i></p> <p>For ground-to-air calls, the SATVOICE system shall be capable of contacting the aircraft and enabling the ground party/system to provide, as a minimum, the following:</p> <ul style="list-style-type: none"> a) secure calling; b) priority level as defined in Table 2-1; and c) aircraft SATVOICE number, which is the aircraft address expressed as an 8-digit octal number. 	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 2 Reference 2.5.2 Standard	For ground-to-air calls, the SATVOICE system shall be capable of locating the aircraft in the appropriate airspace regardless of the satellite and ground earth station (GES) to which the aircraft is logged on.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.5.3 Standard	For air-to-ground calls, the SATVOICE system shall be capable of: a) contacting the aeronautical station via an assigned SATVOICE number, which is a unique 6-digit number or public switched telephone network (PSTN) number; and b) allowing the flight crew and/or aircraft system to specify the priority level for the call as defined in Table 2-1.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference														
Chapter 3 Reference 3.1 Recommendation	<p style="text-align: center;">CHAPTER 3. SELCAL SYSTEM</p> <p>Recommendation.— <i>Where a SELCAL system is installed, the following system characteristics should be applied:</i></p> <ul style="list-style-type: none"> a) Transmitted code. <i>Each transmitted code should be made up of two consecutive tone pulses, with each pulse containing two simultaneously transmitted tones. The pulses should be of 1.0 plus or minus 0.25 seconds duration, separated by an interval of 0.2 plus or minus 0.1 second.</i> b) Stability. <i>The frequency of transmitted tones should be held to plus or minus 0.15 per cent tolerance to ensure proper operation of the airborne decoder.</i> c) Distortion. <i>The overall audio distortion present on the transmitted RF signal should not exceed 15 per cent.</i> d) Per cent modulation. <i>The RF signal transmitted by the ground radio station should contain, within 3 dB, equal amounts of the two modulating tones. The combination of tones should result in a modulation envelope having a nominal modulation percentage as high as possible and in no case less than 60 per cent.</i> e) Transmitted tones. <i>Tone codes should be made up of various combinations of the tones listed in the following table and designated by colour and letter as indicated:</i> <table style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: left;"><i>Designation</i></th> <th style="text-align: left;"><i>Frequency (Hz)</i></th> </tr> </thead> <tbody> <tr> <td><i>Red A</i></td> <td><i>312.6</i></td> </tr> <tr> <td><i>Red B</i></td> <td><i>346.7</i></td> </tr> <tr> <td><i>Red C</i></td> <td><i>384.6</i></td> </tr> <tr> <td><i>Red D</i></td> <td><i>426.6</i></td> </tr> <tr> <td><i>Red E</i></td> <td><i>473.2</i></td> </tr> <tr> <td><i>Red F</i></td> <td><i>524.8</i></td> </tr> </tbody> </table>	<i>Designation</i>	<i>Frequency (Hz)</i>	<i>Red A</i>	<i>312.6</i>	<i>Red B</i>	<i>346.7</i>	<i>Red C</i>	<i>384.6</i>	<i>Red D</i>	<i>426.6</i>	<i>Red E</i>	<i>473.2</i>	<i>Red F</i>	<i>524.8</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
<i>Designation</i>	<i>Frequency (Hz)</i>																		
<i>Red A</i>	<i>312.6</i>																		
<i>Red B</i>	<i>346.7</i>																		
<i>Red C</i>	<i>384.6</i>																		
<i>Red D</i>	<i>426.6</i>																		
<i>Red E</i>	<i>473.2</i>																		
<i>Red F</i>	<i>524.8</i>																		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.1.1 Standard	<p align="center">CHAPTER 4. AERONAUTICAL SPEECH CIRCUITS</p> <p align="center">4.1 TECHNICAL PROVISIONS RELATING TO INTERNATIONAL AERONAUTICAL SPEECH CIRCUIT SWITCHING AND SIGNALLING FOR GROUND-GROUND APPLICATIONS</p> <p><i>Note.— Guidance material on the implementation of aeronautical speech circuit switching and signalling for ground-ground applications is contained in the Manual on Air Traffic Services (ATS) Ground-Ground Voice Switching and Signalling (Doc 9804). the material includes explanation of terms, performance parameters, guidance on basic call types and additional functions, references to appropriate ISO/IEC international standards and ITU-T recommendations, guidance on the use of signalling systems, details of the recommended numbering scheme and guidance on migration to future schemes.</i></p> <p>The use of circuit switching and signalling to provide speech circuits to interconnect ATS units not interconnected by dedicated circuits shall be by agreement between the Administrations concerned.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.1.2 Standard	The application of aeronautical speech circuit switching and signalling shall be made on the basis of regional air navigation agreements.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.1.3 Recommendation	Recommendation. — <i>The ATC communication requirements defined in Annex 11, Section 6.2 should be met by implementation of one or more of the following basic three call types:</i> a) <i>instantaneous access;</i> b) <i>direct access; and</i> c) <i>indirect access.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.1.4 Recommendation	Recommendation. — <i>In addition to the ability to make basic telephone calls, the following functions should be provided in order to meet the requirements set out in Annex 11:</i> a) <i>means of indicating the calling/called party identity;</i> b) <i>means of initiating urgent/priority calls; and</i> c) <i>conference capabilities.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.1.5 Recommendation	Recommendation. — <i>The characteristics of the circuits used in aeronautical speech circuit switching and signalling should conform to appropriate ISO/IEC international standards and ITU-T recommendations.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.1.6 Recommendation	Recommendation. — <i>Digital signalling systems should be used wherever their use can be justified in terms of any of the following:</i> a) <i>improved quality of service;</i> b) <i>improved user facilities; or</i> c) <i>reduced costs where quality of service is maintained.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.1.7 Recommendation	Recommendation. — <i>The characteristics of supervisory tones to be used (such as ringing, busy, number unobtainable) should conform to appropriate ITU-T recommendations.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 4 Reference 4.1.8 Recommendation	Recommendation. — <i>To take advantage of the benefits of interconnecting regional and national aeronautical speech networks, the international aeronautical telephone network numbering scheme should be used.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.1.1 Standard	<p style="text-align: center;">CHAPTER 5. EMERGENCY LOCATOR TRANSMITTER (ELT) FOR SEARCH AND RESCUE</p> <p style="text-align: center;">5.1 GENERAL</p> <p>Until 1 January 2005, emergency locator transmitters shall operate either on both 406 MHz and 121.5 MHz or on 121.5 MHz.</p> <p><i>Note.— From 1 January 2000, ELTs operating on 121.5 MHz will be required to meet the improved technical characteristics contained in 5.2.1.8.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.2 Standard	All installations of emergency locator transmitters operating on 406 MHz shall meet the provisions of 5.3.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.1.3 Standard	All installations of emergency locator transmitters operating on 121.5 MHz shall meet the provisions of 5.2.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.1.4 Standard	From 1 January 2005, emergency locator transmitters shall operate on 406 MHz and 121.5 MHz simultaneously.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.1.5 Standard	All emergency locator transmitters installed on or after 1 January 2002 shall operate simultaneously on 406 MHz and 121.5 MHz.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.1.6 Standard	The technical characteristics for the 406 MHz component of an integrated ELT shall be in accordance with 5.3.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.7 Standard	The technical characteristics for the 121.5 MHz component of an integrated ELT shall be in accordance with 5.2.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.1.8 Standard	States shall make arrangements for a 406 MHz ELT register. Register information regarding the ELT shall be immediately available to search and rescue authorities. States shall ensure that the register is updated whenever necessary.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.9 Standard	<p>ELT register information shall include the following:</p> <ul style="list-style-type: none"> a) transmitter identification (expressed in the form of an alphanumeric code of 15 hexadecimal characters); b) transmitter manufacturer, model and, when available, manufacturer's serial number; c) COSPAS-SARSAT* type approval number; d) name, address (postal and e-mail) and emergency telephone number of the owner and operator; e) name, address (postal and e-mail) and telephone number of other emergency contacts (two, if possible) to whom the owner or the operator is known; f) aircraft manufacturer and type; and g) colour of the aircraft. <p>N1. <i>Various coding protocols are available to States. Depending on the protocol adopted. States may, at their discretion, include one of the following as supplementary identification information to be registered:</i></p> <ul style="list-style-type: none"> b) <i>aircraft operating agency designator and operator's serial number; or</i> c) <i>24-bit aircraft address; or</i> d) <i>aircraft nationality and registration marks.</i> <p><i>The aircraft operating agency designator is allocated to the operator by ICAO through the State administration, and the operator's serial number is allocated by the operator from the block 0001 to 4096.</i></p> <p>N5. <i>At their discretion, depending on arrangements in place, States may include other relevant information to be registered such as the last date of register, battery expiry date and place of ELT in the aircraft (e.g. "primary ELT" or "life-raft No. 1").</i></p> <hr/> <p>* COSPAS = Space system for search of vessels in distress; SARSAT = Search and rescue satellite-aided tracking.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.1 Standard	<p align="center">5.2 SPECIFICATION FOR THE 121.5 MHz COMPONENT OF EMERGENCY LOCATOR TRANSMITTER (ELT) FOR SEARCH AND RESCUE</p> <p><i>N1. Information on technical characteristics and operational performance of 121.5 MHz ELTs is contained in RTCA Document DO-183 and European Organization for Civil Aviation Equipment (EUROCAE) Document ED.62.</i></p> <p><i>N2. Technical characteristics of emergency locator transmitters operating on 121.5 MHz are contained in ITU-R Recommendation M.690-1. The ITU designation for an ELT is Emergency Position — Indicating Radio Beacon (EPIRB).</i></p> <p align="center">5.2.1 Technical characteristics</p> <p>Emergency locator transmitters (ELT) shall operate on 121.5 MHz. The frequency tolerance shall not exceed plus or minus 0.005 per cent.</p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.2.1.2 Standard	The emission from an ELT under normal conditions and attitudes of the antenna shall be vertically polarized and essentially omnidirectional in the horizontal plane.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.2.1.3 Standard	Over a period of 48 hours of continuous operation, at an operating temperature of minus 20°C, the peak effective radiated power (PERP) shall at no time be less than 50 mW.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.4 Standard	The type of emission shall be A3X. Any other type of modulation that meets the requirements of 5.2.1.5, 5.2.1.6 and 5.2.1.7 may be used provided that it will not prejudice precise location of the beacon by homing equipment. <i>Note.— Some ELTs are equipped with an optional voice capability (A3E) in addition to the A3X emission.</i>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.2.1.5 Standard	The carrier shall be amplitude modulated at a modulation factor of at least 0.85.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.2.1.6 Standard	The modulation applied to the carrier shall have a minimum duty cycle of 33 per cent.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.2.1.7 Standard	The emission shall have a distinctive audio characteristic achieved by amplitude modulating the carrier with an audio frequency sweeping downward over a range of not less than 700 Hz within the range 1 600 Hz to 300 Hz and with a sweep repetition rate of between 2 Hz and 4 Hz.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.2.1.8 Standard	After 1 January 2000, the emission shall include a clearly defined carrier frequency distinct from the modulation sideband components; in particular, at least 30 per cent of the power shall be contained at all times within plus or minus 30 Hz of the carrier frequency on 121.5 MHz.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.1.1 Standard	<p align="center">5.3 SPECIFICATION FOR THE 406 MHz COMPONENT OF EMERGENCY LOCATOR TRANSMITTER (ELT) FOR SEARCH AND RESCUE</p> <p align="center">5.3.1 Technical characteristics</p> <p><i>N1. Transmission characteristics for 406 MHz emergency locator transmitters are contained in ITU-R M.633.</i></p> <p><i>N2. Information on technical characteristics and operational performance of 406 MHz ELTs is contained in RTCA Document DO-204 and European Organization for Civil Aviation Equipment (EUROCAE) Document ED-62.</i></p> <p>Emergency locator transmitters shall operate on one of the frequency channels assigned for use in the frequency band 406.0 to 406.1 MHz.</p> <p><i>Note.— The COSPAS-SARSAT 406 MHz channel assignment plan is contained in COSPAS-SARSAT Document C/S T.012.</i></p>	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.3.1.2 Standard	The period between transmissions shall be 50 seconds plus or minus 5 per cent.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.3.1.3 Standard	Over a period of 24 hours of continuous operation at an operating temperature of -20°C , the transmitter power output shall be within the limits of 5 W plus or minus 2 dB.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.1.4 Standard	The 406 MHz ELT shall be capable of transmitting a digital message.	CV CAR 19, 19.B.230, (a),(1)	No Difference		
Chapter 5 Reference 5.3.2.1 Standard	<p style="text-align: center;">5.3.2 Transmitter identification coding</p> Emergency locator transmitters operating on 406 MHz shall be assigned a unique coding for identification of the transmitter or aircraft on which it is carried.	CV CAR 19, 19.B.230, (a),(1)	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																						
Chapter 5 Reference 5.3.2.2 Standard	<p>The emergency locator transmitter shall be coded in accordance with either the aviation user protocol or one of the serialized user protocols described in Appendix 1 to this chapter, and shall be registered with the appropriate authority.</p> <p style="text-align: center;">Table 5-1. Modified Baudot code</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;"><i>Code</i></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>Code</i></td> <td></td> </tr> <tr> <td style="text-align: center;"><i>Letter</i></td> <td style="text-align: center;"><i>MSB LSB</i></td> <td style="text-align: center;"><i>MSB</i></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>Figure</i></td> <td></td> </tr> <tr> <td style="text-align: center;"><i>LSB</i></td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">A</td> <td style="text-align: center;">111000 011000</td> <td style="text-align: center;">(-)*</td> </tr> <tr> <td style="text-align: center;">B</td> <td style="text-align: center;">110011</td> <td></td> </tr> <tr> <td style="text-align: center;">C</td> <td style="text-align: center;">101110</td> <td></td> </tr> <tr> <td style="text-align: center;">D</td> <td style="text-align: center;">110010</td> <td></td> </tr> <tr> <td style="text-align: center;">E</td> <td style="text-align: center;">110000 010000</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="text-align: center;">F</td> <td style="text-align: center;">110110</td> <td></td> </tr> <tr> <td style="text-align: center;">G</td> <td style="text-align: center;">101011</td> <td></td> </tr> <tr> <td style="text-align: center;">H</td> <td style="text-align: center;">100101</td> <td></td> </tr> <tr> <td style="text-align: center;">I</td> <td style="text-align: center;">101100</td> <td></td> </tr> <tr> <td style="text-align: center;">J</td> <td style="text-align: center;">111010 001100</td> <td style="text-align: center;">8</td> </tr> <tr> <td style="text-align: center;">K</td> <td style="text-align: center;">111110</td> <td></td> </tr> <tr> <td style="text-align: center;">L</td> <td style="text-align: center;">101001</td> <td></td> </tr> <tr> <td style="text-align: center;">M</td> <td style="text-align: center;">100111</td> <td></td> </tr> </table>		<i>Code</i>			<i>Code</i>		<i>Letter</i>	<i>MSB LSB</i>	<i>MSB</i>		<i>Figure</i>		<i>LSB</i>			A	111000 011000	(-)*	B	110011		C	101110		D	110010		E	110000 010000	3	F	110110		G	101011		H	100101		I	101100		J	111010 001100	8	K	111110		L	101001		M	100111		CV CAR 19, 19.B.230, (a),(1)	No Difference		
	<i>Code</i>																																																										
	<i>Code</i>																																																										
<i>Letter</i>	<i>MSB LSB</i>	<i>MSB</i>																																																									
	<i>Figure</i>																																																										
<i>LSB</i>																																																											
A	111000 011000	(-)*																																																									
B	110011																																																										
C	101110																																																										
D	110010																																																										
E	110000 010000	3																																																									
F	110110																																																										
G	101011																																																										
H	100101																																																										
I	101100																																																										
J	111010 001100	8																																																									
K	111110																																																										
L	101001																																																										
M	100111																																																										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	N 100110				
	O 100011 9 000011				
	P 101101 0 001101				
	Q 111101 1 011101				
	R 101010 4 001010				
	S 110100				
	T 100001 5 000001				
	U 111100 7 011100				
	V 101111				
	W 111001 2 011001				
	X 110111 / 010111				
	Y 110101 6 010101				
	Z 11001				
	()** 100100				
	MSB = most significant bit LSB = least significant bit * = hyphen ** = space				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference

- END -